



Technical Data Sheet

3M™ Economy Reinforced Water Activated Paper Tape 6144



[Product Details](#)

Product Description

3M™ Economy Reinforced Water Activated Paper Tape 6144 is used for box sealing and other packaging applications. This product has a fiberglass reinforced paper backing and a high tack water activated adhesive system.

Product Features

- Recommended for sealing packages weighing a maximum of 25 lbs.
- Used for two C clips on cartons – top and bottom.
- Works well on recycled cartons and non-unitized loads.
- Construction assures a reliable performance in a range of environments and applications.
- Tape is available in kraft only.

Technical Information Note

The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

Typical Physical Properties

Attribute Name	Value
Adhesive Type	High Tack, Water Activated, modified Starch Based Adhesive
Fiber Reinforcement	3 Way Fiber Glass Reinforcing Pattern • Pattern: Lengthwise threads with diamond cross-machine pattern • Lengthwise Threads: 110 Denier Fiberglass -5/8" Spacing (1-1-1-1-1) • Cross Machine Threads: 150 Denier Fiberglass – Diamond Pattern less than 1-1/4" spacing between threads
Bottom Sheet	23 lbs/ream MG Natural High Strength Virgin Kraft
Top Sheet	23 lbs/ream Natural Virgin Kraft
Laminating Matl	Polypropylene based polymer
Thickness	0.12 mm (4.9 mil)

Typical Performance Characteristics

Tensile Strength

Test Condition	Value
Machine Direction	788 — 876 N/100mm (45 — 50 lb/in)
Cross Direction	22 — 27 N/100mm (385 — 473 lb/in)

Handling/Application Information

Application Techniques

Semi-automatic application equipment is available. Application is most easily accomplished at room temperature. Once applied, the tape performs well throughout the normal temperature ranges typically encountered by packaged products in shipping and storage environments.

Storage and Shelf Life

Store under normal conditions of 16° to 27°C (60° to 80°F) and 40 to 60% relative humidity in the original packaging, out of direct sunlight. For best performance, use this product within 12 months from date of manufacture.

Available Sizes

Attribute Name	Value
Packaging	10 rolls per case
Standard Roll Length	137 m (450 ft)
Standard Width	70 mm (2.8 in)

Information

Technical Information: The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

Product Selection and Use: Many factors beyond 3M’s control and uniquely within user’s knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer’s application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

Warranty, Limited Remedy, and Disclaimer: Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M’s option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

Disclaimer: 3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, or death. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit www.3M.com.

ISO Statement

This product was manufactured under a 3M quality system registered to ISO 9001 standards.

3M™ Industrial Specialties Division
3M Center, St. Paul, MN 55144-1000
www.3M.com

3M is a trademark of 3M Company.
©3M 2024 (6/24)