

# 3310 Series Fan Forced Wall Heater - With Summer Fan Switch

45



## Features

- Powder coated 18 gauge steel front.
- Automatic reset thermal limit.
- Steel block fin element.
- Weight 22 lbs.
- Vane axial fan blade: 600 RPM / 175 CFM.
- Grill dimensions: 15 3/8" Wide x 20 3/4" High.
- Rough in dimensions: 14 3/16" Wide x 19 5/16" High x 4" Deep.
- Units with dual wattage, factory wired to highest wattage.
- Wattage selectable at time of installation on some models.
- Made in U.S.A.



## Product Specifications

Typical Specifications: Furnish and install Electric Forced Air Heaters where specified. The heaters shall be constructed of a heavy gauge steel housing. The rough-in dimensions are 14 3/16" Wide x 19 5/16" High x 4" Deep. The finish shall be powder coated paint in ivory or white color. The units shall be available in ratings from 750 through 4800 Watts. The heaters shall have a low speed 600 RPM motor which drives a vane axial blower to deliver a quiet 175 CFM of down flow air. The heating element shall be of the sealed block fin type with large, parallel steel fins for quick heat transfer. Unit shall have a standard thermal overload cutoff for added safety, a fan switch for fan only operation, and is available with a single pole, or double pole built-in thermostat, or no thermostat. The in-built thermostat shall be calibrated to provide a range of 0 degrees F. to 110 degrees F. All heaters shall be listed by ETL. The heating element shall be supplied with a manufacturer's 1 year limited warranty.

## Standard Models

| MODELS WITH IN-BUILT DOUBLE POLE THERMOSTAT (0° - 110°F TEMPERATURE RANGE) |                  |                    |                  |             |          |           |             |
|----------------------------------------------------------------------------|------------------|--------------------|------------------|-------------|----------|-----------|-------------|
| IVORY                                                                      |                  | WHITE              |                  | WATTS       | MAX BTUs | VOLTS     | AMPS        |
| MFG CATALOG NUMBER                                                         | MFG MODEL NUMBER | MFG CATALOG NUMBER | MFG MODEL NUMBER |             |          |           |             |
| 03260602                                                                   | E3312T2SRP       | 03262002           | E3312T2SRPW      | 1000        | 3413     | 120       | 8.3         |
| 03260702                                                                   | E3313T2SRP       | 03262102           | E3313T2SRPW      | 1500        | 5120     |           | 12.5        |
|                                                                            |                  |                    |                  | 750         | 2560     |           | 6.25        |
| 03260802                                                                   | F3316T2SRP       | 03262202           | F3316T2SRPW      | 4000        | 13648    | 208       | 19.2        |
| 03260902                                                                   | F3317T2SRP       | 03262302           | F3317T2SRPW      | 4800        | 16380    |           | 23          |
| 03261202                                                                   | HF3315T2SRP      | 03262602           | HF3315T2SRPW     | 3000 / 2250 | 10240    | 240 / 208 | 12.5 / 10.8 |
|                                                                            |                  |                    |                  | 1500 / 1125 | 5120     |           | 6.2 / 5.4   |
| 03261302                                                                   | HF3316T2SRP      | 03262702           | HF3316T2SRPW     | 4000 / 3000 | 13648    |           | 16.8 / 14.4 |
|                                                                            |                  |                    |                  | 2000 / 1500 | 6826     |           | 8.3 / 7.2   |
| 03261402                                                                   | H3317T2SRP       | 03262802           | H3317T2SRPW      | 4800        | 16380    | 240       | 20.0        |

| MODELS WITH IN-BUILT SINGLE POLE THERMOSTAT (0° - 110°F TEMPERATURE RANGE) |            |          |             |             |       |           |             |
|----------------------------------------------------------------------------|------------|----------|-------------|-------------|-------|-----------|-------------|
| 03825702                                                                   | E3312TSRP  | 03825902 | E3312TSRPW  | 1000        | 3413  | 120       | 8.3         |
| 03796102                                                                   | E3313TSRP  | 03840102 | E3313TSRPW  | 1500        | 5120  |           | 12.5        |
|                                                                            |            |          |             | 750         | 2560  |           | 6.25        |
| 03777102                                                                   | F3316TSRP  | 03840202 | F3316TSRPW  | 4000        | 13648 | 208       | 19.2        |
| 03777802                                                                   | F3317TSRP  | 03840302 | F3317TSRPW  | 4800        | 16380 |           | 23          |
| 03776002                                                                   | HF3315TSRP | 03840702 | HF3315TSRPW | 3000 / 2250 | 10240 | 240 / 208 | 12.5 / 10.8 |
|                                                                            |            |          |             | 1500 / 1125 | 5120  |           | 6.2 / 5.4   |
| 03776902                                                                   | HF3316TSRP | 03840802 | HF3316TSRPW | 4000 / 3000 | 13648 |           | 16.8 / 14.4 |
|                                                                            |            |          |             | 2000 / 1500 | 6826  |           | 8.3 / 7.2   |
| 03777602                                                                   | H3317TSRP  | 03840902 | H3317TSRPW  | 4800        | 16380 | 240       | 20.0        |
| International Models                                                       |            |          |             |             |       |           |             |
| ----                                                                       | ----       | 03964802 | M3315T2SRPW | 3360        | 11468 | 220       | 15.27       |
|                                                                            |            |          |             | 1680        | 5734  |           | 7.64        |
| ----                                                                       | ----       | 03964902 | M3316T2SRPW | 4032        | 13761 |           | 18.33       |
|                                                                            |            |          |             | 2016        | 6881  |           | 9.16        |

Note: Fan switch not available on 277V models. 277V models are available without a fan switch on previous page.

## Accessories - All Models

| IVORY              |                  | WHITE              |                  | DESCRIPTION            | ACCESSORY TYPE    |
|--------------------|------------------|--------------------|------------------|------------------------|-------------------|
| MFG CATALOG NUMBER | MFG MODEL NUMBER | MFG CATALOG NUMBER | MFG MODEL NUMBER |                        |                   |
| 03778502           | BOX3310          | 03778502           | BOX3310          | ADDITIONAL BACK CAN    | Field Installed   |
| 03299502           | 3310EX33R        | 03299602           | 3310EX33WR       | SURFACE MOUNTING FRAME |                   |
| SUFFIX D           |                  |                    |                  | DISCONNECT SWITCH      | Factory Installed |