

DRILLS-MASONRY

**Long Length General Purpose
Masonry Drills (cont.)**

Carbide Tipped – Regular Helix



LIST NO. 543			
24" OAL			
DIAMETER	OVERALL LENGTH	SHANK DIAMETER	EDP NO.
1/4	24	1/4	84300
9/32	24	1/4	84301
5/16	24	5/16	84302
3/8	24	3/8	84303
7/16	24	3/8	84304
1/2	24	3/8	84305
9/16	24	3/8	84306
5/8	24	1/2	84307
11/16	24	1/2	84308
3/4	24	1/2	84309
13/16	24	1/2	84310
7/8	24	1/2	84311
1	24	1/2	84312
1 1/8	24	1/2	84313
1 1/4	24	1/2	84314
1 3/8	24	1/2	84315
1 1/2	24	1/2	84316
36" OAL			
1/4	36	1/4	84320
9/32	36	1/4	84321
5/16	36	5/16	84322
3/8	36	3/8	84323
7/16	36	3/8	84324
1/2	36	1/2	84325
9/16	36	1/2	84326
5/8	36	1/2	84327
11/16	36	1/2	84328
3/4	36	1/2	84329
13/16	36	1/2	84330
7/8	36	1/2	84331
1	36	1/2	84332
1 1/8	36	1/2	84333
1 1/4	36	1/2	84334
1 3/8	36	1/2	84335
1 1/2	36	1/2	84336
48" OAL			
1/4	48	1/4	84340
5/16	48	5/16	84341
3/8	48	3/8	84342
1/2	48	1/2	84343
5/8	48	1/2	84344
3/4	48	1/2	84345
7/8	48	1/2	84346
1	48	1/2	84347
1 1/8	48	1/2	84348
1 1/4	48	1/2	84349
1 3/8	48	1/2	84350
1 1/2	48	1/2	84351

Carbide Tipped – Regular Helix

USE

For use in all rotary style drill motors.

SPECS

Regular Helix features wide flutes for fast dust removal especially in softer materials.

STANDARD PACKAGE

All sizes — 1 each

MADE IN USA