Miller HP Series Non-Stretch Harnesses Models: 650T Family

Materials

Webbing 1 ¾" Polyester

Minimum Tensile 5,000 lbs. (22kN) on webbing

Thread: 6 cord bonded 3 strand polyester thread.

Minimum tensile of 42 lbs.

Label Pack: Evoprene, Nylon

Labels: Valeron Grommets Brass

Hardware Steel Minimum Tensile strength

- D-Ring 5,000 lbs. (22kN) - Buckles 4,000 lbs. (18kN)

* All hardware meets ASTM (50) fifty-hour salt spray test requirements.

Technical

Max Working Load: 400 lbs (181.4 kg)

Certification

Meets OSHA 1926.502, ANSI A10.32, Z359.1

and CSA requirements.





Model No.	Front D-ring	Side D-Rings	Shoulder D-Rings	Shoulder Strap	Leg Strap	Chest Strap	Special Features	Weight
650T/UGK	option	No	No	Friction	Mating	Mating	Pull-free lanyard rings, Belt loops	2.90 lbs. (1.3kg)
650T-3/UGK	option	No	Yes	Friction	Mating	Mating	Pull-free lanyard rings, Belt loops	5.00 lbs. (2.3kg)
650T-4/UGK	option	No	No	Friction	Tongue	Mating	Pull-free lanyard rings, Belt loops	3.50 lbs. (1.6kg)
650T-7/UGK	option	Yes	No	Friction	Mating	Mating	Pull-free lanyard rings, Belt loops	3.50 lbs. (1.6kg)
650T-58/UGK	option	Yes	No	Friction	Tongue	Mating	Pull-free lanyard rings, Belt loops	4.10 lbs. (1.9kg)
650T-61/UGK	option	Yes	No	Friction	Tongue	Mating	Shoulder pads, Back pad, Lanyard rings, Belt loops, Removable waist belt	5.10 lbs. (2.4kg)
650T-64/UGK	option	No	Yes	Friction	Tongue	Mating	Pull-free lanyard rings, Belt loops	3.7 lbs. (1.7kg)
650T-76 /UGK	option	Yes	No	Friction	Tongue	Mating	6" (152mm) back pad, Tool belt, Shoulder pads, Pull-free lanyard rings, Belt loops	5.10 lbs. (2.4kg)
650T-77/UGK	option	Yes	No	Friction	Tongue	Mating	6" (152mm) back pad, Tool belt, Pull-free lanyard rings, Belt loops	5.00 lbs. (2.3kg)



Toll Free 800-873-5242 • Phone 814.432.2118 • Fax 814.437.2973 • www.millerfallprotection.com