



### Product Family







## Miller MightyLite Leading Edge Self-Retracting Lifeline

The Miller MightyLite Leading Edge Self-Retracting Lifeline (LE SRL) is designed to protect a worker if a fall occurs that involves going over an edge and features a shock absorber pack integrated into the lifeline, lowering fall arrest forces. The MightyLite LE SRL is engineered for use in leading edge applications or with a traditional overhead anchorage.

Visit [MillerFallProtection.com](http://MillerFallProtection.com) >



### Product Numbers & Ordering Information

	Product Numbers	Details
	RL20G-Z7LE/20FT	<b>Miller MightyLite LE SRL w/ Shock-Absorbing Packs</b> MightyLite LE SRLs are corrosion-resistant stainless steel and aluminum construction with galvanized wire rope (3/16-in.) lifeline, integrated leading edge shock-absorbing pack, carabiner and tagline.
	RLS30G-Z7LE/30FT	<b>Miller MightyLite LE SRL w/ Shock-Absorbing Packs</b> MightyLite LE SRLs are corrosion-resistant stainless steel and aluminum construction with galvanized wire rope (3/16-in.) lifeline, integrated leading edge shock-absorbing pack, carabiner and tagline.
	RL50G-Z7LE/50FT	<b>Miller MightyLite LE SRL w/ Shock-Absorbing Packs</b> MightyLite LE SRLs are corrosion-resistant stainless steel and aluminum construction with galvanized wire rope (3/16-in.) lifeline, integrated leading edge shock-absorbing pack, carabiner and tagline.
	RL65G-Z7LE/65FT	<b>Miller MightyLite LE SRL w/ Shock-Absorbing Packs</b> MightyLite LE SRLs are corrosion-resistant stainless steel and aluminum construction with galvanized wire rope (3/16-in.) lifeline, integrated leading edge shock-absorbing pack, carabiner and tagline.
	RL20G-Z7LEK/20FT	<b>Miller MightyLite LE SRL w/ Kevlar Shock-Absorbing Packs (for Welding Applications)</b> MightyLite LE SRLs are corrosion-resistant stainless steel and aluminum construction with galvanized wire rope (3/16-in.) lifeline, integrated leading edge shock-absorbing pack, carabiner and tagline.
	RL30G-Z7LEK/30FT	<b>Miller MightyLite LE SRL w/ Kevlar Shock-Absorbing Packs (for Welding Applications)</b> MightyLite LE SRLs are corrosion-resistant stainless steel and aluminum construction with galvanized wire rope (3/16-in.) lifeline, integrated leading edge shock-absorbing pack, carabiner and tagline.



RL50G-Z7LEK/50FT

**Miller MightyLite LE SRL w/ Kevlar Shock-Absorbing Packs (for Welding Applications)**

MightyLite LE SRLs are corrosion-resistant stainless steel and aluminum construction with galvanized wire rope (3/16-in.) lifeline, integrated leading edge shock-absorbing pack, carabiner and tagline.



RL65G-Z7LEK/65FT

**Miller MightyLite LE SRL w/ Kevlar Shock-Absorbing Packs (for Welding Applications)**

MightyLite LE SRLs are corrosion-resistant stainless steel and aluminum construction with galvanized wire rope (3/16-in.) lifeline, integrated leading edge shock-absorbing pack, carabiner and tagline.

## Overview

### Key Features

- **Extended service life**  
Durable, corrosion-resistant stainless steel and aluminum construction.
- **30% lighter than competitive models in class for easy handling**
- **Lifeline twisting minimized**  
A dual swivels design (unit top and snap hook) minimizes lifeline twisting during use.
- **Quick, easy installation**  
Carabiner and tagline included for easy lifeline access and connection.
- **Dual capacity rating**  
Rated for up to a 310 lb. worker in leading edge applications and up to a 400 lb. worker when mounted overhead.
- **Meets testing requirements for ANSI Z359.14**

### Recommended Industries/Use

- Construction
- Welding

### Hazards

- Fall from height

### Regulations

- Meets all applicable OSHA and ANSI standards

### Warranty Information

We sincerely believe that our fall protection equipment is the best in the world. Our products endure rigorous test to ensure that the fall protection equipment you trust is manufactured to the highest standards. Miller fall protection products are tested to withstand normal wear and tear, but are not indestructible and can be damaged by misuse. Our Limited Lifetime Warranty does not apply to normal wear and tear or abusive treatment of the product. In the unlikely event that you should discover defects in either workmanship or materials, under our Limited Lifetime Warranty, we will repair or replace the product at our expense. If a replacement is necessary and your product is no longer available, a comparable product will be substituted. Should a product issue surface, contact us at 800/873-5242. Manufacturing specifications are subject to change without notice.

## Specifications

### Maximum Working Capacity

- Rated for up to a 310 lb. worker in leading edge applications and up to 400 lb. worker when mounted overhead

### Specification Sheets

- For a full engineering specification sheet, go to literature and documents

## Literature & Documents

Miller\_LE-SRL-flyer - US

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fall\\_Limiters](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters)

[/Self-Retracting\\_Lifelines/4294971504/1033.aspx](#)

Learn more about the MightyLite Leading Edge Self-Retracting Lifeline

**SP463 - Miller LE-SRL - US**

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fall\\_Limiters/Self-Retracting\\_Lifelines/4294971505/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/4294971505/1033.aspx)

Miller Leading Edge Self-Retracting Lifeline Spec Sheet

**Miller MightyLite LE SRL FAQ - US**

[http://www.honeywellsafety.com/Supplementary/Documents\\_and\\_Downloads/Fall\\_Protection/Fall\\_Limiters/Self-Retracting\\_Lifelines/4294971558/1033.aspx](http://www.honeywellsafety.com/Supplementary/Documents_and_Downloads/Fall_Protection/Fall_Limiters/Self-Retracting_Lifelines/4294971558/1033.aspx)

Download the Miller MightyLite Leading Edge SRL Frequently Asked Questions

## Training & Proper Use

Proper product training and professional fall protection training is recommended. Refer to Product Use Instructions enclosed with products.

## Additional Information

800/873-5242 or email: [hsptechsupport@honeywell.com](mailto:hsptechsupport@honeywell.com)

## Technical Support

Contact Honeywell Technical Service at 800/873-5242 or email: [hsptechsupport@honeywell.com](mailto:hsptechsupport@honeywell.com)

### RELATED PRODUCTS