G304/G304T/G304TN

TOP SHELF CHEMICAL SPLASH GOGGLE





PART LENS
G304*** Clear
G304T**** Clear (Anti-Fog)

G304TN** Clear (Anti-Fog)

- · Body tinted to reduce glare.
- · Lenses provides 99.9% protection against harmful UV rays.
- Special one-way vent allows air to enter while keeping liquids out.
- Top shelf chemical splash goggle features generously sized heavy duty body and lens.

GENERAL SPECIFICATION Bridge: 42mm Lens Base: 4.25 curve Lens Size Diagonal: 150mm Lens Size Vertical: 76mm Lens Thickness: 2.2mm Overall Length (Lens-Tip): N/A Overall Width (Hinge-Hinge): 180mm PD: 68mm Weight: 68gm

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 144 pcs

G304/G304T/G304TN

TOP SHELF CHEMICAL SPLASH GOGGLE

COMPONENT	MATERIAL	FEATURES	
Lens	Polycarbonate	Lens inset in PVC frame	
Frame	PVC	Polyvinyl chloride, flexible fit	
Nose Piece	PVC	Integral to frame	
2 cap vents	LPDE	Also hold elastic band in place	
Elastic Band	60% polyester 40% rubber thread	N/A	

PART	LENS	LENS MARKING	FRAME MARKING
G304	Clear	P	P Z 8 7 + / P c SEI CAN/CSA Z 94.3-07
G304T	Clear (Anti-Fog)	P	P Z87 + / P c SEI CAN/CSA Z94.3-07
G304TN	Clear (Anti-Fog)	Р	P Z 8 7 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices