

# Mini Intruder®

Designed for smaller facial features



#### Part

S4110SN••

S4110SNT•

S4120SN•

S4180SN•

#### Lens & Temples

Clear

Clear Anti-Fog

Gray

I/O Mirror

#### Multi-Color Frame

S4110SNMP••  Clear

- Superior comfort and fit.
- Lightweight, frameless protection is ideal for all-day wear.
- Mini Intruder has all the great features of Intruder in a design better suited for smaller facial sizes.
- Coated lens provides excellent side protection and 99.9% protection against harmful UV rays.

#### GENERAL SPECIFICATION

Bridge: 14.17mm

Closest Point Between Lens: 14.38mm

Closest Point Between Temples: 77.83mm

Lens Base: 11 curve

Lens Size Diagonal: 69.43mm

Lens Size Vertical: 39.92

Lens Thickness: 2.1mm

Overall Length (Lens-Tip): 144mm

Overall Width (Hinge-Hinge): 121.8mm

PD: 62mm

Weight: 17.9g

#### Mini Intruder

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

#### Mini Multi-color Intruder

Polybag: 1pc

Inner Box: 12 pcs

Case: 25 pcs

# Mini Intruder®

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	9 base curve
Temple	Polycarbonate	Straight
Hinge	Polycarbonate	Integral to temples
Screw	Stainless steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
S4110SN	 Clear	P Z87 + H U6	P Z87 +
S4110SNT	 Clear Anti-Fog	P Z87 + H U6	P Z87 +
S4120SN	 Gray	P Z87 + H U6 L3	P Z87 +
S4180SN	 Indoor/Outdoor Mirror	P Z87 + H U6 L1.7	P Z87 +
S4110SNMP	 Clear	P Z87 + H U6	P Z87 + / P c SEI CAN/CSA Z94.3-07

## LENS MARKING

### Symbols:

P: Manufacturer's mark  
 Z87: ANSI standard for Eye and Face protection devices  
 +: High Impact  
 H: Small Head Size  
 S: Special Purpose

### UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%  
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%  
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%  
 U4: Max Effective Far UV= .04% / Max Near UV= .5%  
 U5: Max Effective Far UV= .02% / Max Near UV= .2%  
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

### Visible Light Filters:

L1.3: 85% Max. Visible Light  
 L1.7: 55% Max. Visible Light  
 L2.5: 29% Max. Visible Light  
 L3: 18% Max. Visible Light

## FRAME MARKING

### Symbols:

P: Manufacturer's mark  
 Z87: ANSI standard for Eye and Face protection devices  
 +: High Impact  
 P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices