

ACHIEVA®

INNOVATIVE AND SPORTY DESIGN



PART

SG6510S*

SG6510ST**

SG6520S*

SG6580S*

LENS

Clear

Clear (Anti-Fog)

Gray

Indoor/Outdoor Mirror

PART

SP6510S*

SP6520S*

SP6580S*

LENS

Clear

Gray

Indoor/Outdoor Mirror

- Brow guard deflects airborne particles.
- Innovative and sporty safety spectacle.
- Built-in rubber nose piece provides all day comfort.
- Lightweight, frameless protection is ideal for all-day wear.
- Extended lens provides excellent side protection, provides 99.9% protection against harmful UV rays.

GENERAL SPECIFICATION

Bridge: 14.5mm

Closest Point Between Lens: 12.5mm

Closest Point Between Temples Tips: 93.5mm

Lens Base: 8 Curve

Lens Size Diagonal: 145mm

Lens Size Vertical: 44.2mm

Lens Thickness: 2.3mm

Overall Length (Lens-Tip): 160mm

Overall Width (Hinge-Hinge): 141mm

PD: 68mm

Weight: 26gm

PACKAGING

Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

ACHIEVA®

INNOVATIVE AND SPORTY DESIGN

COMPONENT	MATERIAL	FEATURES
Temple Tips	PVC	Spatula with soft tip end
Frame	N/A	N/A
Lens	Polycarbonate	8 base curve, wrap around design with side protection
Side Shield	Polycarbonate	Integral to lens
Nose Piece	PC	Co-material injected, soft nose pad for the ultimate in comfort
	HTPE	
Hinge	Polycarbonate	3 barrel type, integral to frame/temple
Screw	Stainless Steel	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SG6510S	 Clear	P Z87 +	P Z87 +
SG6510ST	 Clear (Anti-Fog)	P Z87 +	P Z87 +
SG6520S	 Gray	P Z87 + S	P Z87 +
SG6580S	 Indoor/Outdoor Mirror	P Z87 + S	P Z87 +
SP6510S	 Clear	P Z87 +	P Z87 +
SP6520S	 Gray	P Z87 + S	P Z87 +
SP6580S	 Indoor/Outdoor Mirror	P Z87 + S	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact