

Tooling Systems 2026.1





At Seco, we make tools, tech, and solutions for the most advanced manufacturing challenges on Earth. From our founding in Fagersta Sweden, to today's global company, our business has always been made to measure, and built on trust.

Combining cutting-edge, precision tools with lasting, personal partnerships, we're a true people company helping our partners discover the future of the manufacturing industry.

We're proud to make for makers, invent for inventors, and partner with pioneers. Driving the future forward with our focus on innovation. In short - if the right tool for the job exists, we'll deliver it. If it doesn't, we'll create it.

We're proud to put sustainability at the heart of everything we do, challenging perceptions of our industry, changing the process of manufacturing, and playing our own small part in shaping a brighter looking future.

Guide

Welcome	9
Content overview	10
Code Keys	13
ISO attribute information	15
Tool holders for modern machining	16
Tool holders for round tools clamping	17
Collet chucks, accessories	21
Shrinkfit holders	25
Easyshrink® EVO, Accessories and Spare parts	28
Hydraulic chucks	31
Power Milling Chucks, accessories	34
Tapping chucks with micro-compensation	36
Combimaster	37
Shell mill holders	38
Steadyline® holders	39
Graflex Modular system	41
Accessories and Spare parts	42
Custom products	43
Balancing, RFID holes	44
Clamping torque, max RPM, mounting recommendations	45
Safety, maintenance and recycling rules for tool holders	54

HSK-A

General Information	55	Combimaster
Norm dimensions	56	
Shell mill holders	57	Graflex
Disc mill holders	67	
Side lock holders, Weldon	68	Seco Capto™
Shrinkfit holders	73	
High precision collet chucks	92	
Hydraulic chucks	95	Others
Power Milling Chucks	98	
ER Collet chucks	100	Operating & setting accessories
Drill chucks	102	
Tapping chucks	103	
Greenstock blanks	104	Shrinkfit
Control bars	105	

HSK-E

General Information	106	Shrinkfit
Norm dimensions	107	

Guide	Shrinkfit holders	108
	High precision collet chucks	111
DIN69871		
HSK-A	General Information	113
	Norm dimensions	114
HSK-E	Shell mill holders	115
	Disc mill holders	121
	Side lock holders, Weldon	122
	Shrinkfit holders	125
DIN	High precision collet chucks	130
	Hydraulic chucks	132
	Power Milling Chucks	134
	ER Collet chucks	135
BT JIS	Drill chucks	137
	Tapping chucks	138
	Taper adapters	139
	Greenstock blanks	140
CAT	Control bars	141
	BT JIS	
Combimaster	General Information	142
	Norm dimensions	143
	Shell mill holders	144
	Disc mill holders	152
Graflex	Side lock holders, Weldon	153
	Shrinkfit holders	157
	High precision collet chucks	164
	Hydraulic chucks	166
Seco Capto™	Power Milling Chucks	169
	ER Collet chucks	170
	Drill chucks	172
	Tapping chucks	173
Others	Taper adapters	174
	Greenstock blanks	175
	Control bars	176
Operating & setting accessories	BT JIS TF	
	General Information	177
Shrinkfit	Norm dimensions	178
	Shell mill holders	179
	Side lock holders, Weldon	186
	Shrinkfit holders	189

High precision collet chucks	192	Guide
Hydraulic chucks	194	
Power Milling Chucks	196	
ER Collet chucks	197	

CAT

General Information	198	HSK-A
Shell mill holders	199	
Disc mill holders	201	HSK-E
Side lock holders, Weldon	202	
Shrinkfit holders	205	DIN
High precision collet chucks	211	
Hydraulic chucks	213	
Power Milling Chucks	216	
ER Collet chucks	217	BT JIS
Tapping chucks	219	

CAT TF

General Information	220	CAT
Shell mill holders	221	
Side lock holders, Weldon	223	Combimaster
Shrinkfit holders	224	
High precision collet chucks	227	
Hydraulic chucks	228	
Power Milling Chucks	230	Graflex
ER Collet chucks	231	

Combimaster

General Information	233	Seco Capto™
Norm dimensions	234	
Arbors	235	Others
Extensions	254	
Reducers	255	
Shrinkfit holders	256	

Graflex®

General Information	257	Operating & setting accessories
Norm dimensions	258	
Arbors	259	
Extensions	274	
Reducers	276	Shrinkfit
Enlargers	280	
Shell mill holders	281	

Guide	Disc mill holders	285
	Side lock holders, Weldon	286
	High precision collet chucks	288
	Hydraulic chucks	289
HSK-A	ER Collet chucks	290
	Drill chucks	291
Seco Capto™		
HSK-E	General Information	292
	Norm dimensions	293
	Basic arbors	294
DIN	Extensions	315
	Reducers	319
	Shell mill holders	323
BT JIS	Disc mill holders	332
	Side lock holders, Seco-Weldon	333
	Side lock holders for type 7 drill shanks	336
CAT	Shrinkfit holders	338
	High precision collet chucks	344
	Hydraulic chucks	346
	Power Milling Chucks	348
Combimaster	ER Collet chucks	349
	Tapping chucks	351
Others (Cylindrical / Weldon)		
Graflex	General Information	353
	Cylindrical Extensions	354
	Shrinkfit holders	357
	Hydraulic chucks	359
Seco Capto™	High precision collet chucks	360
	ER Collet chucks	362
	Tapping chucks	364
	Combimaster	367
Operating and setting accessories		
Operating & setting accessories	General Information	369
	HSK coolant tubes, tube spanners and sealing plugs	370
	Accessories, coolant tubes for MQL1	371
	Accessories, coolant tubes for MQL1 for DIN4,5° shrinkfit chucks	372
Shrinkfit	Pull studs	373
	Reduction sleeves	381
	Stop screws for through coolant, for Power milling chucks	387
	ER HP collets	389

ER collets	399	Guide
ER tapping collets with square drive	407	
ER sealing rings	410	
Assembly supports, Tool Boy	412	
Keys for Collet Chucks	413	HSK-A
Axial stop end screws for ERHP Collet chucks	415	

Shrinkfit devices

General Information	416	HSK-E
Easyshrink® EVO / Refrigeration unit	417	
Accessories for Easyshrink® EVO	418	DIN
Spare parts for Easyshrink® EVO	420	

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Guide	0	
	01B5875	410-411
	02E93	370
	03E93	370
	05FHC	381-384
	05FPMC	385-386
HSK-A	1	
	19BPMC	387
	19MQL	372
HSK-E	2	
	20E93	370-371
DIN	3	
	393.14	407-408
	5	
	5672	389-397
BT JIS	5880	399-402
	5680094	370
CAT	A	
	A393.14	409
Combimaster	B	
	BD / 1155	358
Graflex	BD / 1195	358
	BD / 5801	357
Seco Capto™	BD / 5820	355-356
	BD / 5821	354-356
Others	BD / 5822	354-356
	BD / 5867	364
Operating & setting accessories	BS / 5603	256
	BS / 5820	254-255
Shrinkfit	BT.AD / EM	155
	BT.AD / ER	170-171
Others	BT.AD / ERHP	164-165
	BT.AD / PMC	169
Operating & setting accessories	BT.AD / SM	118-119,147-148
	BT.AD / SMF	151
Others	BT.ADB / EM	153-154,156
	BT.ADB / HC	166
Operating & setting accessories	BT.ADB / HCR	167
	BT.ADB / HCS	168
Others	BT.ADB / M	242-244
	BT.ADB / SM	145-146,149-150
Operating & setting accessories	BT.TFAD / EM	186-187
	BT.TFAD / ER	197
Others	BT.TFAD / ERHP	192-193
	BT.TFAD / PMC	196
Operating & setting accessories	BT.TFAD / SM	180-181
	BT.TFADB / EM	188
Others	BT.TFADB / HCR	194
	BT.TFADB / HCS	195
Operating & setting accessories	BT.TFADB / PMC	196
	BT.TFADB / SM	182-185
Others	BW / 5821	367-368
	BW / 5822	368
Operating & setting accessories	BW / 5867	365-366
	C	
Others	C-390.00	294-295
	C-390.411	300
Operating & setting accessories	C-390.55	306-307
	C-390.605	308
Others	C-390B.140	302-303
	C-390B.55	306-307
Operating & setting accessories	C-390B.58	306-307
	C-391.01	315-317
Others	C-391.02	319-322
	C-391.0401	272-273
Operating & setting accessories	C-391.0552	329-330
	C-391.27	336-337
Others	C-391.5524	326-327
	C-391.5525	326-328
Operating & setting accessories	C-391.5555	323-325
	C-391.5556	323,325
Others	C-391.5600	342-343
	C-391.5603	338-341
Operating & setting accessories	C-391.5657	332
	C-391.5820	252-253
Others	C-391.5867	351-352
	C-391.K820	251
Operating & setting accessories	C-391.K821	251
	C-A390B.45	296-297
Others	C-A391.05	331
	C-EM	333-335
Operating & setting accessories	C-ER	349-350
	C-ERHP	344-345
Others	C-HC	289,346
	C-HCR	347
Operating & setting accessories	C-M	252-253
	C-PMC	348
Others	CAT.AD / ERHP	211-212
	CAT.AD / PMC	216
Operating & setting accessories	CAT.ADB / EM	202-204
	CAT.ADB / ER	217-218
Others	CAT.ADB / HC	213-214
	CAT.ADB / HCR	215
Operating & setting accessories	CAT.ADB / M	246
	CAT.ADB / PMC	216
Others	CAT.ADB / SM	199-200
	CAT.TFAD / ERHP	227
Operating & setting accessories	CAT.TFAD / PMC	230
	CAT.TFADB / EM	223
Others	CAT.TFADB / ER	231-232
	CAT.TFADB / HC	228
Operating & setting accessories	CAT.TFADB / HCR	229
	CAT.TFADB / HR	231-232
Others	CAT.TFADB / M	249
	CAT.TFADB / PMC	230
Operating & setting accessories	CAT.TFADB / SM	222
	D	
Others	DIN.AD / ER	135-136
	DIN.AD / ERHP	130-131
Operating & setting accessories	DIN.AD / PMC	134
	DIN.AD / SM	118-120
Others	DIN.ADB / EM	122-124
	DIN.ADB / HC	132
Operating & setting accessories	DIN.ADB / HCR	133
	DIN.ADB / M	239
Others	DIN.ADB / SM	116-119
Operating & setting accessories	E	
	E2342 / 5191	312
Others	E2344 / 5191	312
	E2502 / 5600	209-210
Operating & setting accessories	E2502 / 5603	205-208
	E2502 / 5820	246
Others	E2502 / 5821	246
	E2504 / 5600	210
Operating & setting accessories	E2504 / 5603	205-208
	E2504 / 5820	246
Others	E2522 / 5657	201
	E2524 / 5657	201
Operating & setting accessories	E2542 / 5600	226
	E2602 / 5820	247
Others	E2602 / 5821	247
	E2604 / 5820	247
Operating & setting accessories	E2622 / 5867	219
	E2624 / 5867	219
Others	E2642 / 5603	224-225
	E2642 / 5820	250
Operating & setting accessories	E2642 / 5821	250
	E2644 / 5556	221
Others	E2644 / 5603	225
	E2644 / 5820	250
Operating & setting accessories	E2644 / K821	248
	E3114 / 5191	310-311
Others	E3116 / 5191	310-311

E3169 / 5191	304
E3171 / 5191	304
E3214 / 5600	191
E3214 / 5820	245
E3216 / 5555	179
E3216 / 5600	191
E3216 / 5820	245
E3414 / 5023	175
E3414 / 5085	172
E3414 / 5555	144
E3414 / 5600	161-162
E3414 / 5603	158-160
E3414 / 5801	163
E3414 / 5820	243-244
E3414 / 5821	243
E3416 / 5023	175
E3416 / 5085	172
E3416 / 5555	144
E3416 / 5556	144
E3416 / 5600	161-162
E3416 / 5603	158-159
E3416 / 5820	244
E3416 / K821	242
E3469 / 5023	140
E3469 / 5085	137
E3469 / 5600	127-128
E3469 / 5603	125-126
E3469 / 5821	239
E3469 / K821	238
E3471 / 5023	140
E3471 / 5085	137
E3471 / 5555	115
E3471 / 5556	115
E3471 / 5600	127-128
E3471 / 5603	125-126
E3471 / 5820	239
E3471 / K821	238
E3476 / 5801	129
E3476 / 5820	240-241
E3476 / 5821	240-241
E3478 / 5820	241
E4002 / 5191	310-311
E4002 / 5525	310-311
E4002 / 5603	189-190
E4002 / 5820	245
E4040 / 5603	157
E4040 / 5867	173
E4041 / 5657	152
E4041 / 586	176
E4041 / 5867	173
E4469 / 5657	121
E4469 / 586	141
E4469 / 5867	138
E4471 / 543	139
E4471 / 5657	121
E4471 / 586	141
E4471 / 5867	138
E5766 / 543	174
E5766 / 5657	152
E5766 / 5867	173
E9302 / 5023	104
E9302 / 5603	73,75
E9302 / 5801	90
E9304 / 5023	104
E9304 / 5085	102
E9304 / 5402	78-80
E9304 / 5403	73-75
E9304 / 5403M	81-82
E9304 / 5403M1	83-84
E9304 / 5555	57-58
E9304 / 5556	57
E9304 / 5600	85-87
E9304 / 5603	76-77
E9304 / 5657	67

E9304 / 5801	90
E9304 / 5820	236
E9304 / 5821	236
E9304 / 586	105
E9304 / 5867	103
E9304 / K820	235
E9304 / K821	235
E9306 / 5023	104
E9306 / 5085	102
E9306 / 5402	79
E9306 / 5403	74
E9306 / 5403M	82
E9306 / 5403M1	84
E9306 / 5555	57-59
E9306 / 5556	57
E9306 / 5600	85-87
E9306 / 5603	76
E9306 / 5657	67
E9306 / 5801	90-91
E9306 / 5820	237
E9306 / 586	105
E9306 / 5867	103
E9306 / K820	235
E9306 / K821	235
E9342 / 5603	108-109
E9342 / 5801	110
E9343 / 5603	108-109
E9343 / 5801	110
E9474 / 5191	314
EM / 2502	269-270
EM / 2504	269-270
EM / 3214	267-268
EM / 3216	267-268
EM / 4002	267-268
EM0040	263
EM0050	263
EM2502	269-270
EM2504	269-270
EM2642	271
EM2644	271
EM3414	265-266
EM3416	265-266
EM3469	261-262
EM3471	261-262
EM4040	264
EM9303	259-260
EM9304	259-260
EM9306	259-260
G	
G-ER	290
G-ERHP	288
H	
HA.-C	298-299
HSKA / C	298-299
HSKA / EM	68-72
HSKA / ER	100-101
HSKA / -ERHP	92-94
HSKA / G	259
HSKA / HC	95
HSKA / HCR	96
HSKA / HCS	97
HSKA / M	235,237
HSKA / PMC	98-99
HSKA / SFD	74-76
HSKA / SFR	88-89
HSKA / SM	60-64
HSKA / SMF	65-66
HSKE / ERHP	111-112
M	
M100	412
M211	412
M402	274-275

Guide	M403 276-280
	M5085 291
	M5524 281-282
	M5525 281-283
	M5656 285
	M569 284
	M584 286-287
HSK-A	P
	PS-B.. 375-377
	PS-L.. 373-374
	PS-V.. 378-380
HSK-E	
DIN	
BT JIS	
CAT	
Combimaster	
Graflex	
Seco Capto™	
Others	
Operating & setting accessories	
Shrinkfit	

S	
ST-ER	362-363
ST-ERHP	360-361
ST.HC	359
Z	
ZFAD05	418
ZFAG01	420
ZFAR03C	420
ZFAR10D	418-419
ZFAT	420
ZFM30	417
ZFS07IN	420

Welcome to Seco Tools Tooling Systems



STTS (Seco Tools Tooling Systems), formerly EPB, was created in 1924 in Bouxwiller located in the eastern part of France, near the German border.










STTS is the competence center for CNC Tooling systems, responsible for the development and the manufacturing of rotating tool holders, Boring heads, and Antivibration solutions within the Seco Tools Group.

With modern production means from latest's generation, and a high degree of automation, STTS is producing a range of Premium solutions with the utmost quality and performance, with an environmental focus.









STTS offers a comprehensive range of rotating tool holders including:

- High precision collet chucks, and standard ER collet chucks
- A large range of Shrinkfit holders, standard DIN, reinforced and slim designs
- Hydraulic expansion chucks
- Power Milling chucks
- Synchronized tapping chucks
- Basic holders for the Seco screw-in system Combimaster, also in Steadyline antivibration style
- Different type of face mill holders for tenon driven cutters and disc mill cutters, also in Steadyline antivibration version
- Endmill holders with coolant channels through the face
- NC drill chucks
- Blanks
- Easyshrink EVO Heating device
- Operating accessories like pullstuds, collets, ToolBoy... coming in all kind of classical taper back ends.

Tool holders – Machine side vs Workpiece side

Guide									
HSK-A	ER HP Collet chucks	ER Collet chucks	Shrinkfit DIN 4,5°	Shrinkfit HD	Shrinkfit M&D	Hydro chucks	PMC	ER Tapping chucks	Combimaster
HSK-E									
	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)
DIN	HSK-A	92, 93, 94	100, 101	73, 74, 75-83, 84	85, 86-89	90, 91	95, 96, 97	98-99	103
	HSK-E	111, 112		108, 109		110			
	DIN69871 DIN T/F	130, 131	135, 136	125, 126	127, 128	129	132, 133	134	138
BT JIS	DIN2080								238-240, 241
	BT JIS	164, 165	170, 171	157-158, 159, 160	161, 162	163	166, 167, 168	169	173
	BT T/F	192, 193	197	189-190	191		194, 195	196	242-243, 244
CAT	CAT-V	211, 212	217, 218	205, 206-207, 208	209-210		213, 215	216	219
	CAT-V T/F	227	231, 232	224-225	[XXX]-226		228, 229	230	246-247
									248-250
Combimaster	Capto	344, 345	349, 350	338, 339-340, 341	342-343		346, 347	348	351, 352
	Graflex	288	290				289		251-252, 253
	Combimaster			256					254-255
Graflex	Cylindrical Weldon MT	360, 361	362, 363			357-358		364, 365-366	354, 355, 367, 368
Seco Capto™									
Others									
Operating & setting accessories									
Shrinkfit									

Tool holders – Machine side vs Workpiece side

	Shell mill holders	Weldon	NC Drill Chucks	SAXSA adapter	Blanks	Control bars	Seco Capto	Graflex
								
	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)	Page(s)
HSK-A	57, 58-67	68, 69-72	102		104	105	298, 299-300, 301	259, 260
HSK-E								
DIN69871 DIN T/F	115-121	122, 123-124	137	139	140	141	302, 303-304, 305	261, 262
DIN2080							294, 295	263
BT JIS	144-152	153, 154-156	172	174	175	176	306, 307-308, 309	264-265, 266
BT T/F	179-184, 185	186-188					310, 311	267, 268
CAT-V	199, 200-201	202-203, 204					296, 297	269, 270
CAT-V T/F	221-222	223					312, 313-314	271
Capto	323, 324-331	333, 334, 335, 336, 337					315, 316-321, 322	272, 273
Graflex	281, 282-285	286, 287	291					274, 275-280
Combimaster								
Cylindrical Weldon MT								

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Operating & setting accessories

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit


ER HP Collets



Page(s)

389, 390, 391-397


ER collets



Page(s)

399, 400, 401, 402


ER tapping collets with square drive



Page(s)

407, 408-409


ER sealing rings



Page(s)

410, 411


Hydro chucks sleeves



Page(s)

381, 382, 383, 384


PMC Sleeves



Page(s)

385-386


PMC coolant stop screws



Page(s)

387-388


Pull studs



Page(s)

373-380


HSK coolant tubes and sealing plugs (incl. tube fitting keys)



Page(s)

370-371


MQL coolant tubes & screws



Page(s)

371-372

Assembly supports, Tool Boy



Page(s)

412

Easyshrink® Evo



Page(s)

417

Easyshrink® Evo accessories and spare parts



Page(s)

418, 419-420

New codes (after September 2018)



1	2	3	4
Machine side taper type	Workpiece side	Tool fitting size	Gage length

Codes (before September 2018)



1	2	3	4	5
Monobloc holder (EM for Graflex)	Machine side taper type	Workpiece side	Tool fitting size	Gage length

BT40ADB	-	PMC	32	-	090
1		2	3		4

E	3414	5555	22	210
1	2	3	4	5

Guide	Products released for sales before Seco News 2018-2		Products released for sales from Seco News 2018-2	
HSK-A	5555/5556	SM...KL1	Steadyline®, vibration damping shell mill holders	
	5525	SM...L1	Shell mill holders, with through coolant channels	
	552	SM...F3	Shell mill holders, small face	
	5524	SM...F3L1	Shell mill holders, small face with through coolant channels	
HSK-E	569	SMF	Milling cutter holders, flange mounting	
	5656/5657	DM	Disc mill holders	
	584	EM	Side lock holders, Weldon	
	5842	EM...F5	Side lock holders, Weldon short	
DIN	5603/5403	SFD	Shrinkfit holders, DIN type	
	5402	SFD...L1	Shrinkfit holders, DIN type, with peripheral coolant channels	
	5403M, 5403M1	SFD...M, SFD...M1	Shrinkfit holders, MQL type	
	5600	SFR	Shrinkfit holders reinforced	
BT JIS	5801	SFS	Shrinkfit holders, Mold and Die type	
	5672	ERHP	High precision collet chucks	
	5834	HC	Hydraulic chucks	
	–	HCR	Hydraulic chucks reinforced	
CAT	–	HCS	Hydraulic chucks slim	
	–	PMC	Power milling chucks	
	5675	ER	ER collet chucks	
	5450	ER	ER collet chucks, with cylindrical shank	
Combimaster	5085	UDC	Drill chucks	
	5867	TCER	Tapping chucks for synchronized tapping, with micro compensation	
	543	TA	Taper adapters SA	
	5023	BLK	Greenstock blanks	
Graflex	586	CTRB	Control bars	
	K820/K821	M...-K	Steadyline® vibration damping Combimaster holders	
	5820/5821/5822	M	Combimaster holders	
	GL/BA	GL/BA	Steadyline® vibration damping turning/boring bars	
Seco Capto™	401/402/403	G	Graflex® adapters	
	C	C	Seco Capto™ adapters	
Others				
Operating & setting accessories				
Shrinkfit				

ISO attributes


ISO attribute	Explanation	
ADIF1	Additional information 1	Guide
ADIF2	Additional information 2	
ADIF3	Additional information 3	
BD	Body diameter	HSK-A
BD1	Body diameter 1	
BD2	Body diameter 2	
BD3	Body diameter 3	HSK-E
BHTA	Body half taper angle	
BHTA1	Body half taper angle 1	
CBDP	Connection bore depth	DIN
CND	Coolant entry diameter	
CNDP	Coolant entry depth	
CNT	Coolant entry thread size	BT JIS
CRKS	Connection retention knob thread size	
CTMS	Connection text machine side	
CTWS	Connection text workpiece side	CAT
DCB	Connection bore diameter	
DCBN	Connection bore diameter minimum	
DCBX	Connection bore diameter maximum	Combimaster
DCN	Cutting diameter minimum	
DCON	Connection diameter	
DCX	Cutting diameter maximum	Graflex
DF	Flange diameter	
DMM	Shank diameter	
FLGT	Flange thickness	Seco Capto™
KWW	Keyway width	
LB	Body length	
LB1	Body length 1	Others
LB2	Body length 2	
LB3	Body length 3	
LB4	Body length 4	Operating & setting accessories
LCOG	Position of the center of gravity	
LF	Functional length	
LFN	Minimum functional length	Shrinkfit
LFS	Functional length secondary	
LPR	Protruding length	
LSC	Clamping length	
LSCN	Clamping length minimum	
LSCX	Clamping length maximum	
LU	Usable length	
OAL	Overall length	
RFID	Data chip provision	
RL	Radial location (of the balancing screw)	
RPM	Rotational speed	
SRR	Recommended stock removal	
SW	Wrench size	
TDZ	Thread diameter size	
TDZ1	Thread diameter size 1	
TDZ2	Thread diameter size 2	
WF	Functional width	

Our value proposition

Precise machine tools and advanced cutting tools together provide outstanding metal cutting productivity. However, the link between the cutting tool and machine spindle – the tool holder – is crucial in fully achieving that productivity. Each application has different requirements for a tool holding system. No holder can cover all the different applications. Seco Tools offer a wide variety of holding methods featuring a repeatable accuracy, high holding power and an adapted design to provide you an affordable way to fully utilize your cutting materials and machine capability to profitable advantages.

Your main expectations

- Less scraps and rework costs
- Finished product first-pass quality yield
- Maximize machine capabilities and spindle utilization
- Control costs / part
- Time reduction
- Achieve tight tolerances in complex workpiece shapes
- Fast and easy tool preparation



Our value proposition

Your benefits

- | | | |
|---|---|--|
| 1 | – Secured tool gripping | <ul style="list-style-type: none"> – Increased rigidity for superior cutting results including high speed applications – Combine with SECO advanced cutting materials for considerable gains in productivity |
| 2 | <ul style="list-style-type: none"> – Optimal designs – Fine balanced in standard or pre-balanced by Design – Made from Premium steels – Through coolant delivery – Pre-drilled holes for RFID tags | <ul style="list-style-type: none"> – Designed for optimal rigidity and ensure workpiece accessibility – Faster speeds and feeds, without vibrations, delivering better surface finishes – Longer service life |
| 3 | – High quality tool holders with exceptional and repeatable concentricity | <ul style="list-style-type: none"> – Even chip load on the cutting tool edges – Extended tool life – Less vibrations excellent surface finishes |
| 4 | – Precisely ground taper back ends, tolerance class $\leq$ AT3 for SA, HSK according to ISO12164, and Seco Capto™ according to ISO 26623-1-PSC | <ul style="list-style-type: none"> – Perfect fit in the spindle for higher torque transmissibility – Better tool centering – No premature spindle wear |

Shrinkfit				
				
		SFD 5403 / 5603	SFR 5600	SFS 5801
Operations	Finishing milling	■ ■ ■ ■ ■	■ ■ ■ ■ □	■ ■ ■ ■ ■
	Medium milling	■ ■ ■ ■ □	■ ■ ■ ■ ■	■ ■ □ □ □
	Rough milling	■ ■ ■ □ □	■ ■ ■ ■ ■	NA
	High speed milling	■ ■ ■ ■ ■	■ ■ ■ ■ □	■ ■ ■ ■ ■
	Drilling	■ ■ ■ □ □	■ ■ ■ □ □	■ ■ ■ □ □
	Reaming	■ ■ ■ □ □	■ ■ □ □ □	■ ■ □ □ □
	Tapping	NA	NA	NA
Characteristics	Clamping range (mm)	Ø3 – Ø32	Ø6 – Ø32	Ø3– Ø16
	Clamping range (inch)	Ø0.25 – Ø1.25	Ø0.5 – Ø1.25	Ø0.125 – Ø0.312
	Run-out	≤3 µm/.0001"	≤3 µm/.0001"	≤3 µm/.0001"
	Max RPM*	45 000 rpm	45 000 rpm	60 000 rpm
	Transmittable torque	550 Nm/405 ft/lb (Ø32 mm/1.25")	750 Nm/553 ft/lb (Ø32 mm/1.25")	180 Nm/132 ft/lb (Ø16 mm/0.312")
	Tool change	Easyshrink device	Easyshrink device	Easyshrink device
	Axial adjustment	Screw / stop rods	Screw / stop rods	Stop rods
	Max coolant pressure*	100 bar/1450 psi	100 bar/1450 psi	100 bar/1450 psi
	Type of cooling	Central	Central + Peripheral	Central
	Balancing quality	G2.5 - 25 000 rpm or U ≤ 1g.mm	G2.5 - 25 000 rpm or U ≤ 1g.mm	G2.5 - 25 000 rpm or U ≤ 1g.mm
Option	MQL Peripheral cooling Balancing screws	Balancing screws	/	
Recommendations		▪ First choice for semi-finishing and finishing in HSC applications, where quality is required ▪ Slim design ideal for 5 axis machines, deep cavities ▪ High static stiffness but low dynamic stiffness not adapted for HD roughing ▪ First choice for heavy roughing applications (HPM) where Weldon finds its limits in terms of precision, balance and bulky design ▪ Can be used for finishing operations as well ▪ Designed for semi-finishing and finishing in deep cavities, like in M&D, or aerospace components		
Tool shank quality		Needs to be: h5 < Ø 6 mm/0.236" h6 ≥ Ø 6 mm/0.236" Needs to be: h5 < Ø 6 mm/0.236" h6 ≥ Ø 6 mm/0.236" Needs to be: h5 < Ø 6 mm/0.236" h6 ≥ Ø 6 mm/0.236"		

Collet chucks



ERHP 5672



ER 5675

Operations		
	ERHP 5672	ER 5675
Finishing milling	■ ■ ■ ■ ■	■ ■ ■ ■ ■
Medium milling	■ ■ ■ ■ ■	■ ■ ■ ■ ■
Rough milling	■ ■ ■ ■ ■	■ ■ ■ ■ ■
High speed milling	■ ■ ■ ■ ■	■ ■ ■ ■ ■
Drilling	■ ■ ■ ■ ■	■ ■ ■ ■ ■
Reaming	■ ■ ■ ■ ■	■ ■ ■ ■ ■
Tapping	■ ■ ■ ■ ■	■ ■ ■ ■ ■
DIN		
	ERHP 5672	ER 5675
Clamping range (mm)	Ø1 – Ø20	Ø0,5 – Ø26
Clamping range (inch)	Ø0.0625 – Ø0.75	Ø0.0625 – Ø1
Run-out	3 µm/.0001" (3x Ø)	15 µm/.0006" (3x Ø)
Max RPM*	60 000 rpm	20 000 rpm
BT JIS		
	ERHP 5672	ER 5675
Transmittable torque	250 Nm/184 ft/lb (Ø20 mm/0.75") 350 Nm/258 ft/lb with ball bearing nut	100 Nm/73 ft/lb (Ø26 mm/1")
CAT		
	ERHP 5672	ER 5675
Tool change	Spanner & torque spanner	Spanner & torque spanner
Axial adjustment	Screw	Screw
Max coolant pressure*	100 bar/1450 psi	100 bar/1450 psi
Combimaster		
	ERHP 5672	ER 5675
Type of cooling	Central + Through collet	Central
Balancing quality	G2.5 - 25 000 rpm or U ≤ 1g.mm	G6.3 - 15 000 rpm G2.5-25 000 rpm or U ≤ 1g.mm – HSK-A63
Option		
	ERHP 5672	ER 5675
Option	Sealed collets Collets with cooling holes Collets with square	Collet with square Nut for sealing discs Sealing discs
Recommendations		
▪ Ideally for precision HSC applications in finishing and light roughing to generate a good surface quality ▪ Alternative to shrinkfit holders (or cold clamping systems) for small diameters (Ø<20 mm/0.75"), offering a great versatility ▪ Damping effect ▪ Tool breakage friendly (Easy to replace compare to shrinkfit holders)		
▪ Popular system, very versatile (one chuck + several collets to clamp a full range) ▪ 15µm/.0006" (3x Ø) ▪ Ideal for general applications ▪ Perfect for small tool shanks <Ø20 mm/0.75"		
Tool shank quality		
Needs to be: h10 max		

	Power milling chuck	Hydraulic chuck HC	Hydraulic chuck HCR	Hydraulic chuck HCS	
					
	PMC	HC 5834	HCR	HCS	
Operations	Finishing milling	■ ■ ■ □ □	■ ■ ■ ■ ■	■ ■ ■ ■ ■	
	Medium milling	■ ■ ■ ■ □	■ ■ ■ □ □	■ ■ □ □ □	
	Rough milling	■ ■ ■ ■ □	NA	NA	
	High speed milling	■ □ □ □ □	■ ■ ■ ■ □	■ ■ ■ ■ □	
	Drilling	■ ■ ■ □ □	■ ■ ■ □ □	■ ■ ■ □ □	
	Reaming	■ ■ □ □ □	■ ■ ■ ■ ■	■ ■ ■ □ □	
	Tapping	NA	NA	NA	
Characteristics	Clamping range (mm)	Ø6 – Ø32	Ø3 – Ø32	Ø12 – Ø20 – Ø32 in direct Ø3 – Ø32 through sleeves	Ø6 – Ø20
	Clamping range (inch)	Ø0.75 – Ø1.25	Ø0.118 – Ø1.25	Ø0.472 – Ø0.787 – Ø1.25 in direct Ø0.118 – Ø1.25 through sleeves	Ø0.236 – Ø0.787
	Run-out	>10 µm/.0004" (3x Ø)	≤3 µm/.0001'	≤3 µm/.0001"	≤3 µm/.0001'
	Max RPM*	15 000 rpm	40 000 rpm	50 000 rpm (Ø32/1.25" max 25 000 rpm)	40 000 rpm
	Transmittable torque	1500 Nm/1106 ft/lb (Ø32 mm/1.25")	650 Nm/480 ft/lb (Ø32 mm/1.25") (250 Nm for Seco Capto™/Graflex)	900 Nm/664 ft/lb (Ø32 mm/1.25")	231 Nm/170 ft/lb (Ø20 mm/0.787")
	Tool change	Spanner	Locking hex key	Locking hex key	Locking hex key
	Axial adjustment	Screw		Screw	Screw
	Max coolant pressure*	30 bar/435 psi	80 bar/1160 psi (70 bar/1015 psi for Seco Capto™/Graflex)	80 bar/1160 psi	80 bar/1160 psi
	Type of cooling	Central	Central	Central	Central
	Balancing quality	Pre-balanced	G2.5 - 25 000 or U≤1g.mm (except Seco Capto™)	G2.5 - 25 000 or U≤1g.mm	G2.5 - 25 000 or U≤1g.mm
	Option	Stop screws for through coolant Sleeves	Sleeves (sealed or peripheral coolant)	Sleeves (sealed or peripheral coolant)	Sleeves (sealed or peripheral coolant)
	Recommendations	▪ Ideal for heavy duty operations, high chips removal rates ▪ Alternative to shrinkfit or Weldon ▪ Easy to implement ▪ Versatile through use of reduction sleeves	▪ Semi-finishing and finishing operations in High Speed Cutting (HSC) ▪ Not recommended for heavy milling with big radial loads ▪ Simple to use, but needs maintenance ▪ Flexibility thru red. sleeves ▪ Dampening effect	▪ Universal chuck, for heavy roughing applications (HPM) or High Speed Cutting (HSC) in all kind of applications ▪ High rigidity, high torques ▪ Very easy to use ▪ Flexibility thru red. Sleeves ▪ Damping effect	▪ For semi-finishing and finishing applications in deep cavities, like M&D ▪ Very easy to use ▪ Flexibility thru red. Sleeves
	Tool shank quality	Recommended: h6 (max h7)	Needs to be: h6		

Guide			
	Side lock	Tapping chuck	Drill chuck
HSK-A			
	EM 584	TCER 5867	UDC 5085
HSK-E	Operations	Finishing milling	NA
		Medium milling	NA
		Rough milling	NA
		High speed milling	NA
		Drilling	■ ■ ■ □ □
		Reaming	NA
		Tapping	NA
DIN	DIN	Clamping range (mm)	Ø6 – Ø50
		Clamping range (inch)	Ø0.25 – Ø2
		Run-out	≤15 µm/.0006" (3x Ø)
		Max RPM*	15 000 rpm
BT JIS	BT JIS	Transmittable torque	NA (Anti-pulling)
		Tool change	Locking hex key
CAT	CAT	Axial adjustment	NA
		Max coolant pressure*	120 bar/1740 psi
Combimaster	Combimaster	Type of cooling	Central + Peripheral
		Balancing quality	Pre-balanced
Graflex	Graflex	Option	/
		Recommendations	- Very simple and quick tool changeover - Most popular anti-pulling solution - Rigid. Good for heavy roughing - Can be very short - Find its limits in terms of balance (flats) and accuracy, especially at HSC (risk to break expensive HPC tools) - Not versatile - Not tool breakage friendly - Bore sizes 20, 25, 32 mm/0.787, 0.984, 1.260" with Seco Weldon ground face
Seco Capto™	Seco Capto™	Recommendations	- First choice for CNC machine tools and synchronized tapping operations - High volume production / high precision - Better surface quality on the flanks of the cut threads - Longer tap life due to less friction and no tap breakage - Greater process security - Very accurate depth control - Will never wear out - Improved chip evacuation due to slim design
Others	Others	Recommendations	- Recommended for standard drills - For carbide drills we highly recommend (for better run out): - ERHP 5672 - SFD 5403/5603 - HC 5834 - Easy handle
Operating & setting accessories	Operating & setting accessories	Tool shank quality	DIN 1835-1 Form B DIN 6535 Form HB
		Tool shank quality	Needs to be: h9 with square
Shrinkfit	Shrinkfit	Tool shank quality	DIN 1835-1 Form A DIN 6535 Form HA
		Tool shank quality	DIN 1835-1 Form A DIN 6535 Form HA

* Depending on the holder's machine side taper type and size

High precision collet chuck ER HP

Seco's ER HP high-precision collet chucks are engineered for exceptional accuracy and performance in high-speed machining. With a runout of just 3 microns at 3xD, these chucks ensure outstanding tool stability and minimal deflection.

Their advanced clamping mechanism delivers high torque transmission and uniform pressure distribution, making them ideal for modern high-performance cutting tools. Designed with a smooth, balanced profile, they support speeds up to 60,000 RPM, offering reliability and precision for the most demanding applications.



Most important features

1	Made from Premium material for long service life	5	Combination of a high precision nut and a high precision collet mounted onto a high precision chuck, resulting in a repeatable runout $\leq 3 \mu\text{m}$ **
2	Fine balanced in standard at G2,5-25,000 rpm or U $\leq 1 \text{ g. mm}^*$ symmetrical design, ideal for high speed applications	6	Quick tool change, large clamping capacity through HP collets (ER08 to ER32)
3	Strong body design for highest static rigidity	7	Selection of HSK-A63 and HSK-A100 ER HP chucks prepared to receive MQL coolant screws
4	Stable and strong tool gripping thanks to a trapezoidal thread, double guidance and a perfect seat for the collet inside the tapered hole	8	4 threaded holes on a selection of HSK-A and E chucks to fine tuning balancing of the assembly chucks + tool mounted, for better surface finishes and longer tool life

* Seco Capto™: at G6,3-20.000 rpm. Graflex: pre-balanced. When using axial stop screw do not exceed 10.000 rpm

** ER08 size runout is $\leq 5 \mu\text{m}$; straight shanks collet chucks have a runout of $\leq 5 \mu\text{m}$; Graflex runout is $\leq 8 \mu\text{m}$

Different designs to suit all kind of applications



Optimized strong body design for best rigidity, different projections available in standard



Reduced body size and nut design for all applications requesting difficult to access surfaces



Cylindrical extensions with reduced nut to build long assemblies for deep reaches

High precision collets ER HP – 5672

The HP ER collets, based on the external design ISO15488-B, feature a 2 µm direct runout and are identified with a blue ring. Produced from special steel, with only 12 slots, they are more rigid. All collets are with an anti-rust coating. To ensure a good clamping force and best accuracy it is recommended to clamp on nominal diameter tools with shank tolerance h10 max (sealed design even h8 max.).

Collet size	Not sealed	Sealed (60-80 bar max)	Sealed with 4 coolant channels (60-80 bar)
ER HP 08R	 Ø 1-5 mm h10 Ø 0.039-0.196" h10		
ER HP 11R	Ø 1-7 mm h10 Ø 0.039-0.275" h10	Ø 3-6 mm h8 Ø 0.118-0.236" h8	
ER HP 16R ER HP 16	Ø 1-10 mm h10 Ø 0.039-0.394" h10	Ø 3-10 mm h8 Ø 0.118-0.394" h8	Ø 3-8 mm h8 Ø 0.118-0.315" h8
ER HP 20	Ø 1-13 mm h10 Ø 0.039-0.511" h10	Ø 3-12 mm h10 Ø 0.118-0.472" h10	Ø 4-12 mm h8 Ø 0.157-0.472" h8
ER HP 25	Ø 2-16 mm h10 Ø 0.079-0.630" h10	Ø 3-16 mm h8 Ø 0.118-0.630" h8	Ø 4-14 mm h8 Ø 0.157-0.551" h8
ER HP 32	Ø 2-20 mm h10 Ø 0.079-0.787" h10	Ø 3-20 mm h10 Ø 0.118-0.787" h10	Ø 4-20 mm h10 Ø 0.157-0.787" h10

Note: when using tool shanks with flats into sealed collets, make sure the tool flat is located behind the rubber seal i.o. to achieve a good sealing



Without sealing



Sealed for tools with internal coolant supply



Sealed for tools with internal coolant supply and additional coolant channels in order to bring the coolant to the cutting edge in tools without coolant supply

Torque wrenches, fix handles, and roller heads for ER HP collet chucks


If you need to tighten the ER HP nuts several times a day, it is recommended that you use a torque wrench (2). However, if you only clamp the nuts occasionally, a fixed handle (1) is acceptable to clamp and unclamp the nut. Fixed handles have an optimized length design that enables the maximum recommended hand force to be generated.

The roller heads (3) are available from ER08 to ER32.

Torque wrenches should not be used to unclamp nuts (except for ER08). To unclamp the nut, use a fixed handle.

Every torque key is delivered with an ISO6789-1:2017 declaration of conformity and can be repaired or recalibrated.

For torque clamping data and maximum recommended rpm, please see "Clamping Torque, Max RPM, mounting recommendations" pages in this catalog.



ER Standard collet chucks ISO15488

Our standard range of ER collet chucks ISO15488 feature a unique 15 µm/.0006" (3x Ø) runout at 3xD.

All ER standard collet chucks are fine balanced to G6.3-15.000 rpm, G2.5-25 000 – HSK-A63 (except CAT-V and Seco Capto™, see product pages) .

ER collet chucks come also in extended version with a cylindrical shank, tolerance h5. They can be used when a long reach is required to access restricted areas. Maximum run out measures between 15 µm/.0006" to 18 µm/.0007".



Sockets for torque keys for standard ER collet chucks

For standard ER nut tightening and releasing, both spanner types , hook or sockets on torque keys are available as accessories, see accessories Product pages.



Standard collets ER ISO15488

Standard ER collets feature 5 µm direct runout. They offer a high flexibility in clamping, from nominal to -0,5 mm to -1 mm (0.020" to 0.039").

Collet size	Capacity	Clamping range
		
ER 08	$\varnothing$ 1 - 5 mm (steps 0,5 mm) $\varnothing$ 0.039 - 0.197" (steps 0.020")	-0,5 mm -0.020"
ER 11	$\varnothing$ 1 - 7 (steps 0,5 mm) $\varnothing$ 0.039 - 0.275" (steps 0.020")	-0,5 mm -0.020"
ER 16	$\varnothing$ 1 - 2 mm (steps 0,5 mm) $\varnothing$ 0.039 - 0.0787" (steps 0.020") $\varnothing$ 2,5 - 10 mm (steps 0,5 mm) $\varnothing$ 0.098 - 0.394" (steps 0.020")	-0,5 mm -0.020" -1 mm -0.039"
ER 20	$\varnothing$ 1 - 2 mm (steps 0,5 mm) $\varnothing$ 0.039 - 0.0787" (steps 0.020") $\varnothing$ 2,5 - 13 mm (steps 0,5 mm) $\varnothing$ 0.098 - 0.0512" (steps 0.020")	-0,5 mm -0.020" -1 mm -0.039"
ER 25	$\varnothing$ 1 - 2 mm (steps 0,5 mm) $\varnothing$ 0.039 - 0.0787" (steps 0.020") $\varnothing$ 2,5 - 16 mm (steps 0,5 mm) $\varnothing$ 0.098 - 0.630" (steps 0.020")	-0,5 mm -0.020" -1 mm -0.039"
ER 32	$\varnothing$ 2 - 20 mm (steps 0,5 mm) $\varnothing$ 0.079 - 0.787" (steps 0.020")	-1 mm -0.039"
ER 40	$\varnothing$ 3 - 26 mm (steps 0,5 mm) $\varnothing$ 0.118 - 1.023" (steps 0.020")	-1 mm -0.039"

Sealing rings for ER sealing nuts

Sealing can be achieved by applying the concave front face of the stop end screw equipping the ER collet chucks onto the tool shank (for tool shanks without groove). The second method, is to use a selection of sealing rings available in most current diameters with a clamping range of nominal to -0,5 mm (-0.020"), to ensure a good flow when using tools with internal coolant. They are mounted on a specific nut. Can be applied up to 100 bar.

Collet size*	Capacity	Clamping range
		
ER 16	$\varnothing$ 3 - 10 mm (steps 0,5 mm) $\varnothing$ 0.118 - 0.394" (steps 0.020")	-0,5 mm -0.020"
ER 20	$\varnothing$ 3 - 12 mm (steps 0,5 mm) $\varnothing$ 0.118 - 0.472" (steps 0.020")	-0,5 mm -0.020"
ER 25	$\varnothing$ 3 - 16 mm (steps 0,5 mm) $\varnothing$ 0.118 - 0.630" (steps 0.020")	-0,5 mm -0.020"
ER 32	$\varnothing$ 3 - 20 (steps 0,5 mm) $\varnothing$ 0.118 to 0.394" (steps 0.020")	-0,5 mm -0.020"

* ER40 and ER50 on request. ER08 and ER11 not available

Heat shrinkfit holders – SFD 5403/5603, SFD 5402, SFR 5600, SFS 5801

Shrinkfit holders are used extensively in complex 5-axis machining because of their ability to maintain excellent runout characteristics over a long tool length, and because they can be used in tight places. Furthermore, shrinkfit chucks are excellent for transferring high torque, and therefore are well-suited for High Performance Machining (HPM) applications. The balanced design, without mechanical moving parts, make them also the ideal system for high-speed machining.



Most important features

1	Made from Premium heat resistant material (maxi 400°C acceptable temperature), through hardened 56 HRC +/- 2	6	Peripheral coolant channels as standard on HSK-A63/100 SFD DIN type and SFR Reinforced type. MQL1 according to DIN69090-3 in standard. Others on request.
2	Fine balanced is standard at G2.5-25,000 rpm or ≤1 g.mm*	7	Grips the cutting tool 360° around the shank, leading to high gripping torque
3	Strong body design for highest static rigidity. SFD DIN version acc. to DIN69882-8; Type SFR is a reinforced version.	8	Slim design, available in different lengths preventing collision with workpiece. Use of extensions provide many options to machine deep cavities
4	Sealed system by design, ideal when machining materials generating dust	9	Threaded holes for balancing screws is standard**
5	Repeatable runout ≤ 3 µm	10	Axial stop screw delivered along with the holder (not mounted), featuring a central hole for coolant through

* Seco Capto™: G6,3-20.000 rpm

** Except Ø 3 to 5 mm (Ø 0.118" to 0.200"), and some SFR- 5600 version, see product pages

Our standard designs

DIN 4.5° version (5403/5603-SFD)

Based on the DIN69882-8 shape, delivered with a stop screw (except diam. 3 and 5 mm), and 4 balancing threaded holes. Comes in diverse lengths.

HSK version is "ready" for MQL option. Coolant channels through the face is standard for some HSK types (see product pages), others on request.



Reinforced version (5600-SFR)

The dimensions of the OD is one size wider compared to the DIN 4.5° type and features a conical reinforced outside contour resulting in higher rigidity and a higher transmittable torque. Coolant channels through the face delivered as standard. (2 channels up to $\varnothing 20$ mm / $\varnothing 0.787$ ", 3 channels for $\varnothing 25$ mm / $\varnothing 0.984$ " and $\varnothing 32$ mm / $\varnothing 1.260$ ").



Slim Mold & Die version (5801-SFS)

Long and slim design with a conical 5°/3° nose for easy access to difficult to reach surfaces like in Mold & Die applications. Also available as cylindrical extensions.



Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

MQL for shrinkfit holders HSK-A DIN type (SFDMx/5403)

MQL (Minimum Quantity Lubrication) is a "near-dry" coolant solution, consisting in a mix of air and oil. Seco offers in standard a range of HSK-A shrinkit DIN 4,5° holders (5403/ SFD) which can be equipped with specific coolant tubes and stop screws to apply MQL1, i.e. coolant through one channel.

Type SFD 5403M

Shrinkfit holders, according to standard DIN 69090-3, prepared for MQL1. Accessories to be ordered separately.



Type SFD 5403M1

Shrinkfit holders ready for MQL1, delivered with MQL accessories fitted. MQL1 Shrinkfit holders, coolant tubes and stop screws according to standard DIN 69090-3.



Accessories for MQL Shrinkfit holders


MQL 1: coolant tubes

- HSK-A63, MQL1 Shrinkfit holders need a conventional coolant tube 20E9304, as available for DIN type Shrinkfit holders.
- HSK-A100, MQL1 Shrinkfit holders need a specific coolant tube 20E9306M1: the internal diameters are optimized for MQL flow.



MQL1: Stop screws

Stop screws for MQL1 feature a tapered face, for efficient contact with tapered MQL tool shanks, according to standard DIN 69090-3.



Easyshrink EVO

The easyshrink EVO offers fast, ergonomic shrinking and unshrinking for steel, high speed steel (HSS), heavy metal or carbide tools, reducing tool-change downtime. Featuring a heating unit with optimized automatic heating programs, the Easyshrink EVO uses an induction heating element to prevent overheating, minimize energy consumption and keep focused on the clamping area.

Simple, Ergonomic and easy to use.



Most important features

- | | | | |
|---|---|---|---|
| 1 | Different sizes of stop rods to easily adjust the depth of tool | 6 | Shrink and unshrink tool holders with a maximum length of: <ul style="list-style-type: none"> – 480 mm (18.898") with HSK-32 finned support – 430 mm (16.929") with SA50 finned support – 490 mm (19.291") with other finned support |
| 2 | Set of heat focusing stoppers enabling shrinking of Carbide and HSS tool shanks Ø3 to 32 mm (0.118 to 1.260"). Split version available for large tools | 7 | Inductor: fast and optimized shrink and unshrink cycles for steel, HSS, heavy metal or carbide tools with Seco Tools holders |
| 3 | Small computer allowing a smart web interface through WIFI or ethernet (RJ45) connection <ul style="list-style-type: none"> – TDM Systems compatible – Special program easily programmable – Global view of the System status | 8 | Water cooler unit including 2 cooling bells and a water tank (optional, sold separately) |
| 4 | Simple control panel with led indicator: <ul style="list-style-type: none"> – 3 Standards programs for all Seco Tools Holders – 1 programmable mode for other tool holders (specific shape or competitors) – 1 manual mode | 9 | All new holders (>SN2020.1) are marked with a program code, helping operator to easily select the adapted heating mode of the device, preventing overheating and thus ensuring a long service life |
| 5 | Rotary plate with shrink depth setting <ul style="list-style-type: none"> – Prevents the user to have any contact with hot holders and allow to switch from the heating position to a cooling position – Adjustment for setting the depth of the cutting tool in your holder by moving the stop rod up & down – Standard integrated air fan cooler | | |

Easyshrink EVO Features

Power	Capacity	Max. tool length	Max. machine interface	Dimensions (WxDxH)	Weight	Cooling time	Connections
16 Kw	Ø3-32 mm Ø0.118-1.260"	430 to 490 mm 16.929 to 19.291"	HSK-A125	317x943x820 mm 12.480x37.126x32.283"	50 kg 115 lb	±7 min	The device accepts following voltage : AC 3 x 400V (+/-10%) + PEN/25A/50-60Hz AC 3 x 400V (+/-10%) + N + PE/25A/50-60Hz For other voltages, a specific device is available on demand.

DELIVERY CONTENT: 5 standard heat focusing stoppers for Ø3 to Ø32, 8 stop rods, 2 cooling bells, 1 pair of gloves, 1 operating instructions

Accessories

Finned support

Provides positioning of the tool holder onto the support module.
Finned supports for each type of machine side taper used on Shrinkfit tool holders.
Available for all types of tool holders



Contact bushing

Contact bushing for each type and size of Shrinkfit tool holder used.
Available for all types of Shrinkfit holders and diameters.
Required to extract heat from the front end of the holder towards the liquid cooling bell.



Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Spare parts

Stops rods

Set of standard and thin stop rods.

Enables the tool shrinking depth setting and ejection of broken tools.

4 stop rods with 2.5 mm (0.098") front end & 4 stop rods with 5 mm (0.197") front end covering a shrink depth capacity 0 to 240 mm (0 to 9.449") : 0-60 (0 to 2.362") / 60-120 (2.362"-4.724") / 120-180 (4.724-7.087") / 180-240 mm (7.087-9.449")



Air cooling cone

Directs the air stream against the front end of the holder for cooling.



Heat focusing stopper

Magnetic insulator that allows the magnetic field to be concentrated on the front part of the tool holder and to achieve optimised heating.

Available for shrinking and unshrinking tool holders Ø3 to Ø32 mm (Ø0.118" to Ø1.26").



Split heat focusing stopper

Split magnetic insulator that allows the magnetic field to be concentrated on the front part of the tool holder and to achieve optimised heating of tools with a front end that is larger than shank.



Water cooler Features

Cooling time	Extension table	Dimensions of refrigeration unit (WxDxH)	Weight
±1min	Storage of 5 contact bushings & 1 cooling bell	314x650x285 mm 12.362x25.590x11.220"	35 kg 77 lb

DELIVERY CONTENT: 1 refrigeration unit, tubes support, 2 bells, 1 extension table.

For the use on a 60hz electricity grid, a specific water cooler is required and available on demand.



Hydraulic expansion chucks – HC (former 5834), HCR and HCS

Hydraulic chucks, that use oil pressure to compress an internal membrane within the holder body, feature repeatable low runout, quick and easy tool change, and are effective for reaming, drilling, threading and light milling with end mills at high spindle speeds. The HCR Power version can perform High Machining Performance thanks to a high radial rigidity, as well as High-Speed Machining.

Most important features

- 1 Fine balanced in standard at G2,5-25,000 rpm or ≤ 1 g.mm
(Seco Capto™: G6,3-20.000 rpm)
- 2 HC version with body shape according to DIN69882-7
- 3 Made from Premium material, high mechanical strength and good resistance to thermal shocks
- 4 Very easy to use, just turn one screw until stop. Not additional equipment needed
- 5 Good gripping forces (shank tolerance h6 maximum), especially Power version offering high clamping forces
- 6 Repeatable runout $\leq 3 \mu\text{m}$
HC Straight shanks: runout $\leq 6 \mu\text{m}$
- 7 Helical groove to ensure oil-free or debris-free tool shank surface
- 8 Oil reservoir acts as a damping agent
- 9 Axial stop screw for tool length adjustment



Our standard designs

HC Conventional version

The HC conventional hydro-chucks are an easy and efficient solution for high precision works like for drilling, reaming, threading, and light milling in all kind of components. Can be used along with slotted reduction sleeves offering a great flexibility.

Very easy tool changes, reducing set-up times, without need of peripheral equipment's.



HCR Reinforced version

The HCR reinforced version is a universal solution for round tools, dedicated for all kind of machining applications from high performance machining (HPM) to high-speed cutting (HSC)

Its short and compact design offers a high radial rigidity, and high gripping forces (up to 900 Nm for diam 32 !)

Fine balanced, it is suitable for high-speed applications up to 50.000 rpm (diam. 12 and 20 mm).

The range features a direct clamping for diam. 12, 20 and 32, but various other diameters can be clamped through slotted reduction sleeves. All kind of tool shank types can be clamped even in direct mount.



HCS Slim 3° version

The HCS Slim 3° designs are ideal for excellent workpiece accessibility, machining of narrow and deep areas in light milling and drilling operations.

This range is completed with cylindrical extensions enabling to build long and slim assemblies once mounted into the HCR Power chucks for example.



Reduction sleeves for hydraulic chucks

Slotted reduction sleeves from diam. 12, 20 and 32 mm allow the clamping of several different tool shank sizes with just one toolholder, offering a great flexibility and reducing inventory costs.

They are available in two versions:

- coolant-proof for tools with coolant facilities,
- with peripheral coolant channels for tools without internal cooling holes.

Both versions are equipped with a length pre-adjustment ring.

Runout and transmissible torque will remain unchanged.

All kind of tool shank types can be mounted into the sleeves



Sealed reduction sleeves
05FHC for tools with coolant
holes



Reduction sleeves 05FHC...
L1 with peripheral coolant
channels for tools without
coolant holes

Acceptable tool shanks

Designs		Cylindrical Form A	Weldon 1 flat Form B	Weldon 2 flats Form B	Whistle Notch Form E
					
Direct clamping	HC (Conventional)	Ø 6 - 32 mm Ø 0.236 - 1.260"	Ø 6 - 20 mm Ø 0.236 - 0.787"	Ø 25 - 32 mm Ø 1 - 1.260"	Ø 6 - 32 mm Ø 0.236 - 1.260"
	HCR (Reinforced)	Ø 6 - 32 mm Ø 0.236 - 1.260"	Ø 6 - 20 mm Ø 0.236 - 0.787"	Ø 25 - 32 mm Ø 1 - 1.260"	Ø 6 - 32 mm Ø 0.236 - 1.260"
	HC (Capto/Graflex)	Ø 6 - 32 mm Ø 0.236 - 1.260"	Ø 6 - 20 mm Ø 0.236 - 0.787"	cannot be clamped in direct	cannot be clamped in direct
	HCS (Slim)	Ø 6 - 32 mm Ø 0.236 - 1.260"	Ø 6 - 20 mm Ø 0.236 - 0.787"	cannot be clamped in direct	cannot be clamped in direct
Through reduction sleeves	HC (Conventional)	Ø 3 - 25 mm Ø 0.118 - 1"	Ø 6 - 20 mm Ø 0.236 - 0.787"	Ø 25 mm Ø 1"	Ø 6 - 25 mm Ø 0.236 - 1"
	HCR (Reinforced)	Ø 3 - 25 mm Ø 0.118 - 1"	Ø 6 - 20 mm Ø 0.236 - 0.787"	Ø 25 mm Ø 1"	Ø 6 - 25 mm Ø 0.236 - 1"
	HCS (Slim)	Ø 3 - 25 mm Ø 0.118 - 1"	Ø 6 - 20 mm Ø 0.236 - 0.787"	Ø 25 mm Ø 1"	Ø 6 - 25 mm Ø 0.236 - 1"

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Power Milling Chucks (PMC)

Mechanical milling chucks provide strong gripping force and high radial rigidity via multiple rows of needle bearings. The design enables heavy milling and quick tool changes as an alternative to shrink fit holders. When using reduction sleeves, a larger clamping capacity can be covered with just one holder, reducing shop's inventory. Optional coolant-stop screws enable Power Milling Chucks to engage through-tool coolant.



Most important features

- | | | | |
|---|--|---|---|
| 1 | Pre-balanced by design, maxi 15,000 Rpm for Ø20 mm (0.787") and 10,000 Rpm for Ø32 mm (1.260") | 4 | High gripping forces enabling torques transmissions up to 640 Nm (472 ft/lbf) minimum for Ø20 mm (Ø 0.787") and 1500 Nm (1106 ft/lbf) minimum for Ø32 mm (Ø 1.260") Shank tolerance maxi h6 |
| 2 | Strong body shape, high rigidity | 5 | Needle bearing design for better clamping power |
| 3 | Runout: 10 to 15 µm at 3 x D | 6 | Axial stop screw for tool length adjustment (not for HSK and Seco Capto™). Stop screw for coolant in option |

Reduction sleeves for PMC

Reduction sleeves allow a great clamping versatility: with only one chuck and several sleeves you can cover a large range of clamping capacity and reduce your tool inventory.

Care: PMC reduction sleeves are only intended for PMC holders (all other sleeves not compatible).



Through coolant capabilities and accessories

For tools without coolant channels

- Direct chuck clamping: coolant flows through grooves in chucks' bore, along the tool
- Clamping through reduction sleeve: coolant flows through sleeve slots along the tool
- Chucks delivered with stop end screw: to ensure the best coolant flow, rotate the screw backwards or remove it completely.



For tools with coolant channels

For reliable coolant flow, use a "stop screws for through coolant", available as accessories. Select the suitable screw according to chuck size, or reduction sleeve thanks to the chart shown in the product pages.



Acceptable tool shanks

Shank types	Cylindrical DIN1835-1A DIN6535 HA	Weldon DIN1835-1 B DIN6535 HB	Weldon DIN1835-1 B DIN6535 HB	Whistle & Notch
				
Direct clamping	Ø 20 - 32 mm Ø 0.750 - 1.260"	Ø 20 mm Ø 0.787"	Do not clamp Ø 32 mm / Ø 1.260"	Do not clamp
Clamping with reduction sleeves	Ø 6 - 25 mm Ø 0.236 - 0.984"	Ø 6 - 20 mm Ø 0.236 - 0.787"	Ø 25 mm Ø 10.984"	Ø 6 - 25 mm Ø 0.236 - 10.984"

Tapping chucks with micro-compensation, for synchronized tapping TCER5867

Improves tapping performances during synchronized tapping. The built-in axial micro flexure (+/- 0,5 mm) prevents stress on taps, which may appear from micro-deviation of the synchronism between the spindle rotation, feed and tap pitch. That micro-compensation mechanism offers longer tap life, protects taps against breakage, increases productivity and improves thread quality.



Most important features

- | | | | |
|---|---|---|---|
| 1 | Internal coolant through, or through sealing discs in specific nuts up to 80 bar /1160 psi | 3 | Built-in patented axial micro flexure (+/- 0,5mm) preventing from tap stress |
| 2 | Using standard ER Collets with square drives, ER11 (M2-M5), ER20 (M4-M12, ER25 (M8-M20), ER40 (M16-M30), ER50 (M20-M48) | 4 | Strong body shape, Available as straight shanks with Weldon flats, HSK, DIN, BT and Seco Capto™ high rigidity |

ER Collets with inner square

The specific ER collets feature an internal driving square at the back to fit the tap's square in order to prevent it from rotating in the collet.

Dedicated clamping size on the nominal diameter.

Collet size	Capacity	Clamping range	Collet size*	Capacity with sealing rings	Clamping range
					
ER 11	Ø 2,5 to 6 mm Ø 0.098 to 0.236"	0	ER 16	Ø 3 to 10 mm (steps 0,5 mm) Ø 0.118 to 0.394" (steps 0.020")	-0,5 mm -0.020"
ER 20	Ø 4 to 12 mm Ø 0.157 to 0.472"	0	ER 20	Ø 3 to 12 mm (steps 0,5 mm) Ø 0.118 to 0.472" (steps 0.020")	-0,5 mm -0.020"
ER 25	Ø 4 to 16 mm Ø 0.0157 to 0.629"	0	ER 25	Ø 3 to 16 mm (steps 0,5 mm) Ø 0.118 to 0.630" (steps 0.020")	-0,5 mm -0.020"
ER 40	Ø 12 to 22 mm Ø 0.472 to 0.866"	0	ER 32	Ø 3-20 (steps 0,5 mm) Ø 0.118 to 0.394" (steps 0.020")	-0,5 mm -0.020"
ER 50	Ø 22 to 36 mm Ø 0.866 to 1.417"	0	* ER40 and ER50 on request. ER08 and ER11 not available Note: ER50 collet comes without square (included in the chuck)		


Combimaster – 5820/5821/5822/K820/K821

Combimaster is a modular milling cutter system with a wide range of shank types, lengths, and interchangeable cutter heads.

With square shoulder and end mills, copy mills, face mills, plunge mills and disc mills included, the system offers maximum flexibility over a wide range of applications. All Combimaster heads and shanks have coolant holes and many of the cutter heads are available in different pitch versions. The range includes the Steadyline vibration damping holders that automatically counteracts and eliminates tool vibration, and an ER collet system for face, disc and side milling operations.

Most important features

- | | |
|--|--|
| <p>1 A variety of extensions and reducers allow to build the optimal suited tool for best workpiece accessibility.
Includes cylindrical extensions in steel, heavy metal and carbide allowing applications up to 10xD</p> | <p>4 "Screw-in" connection system in different pitches from M6 to M20. Very rigid and precise. Suitable for HSM</p> |
| <p>2 Optimized designs to improve stability. Exist in conical shape for highest rigidity (5820) or straight forms (5821) for best accessibility, all fine balanced G6,3-20.000</p> | <p>5 All adapters have coolant through facility</p> |
| <p>3 Steadyline antivibration version for optimum workpiece access, conical shape for highest rigidity (K820) or straight shape for best accessibility (K821) available in several lengths</p> | |



Combimaster to shrinkfit DIN holders

A range of DIN 4,5° shrinkfit adapters with M16 Combimaster connection size allow to use round tools like solid end mills with shanks diameter 6, 8, 10 and 12 mm ($\varnothing$ 0.236", 0.315", 0.394" and 0.472")

Note: when mounted on Steadyline version fine tuning of assembly is recommended-please request.



Milling cutters holders

Seco Tools offers a broad range of shell mill holders based on spigot and tenon drive features according to ISO 3937 or DIN6357. Providing excellent results in rough to fine milling applications, this portfolio includes options for most machine side connections, as well as most workpiece side diameters.



Type	Features	Designs
Type SM...L1 (5525) Holder for tenon driven milling cutters, enlarged bearing face with coolant channels	– Spigot and tenon drive acc. to ISO 3937, with enlarged (>ISO) bearing face for optimized rigidity – Multiple coolant channels through the spigot's face – Diam. 40 mm (1.575") with 4 threaded holes acc. to DIN6357 – Available in standard in Steadyline antivibration version – In case the cutter has no through coolant, use cross head center bolt with coolant channels, available in option – G6.3-20.000 rpm balancing (except CAT, HSK-A125 and Graflex)	
Type SM...F3L1 (5524) Holder for tenon driven milling cutters and disc mills type B, small bearing face with coolant channels	– Spigot and tenon drive acc. to ISO 3937, small bearing face – Suitable for disc mill cutters type B – Multiple coolant channels through the spigot's face – In case the cutter has no through coolant, use cross head center bolt with coolant channels, option available – G6.3-20.000 rpm balancing (except CAT, HSK-A125 and Graflex)	
Type SMF (569) Holder for tenon driven milling cutters, large bearing face	– Spigot and large tenon drive as well as enlarged bearing face acc. to DIN6357/DIN2079 with 4 screws to secure clamping when heavy roughing applications with high torque transmissions – Coolant through the spigot, one central channel – G6.3-20.000 rpm balancing (except CAT, HSK-A125 and Graflex)	
Type DM (5656/5657) Disc mill holder piston type, for disc mills type A	– The disc mill is held by an adjustable sliding shaft arbor equipped with a driving key. The arbor and disc mill are locked using a pulling screw. – Slim workpiece side clamping flange for optimized accessibility – Prebalanced by design	

Steadyline Milling cutter holders

As the use of long overhang tools becomes increasingly popular throughout the manufacturing industry, Seco offers a patented line of Steadyline® damping tools including shell mill holders and Combimaster holders covering a broad range of milling applications from Ø20 (Ø0.787") to over Ø160 mm (Ø6.299").

The highly rigid and stable Steadyline® system effectively reduces unwanted vibrations in extreme cutting conditions via a "dynamic passive system" inside the holder body where a damping mass counter vibrates against the first flex vibration.

As such, these products can perform typical long overhang operations twice as fast as traditional tools, reduce spindle stress as well as offer high metal-removal rates, smooth part surface finishes and long tool life.

Inside view of a Steadyline Combimaster screw in system equipped with a R217.96-1640.RE-08-3A Square 6 shoulder and slot milling cutter

Inside view of Steadyline Shell mill holder equipped with a R220.69-0040-10-6A Turbo Mill cutter for challenging face milling applications



Machined with Steadyline



Machined with conventional holder, equivalent dimension



Designs

Steadyline Shell mill holder

Steadyline Combimaster

– **Conical-reinforced shape** maximizes the rigidity of the holder, to achieve high static and up to three times greater dynamic rigidity than equivalent solid holders

SM-KM-L1 ("5556 ") conical-reinforced shape



– Spigot sizes from Ø16 to 40 mm (Ø0.630 to 1.575")
– Enlarged bearing face
– Multiple coolant channels through the spigot's face
– Available in different projections up to 350 mm (Ø13.780")

M...K (K820) conical reinforced shape



– Connection sizes from M12 to M20
– Rigid and accurate Screw-in system, enabling to mount a large panel of replaceable milling heads for all kind of applications
– Available in different projections

– When the accessibility to the machining area does not allow conical holders, the **cylindrical shape** provides an excellent compromise between strong rigidity and accessibility. This enables machining over 5xD overhang with cutting speeds similar to short assemblies, increasing depth of cut by up to 3 times compared to classic long holders

SM-K-L1 ("5555") cylindrical shape



M...K (K821) cylindrical shape



Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Interested in finding out how to overcome tool overhang challenges?

Then we have an great overview of our Steadyline® products, which include cost-effective milling holders as well as turning and boring bars, perform typical long overhang operations twice as fast as traditional tools. Plus, these highly productive vibration-damping solutions offer high metal-removal rates, smooth part surface finishes and long tool life – all while reducing machine tool stress.

You will find out how the very accurate and rigid GL Connection will enable you to exchange in record times the front heads or just get expertise on how to achieve stable conditions with our solutions.

Visit secotools.com for all the latest information, machining data, manufacturing techniques and other developments on Steadyline® products or access our comprehensive Steadyline® brochure directly thru the QR code.



Graflex Modular system

Graflex assemblies include arbors, intermediates, tool holders and boring heads that can be rapidly built together when they are needed.

Suitable for milling, drilling, tapping, reaming and boring, Graflex modules offer tooling of variable lengths and diameters and can be fitted on all types of machines simply by substituting the Graflex basic arbor.

Excellent connection rigidity and precision enables Graflex assemblies to be used in similar machining conditions as the same sized Monobloc holders. The wide range of modules permits tooling dimensions closest to the required machining operation for optimized cutting conditions.



Most important features

- | | |
|--|---|
| <p>1 The tenon secures the assembly. For operations involving interrupted cuts , the blocking screw on the tenon can be tightened to avoid micro rotational movements</p> | <p>3 Two ball screws, with fine pitched thread , turn radial pressure into axial locking pressure that forces the two faces together. The self-locking features amplifies the interfacial pressure: the harder the cutting forces, the tighter the connection becomes and the higher the rigidity of the assembly
Radial access to the ball screw makes it very easy to handle, even directly on the machine</p> |
| <p>2 Great flexibility: assemblies of variable lengths and diameters can rapidly be built together, when they are needed. Graflex® modules e.g. tool holders and boring heads, as well as cutting tools can be fitted on all types of machines, by the substitution of only the basic Graflex® arbors, available in variety of machine side connections (HSK-A, HSK-E, DIN, BT, CAT, Seco Capto™ ...).</p> <p>The Graflex® modules are suitable for milling, drilling, tapping, reaming and boring.</p> | <p>4 The long spigot and face connection, combined with tight manufacturing tolerances, offer a strong and very accurate clamping of the assemblies.</p> |

WARNING:

Using holders without a coolant tube or a plug fitted, when required by machine tool builder, could cause unseen machine spindle damages.



HSK-A and HSK-E coolant tubes and sealing plugs

- | | | | |
|---|--|---|---|
| 1 | Sealing plugs are recommended to protect the spindle | 3 | Key need to be ordered separately (see product pages) |
| 2 | Coolant tubes are screwed into the backend of the HSK-A and HSK-E holders (HSK-C and F not required) to allow the distribution of the coolant from spindle to tool and protect the spindle and have a $\pm 1^\circ$ of angular motion. This degree of freedom is provided to compensate for any misalignment during HSK clamping process | | |

Pull studs (retention knobs)

The pull stud is the component on which the machine drawbar grabs to pull back the tapered back end of the holder into the spindle.

Mainly designed according to international standards (DIN, BT-JIS ANSI, ISO...), it can also exist in different specific designs (on request). It is important to select the appropriate pull stud to avoid damages to the spindle



Assembly supports, Tool Boy

Provides a safe and efficient tool preparation facility. Can be easily fixed on a workbench. The head can be oriented in 4 indexed positions (horizontal and vertical). Different locking systems designs, depending on the holder's tapers designs (see product pages).

Tool boy is composed by a base unit and an interchangeable head but delivered as a complete unit.



Seco Tools Tooling Systems can offer you all kind of special made rotating tool holders, fine and roughing boring bars as well as Steadyline holders for turning, boring and milling.

With our long experience, over 60 years in the industry, we have the expertise to design and manufacture your custom-made tools with the highest quality and best performance guarantees.

A team of global product specialists can support you to develop the best adapted solutions for your specific needs. Our design team will provide you with an approval drawing before manufacturing.

And finally, a dedicated workshop, only for custom-made orders, located in France, will produce your solutions within promised lead times.

We have already supplied a large number of winning solutions in the past to customers active in all main industry segments (Aerospace, Automotive, Power generation, General engineering, ...) which helped them to stay competitive, cost-effective, and deliver in time their finished components.

Please contact your Seco representative.



Balancing qualities

At high spindle speeds (rpm) raises a number of dynamic forces which generate vibrations, shortening tool life, lowers quality of the machined surface, and creates machine wear. Not all holders are dedicated to run at higher rotations, depending also from the back-end types and sizes, it's why at Seco Tooling Systems, we apply a specific balancing strategy based on the commonly accepted industry standard (ISO1940) which express the balancing quality with G grades.

You will find through the product pages (under column "balancing") and through this guide pages, indications about the balancing quality for each of our holders:

- not balanced at all
- PB: pre-balanced holders by design
- G6.3-20.000 rpm
- G2.5-25.000 rpm or $U \leq 1$ g.mm for all holders dedicated for High Speed Cutting applications

On request, and if feasible, we can fine balance all holders to G2.5.



Holes for RFID carrier

Product pages contain a column 'RFID hole', mentioning if a hole for RFID carrier is available on the tool holders:

RFID hole = 1: the tool holder feature a hole for RFID carrier, according to respective machine side norms.

RFID carriers can be fitted on request, please enquire.

RFID hole = 0: RFID carrier hole not available. Holes for RFID carriers can be machined and RFID carriers fitted on request, please enquire.

Clamping torques, fixed handles, torque keys and roller heads for ER HP Collet chucks

- For nut tightening use either the fixed handle or a torque key. For releasing the nut use only fixed handles (except for size ER08 where a torque key can be used to release the nut)
- To ensure best low runout, clamp only cylindrical tool shanks DIN 1835-1 Form A/DIN 6535 Form HA, shank tolerance maxi h10, clamped on nominal diameter
- The maximum indicated rpm will depend on taper back-end type and size
- See Accessories Product pages for more details

Collet size	Nut OD	Capacity DCBN-DCBX	Recommended clamping torque	Fixed handle ref.	Torque key ref.	Roller head ref.	Max recommended RPM
ER HP 08R	10	1,0-5,0 mm 0.039-0.197"	8 Nm 5.900 ft lb		03DYE003025	03ERB010	60.000
ER HP 11R	16	1,0-2,5 mm 0.039-0.098"	10 Nm 7.376 ft lb	03LME0912140	03DYE003025	03ER016	60.000
		3,0-7,0 mm 0.118-0.275"	20 Nm 14.75 ft lb				
ER HP 16R	22	1,0-4,5 mm 0.039-0.138"	20 Nm 14.75 ft lb	03LME0912140	03DYE010050	03ER022	60.000
		5,0-10,0 mm 0.196-0.394"	30 Nm 22.13 ft lb				
ER HP 16	30	1,0-4,5 mm 0.039-0.138"	30 Nm 22.13 ft lb	03LME1418260	03DYE10100B	03ER030B	42.000
		5,0-10,0 mm 0.196-0.394"	80 Nm 59.00 ft lb				
ER HP 20	32	1,0-5,5 mm 0.039-0.217"	40 Nm 29.50 ft lb	03LME1418260	03DYE10100B	03ER032B	30.000
		6,0-13 mm 0.236-0.512"	80 Nm 59.00 ft lb				
ER HP 25	40	1,0-5,5 mm 0.039-0.217"	40 Nm 29.50 ft lb	03LME1418260	03DYE10100B	03ER040	25.000
		6,0-13 mm 0.236-0.512"	90 Nm 73.00 ft lb				
ER HP 32	50	2,0-5,5 mm 0.078-0.217"	40 Nm 29.50 ft lb	03LME1418370	03DYE040200	03ER050	25.000
		6,0-15,5 mm 0.236-0.590"	120 Nm 88.50 ft lb				
		16,0-19,5 mm 0.629-0.768"	140 Nm 103.26 ft lb				
		20,0 mm 0.787"	180 Nm 132.76 ft lb				

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Clamping torques, torque keys, and sockets for standard ER Collet chucks

For standard ER nut tightening and releasing, both spanner types , hook or sockets on torque keys are available as accessories, see Product pages and accessories Product pages

Collet size	Nut OD	Capacity DCBN-DCBX	Recommended tightening torque	Torque key		Socket type
				Torque key ref.	Torque capacity	
ER 16	27	0,5-10 mm 0.020-0.394"	56 Nm max 41.2 ft lb max	03DYE10100B	10-100 Nm	03EF1425S
ER20	30	0,5-13 mm 0.020-0.512"	80 Nm max 59 ft lb max	03DYE10100B	10-100 Nm	03EF1430S
ER25	22	1,0-16 mm 0.039-0.630"	104 Nm max 76.7 ft lb max	03DYE040200	40-200 Nm	03EF1425E
ER32	50	2,0-20mm 0.079-0.787"	136 Nm max 100.3 ft lb max	03DYE040200	40-200 Nm	03EF1432E
ER40	32	2,0-26 mm 0.079-0.118"	176 Nm max 129.81 ft lb max	03DYE040200	40-200 Nm	03EF1440E

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

ER Collet chucks, cylindrical extensions (ER-5450)

Collet size	Capacity DCBN-DCBX	Recommended tightening torque*, max
ER 08R	$\varnothing$ 0,5 - 5 mm $\varnothing$ 0.020 - 0.197"	6 Nm max 4.42 ft lb max
ER 11R	$\varnothing$ 0,5 - 7 mm $\varnothing$ 0.020 - 0.276"	16 Nm max 11.80 ft lb max
ER 16R	$\varnothing$ 5,0 - 10 mm $\varnothing$ 0.020 - 0.394"	24 Nm max 17.70 ft lb max
ER 20R	$\varnothing$ 5,0 - 13 mm $\varnothing$ 0.020 - 0.512"	28 Nm max 20.65 ft lb max
ER 25R	$\varnothing$ 1,0 - 16 mm $\varnothing$ 0.039 - 0.630"	32 Nm max 23.60 ft lb max

* For nut tightening and releasing, both key types hook and roller (torque spanner and classic spanner) are available as Accessories, see Product Pages

Note: To ensure lowest runout, clamp only cylindrical tool shanks DIN 1835-1 Form A/ DIN 6535 Form HA, shank tol. maxi h10, clamped on nominal diameter. Runout can vary when using axial stop screw.

Mounting advice

Collet

- Insert collet into the nut aligned with the mark. Push collet by applying pressure (A) until hearing a « click ».
- Fit the tool and screw the nut onto the tool holder.
- To release the collet, unscrew the nut from the tool holder, apply radial pressure (B).
- Never lock the nut without a tool in place.



Sealing ring

- Insert sealing ring into the nut from the back, until it "clicks" into the nut's front face. The sealing ring's marked face should be oriented inside the nut to avoid erosion of the diameter information marking.
- Release by pressure onto the sealing ring's front face



Shrinkfit holders

Recommended Max RPM**

Clamping $\varnothing$	Type DIN (SFD-/SFD...L1-5603/5403)/5402)*	Type reinforced (SFR-5600)	Type Slim M&D (SFS-5801)
3 mm 0.118"	45.000	–	60.000
4 mm 0.157"	45.000	–	60.000
5 mm 0.196"	45.000	–	60.000
6 mm 0.236"	45.000	45.000	40.000
8 mm 0.315"	45.000	45.000	40.000
10 mm 0.394"	40.000	40.000	40.000
12 mm 0.472"	40.000	40.000	40.000
14 mm 0.551"	38.000	–	40.000
16 mm 0.630"	38.000	38.000	40.000
18 mm 0.708"	35.000	–	–
20 mm 0.787"	35.000	35.000	–
25 mm 0.984"	32.000	30.000	–
32 mm 1.260"	30.000	25.000	–

* Tool shanks

– Type: Cylindrical DIN 1835-1 Form A/ DIN 6535 Form HA

– Tolerances: $\varnothing$ 3 to 5 mm ($\varnothing$ 0.118" to 0.197") maximum h5, tool shank must be carbide or heavy metal (e.g. Densimet). $\varnothing$ 6 to 32 mm ($\varnothing$ 0.236" to 1.260") maximum h6, tool shank can be steel, HSS, carbide or heavy metal. Using h5 for $\varnothing$ 6 to 32 mm ($\varnothing$ 0.236" to 1.260") provides a safer minimum clamping torque. Make sure the minimum shrinking depth LSC shown in the Product pages for each holder is followed when fitting the tool shank into the holder.


** For Shrink fit holders equipped with MQL1: maxi 16.000 rpm.

***Heat resistance: maximum acceptable temperature: 400°C

Kit of balancing screws for Shrinkfit holders (all except Slim types)

These kits contain screws of different sizes, to be mounted into the balancing threaded holes of all shrinkfit holders except the slim version. The screws will allow to fine tune the balancing quality of the assemblies holder+tool on a suitable balancing machine. The screws must be inserted until stop in the threaded holes with a torque of 1 Nm (0.736 ft lb).





Hydraulic chucks are not Shrinkfit chucks: don't heat them!

Hydraulic expansion chucks (HC-5834)

Clamping Ø	Max rpm (min ⁻¹)					Minimum clamping depth
	Standard design HC		Reinforced design HCR	Slim design 3° HCS		
	HSK-A, DIN, BT, BT T/F, CAT	Seco Capto™, Graflex, CAT T/F	All	All	Standard HC and Reinforced HCR in HSK-A, DIN, BT, BT T/F, CAT, Seco Capto™, Graflex	
6 mm 0.236"	50.000	40.000		40.000	27 mm 1.063"	27 mm 1.063"
8 mm 0.315"	50.000	40.000		40.000	27 mm 1.063"	27 mm 1.063"
10 mm 0.394"	50.000	40.000		40.000	31 mm 1.220"	32 mm 1.260"
12 mm 0.472"	50.000	40.000	50.000	40.000	36 mm 1.417"	37 mm 1.457"
14 mm 0.551"	50.000	40.000		40.000	36 mm 1.417"	37 mm 1.457"
16 mm 0.630"	50.000	40.000		40.000	39 mm 1.535"	42 mm 1.654"
20 mm 0.787"	50.000	40.000	50.000	40.000	41 mm 1.614"	42 mm 1.654"
25 mm 0.984"	25.000	25.000		25.000	47 mm 1.850"	48 mm 1.890"
32 mm 1.260"	25.000	25.000	25.000	25.000	51 mm 2.000"	55 mm 2.165"

– Operating temperature: 20-50°C

– Max. coolant pressure: 80 bar/1160 psi, Seco Capto™ and Graflex: 70 bar/1015 psi

– Adjustment range of the length: 10 mm. Tool must be inserted at recommended minimum clamping length (see chart)

– Tool shank quality: h6 or better

– Adapt your parameters in case of long tools, heavy tools, and when using extensions

– HC Straight shanks limited to maxi 10.000 rpm

Tapping chucks with micro-compensation (TCER-5867)

Tapping chuck size	Recommended tightening torque
ER 11	30 Nm 22.13 ft lb
ER 20	100 Nm 73.76 ft lb
ER 25	130 Nm 95.88 ft lb
ER 40	220 Nm 163.26 ft lb
ER 50	260 Nm 191.77 ft lb

– For nut tightening and releasing, both spanner types: hook and roller (torque spanner and classic spanner) are available as Accessories, see Product Pages and detailed description of the roller spanners in chapter Operating & setting accessories.

NC Drill chucks (UDC-5085)

Capacity Ø	Minimum transmissible torque	Maximum tightening torque
Ø 1 - 13 mm Ø 0.039 - 0.512"	80 Nm 59.00 ft lb	10 - 15 Nm 7.37 - 11.06 ft lb
Ø 2,5 - 16 mm Ø 0.098 - 0.630"	120 Nm 88.51 ft lb	10 - 15 Nm 7.37 - 11.06 ft lb

Combimaster (M-5820/5821/5822)

Combimaster connection size	Tightening torque	Tightening key size SW
M6	10 Nm 7.38 ft lb	9 mm 0.354"
M8	25 Nm 18.44 ft lb	11 mm 0.433"
M10	40 Nm 29.50 ft lb	15 mm 0.590"
M12	60 Nm 44.25 ft lb	19 mm 0.748"
M16	80 Nm 59.00 ft lb	26 mm 1.023"
M20	120 Nm 88.51 ft lb	32 mm 1.260"

Recommendations of use for Combimaster extensions in Heavy Metal and Carbide:

- Heavy Metal and Carbide extensions are recommended for long overhangs
- Heavy Metal provides a high modulus of rigidity, but is sensitive to bending. Carbide is very rigid but brittle, thus sensitive to shocks. Only to use for finishing operations with small ap and ae
- Use Combimaster cutters with fewer inserts to reduce vibrations
- Select inserts with light geometries, with small edge rounding and preferably with PVD coating
- High feed is a perfect solution in correlation for long applications
- Ensure a very good chips evacuations

Seco Capto™

Seco Capto™ sizes	Center Bolt tightening torque	Cam tightening torque for receivers with segment clamping
C3	40 - 50 Nm <i>29.50 - 36.88 ft lb</i>	35 Nm <i>25.81 ft lb</i>
C4	50 - 60 Nm <i>36.88 - 44.25 ft lb</i>	50 Nm <i>36.88 ft lb</i>
C5	90 - 100 Nm <i>66.38 - 73.76 ft lb</i>	70 Nm <i>51.69 ft lb</i>
C6	160 - 180 Nm <i>118.00 - 132.76 ft lb</i>	90 Nm <i>66.38 ft lb</i>
C8	160 - 180 Nm <i>118.00 - 132.76 ft lb</i>	130 Nm <i>95.88 ft lb</i>

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Graflex Modular System



Case 1: normal cuts

- Clean properly the pieces to be assembled
- Lightly tighten screw #1 until it makes contact
- Lightly tighten screw #2 until it makes contact
- Torque screw #1 (low values= light cutting; High values= heavy duty cutting)
- Torque screw #2 (low values= light cutting; High values= heavy duty cutting)

Case 2: intermittent cuts

- Tighten key with radial screw #3, before final tightening of screw #1 and #2

Graflex size	Graflex screws 1 and 2		Tenon blocking screw 3
	Low – High		
G0	1,5 - 2 Nm 1.106 - 1.47 ft lb	–	
G1	1,5 - 2 Nm 1.106 - 1.47 ft lb	–	
G2	2,5 - 4 Nm 1.844 - 2.95 ft lb	–	
G3	5 - 8 Nm 3.69 - 5.90 ft lb	0,4 Nm 0.29 ft lb	
G4	13 - 20 Nm 9.59 - 14.75 ft lb	0,7 Nm 0.52 ft lb	
G5	17 - 25 Nm 12.54 - 18.44 ft lb	2 Nm 1.47 ft lb	
G6	23 - 35 Nm 16.97 - 25.81 ft lb	4 Nm 2.95 ft lb	
G7	40 - 60 Nm 29.50 - 44.25 ft lb	8 Nm 5.9 ft lb	

Sealing screws and sealing dowels

Tool holders with steep tapers (DIN, BT, CAT) featuring ADB coolant holes, are equipped with two removable sealing screws or sealing dowels mounted into the flange.

Sealing screws Part No 950A0406 for taper size 40 and Part No 950A0606 for taper size 50 (reusable)

- To use the coolant channels through the flange (Form B type), remove the sealing screws / Dowel, and utilize a sealed pull stud
- To use coolant through the center (Form AD type), be sure the plugs are mounted in the flanges, and utilize a pull stud with a drilled coolant channel
- To mount the sealing screws: clean, apply some sealing paste onto the thread (recommended: Loctite 577); screw the sealing screw until its back face is flush with holder's flange; It is recommended to wait 24 hours to reach the maximum sealing resistance (100 bar)



Sealing dowels Part No 564301701 for taper size 40 and Part No 564301702 for taper size 50 (single use only !)

1.1

The holders are delivered from stock with plugged B coolant channels (ready for central coolant form AD) with two plastic dowels

Dismounting:

2.1

To allow coolant through the flange (Form B type), remove the dowel locking screw with a hex key 1,5 mm

2.2

Mount two hexagon socket head screws M3 by screwing it 1,5 to 2 turns into the plastic body 2.3-With pliers, pull out the screw and the plastic body together

2.3

With pliers, pull out the screw and the plastic body together

Mounting:

3.1

Sealing dowels, available as spare parts are for single use only.

3.2

Introduce the two new sealing dowel's plastic bodies, without screw, completely into the two through coolant channels by using an assembly tool, the dowels must not stand out of the flange.

3.3

Tighten the two dowels completely with a size 1,5 mm hex key.



Fig. 2.1



Fig. 2.2



Fig. 2.3



Fig. 3.2



Fig. 3.3

Safety

- Always select the best appropriate tool holder type in accordance with your machining application, and tool shank design (see advices in the technical guide)
- Tool must be inserted all the way and securely clamped into or onto the tool holder, using appropriate means (like torque wrenches when clamping torque is recommended). In any case don't over torque, or do not overheat when using a shrink fit heating device.
- Use a Toolboy fixture strongly bolted on a workbench to handle tool assembling/disassembling in safe conditions
- Carefully follow the instructions when delivered along with the products. Special care is requested for the use of the Easyshrink EVO and the Steadylife antivibration holders.
- Use gloves to protect hands and wear protective foot wear. Direct touch of sharp cutting edges may cause injuries
- Handle and carry heavy assemblies with appropriate lifting equipment's
- Make sure to never exceed the maximum cutting conditions recommended for the tool and/or the tool holder
- Do not touch the tool or tool holders when rotating on the machine



Maintenance

- Check on a regular basis the machine spindle's pulling power
- Thoroughly clean all parts (tool holder inner bore and taper, tool shank, spindle,...) before and after use to guarantee best performance.
- Dismount your assemblies periodically to clean and oil them
- Store the holders in a clean and dry place; spray a fine layer of oil to prevent corrosion
- Look for wear on the taper (fretting corrosion) and bores, as well as on the accessories like collets, pull studs,... replace them whenever needed. Make sure the tool shank is undamaged before insertion
- We can offer maintenance/repair services for all our Hydro chucks, please send a request. Never remove the pressurizing screw or the air-release screw



Recycling

- Recycling of our products, when they have come to the end of their useful life, must be done following the local regulations and legislations. Preferably dismantle products to sort out parts of the tool holders according to material type: ferrous materials (steel), nonferrous materials, plastics, others.
- Most of the products are delivered in paper card or plastic boxes which can be recycled accordingly to local regulations and legislations
- Some products are wrapped in anti-corrosion protection papers which can be treated like brown/craft paper according to local regulations and legislations.
- Products which are wrapped in oily plastic bags can be considered as Industrial hazardous waste to be treated according to local regulations and legislations.



Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories


Shrinkfit



HSK-A

Seco allows you to get the most out of both your machine and tools by offering a comprehensive range of tool holders to connect them. **HSK-A** is a lighter weight tool compared to ISO-tapers and offers high consistency in terms of radial and axial accuracy. The range covers all standard workpiece side connections, as well Seco's unique connections.

- Steadyline, vibration damping shell mill holders
- Shell mill holders, with through coolant channels
- Milling cutter holders, flange mounting
- Disc mill holders
- Side lock holders, Weldon
- Shrinkfit holders
- High precision collet chucks
- Hydraulic chucks and Power milling chucks
- ER collet chucks
- Drill chucks and Tapping chucks
- Greenstock blanks and Control bars



DIN	Machine side catalogue designation	Hole for RFID carrier**	d_1	d_2	d_9 max	d_3	d_{10}	d_4	f_1	f_2	f_3	l_1	l_2	l_3	l_4	b_1	b_2	b_3	h_1	h_2	$h_3^{+0.2}$
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
BT JIS	HSK-A32	**	32 1.260	24 0.945	26 1.024	17 0.669	26,5 1.043	20,5 0.807	20 0.787	35 1.378	16 0.630	16 0.630	3,2 0.126	5 0.197	3 0.118	7,05 0.278	7 0.276	9 0.354	13 0.512	9,5 0.374	5,4 0.213
	HSK-A100	**	100 3.937	75 2.953	88 3.465	53 2.087	92 3.622	63 2.480	29 1.142	45 1.772	20 0.787	50 1.969	10 0.394	15 0.591	10 0.394	20,02 0.788	20 0.787	22 0.866	44 1.732	31,5 1.240	4,9 0.193
CAT	HSK-A125	**	125 4.921	95 3.740	111 4.370	67 2.638	117 4.606	80 3.150	29 1.142	45 1.772	20 0.787	63 2.480	12,5 0.492	19 0.748	12 0.472	25,02 0.985	25 0.984	28 1.102	55,5 2.185	31,5 1.240	4,8 0.189
	HSK-A40	**	40 1.575	30 1.181	34 1.339	21 0.827	34,8 1.370	25,5 1.004	20 0.787	35 1.378	16 0.630	20 0.787	4 0.157	6 0.236	3,5 0.138	8,05 0.317	9 0.354	11 0.433	17 0.669	12 0.472	5,2 0.205
	HSK-A50	**	50 1.969	38 1.496	42 1.654	26 1.024	43 1.693	32 1.260	26 1.024	42 1.654	18 0.709	25 0.984	5 0.197	7,5 0.295	4,5 0.177	10,54 0.415	12 0.472	14 0.551	231 9.094	15,5 0.610	5,1 0.201
Combimaster	HSK-A63	**	63 2.480	48 1.890	53 2.087	34 1.339	55 2.165	40 1.575	26 1.024	42 1.654	18 0.709	32 1.260	6,3 0.248	10 0.394	6 0.236	12,54 0.494	16 0.630	18 0.709	26,5 1.043	20 0.787	5 0.197
	HSK-A80	**	80 3.150	60 2.362	67 2.638	42 1.654	70 2.756	50 1.969	26 1.024	42 1.654	18 0.709	40 1.575	8 0.315	12 0.472	8 0.315	16,04 0.631	18 0.709	20 0.787	34 1.339	25 0.984	4,9 0.193

Seco's holders HSK-A have a radial hole through the taper for manual clamping, compatible with HSK-C.

Note: These machine side dimensions are applied to all the holders shown in the Product pages.

** In order to know if a hole for RFID carrier exists, see 'RFID hole' column in Product pages:

1= hole for RFID carrier available, if required a carrier can be fitted on request, please enquire.


0= hole for RFID carrier not available, if required hole can be machined and a carrier can be fitted on request, please enquire.

Steadylite®, vibration damping
 – Metric/ Inch


HSK-A/ ISO12164-1-HSK-A



Design 1 (5555)



Design 2 (5556)




– DMM 40 mm / 1.575", includes 4 threaded holes for M12 screws on the bearing face $\varnothing 66,7$ mm / 2.626" according to DIN 6357
 – For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
 – For ISO attribute explanation, see page 15

Accessories:
 4 = Bolt, through coolant


Spare parts:
 1 = Bolt
 2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	BD1	OAL	LB	LSC	Design	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E9304555516160	02706254	HSK-A63	16,0 0.630	160,0 6.299	38,0 1.496	38,0 1.496	209,0 8.228	134,0 5.276	17,0 0.669	1	–	1	PB	2,4 5.290
E9304555522210	02675615	HSK-A63	22,0 0.866	210,0 8.268	48,0 1.890	48,0 1.890	261,0 10.276	184,0 7.244	19,0 0.748	1	–	1	PB	3,54 7.800
E9304555622260	02675617	HSK-A63	22,0 0.866	260,0 10.236	48,0 1.890	63,925 2.517	311,0 12.244	234,0 9.213	19,0 0.748	2	1,8	1	PB	5,38 11.860
E9304555527260	02675619	HSK-A63	27,0 1.063	260,0 10.236	60,0 2.362	60,0 2.362	313,0 12.323	234,0 9.213	21,0 0.827	1	–	1	PB	6,56 14.460
E9306555522210	02675620	HSK-A100	22,0 0.866	210,0 8.268	48,0 1.890	48,0 1.890	279,0 10.984	181,0 7.126	19,0 0.748	1	–	1	PB	4,8 10.580
E9306555622260	02675621	HSK-A100	22,0 0.866	260,0 10.236	48,0 1.890	65,0 2.559	329,0 12.953	231,0 9.094	19,0 0.748	2	2,0	1	PB	6,78 14.950
E9306555527260	02670609	HSK-A100	27,0 1.063	260,0 10.236	60,0 2.362	60,0 2.362	331,0 13.031	231,0 9.094	21,0 0.827	1	–	1	PB	7,92 17.460
E9306555627320	02670605	HSK-A100	27,0 1.063	320,0 12.598	60,0 2.362	82,0 3.228	391,0 15.394	291,0 11.457	21,0 0.827	2	2,0	1	PB	11,86 26.150
E930655532330	02706255	HSK-A100	32,0 1.260	330,0 12.992	78,0 3.071	78,0 3.071	404,0 15.906	301,0 11.850	24,0 0.945	1	–	1	PB	14,42 31.790
E9306555540350	02753468	HSK-A100	40,0 1.575	350,0 13.780	89,0 3.504	89,0 3.504	427,0 16.811	321,0 12.638	27,0 1.063	1	–	1	PB	19,4 42.770

Accessories

For	Bolt, through coolant	Spanner 3
		
16 / 0.630	5801608L	03E9304
22 / 0.866	5802210L	03E9304
22 / 0.866	5802210L	03E9306
27 / 1.063	5802712L	03E9304
27 / 1.063	5802712L	03E9306
32 / 1.260	5803216L	03E9306
40 / 1.575	5804020L	03E9306

Spare Parts, included in delivery


Guide	Spare Parts, included in delivery			
	For	Bolt	Screw	Tenon
				
HSK-A	16 / 0.630	5801608	950D0312	16C2080810A
	22 / 0.866	5802210	950D0416	16C2101111
	27 / 1.063	5802712	950D0516	16C2121214A
	32 / 1.260	5803216	950D0516	16C2141421A
	40 / 1.575	5804020	950D0616	16C2161621A
HSK-E				
DIN				
BT JIS				
CAT				
Combimaster				
Graflex				
Seco Capto™				
Others				
Operating & setting accessories				
Shrinkfit				

Steadyline®, vibration damping
– Inch


HSK-A/ ISO12164-1-HSK-A



Design 1 (5555)



Design 2 (5556)




–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw


Designation	Item number	CTMS	DMM	LF	BD	BD1	OAL	LB	LSC	Design	BHTA°	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch	inch					lbs
E9306555075750	02689508	HSK-A100	0.750	7.500	1.750	1.750	10.157	6.358	0.689	1	–	1	PB	9.480

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
			
0.750	58211905	950D0312	16C2080712A

With through coolant channels – ISO 3937
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



–DMM 40 mm / 1.575", includes 4 threaded holes for M12 screws on the bearing face Ø66,7 mm / 2.626" according to DIN 6357
–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15


Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw


Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
HSKA63-SM16-050-L1	03301550	HSK-A63	16,0 0.630	50,0 1.969	38,0 1.496	99,0 3.898	24,0 0.945	17,0 0.669	1	G6.3	0,9 1.980
HSKA63-SM16-100-L1	03301551	HSK-A63	16,0 0.630	100,0 3.937	38,0 1.496	148,0 5.827	74,0 2.913	17,0 0.669	1	G6.3	1,4 3.090
HSKA63-SM16-145-L1	03301552	HSK-A63	16,0 0.630	145,0 5.709	38,0 1.496	194,0 7.638	119,0 4.685	17,0 0.669	1	G6.3	1,8 3.970
HSKA63-SM22-050-L1	03301556	HSK-A63	22,0 0.866	50,0 1.969	48,0 1.890	101,0 3.976	24,0 0.945	19,0 0.748	1	G6.3	1,1 2.430
HSKA63-SM22-100-L1	03301557	HSK-A63	22,0 0.866	100,0 3.937	48,0 1.890	151,0 5.945	74,0 2.913	19,0 0.748	1	G6.3	1,8 3.970
HSKA63-SM22-160-L1	03301558	HSK-A63	22,0 0.866	160,0 6.299	48,0 1.890	211,0 8.307	134,0 5.276	19,0 0.748	1	G6.3	2,6 5.730
HSKA63-SM27-060-L1	03301563	HSK-A63	27,0 1.063	60,0 2.362	60,0 2.362	113,0 4.449	34,0 1.339	21,0 0.827	1	G6.3	1,4 3.090
HSKA63-SM27-100-L1	03301564	HSK-A63	27,0 1.063	100,0 3.937	60,0 2.362	153,0 6.024	74,0 2.913	21,0 0.827	1	G6.3	2,3 5.070
HSKA63-SM27-160-L1	03301565	HSK-A63	27,0 1.063	160,0 6.299	60,0 2.362	213,0 8.386	134,0 5.276	21,0 0.827	1	G6.3	3,1 6.830
HSKA63-SM32-060-L1	03301568	HSK-A63	32,0 1.260	60,0 2.362	78,0 3.071	116,0 4.567	34,0 1.339	24,0 0.945	1	G6.3	1,7 3.750
HSKA63-SM32-100-L1	03301569	HSK-A63	32,0 1.260	100,0 3.937	78,0 3.071	156,0 6.142	74,0 2.913	24,0 0.945	1	G6.3	3,1 6.830
HSKA63-SM40-060-L1	03301571	HSK-A63	40,0 1.575	60,0 2.362	89,0 3.504	119,0 4.685	34,0 1.339	27,0 1.063	1	G6.3	2,1 4.630
HSKA100-SM16-100-L1	03301572	HSK-A100	16,0 0.630	100,0 3.937	38,0 1.496	167,0 6.575	71,0 2.795	17,0 0.669	1	G6.3	2,7 5.950
HSKA100-SM22-050-L1	03301576	HSK-A100	22,0 0.866	50,0 1.969	48,0 1.890	119,0 4.685	21,0 0.827	19,0 0.748	1	G6.3	2,4 5.290
HSKA100-SM22-100-L1	03301577	HSK-A100	22,0 0.866	100,0 3.937	48,0 1.890	169,0 6.654	71,0 2.795	19,0 0.748	1	G6.3	3,1 6.830
HSKA100-SM22-160-L1	03301578	HSK-A100	22,0 0.866	160,0 6.299	48,0 1.890	229,0 9.016	131,0 5.157	19,0 0.748	1	G6.3	3,9 8.600
HSKA100-SM27-050-L1	03301583	HSK-A100	27,0 1.063	50,0 1.969	60,0 2.362	121,0 4.764	21,0 0.827	21,0 0.827	1	G6.3	2,6 5.730
HSKA100-SM27-100-L1	03301584	HSK-A100	27,0 1.063	100,0 3.937	60,0 2.362	171,0 6.732	71,0 2.795	21,0 0.827	1	G6.3	3,7 8.160
HSKA100-SM27-160-L1	03301585	HSK-A100	27,0 1.063	160,0 6.299	60,0 2.362	231,0 9.094	131,0 5.157	21,0 0.827	1	G6.3	5,0 11.020
HSKA100-SM32-050-L1	03301589	HSK-A100	32,0 1.260	50,0 1.969	78,0 3.071	124,0 4.882	21,0 0.827	24,0 0.945	1	G6.3	3,0 6.610
HSKA100-SM32-100-L1	03301590	HSK-A100	32,0 1.260	100,0 3.937	78,0 3.071	174,0 6.850	71,0 2.795	24,0 0.945	1	G6.3	4,8 10.580
HSKA100-SM32-160-L1	03301591	HSK-A100	32,0 1.260	160,0 6.299	78,0 3.071	234,0 9.213	131,0 5.157	24,0 0.945	1	G6.3	7,1 15.650

Designation	Item number	CTMS	DMM mm inch	LF mm inch	BD mm inch	OAL mm inch	LB mm inch	LSC mm inch	RFID hole	Balan- cing	Weight kg lbs
HSKA100-SM40-060-L1	03301595	HSK-A100	40,0 1.575	60,0 2.362	89,0 3.504	137,0 5.394	31,0 1.220	27,0 1.063	1	G6.3	3,7 8.160
HSKA100-SM40-100-L1	03301596	HSK-A100	40,0 1.575	100,0 3.937	89,0 3.504	177,5 6.988	71,0 2.795	27,0 1.063	1	G6.3	5,6 12.350
HSKA100-SM40-160-L1	03301597	HSK-A100	40,0 1.575	160,0 6.299	89,0 3.504	237,0 9.331	131,0 5.157	27,0 1.063	1	G6.3	8,5 18.740
HSKA125-SM22-100-L1	03229672	HSK-A125	22,0 0.866	100,0 3.937	48,0 1.890	182,0 7.165	71,0 2.795	19,0 0.748	1	PB	4,4 9.700
HSKA125-SM27-100-L1	03229673	HSK-A125	27,0 1.063	100,0 3.937	60,0 2.362	184,0 7.244	71,0 2.795	21,0 0.827	1	PB	5,0 11.020
HSKA125-SM32-100-L1	03229674	HSK-A125	32,0 1.260	100,0 3.937	78,0 3.071	187,0 7.362	71,0 2.795	24,0 0.945	1	PB	6,1 13.450
HSKA125-SM40-100-L1	03229675	HSK-A125	40,0 1.575	100,0 3.937	89,0 3.504	190,0 7.480	71,0 2.795	27,0 1.063	1	PB	6,1 13.450

Accessories


For	Coolant tube	Spanner
		
A63-A100/ 16/ 0.630	20E9304	5811608
A63-A100/ 16/ 0.630	20E9306	5811608
A63-A100/ 22/ 0.866	20E9304	5812210
A63-A100/ 22/ 0.866	20E9306	5812210
A63-A100/ 27/ 1.063	20E9304	5812712
A63-A100/ 27/ 1.063	20E9306	5812712
A63-A100/ 32/ 1.260	20E9304	5813216
A63-A100/ 32/ 1.260	20E9306	5813216
A63-A100/ 40/ 1.575	20E9304	5814020
A63-A100/ 40/ 1.575	20E9306	5814020
A125/ 22/ 0.866	20E9307	5812210
A125/ 27/ 1.063	20E9307	5812712
A125/ 32/ 1.260	20E9307	5813216
A125/ 40/ 1.575	20E9307	5814020

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
			
A63-A100/ 16/ 0.630	5801608	950D0312	16C716A
A63-A100/ 22/ 0.866	5802210	950D0416	16C722A
A63-A100/ 27/ 1.063	5802712	950D0512	16C727A
A63-A100/ 32/ 1.260	5803216	950D0616	16C732A
A63-A100/ 40/ 1.575	5804020	950D0616	16C740A
A125/ 22/ 0.866	5802210	950D0414	16C11012206
A125/ 27/ 1.063	5802712	950D0516	16C11214243
A125/ 32/ 1.260	5803216	950D0516	16C2141421
A125/ 40/ 1.575	5804020	950D0616	16C2161621

With through coolant channels – ISO 3937
– Inch

HSK-A/ ISO12164-1-HSK-A




–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw


Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch			lbs
HSKA63-SM0.750-2.000-L1	03301669	HSK-A63	0.750	2.000	1.750	3.948	0.976	0.688	1	G6.3	2.200
HSKA63-SM0.750-3.000-L1	03301670	HSK-A63	0.750	3.000	1.750	4.948	1.976	0.688	1	G6.3	2.870
HSKA63-SM1.000-2.370-L1	03301671	HSK-A63	1.000	2.370	2.250	4.318	1.346	0.688	1	G6.3	3.090
HSKA63-SM1.250-2.370-L1	03301672	HSK-A63	1.250	2.370	2.750	4.318	1.346	0.688	1	G6.3	3.750
HSKA63-SM1.500-2.370-L1	03301673	HSK-A63	1.500	2.370	3.500	4.570	1.346	0.940	1	G6.3	4.630
HSKA100-SM0.750-4.000-L1	03301674	HSK-A100	0.750	4.000	1.750	6.657	2.858	0.688	1	G6.3	6.390
HSKA100-SM1.000-2.000-L1	03301675	HSK-A100	1.000	2.000	2.250	4.657	0.858	0.688	1	G6.3	5.730
HSKA100-SM1.000-4.000-L1	03301676	HSK-A100	1.000	4.000	2.250	6.657	2.858	0.688	1	G6.3	7.720
HSKA100-SM1.250-4.000-L1	03301677	HSK-A100	1.250	4.000	2.750	6.657	2.858	0.688	1	G6.3	9.480
HSKA100-SM1.500-2.250-L1	03301678	HSK-A100	1.500	2.250	3.500	5.158	1.108	0.940	1	G6.3	8.160
HSKA100-SM2.000-4.000-L1	03301679	HSK-A100	2.000	4.000	4.870	6.908	2.858	0.940	1	G6.3	17.640
HSKA125-SM0.750-4.000-L1	03229702	HSK-A125	0.750	4.000	1.750	7.169	2.858	0.689	1	PB	9.920
HSKA125-SM1.000-4.000-L1	03229703	HSK-A125	1.000	4.000	2.250	7.169	2.858	0.689	1	PB	11.020
HSKA125-SM1.250-4.000-L1	03229704	HSK-A125	1.250	4.000	1.250	7.169	2.858	0.689	1	PB	12.570
HSKA125-SM1.500-4.000-L1	03229705	HSK-A125	1.500	4.000	3.500	7.421	2.858	0.941	1	PB	15.650
HSKA125-SM2.000-4.000-L1	03229706	HSK-A125	2.000	4.000	4.874	7.421	2.858	0.941	1	PB	22.490

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
			
0.750	58271905	950DNC012031	16C71905
0.750 (-A125)	58211905	950D0312	16C11905A
1.000	58272540	950DNC016037	16C72540
1.000 (-A125)	58212540	950D0416	16C12540A
1.250	58273175	950DNC019050	16C73175
1.250 (-A125)	58213175	950D0516	16C23175
1.500	58273810	950DNC025050	16C73810
1.500 (-A125)	58213810	950D0616	16C23810
2.000	58275080	950DNC031075	16C75080
2.000 (-A125)	58215080	–	16C25080

Small face with through coolant channels – ISO 3937
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



– Small workpiece side diameter BD according to ISO 3937, suitable for Seco disc mill cutters Type B
– For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
– For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
HSKA63-SM22-050-F3L1	03301553	HSK-A63	22,0 0.866	50,0 1.969	40,0 1.575	101,0 3.976	24,0 0.945	19,0 0.748	1	G6.3	1,0 2.200
HSKA63-SM22-100-F3L1	03301554	HSK-A63	22,0 0.866	100,0 3.937	40,0 1.575	151,0 5.945	74,0 2.913	19,0 0.748	1	G6.3	1,5 3.310
HSKA63-SM22-160-F3L1	03301555	HSK-A63	22,0 0.866	160,0 6.299	40,0 1.575	211,0 8.307	134,0 5.276	19,0 0.748	1	G6.3	2,0 4.410
HSKA63-SM27-060-F3L1	03301559	HSK-A63	27,0 1.063	60,0 2.362	48,0 1.890	113,0 4.449	34,0 1.339	21,0 0.827	1	G6.3	1,3 2.870
HSKA63-SM27-100-F3L1	03301560	HSK-A63	27,0 1.063	100,0 3.937	48,0 1.890	153,0 6.024	74,0 2.913	21,0 0.827	1	G6.3	1,8 3.970
HSKA63-SM27-160-F3L1	03301561	HSK-A63	27,0 1.063	160,0 6.299	48,0 1.890	213,0 8.386	134,0 5.276	21,0 0.827	1	G6.3	2,7 5.950
HSKA63-SM32-060-F3L1	03301566	HSK-A63	32,0 1.260	60,0 2.362	58,0 2.283	116,0 4.567	34,0 1.339	24,0 0.945	1	G6.3	1,5 3.310
HSKA63-SM32-100-F3L1	03301567	HSK-A63	32,0 1.260	100,0 3.937	58,0 2.283	156,0 6.142	74,0 2.913	24,0 0.945	1	G6.3	2,3 5.070
HSKA63-SM40-060-F3L1	03301570	HSK-A63	40,0 1.575	60,0 2.362	70,0 2.756	119,0 4.685	34,0 1.339	27,0 1.063	1	G6.3	1,8 3.970
HSKA100-SM22-050-F3L1	03301573	HSK-A100	22,0 0.866	50,0 1.969	40,0 1.575	119,0 4.685	21,0 0.827	19,0 0.748	1	G6.3	2,3 5.070
HSKA100-SM22-100-F3L1	03301574	HSK-A100	22,0 0.866	100,0 3.937	40,0 1.575	169,0 6.654	71,0 2.795	19,0 0.748	1	G6.3	2,8 6.170
HSKA100-SM22-160-F3L1	03301575	HSK-A100	22,0 0.866	160,0 6.299	40,0 1.575	229,0 9.016	131,0 5.157	19,0 0.748	1	G6.3	3,4 7.500
HSKA100-SM27-050-F3L1	03301580	HSK-A100	27,0 1.063	50,0 1.969	48,0 1.890	121,0 4.764	21,0 0.827	21,0 0.827	1	G6.3	2,4 5.290
HSKA100-SM27-100-F3L1	03301581	HSK-A100	27,0 1.063	100,0 3.937	48,0 1.890	171,0 6.732	71,0 2.795	21,0 0.827	1	G6.3	3,3 7.280
HSKA100-SM27-160-F3L1	03301582	HSK-A100	27,0 1.063	160,0 6.299	48,0 1.890	231,0 9.094	131,0 5.157	21,0 0.827	1	G6.3	3,9 8.600
HSKA100-SM32-050-F3L1	03301586	HSK-A100	32,0 1.260	50,0 1.969	58,0 2.283	124,0 4.882	21,0 0.827	24,0 0.945	1	G6.3	2,6 5.730
HSKA100-SM32-100-F3L1	03301587	HSK-A100	32,0 1.260	100,0 3.937	58,0 2.283	174,0 6.850	71,0 2.795	24,0 0.945	1	G6.3	3,6 7.940
HSKA100-SM32-160-F3L1	03301588	HSK-A100	32,0 1.260	160,0 6.299	58,0 2.283	234,0 9.213	131,0 5.157	24,0 0.945	1	G6.3	4,9 10.800
HSKA100-SM40-060-F3L1	03301592	HSK-A100	40,0 1.575	60,0 2.362	70,0 2.756	137,0 5.394	31,0 1.220	27,0 1.063	1	G6.3	3,3 7.280
HSKA100-SM40-100-F3L1	03301593	HSK-A100	40,0 1.575	100,0 3.937	70,0 2.756	177,0 6.969	71,0 2.795	27,0 1.063	1	G6.3	4,4 9.700
HSKA100-SM40-160-F3L1	03301594	HSK-A100	40,0 1.575	160,0 6.299	70,0 2.756	237,0 9.331	131,0 5.157	27,0 1.063	1	G6.3	6,2 13.670

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Accessories

Guide	Accessories		
	For	Coolant tube	Spanner
			
HSK-A	22/ 0.866	20E9304	5812210
	22/ 0.866	20E9306	5812210
	27/ 1.063	20E9304	5812712
	27/ 1.063	20E9306	5812712
HSK-E	32/ 1.260	20E9304	5813216
	32/ 1.260	20E9306	5813216
	40/ 1.575	20E9304	5814020
	40/ 1.575	20E9306	5814020


Spare Parts, included in delivery

DIN	Spare Parts, included in delivery			
	For	Bolt	Screw	Tenon
				
BT JIS	22/ 0.866	5802210	950D0410	16C722
	27/ 1.063	5802712	950D0512	16C727
	32/ 1.260	5803216	950D0616	16C732
	40/ 1.575	5804020	950D0616	16C740

CAT
Combimaster
Graflex
Seco Capto™
Others
Operating & setting accessories
Shrinkfit

Flange mounting – DIN 6357/ DIN 2079
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Spare parts:
2 = Tenon/Screw


Designation	Item number	CTMS	DMM	LF	BD	OAL	LSC	DBC	TDZ	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
HSKA100-SMF60-075	03301598	HSK-A100	60,0 2.362	75,0 2.953	129,0 5.079	165,0 6.496	40,0 1.575	101,6 4.000	M16x2	1	G6.3	6,5 14.330
HSKA125-SMF60-085	03229644	HSK-A125	60,0 2.362	85,0 3.346	129,0 5.079	188,0 7.402	40,0 1.575	101,6 4.000	M16x2	1	PB	9,2 20.280

Spare Parts, included in delivery

For	Screw	Tenon
		
HSKA100-SMF60-075	950D1225	16C35060
HSKA125-SMF60-085	950D1225	16C35060

Flange mounting – DIN 6357/ DIN 2079
– Inch

HSK-A/ ISO12164-1-HSK-A



–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15


Spare parts:
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LSC	DBC	TDZ	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch				lbs
HSKA125-SMF2.500-3.500	03229685	HSK-A125	2.500	3.500	4.874	7.122	1.142	4.000	5/8" UNC	1	PB	20.280

Spare Parts, included in delivery

For	Screw	Tenon
		
HSKA125-SMF2.500-3.500	950D1225	16C35060

– Metric/ Inch




- Best suited for Seco disc mill cutters Type A
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Spare parts:
1 = Slide rod
2 = Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	FLGT	LSCN	LSCX	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
E930456572290	02602714	HSK-A63	22,0 0.866	90,0 3.543	35,0 1.378	122,0 4.803	64,0 2.520	4,0 0.157	0,0 0.0	12,0 0.472	1	PB	1,2 2.650
E9304565727120	02602715	HSK-A63	27,0 1.063	120,0 4.724	42,0 1.654	152,0 5.984	94,0 3.701	5,0 0.197	0,0 0.0	15,0 0.591	1	PB	1,7 3.750
E9306565740190	02602720	HSK-A100	40,0 1.575	190,0 7.480	58,0 2.283	240,0 9.449	161,0 6.339	7,0 0.276	0,0 0.0	30,0 1.181	1	PB	5,3 11.680
E9306565750235	02602721	HSK-A100	50,0 1.969	235,0 9.252	72,0 2.835	285,0 11.220	206,0 8.110	8,0 0.315	0,0 0.0	32,0 1.260	1	PB	8,5 18.740


Spare Parts, included in delivery

For	Screw	Slide rod
		
E930456572290	19C565722	565722
E9304565727120	19C565727	565727
E9306565740190	19C565740	565740
E9306565750235	19C565750	565750


DIN 1835 Form B/ DIN 6535 Form HB
– Metric/ Inch



Design 1



Design 2



–Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
–With 2 coolant channels for front lubrication which can be sealed with included screws
–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
HSKA63-EM06-065-L1	03301689	HSK-A63	6,0 0.236	65,0 2.559	39,0 1.535	35,0 1.378	25,0 0.984	97,0 3.819	47,0 1.850	1	1	G6.3	0,8 1.760
HSKA63-EM06-120-L1	10325527	HSK-A63	6,0 0.236	120,0 4.724	94,0 3.701	35,4 1.394	25,0 0.984	152,0 5.984	102,0 4.016	1	1	G6.3	1,0 2.200
HSKA63-EM08-065-L1	03301690	HSK-A63	8,0 0.315	65,0 2.559	39,0 1.535	32,0 1.260	28,0 1.102	97,0 3.819	47,0 1.850	1	1	G6.3	0,8 1.760
HSKA63-EM08-120-L1	03301691	HSK-A63	8,0 0.315	120,0 4.724	94,0 3.701	32,0 1.260	28,0 1.102	152,0 5.984	102,0 4.016	1	1	G6.3	1,1 2.430
HSKA63-EM10-065-L1	03301692	HSK-A63	10,0 0.394	65,0 2.559	39,0 1.535	36,0 1.417	35,0 1.378	97,0 3.819	45,0 1.772	1	1	G6.3	0,9 1.980
HSKA63-EM10-120-L1	03301693	HSK-A63	10,0 0.394	120,0 4.724	94,0 3.701	36,0 1.417	35,0 1.378	152,0 5.984	100,0 3.937	1	1	G6.3	1,3 2.870
HSKA63-EM12-080-L1	03301694	HSK-A63	12,0 0.472	80,0 3.150	54,0 2.126	41,0 1.614	42,0 1.654	112,0 4.409	57,5 2.264	1	1	G6.3	1,2 2.650
HSKA63-EM12-120-L1	03301695	HSK-A63	12,0 0.472	120,0 4.724	94,0 3.701	41,0 1.614	42,0 1.654	152,0 5.984	97,5 3.839	1	1	G6.3	1,6 3.530
HSKA63-EM14-080-L1	03301696	HSK-A63	14,0 0.551	80,0 3.150	54,0 2.126	41,0 1.614	44,0 1.732	112,0 4.409	57,5 2.264	1	1	G6.3	1,2 2.650
HSKA63-EM16-080-L1	03301697	HSK-A63	16,0 0.630	80,0 3.150	54,0 2.126	44,0 1.732	48,0 1.890	112,0 4.409	56,0 2.205	1	1	G6.3	1,3 2.870
HSKA63-EM16-120-L1	03301698	HSK-A63	16,0 0.630	120,0 4.724	94,0 3.701	44,0 1.732	48,0 1.890	152,0 5.984	96,0 3.780	1	1	G6.3	1,9 4.190
HSKA63-EM18-080-L1	03301699	HSK-A63	18,0 0.709	80,0 3.150	54,0 2.126	44,0 1.732	50,0 1.969	112,0 4.409	56,0 2.205	1	1	G6.3	1,4 3.090
HSKA63-EM20-080-L1	03301700	HSK-A63	20,0 0.787	80,0 3.150	54,0 2.126	46,0 1.811	52,0 2.047	112,0 4.409	55,0 2.165	1	1	G6.3	1,4 3.090
HSKA63-EM20-120-L1	03301701	HSK-A63	20,0 0.787	120,0 4.724	94,0 3.701	46,0 1.811	52,0 2.047	152,0 5.984	95,0 3.740	1	1	G6.3	2,1 4.630
HSKA63-EM25-110-L1	03301702	HSK-A63	25,0 0.984	110,0 4.331	68,0 2.677	54,0 2.126	63,0 2.480	142,0 5.591	86,0 3.386	2	1	G6.3	2,3 5.070
HSKA63-EM25-160-L1	10325528	HSK-A63	25,0 0.984	160,0 6.299	134,0 5.276	54,0 2.126	63,0 2.480	192,0 7.559	136,0 5.354	2	1	G6.3	3,5 7.720
HSKA63-EM32-110-L1	10007275	HSK-A63	32,0 1.260	110,0 4.331	84,0 3.307	58,0 2.283	72,0 2.835	142,0 5.591	86,0 3.386	2	1	G6.3	2,6 5.730
HSKA63-EM32-160-L1	10325529	HSK-A63	32,0 1.260	160,0 6.299	134,0 5.276	58,0 2.283	72,0 2.835	192,0 7.559	136,0 5.354	2	1	G6.3	4,2 9.260
HSKA100-EM06-080-L1	03301703	HSK-A100	6,0 0.236	80,0 3.150	51,0 2.008	35,0 1.378	25,0 0.984	130,0 5.118	62,0 2.441	1	1	G6.3	2,2 4.850
HSKA100-EM08-080-L1	03301704	HSK-A100	8,0 0.315	80,0 3.150	51,0 2.008	35,0 1.378	28,0 1.102	130,0 5.118	62,0 2.441	1	1	G6.3	2,2 4.850
HSKA100-EM10-080-L1	03301705	HSK-A100	10,0 0.394	80,0 3.150	51,0 2.008	35,0 1.378	35,0 1.378	130,0 5.118	60,0 2.362	1	1	G6.3	2,4 5.290
HSKA100-EM12-080-L1	03301706	HSK-A100	12,0 0.472	80,0 3.150	51,0 2.008	41,0 1.614	42,0 1.654	130,0 5.118	57,5 2.264	1	1	G6.3	2,5 5.510

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
HSKA100-EM14-080-L1	03301707	HSK-A100	14,0 0.551	80,0 3.150	51,0 2.008	41,0 1.614	44,0 1.732	130,0 5.118	57,5 2.264	1	1	G6.3	2,5 5.510
HSKA100-EM16-100-L1	03301708	HSK-A100	16,0 0.630	100,0 3.937	71,0 2.795	44,0 1.732	48,0 1.890	150,0 5.906	76,0 2.992	1	1	G6.3	2,9 6.390
HSKA100-EM16-160-L1	03301709	HSK-A100	16,0 0.630	160,0 6.299	131,0 5.157	44,0 1.732	48,0 1.890	210,0 8.268	136,0 5.354	1	1	G6.3	3,7 8.160
HSKA100-EM20-100-L1	03301710	HSK-A100	20,0 0.787	100,0 3.937	71,0 2.795	46,0 1.811	52,0 2.047	150,0 5.906	75,0 2.953	1	1	G6.3	3,0 6.610
HSKA100-EM20-160-L1	03301711	HSK-A100	20,0 0.787	160,0 6.299	131,0 5.157	46,0 1.811	52,0 2.047	210,0 8.268	135,0 5.315	1	1	G6.3	4,0 8.820
HSKA100-EM25-100-L1	03301712	HSK-A100	25,0 0.984	100,0 3.937	71,0 2.795	54,0 2.126	65,0 2.559	150,0 5.906	76,0 2.992	2	1	G6.3	3,5 7.720
HSKA100-EM25-160-L1	03301713	HSK-A100	25,0 0.984	160,0 6.299	131,0 5.157	54,0 2.126	65,0 2.559	210,0 8.268	136,0 5.354	2	1	G6.3	5,0 11.020
HSKA100-EM32-100-L1	10007273	HSK-A100	32,0 1.260	100,0 3.937	71,0 2.795	58,0 2.283	72,0 2.835	150,0 5.906	76,0 2.992	2	1	G6.3	3,8 8.380
HSKA100-EM32-160-L1	10007274	HSK-A100	32,0 1.260	160,0 6.299	131,0 5.157	58,0 2.283	72,0 2.835	210,0 8.268	136,0 5.354	2	1	G6.3	5,7 12.570
HSKA100-EM40-120-L1	03301714	HSK-A100	40,0 1.575	120,0 4.724	91,0 3.583	68,0 2.677	80,0 3.150	170,0 6.693	90,0 3.543	2	1	G6.3	4,7 10.360
HSKA100-EM50-130-L1	03301715	HSK-A100	50,0 1.969	130,0 5.118	101,0 3.976	78,0 3.071	100,0 3.937	180,0 7.087	95,0 3.740	2	1	G6.3	6,3 13.890

Spare Parts, included in delivery

For	Coolant screw	Locking screw
		
6 / 0.236	950A0304	951C0610
6 / 0.236	950A0304	951C0610
8 / 0.315	950A0304	951C0810
10 / 0.394	950A0304	951C1012
12 / 0.472	950A0304	951C1216
14 / 0.551	950A0304	951C1214
16 / 0.630 - 18 / 0.709	950A0304	951C1416
20 / 0.787	950A0304	951C1616
25 / 0.984	950A0304	951C1820
25 / 0.984	950A0304	951C1820
32 / 1.260 - 40 / 1.575	950A0304	951C2020
32 / 1.260 - 40 / 1.575	950A0304	951C2020
50 / 1.969	950A0304	951C2425

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

DIN 1835 Form B/ DIN 6535 Form HB
– Inch


HSK-A/ ISO12164-1-HSK-A



Design 1



Design 2



–With 2 coolant channels for front lubrication which can be sealed with included screws
–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch				lbs
HSKA63-EM0.375-2.750-L1	03301734	HSK-A63	0.375	2.750	1.726	1.500	1.000	4.010	2.000	1	1	G6.3	1.760
HSKA63-EM0.500-3.250-L1	03301735	HSK-A63	0.500	3.250	2.226	1.620	1.250	4.510	2.380	1	1	G6.3	2.200
HSKA63-EM0.625-3.250-L1	03301736	HSK-A63	0.625	3.250	2.226	1.870	1.500	4.510	2.340	1	1	G6.3	2.430
HSKA63-EM0.750-3.370-L1	03301737	HSK-A63	0.750	3.370	2.346	2.000	1.750	4.630	2.370	1	1	G6.3	2.650
HSKA63-EM1.000-4.500-L1	03301738	HSK-A63	1.000	4.500	3.476	2.250	2.000	5.760	3.380	2	1	G6.3	3.750
HSKA63-EM1.250-4.500-L1	03301739	HSK-A63	1.250	4.500	3.476	2.250	2.500	5.760	3.380	2	1	G6.3	4.850
HSKA100-EM0.500-6.000-L1	03301740	HSK-A100	0.500	6.000	4.858	1.620	1.250	7.969	5.130	1	1	G6.3	6.170
HSKA100-EM0.625-6.000-L1	03301741	HSK-A100	0.625	6.000	4.858	1.870	1.500	7.969	5.090	1	1	G6.3	6.610
HSKA100-EM0.750-4.000-L1	03301742	HSK-A100	0.750	4.000	2.858	2.000	1.750	5.969	3.000	1	1	G6.3	6.170
HSKA100-EM1.000-4.000-L1	03301744	HSK-A100	1.000	4.000	2.858	2.250	2.000	5.969	2.880	2	1	G6.3	6.170
HSKA100-EM1.250-4.000-L1	03301745	HSK-A100	1.250	4.000	2.858	2.250	2.500	5.969	2.880	2	1	G6.3	7.280
HSKA100-EM1.500-5.000-L1	03301746	HSK-A100	1.500	5.000	3.858	2.620	2.750	6.969	3.880	2	1	G6.3	9.260

Spare Parts, included in delivery


For	Coolant screw	Locking screw
		
0.375	950A0304	951CNF037031
0.500	950A0304	951CNF043037
0.625	950A0304	951CNF056050
0.750-0.875	950A0304	951CNF062050
1.000-1.500	950A0304	951CNF075068

DIN 1835 Form B/ DIN 6535 Form HB
– Metric/ Inch


HSK-A/ ISO12164-1-HSK-A



Design 1



Design 2



- Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
HSKA125-EM16-100	03229629	HSK-A125	16,0 0.630	100,0 3.937	71,0 2.795	46,0 1.811	48,0 1.890	163,0 6.417	76,0 2.992	1	1	PB	4,2 9.260
HSKA125-EM20-100	03229630	HSK-A125	20,0 0.787	100,0 3.937	71,0 2.795	48,0 1.890	52,0 2.047	163,0 6.417	75,0 2.953	1	1	PB	4,5 9.920
HSKA125-EM20-160	03229631	HSK-A125	20,0 0.787	160,0 6.299	131,0 5.157	48,0 1.890	52,0 2.047	223,0 8.780	135,0 5.315	1	1	PB	5,5 12.130
HSKA125-EM25-100	03229632	HSK-A125	25,0 0.984	100,0 3.937	71,0 2.795	54,0 2.126	65,0 2.559	163,0 6.417	76,0 2.992	2	1	PB	4,8 10.580
HSKA125-EM25-160	03229633	HSK-A125	25,0 0.984	160,0 6.299	131,0 5.157	54,0 2.126	65,0 2.559	223,0 8.780	136,0 5.354	2	1	PB	6,4 14.110
HSKA125-EM32-100	03229634	HSK-A125	32,0 1.260	100,0 3.937	71,0 2.795	58,0 2.283	72,0 2.835	163,0 6.417	76,0 2.992	2	1	PB	5,1 11.240
HSKA125-EM32-160	03229635	HSK-A125	32,0 1.260	160,0 6.299	131,0 5.157	58,0 2.283	72,0 2.835	223,0 8.780	136,0 5.354	2	1	PB	7,1 15.650
HSKA125-EM40-120	03229636	HSK-A125	40,0 1.575	120,0 4.724	91,0 3.583	68,0 2.677	80,0 3.150	183,0 7.205	90,0 3.543	2	1	PB	6,0 13.230
HSKA125-EM50-120	03229637	HSK-A125	50,0 1.969	120,0 4.724	91,0 3.583	78,0 3.071	100,0 3.937	183,0 7.205	85,0 3.346	2	1	PB	7,3 16.090


Spare Parts, included in delivery

For	Locking screw
	
16/ 0.630	951C1416
20/ 0.787	951C1616
25/ 0.984	951C1820
32/ 1.260-40/ 1.575	951C2020
50/ 1.969	951C2425


DIN 1835 Form B/ DIN 6535 Form HB
– Inch



Design 1



Design 2



–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15


Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch				lbs
HSKA125-EM0.500-3.500	03229676	HSK-A125	0.500	3.500	2.358	1.614	1.614	5.980	2.630	1	1	PB	8.380
HSKA125-EM0.625-3.750	03229677	HSK-A125	0.625	3.750	2.608	1.870	1.870	6.230	2.840	1	1	PB	9.040
HSKA125-EM0.750-3.750	03229678	HSK-A125	0.750	3.750	2.608	2.008	2.000	6.230	2.750	1	1	PB	9.260
HSKA125-EM0.750-6.000	03229679	HSK-A125	0.750	6.000	4.858	2.008	2.000	8.480	5.000	1	1	PB	11.020
HSKA125-EM1.000-4.250	03229680	HSK-A125	1.000	4.250	3.108	2.244	2.500	6.730	3.130	2	1	PB	10.360
HSKA125-EM1.000-6.000	03229681	HSK-A125	1.000	6.000	4.858	2.244	2.500	8.480	4.880	2	1	PB	13.010
HSKA125-EM1.250-4.250	03229682	HSK-A125	1.250	4.250	3.108	2.244	2.748	6.730	3.130	2	1	PB	11.460
HSKA125-EM1.500-4.500	03229683	HSK-A125	1.500	4.500	3.358	2.618	3.500	6.980	3.000	2	1	PB	14.330
HSKA125-EM2.000-5.250	03229684	HSK-A125	2.000	5.250	4.108	3.110	4.000	7.730	3.840	2	1	PB	18.300

Spare Parts, included in delivery

For	Locking screw
	
0.500	951CNC043037
0.625	951CNC056050
0.750	951CNC062050
1.000	951CNC075068
1.250	951CNC075068
2.000	951CNC062050

DIN type
 – Metric/ Inch

HSK-A/ ISO12164-1-HSK-A


–Run-out $\leq 3 \mu\text{m}$
 –Delivered with one stop screw
 –For Shrinkfit extensions, see page(s) 357-358
 –For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
 –For ISO attribute explanation, see page 15

Spare parts:
 1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBK	LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
E930256030680	02752844	HSK-A40	6,0 0.236	80,0 3.150	60,0 2.362	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	100,0 3.937	44,0 1.732	54,0 2.126	10,5 0.413	M5x0.8	4,5	0	G2.5	0,5 1.100
E930256030880	02752847	HSK-A40	8,0 0.315	80,0 3.150	60,0 2.362	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	100,0 3.937	44,0 1.732	54,0 2.126	10,5 0.413	M6x1	4,5	0	G2.5	0,5 1.100
E930256031080	02752848	HSK-A40	10,0 0.394	80,0 3.150	60,0 2.362	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	100,0 3.937	39,0 1.535	49,0 1.929	13,0 0.512	M8x1	4,5	0	G2.5	0,5 1.100
E930256031290	02752849	HSK-A40	12,0 0.472	90,0 3.543	70,0 2.756	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	110,0 4.331	44,0 1.732	54,0 2.126	13,0 0.512	M10x1	4,5	0	G2.5	0,49 1.080
E930256031690	02752850	HSK-A40	16,0 0.630	90,0 3.543	70,0 2.756	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	110,0 4.331	41,0 1.614	51,0 2.008	14,0 0.551	M12x1	4,5	0	G2.5	0,6 1.320
E930454030680	03098277	HSK-A63	6,0 0.236	80,0 3.150	54,0 2.126	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	112,0 4.409	44,0 1.732	54,0 2.126	10,5 0.413	M5x0.8	4,5	1	G2.5	0,9 1.980
E9304540306120	03098278	HSK-A63	6,0 0.236	120,0 4.724	94,0 3.701	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	152,0 5.984	84,0 3.307	94,0 3.701	10,5 0.413	M5x0.8	4,5	1	G2.5	1,0 2.200
E9304540306160	03098279	HSK-A63	6,0 0.236	160,0 6.299	134,0 5.276	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	192,0 7.559	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	G2.5	1,2 2.650
E930454030880	03098280	HSK-A63	8,0 0.315	80,0 3.150	54,0 2.126	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	112,0 4.409	43,5 1.713	54,0 2.126	10,5 0.413	M6x1	4,5	1	G2.5	0,9 1.980
E9304540308120	03098281	HSK-A63	8,0 0.315	120,0 4.724	94,0 3.701	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	152,0 5.984	83,5 3.287	94,0 3.701	10,5 0.413	M6x1	4,5	1	G2.5	1,0 2.200
E9304540308160	03098282	HSK-A63	8,0 0.315	160,0 6.299	134,0 5.276	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	192,0 7.559	123,5 4.862	134,0 5.276	10,5 0.413	M6x1	4,5	1	G2.5	1,2 2.650
E930454031085	03098283	HSK-A63	10,0 0.394	85,0 3.346	59,0 2.323	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	117,0 4.606	43,0 1.693	54,0 2.126	13,0 0.512	M8x1	4,5	1	G2.5	0,9 1.980
E9304540310120	03098284	HSK-A63	10,0 0.394	120,0 4.724	94,0 3.701	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	152,0 5.984	78,0 3.071	89,0 3.504	13,0 0.512	M8x1	4,5	1	G2.5	1,1 2.430
E9304540310160	03098285	HSK-A63	10,0 0.394	160,0 6.299	134,0 5.276	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	192,0 7.559	118,0 4.646	129,0 5.079	13,0 0.512	M8x1	4,5	1	G2.5	1,4 3.090
E930454031290	03098286	HSK-A63	12,0 0.472	90,0 3.543	64,0 2.520	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	122,0 4.803	43,5 1.713	54,0 2.126	13,0 0.512	M10x1	4,5	1	G2.5	1,0 2.200
E9304540312120	03098287	HSK-A63	12,0 0.472	120,0 4.724	94,0 3.701	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	152,0 5.984	73,5 2.894	84,0 3.307	13,0 0.512	M10x1	4,5	1	G2.5	1,1 2.430
E9304540312160	03098288	HSK-A63	12,0 0.472	160,0 6.299	134,0 5.276	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	192,0 7.559	113,5 4.469	124,0 4.882	13,0 0.512	M10x1	4,5	1	G2.5	1,4 3.090
E930454031490	03098289	HSK-A63	14,0 0.551	90,0 3.543	64,0 2.520	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	122,0 4.803	42,5 1.673	54,0 2.126	14,0 0.551	M10x1	4,5	1	G2.5	1,0 2.200
E9304540314120	03098290	HSK-A63	14,0 0.551	120,0 4.724	94,0 3.701	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	152,0 5.984	72,5 2.854	84,0 3.307	14,0 0.551	M10x1	4,5	1	G2.5	1,2 2.650
E930454031695	03098291	HSK-A63	16,0 0.630	95,0 3.740	69,0 2.717	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	127,0 5.000	45,0 1.772	56,0 2.205	14,0 0.551	M12x1	4,5	1	G2.5	1,0 2.200
E9304540316120	03098292	HSK-A63	16,0 0.630	120,0 4.724	94,0 3.701	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	152,0 5.984	69,0 2.717	81,0 3.189	14,0 0.551	M12x1	4,5	1	G2.5	1,2 2.650
E9304540316160	03098293	HSK-A63	16,0 0.630	160,0 6.299	134,0 5.276	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	192,0 7.559	111,0 4.370	121,0 4.764	14,0 0.551	M12x1	4,5	1	G2.5	1,4 3.090

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

 Operating &
setting acces-
series

Shrinkfit

Guide																			
	Designation	Item number	CTMS	DCBN- DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
HSK-A	E930454031895	03098294	HSK-A63	18,0 0.709	95,0 3.740	69,0 2.717	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	127,0 5.000	44,5 1.752	56,0 2.205	18,0 0.709	M12x1	4,5	1	G2.5	1,2 2.650
	E9304540318120	03098295	HSK-A63	18,0 0.709	120,0 4.724	94,0 3.701	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	152,0 5.984	71,0 2.795	81,0 3.189	18,0 0.709	M12x1	4,5	1	G2.5	1,4 3.090
	E9304540320100	03098296	HSK-A63	20,0 0.787	100,0 3.937	74,0 2.913	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	132,0 5.197	47,5 1.870	59,0 2.323	18,0 0.709	M16x1	4,5	1	G2.5	1,2 2.650
HSK-E	E9304540320120	03098297	HSK-A63	20,0 0.787	120,0 4.724	94,0 3.701	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	152,0 5.984	67,5 2.657	79,0 3.110	18,0 0.709	M16x1	4,5	1	G2.5	1,4 3.090
	E9304540320160	03098298	HSK-A63	20,0 0.787	160,0 6.299	134,0 5.276	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	192,0 7.559	107,5 4.232	119,0 4.685	18,0 0.709	M16x1	4,5	1	G2.5	1,8 3.970
	E9304540325115	03098299	HSK-A63	25,0 0.984	115,0 4.528	89,0 3.504	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	147,0 5.787	58,0 2.283	68,0 2.677	23,5 0.925	M16x1	4,5	1	G2.5	1,8 3.970
DIN	E9304540325160	03098300	HSK-A63	25,0 0.984	160,0 6.299	134,0 5.276	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	192,0 7.559	98,0 3.858	113,0 4.449	23,5 0.925	M16x1	4,5	1	G2.5	2,5 5.510
	E9304540332120	03098301	HSK-A63	32,0 1.260	120,0 4.724	94,0 3.701	70,0 2.756	51,0 2.008	44,0 1.732	53,0 2.087	152,0 5.984	56,5 2.224	69,0 2.717	23,5 0.925	M16x1	4,5	1	G2.5	1,7 3.750
	E930654030685	03098308	HSK-A100	6,0 0.236	85,0 3.346	56,0 2.205	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	135,0 5.315	49,0 1.929	59,0 2.323	10,5 0.413	M5x0.8	4,5	1	G2.5	2,2 4.850
BT JIS	E9306540306120	03098309	HSK-A100	6,0 0.236	120,0 4.724	91,0 3.583	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	170,0 6.693	84,0 3.307	94,0 3.701	10,5 0.413	M5x0.8	4,5	1	G2.5	2,4 5.290
	E9306540306160	03098310	HSK-A100	6,0 0.236	160,0 6.299	131,0 5.157	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	210,0 8.268	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	G2.5	2,5 5.510
	E930654030885	03098311	HSK-A100	8,0 0.315	85,0 3.346	56,0 2.205	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	135,0 5.315	48,5 1.909	59,0 2.323	10,5 0.413	M6x1	4,5	1	G2.5	2,2 4.850
CAT	E9306540308120	03098312	HSK-A100	8,0 0.315	120,0 4.724	91,0 3.583	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	170,0 6.693	83,5 3.287	94,0 3.701	10,5 0.413	M6x1	4,5	1	G2.5	2,3 5.070
	E9306540308160	03098313	HSK-A100	8,0 0.315	160,0 6.299	131,0 5.157	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	210,0 8.268	123,5 4.862	134,0 5.276	10,5 0.413	M6x1	4,5	1	G2.5	2,5 5.510
	E930654031090	03098314	HSK-A100	10,0 0.394	90,0 3.543	61,0 2.402	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	140,0 5.512	48,0 1.890	59,0 2.323	13,0 0.512	M8x1	4,5	1	G2.5	2,3 5.070
Combimaster	E9306540310120	03098315	HSK-A100	10,0 0.394	120,0 4.724	91,0 3.583	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	170,0 6.693	78,0 3.071	89,0 3.504	13,0 0.512	M8x1	4,5	1	G2.5	2,5 5.510
	E9306540310160	03098316	HSK-A100	10,0 0.394	160,0 6.299	131,0 5.157	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	210,0 8.268	118,0 4.646	129,0 5.079	13,0 0.512	M8x1	4,5	1	G2.5	2,7 5.950
	E930654031295	03098317	HSK-A100	12,0 0.472	95,0 3.740	66,0 2.598	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	145,0 5.709	48,5 1.909	59,0 2.323	13,0 0.512	M10x1	4,5	1	G2.5	2,3 5.070
Graflex	E9306540312120	03098318	HSK-A100	12,0 0.472	120,0 4.724	91,0 3.583	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	170,0 6.693	73,5 2.894	86,0 3.386	13,0 0.512	M10x1	4,5	1	G2.5	2,4 5.290
	E9306540312160	03098319	HSK-A100	12,0 0.472	160,0 6.299	131,0 5.157	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	210,0 8.268	113,5 4.469	124,0 4.882	13,0 0.512	M10x1	4,5	1	G2.5	2,7 5.950
	E930654031495	03098320	HSK-A100	14,0 0.551	95,0 3.740	66,0 2.598	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	145,0 5.709	47,5 1.870	59,0 2.323	14,0 0.551	M10x1	4,5	1	G2.5	2,3 5.070
Seco Capto™	E9306540316100	03098321	HSK-A100	16,0 0.630	100,0 3.937	71,0 2.795	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	150,0 5.906	50,0 1.969	61,0 2.402	14,0 0.551	M12x1	4,5	1	G2.5	2,4 5.290
	E9306540316130	03098322	HSK-A100	16,0 0.630	130,0 5.118	101,0 3.976	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	180,0 7.087	78,0 3.071	91,0 3.583	14,0 0.551	M12x1	4,5	1	G2.5	2,5 5.510
	E9306540316160	03098323	HSK-A100	16,0 0.630	160,0 6.299	131,0 5.157	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	210,0 8.268	108,0 4.252	121,0 4.764	14,0 0.551	M12x1	4,5	1	G2.5	2,7 5.950
Others	E9306540318100	03098324	HSK-A100	18,0 0.709	100,0 3.937	71,0 2.795	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	150,0 5.906	51,0 2.008	61,0 2.402	18,0 0.709	M12x1	4,5	1	G2.5	2,5 5.510
	E9306540320105	03098325	HSK-A100	20,0 0.787	105,0 4.134	76,0 2.992	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	155,0 6.102	51,0 2.008	64,0 2.520	18,0 0.709	M16x1	4,5	1	G2.5	2,5 5.510
	E9306540320130	03098326	HSK-A100	20,0 0.787	130,0 5.118	101,0 3.976	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	180,0 7.087	77,5 3.051	89,0 3.504	18,0 0.709	M16x1	4,5	1	G2.5	2,8 6.170
Operating & setting accessories	E9306540320160	03098327	HSK-A100	20,0 0.787	160,0 6.299	131,0 5.157	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	210,0 8.268	107,5 4.232	119,0 4.685	18,0 0.709	M16x1	4,5	1	G2.5	3,1 6.830
	E9306540325115	03098328	HSK-A100	25,0 0.984	115,0 4.528	86,0 3.386	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	165,0 6.496	58,0 2.283	68,0 2.677	23,5 0.925	M16x1	4,5	1	G2.5	3,1 6.830
	E9306540325160	03098329	HSK-A100	25,0 0.984	160,0 6.299	131,0 5.157	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	210,0 8.268	103,0 4.055	113,0 4.449	23,5 0.925	M16x1	4,5	1	G2.5	3,8 8.380
Shrinkfit	E9306540332120	03098330	HSK-A100	32,0 1.260	120,0 4.724	91,0 3.583	70,0 2.756	51,0 2.008	44,0 1.732	53,0 2.087	170,0 6.693	56,5 2.224	69,0 2.717	23,5 0.925	M16x1	4,5	1	G2.5	2,9 6.390
	HSKA125-SFD06-160	03229645	HSK-A125	6,0 0.236	160,0 6.299	131,0 5.157	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	223,0 8.780	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	PB	3,9 8.600
	HSKA125-SFD08-160	03229646	HSK-A125	8,0 0.315	160,0 6.299	131,0 5.157	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	223,0 8.780	124,0 4.882	134,0 5.276	10,5 0.413	M6x1	4,5	1	PB	3,9 8.600
	HSKA125-SFD10-120	03229647	HSK-A125	10,0 0.394	120,0 4.724	91,0 3.583	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	183,0 7.205	79,0 3.110	89,0 3.504	13,0 0.512	M8x1	4,5	1	PB	3,8 8.380

Designation	Item number	CTMS	DCBN- DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
HSKA125-SFD10-160	03229648	HSK-A125	10,0 0.394	160,0 6.299	131,0 5.157	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	223,0 8.780	119,0 4.685	129,0 5.079	13,0 0.512	M8x1	4,5	1	PB	4,1 9.040
HSKA125-SFD10-200	03229649	HSK-A125	10,0 0.394	200,0 7.874	171,0 6.732	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	263,0 10.354	159,0 6.260	169,0 6.654	13,0 0.512	M8x1	4,5	1	PB	4,2 9.260
HSKA125-SFD12-120	03229650	HSK-A125	12,0 0.472	120,0 4.724	91,0 3.583	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	183,0 7.205	74,0 2.913	84,0 3.307	13,0 0.512	M10x1	4,5	1	PB	3,8 8.380
HSKA125-SFD12-160	03229651	HSK-A125	12,0 0.472	160,0 6.299	131,0 5.157	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	223,0 8.780	114,0 4.488	124,0 4.882	13,0 0.512	M10x1	4,5	1	PB	4,1 9.040
HSKA125-SFD12-200	03229652	HSK-A125	12,0 0.472	200,0 7.874	171,0 6.732	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	263,0 10.354	154,0 6.063	166,0 6.535	13,0 0.512	M10x1	4,5	1	PB	4,3 9.480

Accessories

For	Contact Bush
All	ZFAR10D306
All	ZFAR10D310
All	ZFAR10D314
All	ZFAR10D318
All	ZFAR10D325

Spare Parts, included in delivery

For	Stop screw
	
6/ 0.236	19BDR05165
8/ 0.315	19BDR06165
10/ 0.394	19BDR08165
12/ 0.472-14/ 0.551	19BDR10165
16/ 0.630-18/ 0.709	90/ 3.543-100/ 3.937
16/ 0.630-18/ 0.709	120/ 4.724-160/ 6.299
20/ 0.787	19BDR12165
25/ 0.984-32/ 1.260	19BDR12195
	19BDR16190
	19BDR16225

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
sories

Shrinkfit

DIN type
– Inch

HSK-A/ ISO12164-1-HSK-A



–Run-out $\leq 3 \mu\text{m}$
 –Delivered with one stop screw
 –For Shrinkfit extensions, see page(s) 357-358
 –For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
 –For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
E9304560302580	02753196	HSK-A63	0.250	3.150	2.126	1.476	0.866	0.827	1.063	4.409	1.732	2.126	0.413	M5x0.8	4,5	1	G2.5	1.980
E93045603025120	02753194	HSK-A63	0.250	4.724	3.701	1.476	0.866	0.827	1.063	5.984	3.307	3.701	0.413	M5x0.8	4,5	1	G2.5	2.200
E9304560303785	02753198	HSK-A63	0.375	3.346	2.323	1.673	1.220	0.945	1.260	4.606	1.732	2.126	0.512	M8x1	4,5	1	G2.5	1.980
E93045603037120	02753197	HSK-A63	0.375	4.724	3.701	1.673	1.220	0.945	1.260	5.984	3.110	3.504	0.512	M8x1	4,5	1	G2.5	2.650
E9304560305090	02753202	HSK-A63	0.500	3.543	2.520	1.791	1.339	0.945	1.260	4.803	1.811	2.205	0.512	M10x1	4,5	1	G2.5	1.980
E93045603050120	02753200	HSK-A63	0.500	4.724	3.701	1.791	1.339	0.945	1.260	5.984	2.992	3.386	0.512	M10x1	4,5	1	G2.5	2.430
E9304560306295	02753204	HSK-A63	0.625	3.740	2.717	1.988	1.535	1.063	1.339	5.000	1.811	2.205	0.551	M12x1	4,5	1	G2.5	2.200
E93045603062120	02753203	HSK-A63	0.625	4.724	3.701	1.988	1.535	1.063	1.339	5.984	2.795	3.189	0.551	M12x1	4,5	1	G2.5	2.650
E93045603075100	02753206	HSK-A63	0.750	3.937	2.913	2.067	1.614	1.299	1.654	5.197	1.929	2.323	0.709	M16x1	4,5	1	G2.5	2.650
E93045603100115	02753208	HSK-A63	1.000	4.528	3.504	2.303	1.850	1.732	2.087	5.787	2.283	2.677	0.925	M16x1	4,5	1	G2.5	3.970
E9306560302585	02753212	HSK-A100	0.250	3.346	2.205	1.476	0.866	0.827	1.063	5.315	1.929	2.323	0.413	M5x0.8	4,5	1	G2.5	4.850
E93065603025160	02753211	HSK-A100	0.250	6.299	5.157	1.476	0.866	0.827	1.063	8.268	4.882	5.276	0.413	M5x0.8	4,5	1	G2.5	5.510
E9306560303785	02753214	HSK-A100	0.375	3.346	2.205	1.673	1.220	0.945	1.260	5.315	1.732	2.126	0.512	M8x1	4,5	1	G2.5	5.070
E93065603037160	02753213	HSK-A100	0.375	6.299	5.157	1.673	1.220	0.945	1.260	8.268	4.685	5.079	0.512	M8x1	4,5	1	G2.5	5.950
E9306560305095	02753216	HSK-A100	0.500	3.740	2.598	1.791	1.339	0.945	1.260	5.709	2.008	2.402	0.512	M10x1	4,5	1	G2.5	5.070
E93065603050160	02753215	HSK-A100	0.500	6.299	5.157	1.791	1.339	0.945	1.260	8.268	4.567	4.961	0.512	M10x1	4,5	1	G2.5	5.950
E93065603062100	02753217	HSK-A100	0.625	3.937	2.795	1.988	1.535	1.063	1.339	5.906	2.008	2.402	0.551	M12x1	4,5	1	G2.5	5.290
E93065603062160	02753218	HSK-A100	0.625	6.299	5.157	1.988	1.535	1.063	1.339	8.268	4.370	4.764	0.551	M12x1	4,5	1	G2.5	5.950
E93065603075105	02753219	HSK-A100	0.750	4.134	2.992	2.067	1.614	1.299	1.654	6.102	2.126	2.520	0.709	M16x1	4,5	1	G2.5	5.730
E93065603075130	02753220	HSK-A100	0.750	5.118	3.976	2.067	1.614	1.299	1.654	7.087	3.110	3.504	0.709	M16x1	4,5	1	G2.5	6.170
E93065603075160	02753221	HSK-A100	0.750	6.299	5.157	2.067	1.614	1.299	1.654	8.268	4.291	4.685	0.709	M16x1	4,5	1	G2.5	6.830
E93065603100115	02753223	HSK-A100	1.000	4.528	3.386	2.303	1.850	1.732	2.087	6.496	2.283	2.677	0.925	M16x1	4,5	1	G2.5	6.830
E93065603100160	02753224	HSK-A100	1.000	6.299	5.157	2.303	1.850	1.732	2.087	8.268	4.055	4.449	0.925	M16x1	4,5	1	G2.5	8.380
E93065603125120	02753225	HSK-A100	1.250	4.724	3.583	2.461	2.008	1.732	2.087	6.693	2.323	2.717	0.925	M16x1	4,5	1	G2.5	6.610
HSKA125-SFD0.375-4.000	03229686	HSK-A125	0.375	4.000	2.858	1.673	1.220	0.945	1.260	6.480	2.386	2.780	0.512	M8x1	4,5	1	PB	8.160
HSKA125-SFD0.375-6.250	03229688	HSK-A125	0.375	6.250	5.108	1.673	1.220	0.945	1.260	8.730	4.636	5.030	0.512	M8x1	4,5	1	PB	9.040
HSKA125-SFD0.500-4.000	03229689	HSK-A125	0.500	4.000	2.858	1.791	1.339	0.945	1.260	6.480	2.268	2.661	0.512	M10x1	4,5	1	PB	8.160
HSKA125-SFD0.500-6.250	03229691	HSK-A125	0.500	6.250	5.108	1.791	1.339	0.945	1.260	8.730	4.518	4.911	0.512	M10x1	4,5	1	PB	9.480

Accessories

For	Balancing screws
	

All	90ZQ01
-----	--------

Spare Parts, included in delivery

For	Stop screw
	

0.250 - 0.625	19BDR05165
0.375	19BDR08165
0.500	19BDR10165
0.625	19BDR12165
0.750 - 1.250	19BDR16165

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

DIN type, with peripheral coolant channels
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (not plugged)
- Delivered with one stop screw
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

BT JIS																				
	Designation	Item number	CTMS	DCBN-DCBX		LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
				mm inch	mm inch															
CAT	E930454020680	03157532	HSK-A63	6,0 0.236	80,0 3.150	54,0 2.126	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	112,0 4.409	44,0 1.732	54,0 2.126	10,5 0.413	M5x0.8	4,5	1	G2.5	0,9 1.980	
	E9304540206120	03180054	HSK-A63	6,0 0.236	120,0 4.724	94,0 3.701	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	152,0 5.984	84,0 3.307	94,0 3.701	10,5 0.413	M5x0.8	4,5	1	G2.5	1,0 2.200	
	E9304540206160	03157529	HSK-A63	6,0 0.236	160,0 6.299	134,0 5.276	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	192,0 7.559	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	G2.5	1,2 2.650	
Combimaster	E930454020880	03157533	HSK-A63	8,0 0.315	80,0 3.150	54,0 2.126	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	112,0 4.409	43,5 1.713	54,0 2.126	10,5 0.413	M6x1	4,5	1	G2.5	0,9 1.980	
	E9304540208120	03180055	HSK-A63	8,0 0.315	120,0 4.724	94,0 3.701	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	152,0 5.984	83,5 3.287	94,0 3.701	10,5 0.413	M6x1	4,5	1	G2.5	1,0 2.200	
	E9304540208160	03180056	HSK-A63	8,0 0.315	160,0 6.299	134,0 5.276	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	192,0 7.559	123,5 4.862	134,0 5.276	10,5 0.413	M6x1	4,5	1	G2.5	1,2 2.650	
Graflex	E930454021085	03157537	HSK-A63	10,0 0.394	85,0 3.346	59,0 2.323	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	117,0 4.606	43,0 1.693	54,0 2.126	13,0 0.512	M8x1	4,5	1	G2.5	0,9 1.980	
	E9304540210120	03180057	HSK-A63	10,0 0.394	120,0 4.724	94,0 3.701	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	152,0 5.984	78,0 3.071	89,0 3.504	13,0 0.512	M8x1	4,5	1	G2.5	1,1 2.430	
	E9304540210160	03157534	HSK-A63	10,0 0.394	160,0 6.299	134,0 5.276	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	192,0 7.559	118,0 4.646	129,0 5.079	13,0 0.512	M8x1	4,5	1	G2.5	1,4 3.090	
Seco Capto™	E930454021290	03157538	HSK-A63	12,0 0.472	90,0 3.543	64,0 2.520	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	122,0 4.803	43,5 1.713	54,0 2.126	13,0 0.512	M10x1	4,5	1	G2.5	0,9 1.980	
	E9304540212120	03180058	HSK-A63	12,0 0.472	120,0 4.724	94,0 3.701	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	152,0 5.984	73,5 2.894	84,0 3.307	13,0 0.512	M10x1	4,5	1	G2.5	1,1 2.430	
	E9304540212160	03180059	HSK-A63	12,0 0.472	160,0 6.299	134,0 5.276	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	192,0 7.559	113,5 4.469	124,0 4.882	13,0 0.512	M10x1	4,5	1	G2.5	1,3 2.870	
Others	E930454021490	03180060	HSK-A63	14,0 0.551	90,0 3.543	64,0 2.520	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	122,0 4.803	42,5 1.673	54,0 2.126	14,0 0.551	M10x1	4,5	1	G2.5	1,0 2.200	
	E9304540214120	03180061	HSK-A63	14,0 0.551	120,0 4.724	94,0 3.701	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	152,0 5.984	72,5 2.854	84,0 3.307	14,0 0.551	M10x1	4,5	1	G2.5	1,2 2.650	
	E930454021695	03157541	HSK-A63	16,0 0.630	95,0 3.740	69,0 2.717	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	127,0 5.000	45,0 1.772	56,0 2.205	14,0 0.551	M12x1	4,5	1	G2.5	1,0 2.200	
Operating & setting accessories	E9304540216120	03180062	HSK-A63	16,0 0.630	120,0 4.724	94,0 3.701	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	152,0 5.984	69,0 2.717	81,0 3.189	14,0 0.551	M12x1	4,5	1	G2.5	1,2 2.650	
	E9304540216160	03157539	HSK-A63	16,0 0.630	160,0 6.299	134,0 5.276	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	192,0 7.559	111,0 4.370	121,0 4.764	14,0 0.551	M12x1	4,5	1	G2.5	1,4 3.090	
	E930454021895	03180063	HSK-A63	18,0 0.709	95,0 3.740	69,0 2.717	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	127,0 5.000	44,5 1.752	56,0 2.205	18,0 0.709	M12x1	4,5	1	G2.5	1,2 2.650	
Shrinkfit	E9304540218120	03180064	HSK-A63	18,0 0.709	120,0 4.724	94,0 3.701	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	152,0 5.984	71,0 2.795	81,0 3.189	18,0 0.709	M12x1	4,5	1	G2.5	1,4 3.090	
	E9304540220100	03157543	HSK-A63	20,0 0.787	100,0 3.937	74,0 2.913	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	132,0 5.197	47,5 1.870	59,0 2.323	18,0 0.709	M16x1	4,5	1	G2.5	1,2 2.650	
	E9304540220120	03180065	HSK-A63	20,0 0.787	120,0 4.724	94,0 3.701	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	152,0 5.984	67,5 2.657	79,0 3.110	18,0 0.709	M16x1	4,5	1	G2.5	1,4 3.090	
	E9304540220160	03180066	HSK-A63	20,0 0.787	160,0 6.299	134,0 5.276	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	192,0 7.559	107,5 4.232	119,0 4.685	18,0 0.709	M16x1	4,5	1	G2.5	1,8 3.970	

Designation	Item number	CTMS	DCBN- DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight	Guide
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs	
E9304540225115	03180067	HSK-A63	25,0 0.984	115,0 4.528	89,0 3.504	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	147,0 5.787	58,0 2.283	68,0 2.677	23,5 0.925	M16x1	4,5	1	G2.5	1,8 3.970	HSK-A
E9304540225160	03180068	HSK-A63	25,0 0.984	160,0 6.299	134,0 5.276	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	192,0 7.559	98,0 3.858	113,0 4.449	23,5 0.925	M16x1	4,5	1	G2.5	2,5 5.510	
E9304540232120	03180069	HSK-A63	32,0 1.260	120,0 4.724	94,0 3.701	70,0 2.756	51,0 2.008	44,0 1.732	53,0 2.087	152,0 5.984	56,5 2.224	69,0 2.717	23,5 0.925	M16x1	4,5	1	G2.5	1,7 3.750	
E930654020685	03180070	HSK-A100	6,0 0.236	85,0 3.346	56,0 2.205	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	135,0 5.315	49,0 1.929	59,0 2.323	10,5 0.413	M5x0.8	4,5	1	G2.5	2,2 4.850	HSK-E
E9306540206120	03168473	HSK-A100	6,0 0.236	120,0 4.724	91,0 3.583	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	170,0 6.693	84,0 3.307	94,0 3.701	10,5 0.413	M5x0.8	4,5	1	G2.5	2,4 5.290	
E9306540206160	03180071	HSK-A100	6,0 0.236	160,0 6.299	131,0 5.157	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	210,0 8.268	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	G2.5	2,5 5.510	
E930654020885	03180072	HSK-A100	8,0 0.315	85,0 3.346	56,0 2.205	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	135,0 5.315	48,5 1.909	59,0 2.323	10,5 0.413	M6x1	4,5	1	G2.5	2,2 4.850	DIN
E9306540208120	03168475	HSK-A100	8,0 0.315	120,0 4.724	91,0 3.583	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	170,0 6.693	83,5 3.287	94,0 3.701	10,5 0.413	M6x1	4,5	1	G2.5	2,4 5.290	
E9306540208160	03180073	HSK-A100	8,0 0.315	160,0 6.299	131,0 5.157	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	210,0 8.268	123,5 4.862	134,0 5.276	10,5 0.413	M6x1	4,5	1	G2.5	2,5 5.510	
E930654021090	03180074	HSK-A100	10,0 0.394	90,0 3.543	61,0 2.402	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	140,0 5.512	48,0 1.890	59,0 2.323	13,0 0.512	M8x1	4,5	1	G2.5	2,3 5.070	BT JIS
E9306540210120	03168476	HSK-A100	10,0 0.394	120,0 4.724	91,0 3.583	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	170,0 6.693	78,0 3.071	89,0 3.504	13,0 0.512	M8x1	4,5	1	G2.5	2,5 5.510	
E9306540210160	03180075	HSK-A100	10,0 0.394	160,0 6.299	131,0 5.157	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	210,0 8.268	118,0 4.646	129,0 5.079	13,0 0.512	M8x1	4,5	1	G2.5	2,7 5.950	
E930654021295	03180076	HSK-A100	12,0 0.472	95,0 3.740	66,0 2.598	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	145,0 5.709	48,5 1.909	59,0 2.323	13,0 0.512	M10x1	4,5	1	G2.5	2,3 5.070	CAT
E9306540212120	03167256	HSK-A100	12,0 0.472	120,0 4.724	91,0 3.583	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	170,0 6.693	73,5 2.894	86,0 3.386	13,0 0.512	M10x1	4,5	1	G2.5	2,4 5.290	
E9306540212160	03180077	HSK-A100	12,0 0.472	160,0 6.299	131,0 5.157	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	210,0 8.268	113,5 4.469	124,0 4.882	13,0 0.512	M10x1	4,5	1	G2.5	2,7 5.950	
E930654021495	03180078	HSK-A100	14,0 0.551	95,0 3.740	66,0 2.598	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	145,0 5.709	47,5 1.870	59,0 2.323	14,0 0.551	M10x1	4,5	1	G2.5	2,3 5.070	Combimaster
E9306540216100	03180079	HSK-A100	16,0 0.630	100,0 3.937	71,0 2.795	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	150,0 5.906	50,0 1.969	61,0 2.402	14,0 0.551	M12x1	4,5	1	G2.5	2,3 5.070	
E9306540216130	03180080	HSK-A100	16,0 0.630	130,0 5.118	101,0 3.976	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	180,0 7.087	78,0 3.071	91,0 3.583	14,0 0.551	M12x1	4,5	1	G2.5	2,5 5.510	
E9306540216160	03180081	HSK-A100	16,0 0.630	160,0 6.299	131,0 5.157	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	210,0 8.268	108,0 4.252	121,0 4.764	14,0 0.551	M12x1	4,5	1	G2.5	2,7 5.950	Graflex
E9306540218100	03180082	HSK-A100	18,0 0.709	100,0 3.937	71,0 2.795	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	150,0 5.906	52,5 2.067	61,0 2.402	18,0 0.709	M12x1	4,5	1	G2.5	2,5 5.510	
E9306540220105	03180083	HSK-A100	20,0 0.787	105,0 4.134	76,0 2.992	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	155,0 6.102	51,0 2.008	64,0 2.520	18,0 0.709	M16x1	4,5	1	G2.5	2,6 5.730	
E9306540220130	03180084	HSK-A100	20,0 0.787	130,0 5.118	101,0 3.976	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	180,0 7.087	77,5 3.051	89,0 3.504	18,0 0.709	M16x1	4,5	1	G2.5	2,5 5.510	Seco Capto™
E9306540220160	03180085	HSK-A100	20,0 0.787	160,0 6.299	131,0 5.157	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	210,0 8.268	107,5 4.232	119,0 4.685	18,0 0.709	M16x1	4,5	1	G2.5	3,1 6.830	
E9306540225115	03180087	HSK-A100	25,0 0.984	115,0 4.528	86,0 3.386	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	165,0 6.496	58,0 2.283	68,0 2.677	23,5 0.925	M16x1	4,5	1	G2.5	3,1 6.830	
E9306540225160	03180088	HSK-A100	25,0 0.984	160,0 6.299	131,0 5.157	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	210,0 8.268	103,0 4.055	113,0 4.449	23,5 0.925	M16x1	4,5	1	G2.5	3,8 8.380	Others
E9306540232120	03180089	HSK-A100	32,0 1.260	120,0 4.724	91,0 3.583	70,0 2.756	51,0 2.008	44,0 1.732	53,0 2.087	170,0 6.693	56,5 2.224	69,0 2.717	23,5 0.925	M16x1	4,5	1	G2.5	3,0 6.610	

Accessories

For	Balancing screws		90ZQ01
All			

Operating &
setting acces-
series


Shrinkfit

Spare Parts, included in delivery

Guide	For		Stop screw
			
HSK-A	6/ 0.236		19BDR05165
	8/ 0.315		19BDR06165
	10/ 0.394		19BDR08165
	12/ 0.472-14/ 0.551		19BDR10165
HSK-E	16/ 0.630-18/ 0.709 95/ 3.740-100/ 3.937		19BDR12165
	16/ 0.630-18/ 0.709 120/ 4.724-160/ 6.299		19BDR12195
	20/ 0.787		19BDR16190
	25/ 0.984-32/ 1.260		19BDR16225
DIN			
BT JIS			
CAT			
Combimaster			
Graflex			
Seco Capto™			
Others			
Operating & setting accessories			
Shrinkfit			

MQL 1, DIN type – DIN 69090-3 – Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



- Run-out $\leq 3 \mu\text{m}$
- Designed for MQL1, accessories to be ordered separately
- For MQL1 coolant tubes and stop screws, see page(s) 371-372
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E930454030680M	03098401	HSK-A63	6,0 0.236	80,0 3.150	54,0 2.126	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	112,0 4.409	10,5 0.413	M5x0.8	4,5	1	G2.5	0,9 1.980
E9304540306120M	03098402	HSK-A63	6,0 0.236	120,0 4.724	94,0 3.701	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	152,0 5.984	10,5 0.413	M5x0.8	4,5	1	G2.5	1,1 2.430
E9304540306160M	03098403	HSK-A63	6,0 0.236	160,0 6.299	134,0 5.276	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	192,0 7.559	10,5 0.413	M5x0.8	4,5	1	G2.5	1,2 2.650
E930454030880M	03098404	HSK-A63	8,0 0.315	80,0 3.150	54,0 2.126	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	112,0 4.409	10,5 0.413	M6x1	4,5	1	G2.5	0,9 1.980
E9304540308120M	03098405	HSK-A63	8,0 0.315	120,0 4.724	94,0 3.701	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	152,0 5.984	10,5 0.413	M6x1	4,5	1	G2.5	1,0 2.200
E9304540308160M	03098406	HSK-A63	8,0 0.315	160,0 6.299	134,0 5.276	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	192,0 7.559	10,5 0.413	M6x1	4,5	1	G2.5	1,2 2.650
E930454031085M	03098407	HSK-A63	10,0 0.394	85,0 3.346	59,0 2.323	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	117,0 4.606	13,0 0.512	M8x1	4,5	1	G2.5	0,9 1.980
E9304540310120M	03098408	HSK-A63	10,0 0.394	120,0 4.724	94,0 3.701	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	152,0 5.984	13,0 0.512	M8x1	4,5	1	G2.5	1,2 2.650
E9304540310160M	03098409	HSK-A63	10,0 0.394	160,0 6.299	134,0 5.276	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	192,0 7.559	13,0 0.512	M8x1	4,5	1	G2.5	1,4 3.090
E930454031290M	03098410	HSK-A63	12,0 0.472	90,0 3.543	64,0 2.520	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	122,0 4.803	13,0 0.512	M10x1	4,5	1	G2.5	0,9 1.980
E9304540312120M	03098411	HSK-A63	12,0 0.472	120,0 4.724	94,0 3.701	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	152,0 5.984	13,0 0.512	M10x1	4,5	1	G2.5	1,1 2.430
E9304540312160M	03098412	HSK-A63	12,0 0.472	160,0 6.299	134,0 5.276	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	192,0 7.559	13,0 0.512	M10x1	4,5	1	G2.5	1,4 3.090
E930454031490M	03098413	HSK-A63	14,0 0.551	90,0 3.543	64,0 2.520	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	122,0 4.803	14,0 0.551	M10x1	4,5	1	G2.5	1,0 2.200
E9304540314120M	03098414	HSK-A63	14,0 0.551	120,0 4.724	94,0 3.701	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	152,0 5.984	14,0 0.551	M10x1	4,5	1	G2.5	1,2 2.650
E930454031695M	03098415	HSK-A63	16,0 0.630	95,0 3.740	69,0 2.717	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	127,0 5.000	14,0 0.551	M10x1	4,5	1	G2.5	1,1 2.430
E9304540316120M	03098416	HSK-A63	16,0 0.630	120,0 4.724	94,0 3.701	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	152,0 5.984	14,0 0.551	M10x1	4,5	1	G2.5	1,2 2.650
E9304540316160M	03098417	HSK-A63	16,0 0.630	160,0 6.299	134,0 5.276	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	192,0 7.559	14,0 0.551	M10x1	4,5	1	G2.5	1,5 3.310
E930454031895M	03098418	HSK-A63	18,0 0.709	95,0 3.740	69,0 2.717	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	127,0 5.000	18,0 0.709	M10x1	4,5	1	G2.5	1,2 2.650
E9304540318120M	03098419	HSK-A63	18,0 0.709	120,0 4.724	94,0 3.701	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	152,0 5.984	18,0 0.709	M10x1	4,5	1	G2.5	1,5 3.310
E9304540320100M	03098420	HSK-A63	20,0 0.787	100,0 3.937	74,0 2.913	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	132,0 5.197	18,0 0.709	M10x1	4,5	1	G2.5	1,2 2.650
E9304540320120M	03098421	HSK-A63	20,0 0.787	120,0 4.724	94,0 3.701	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	152,0 5.984	18,0 0.709	M10x1	4,5	1	G2.5	1,4 3.090
E9304540320160M	03098422	HSK-A63	20,0 0.787	160,0 6.299	134,0 5.276	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	192,0 7.559	18,0 0.709	M10x1	4,5	1	G2.5	1,8 3.970

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

Guide																	
	Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
HSK-A	E9304540325115M	03098423	HSK-A63	25,0 0.984	115,0 4.528	89,0 3.504	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	147,0 5.787	23,5 0.925	M10x1	4,5	1	G2.5	1,8 3.970
	E9304540325160M	03098424	HSK-A63	25,0 0.984	160,0 6.299	134,0 5.276	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	192,0 7.559	23,5 0.925	M10x1	4,5	1	G2.5	2,5 5.510
	E9304540332120M	03098425	HSK-A63	32,0 1.260	120,0 4.724	94,0 3.701	70,0 2.756	51,0 2.008	44,0 1.732	53,0 2.087	152,0 5.984	23,5 0.925	M10x1	4,5	1	G2.5	1,6 3.530
HSK-E	E930654030685M	03098582	HSK-A100	6,0 0.236	85,0 3.346	56,0 2.205	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	135,0 5.315	10,5 0.413	M5x0.8	4,5	1	G2.5	2,2 4.850
	E9306540306120M	03098583	HSK-A100	6,0 0.236	120,0 4.724	91,0 3.583	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	170,0 6.693	10,5 0.413	M5x0.8	4,5	1	G2.5	2,4 5.290
	E9306540306160M	03098584	HSK-A100	6,0 0.236	160,0 6.299	131,0 5.157	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	210,0 8.268	10,5 0.413	M5x0.8	4,5	1	G2.5	2,0 4.410
DIN	E930654030885M	03098585	HSK-A100	8,0 0.315	85,0 3.346	56,0 2.205	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	135,0 5.315	10,5 0.413	M6x1	4,5	1	G2.5	2,2 4.850
	E9306540308120M	03098586	HSK-A100	8,0 0.315	120,0 4.724	91,0 3.583	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	170,0 6.693	10,5 0.413	M6x1	4,5	1	G2.5	2,4 5.290
	E9306540308160M	03098587	HSK-A100	8,0 0.315	160,0 6.299	131,0 5.157	38,0 1.496	26,0 1.024	21,0 0.827	27,0 1.063	210,0 8.268	10,5 0.413	M6x1	4,5	1	G2.5	2,6 5.730
BT JIS	E930654031090M	03098588	HSK-A100	10,0 0.394	90,0 3.543	61,0 2.402	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	140,0 5.512	13,0 0.512	M8x1	4,5	1	G2.5	2,3 5.070
	E9306540310120M	03098589	HSK-A100	10,0 0.394	120,0 4.724	91,0 3.583	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	170,0 6.693	13,0 0.512	M8x1	4,5	1	G2.5	2,0 4.410
	E9306540310160M	03098590	HSK-A100	10,0 0.394	160,0 6.299	131,0 5.157	43,5 1.713	31,0 1.220	24,0 0.945	32,0 1.260	210,0 8.268	13,0 0.512	M8x1	4,5	1	G2.5	2,9 6.390
CAT	E930654031295M	03098591	HSK-A100	12,0 0.472	95,0 3.740	66,0 2.598	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	145,0 5.709	13,0 0.512	M10x1	4,5	1	G2.5	2,3 5.070
	E9306540312120M	03098592	HSK-A100	12,0 0.472	120,0 4.724	91,0 3.583	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	170,0 6.693	13,0 0.512	M10x1	4,5	1	G2.5	2,5 5.510
	E9306540312160M	03098593	HSK-A100	12,0 0.472	160,0 6.299	131,0 5.157	48,0 1.890	34,0 1.339	24,0 0.945	32,0 1.260	210,0 8.268	13,0 0.512	M10x1	4,5	1	G2.5	2,7 5.950
Combimaster	E930654031495M	03098594	HSK-A100	14,0 0.551	95,0 3.740	66,0 2.598	49,0 1.929	34,0 1.339	27,0 1.063	34,0 1.339	145,0 5.709	14,0 0.551	M10x1	4,5	1	G2.5	2,4 5.290
	E9306540316100M	03098595	HSK-A100	16,0 0.630	100,0 3.937	71,0 2.795	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	150,0 5.906	14,0 0.551	M10x1	4,5	1	G2.5	2,4 5.290
	E9306540316130M	03098596	HSK-A100	16,0 0.630	130,0 5.118	101,0 3.976	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	180,0 7.087	14,0 0.551	M10x1	4,5	1	G2.5	2,6 5.730
Graflex	E9306540316160M	03098597	HSK-A100	16,0 0.630	160,0 6.299	131,0 5.157	52,5 2.067	39,0 1.535	27,0 1.063	34,0 1.339	210,0 8.268	14,0 0.551	M10x1	4,5	1	G2.5	2,9 6.390
	E9306540318100M	03098598	HSK-A100	18,0 0.709	100,0 3.937	71,0 2.795	53,0 2.087	39,0 1.535	33,0 1.299	42,0 1.654	150,0 5.906	18,0 0.709	M10x1	4,5	1	G2.5	2,6 5.730
	E9306540320105M	03098599	HSK-A100	20,0 0.787	105,0 4.134	76,0 2.992	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	155,0 6.102	18,0 0.709	M10x1	4,5	1	G2.5	2,6 5.730
Seco Capto™	E9306540320130M	03098600	HSK-A100	20,0 0.787	130,0 5.118	101,0 3.976	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	180,0 7.087	18,0 0.709	M10x1	4,5	1	G2.5	2,8 6.170
	E9306540320160M	03098601	HSK-A100	20,0 0.787	160,0 6.299	131,0 5.157	55,5 2.185	41,0 1.614	33,0 1.299	42,0 1.654	210,0 8.268	18,0 0.709	M10x1	4,5	1	G2.5	3,3 7.280
	E9306540325115M	03098602	HSK-A100	25,0 0.984	115,0 4.528	86,0 3.386	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	165,0 6.496	23,5 0.925	M10x1	4,5	1	G2.5	3,1 6.830
Others	E9306540325160M	03098603	HSK-A100	25,0 0.984	160,0 6.299	131,0 5.157	63,5 2.500	47,0 1.850	44,0 1.732	53,0 2.087	210,0 8.268	23,5 0.925	M10x1	4,5	1	G2.5	3,8 8.380
	E9306540332120M	03098604	HSK-A100	32,0 1.260	120,0 4.724	91,0 3.583	70,0 2.756	51,0 2.008	44,0 1.732	53,0 2.087	170,0 6.693	23,5 0.925	M10x1	4,5	1	G2.5	3,1 6.830
Accessories																	
For																	
Balancing screws																	
																	
All																	
90ZQ01																	

MQL 1, DIN type – DIN 69090-3
 – Metric/ Inch

HSK-A/ ISO12164-1-HSK-A


- Run-out $\leq 3 \mu\text{m}$
- Delivered ready for MQL1 with stop screw and coolant tube fitted
- For MQL1 coolant tubes and stop screws, see page(s) 371-372
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LFN	LF	TDZ	Weight	Tool holders	Coolant tube MQL1	Stop screw MQL1
			mm inch	mm inch	mm inch	mm inch	mm inch		kg lbs			
E930454030680M1	03098623	HSK-A63	6,0 0.236	80,0 3.150	54,0 2.126	44,0 1.732	54,0 2.126	M5x0.8	0,9 1.980	E930454030680M	20E9304	19MQL106S
E9304540306120M1	03098624	HSK-A63	6,0 0.236	120,0 4.724	94,0 3.701	84,0 3.307	94,0 3.701	M5x0.8	1,1 2.430	E9304540306120M	20E9304	19MQL106L
E9304540306160M1	03098625	HSK-A63	6,0 0.236	160,0 6.299	134,0 5.276	124,0 4.882	134,0 5.276	M5x0.8	1,3 2.870	E9304540306160M	20E9304	19MQL106L
E930454030880M1	03098626	HSK-A63	8,0 0.315	80,0 3.150	54,0 2.126	44,0 1.732	54,0 2.126	M6x1	0,9 1.980	E930454030880M	20E9304	19MQL108S
E9304540308120M1	03098627	HSK-A63	8,0 0.315	120,0 4.724	94,0 3.701	84,0 3.307	94,0 3.701	M6x1	1,1 2.430	E9304540308120M	20E9304	19MQL108L
E9304540308160M1	03098628	HSK-A63	8,0 0.315	160,0 6.299	134,0 5.276	124,0 4.882	134,0 5.276	M6x1	1,2 2.650	E9304540308160M	20E9304	19MQL108L
E930454031085M1	03098629	HSK-A63	10,0 0.394	85,0 3.346	59,0 2.323	44,0 1.732	54,0 2.126	M8x1	1,0 2.200	E930454031085M	20E9304	19MQL110S
E9304540310120M1	03098630	HSK-A63	10,0 0.394	120,0 4.724	94,0 3.701	79,0 3.110	89,0 3.504	M8x1	1,2 2.650	E9304540310120M	20E9304	19MQL110L
E9304540310160M1	03098631	HSK-A63	10,0 0.394	160,0 6.299	134,0 5.276	119,0 4.685	129,0 5.079	M8x1	1,4 3.090	E9304540310160M	20E9304	19MQL110L
E930454031290M1	03098632	HSK-A63	12,0 0.472	90,0 3.543	64,0 2.520	44,0 1.732	54,0 2.126	M10x1	1,0 2.200	E930454031290M	20E9304	19MQL112S
E9304540312120M1	03098633	HSK-A63	12,0 0.472	120,0 4.724	94,0 3.701	74,0 2.913	84,0 3.307	M10x1	1,2 2.650	E9304540312120M	20E9304	19MQL112L
E9304540312160M1	03098634	HSK-A63	12,0 0.472	160,0 6.299	134,0 5.276	114,0 4.488	124,0 4.882	M10x1	1,4 3.090	E9304540312160M	20E9304	19MQL112L
E930454031490M1	03098635	HSK-A63	14,0 0.551	90,0 3.543	64,0 2.520	44,0 1.732	54,0 2.126	M10x1	1,1 2.430	E930454031490M	20E9304	19MQL114S
E9304540314120M1	03098636	HSK-A63	14,0 0.551	120,0 4.724	94,0 3.701	74,0 2.913	84,0 3.307	M10x1	1,0 2.200	E9304540314120M	20E9304	19MQL114L
E930454031695M1	03098637	HSK-A63	16,0 0.630	95,0 3.740	69,0 2.717	46,0 1.811	56,0 2.205	M10x1	1,1 2.430	E930454031695M	20E9304	19MQL116S
E9304540316120M1	03098638	HSK-A63	16,0 0.630	120,0 4.724	94,0 3.701	71,0 2.795	81,0 3.189	M10x1	1,2 2.650	E9304540316120M	20E9304	19MQL116L
E9304540316160M1	03098639	HSK-A63	16,0 0.630	160,0 6.299	134,0 5.276	111,0 4.370	121,0 4.764	M10x1	1,5 3.310	E9304540316160M	20E9304	19MQL116L
E930454031895M1	03098640	HSK-A63	18,0 0.709	95,0 3.740	69,0 2.717	46,0 1.811	56,0 2.205	M10x1	1,2 2.650	E930454031895M	20E9304	19MQL118S
E9304540318120M1	03098641	HSK-A63	18,0 0.709	120,0 4.724	94,0 3.701	71,0 2.795	81,0 3.189	M10x1	1,5 3.310	E9304540318120M	20E9304	19MQL118L
E9304540320100M1	03098642	HSK-A63	20,0 0.787	100,0 3.937	74,0 2.913	49,0 1.929	59,0 2.323	M10x1	1,3 2.870	E9304540320100M	20E9304	19MQL120S
E9304540320120M1	03098643	HSK-A63	20,0 0.787	120,0 4.724	94,0 3.701	69,0 2.717	79,0 3.110	M10x1	1,4 3.090	E9304540320120M	20E9304	19MQL120L
E9304540320160M1	03098644	HSK-A63	20,0 0.787	160,0 6.299	134,0 5.276	109,0 4.291	119,0 4.685	M10x1	1,9 4.190	E9304540320160M	20E9304	19MQL120L

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating & setting accessories

Shrinkfit

Guide													
	Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LFN	LF	TDZ	Weight	Tool holders	Coolant tube MQL1	Stop screw MQL1
				mm inch	mm inch	mm inch	mm inch	mm inch		kg lbs			
HSK-A	E9304540325115M1	03098645	HSK-A63	25,0 0.984	115,0 4.528	89,0 3.504	58,0 2.283	68,0 2.677	M10x1	1,8 3.970	E9304540325115M	20E9304	19MQL125S
	E9304540325160M1	03098646	HSK-A63	25,0 0.984	160,0 6.299	134,0 5.276	103,0 4.055	113,0 4.449	M10x1	2,6 5.730	E9304540325160M	20E9304	19MQL125L
	E9304540332120M1	03098647	HSK-A63	32,0 1.260	120,0 4.724	94,0 3.701	59,0 2.323	69,0 2.717	M10x1	1,7 3.750	E9304540332120M	20E9304	19MQL132S
HSK-E	E930654030685M1	03099158	HSK-A100	6,0 0.236	85,0 3.346	56,0 2.205	49,0 1.929	59,0 2.323	M5x0.8	2,3 5.070	E930654030685M	20E9306M1	19MQL106S
	E9306540306120M1	03099159	HSK-A100	6,0 0.236	120,0 4.724	91,0 3.583	84,0 3.307	94,0 3.701	M5x0.8	2,5 5.510	E9306540306120M	20E9306M1	19MQL106L
	E9306540306160M1	03099160	HSK-A100	6,0 0.236	160,0 6.299	131,0 5.157	124,0 4.882	134,0 5.276	M5x0.8	2,6 5.730	E9306540306160M	20E9306M1	19MQL106L
DIN	E930654030885M1	03099161	HSK-A100	8,0 0.315	85,0 3.346	56,0 2.205	49,0 1.929	59,0 2.323	M6x1	2,6 5.730	E930654030885M	20E9306M1	19MQL108S
	E9306540308120M1	03099162	HSK-A100	8,0 0.315	120,0 4.724	91,0 3.583	84,0 3.307	94,0 3.701	M6x1	2,5 5.510	E9306540308120M	20E9306M1	19MQL108L
	E9306540308160M1	03099163	HSK-A100	8,0 0.315	160,0 6.299	131,0 5.157	124,0 4.882	134,0 5.276	M6x1	2,8 6.170	E9306540308160M	20E9306M1	19MQL108L
BT JIS	E930654031090M1	03099164	HSK-A100	10,0 0.394	90,0 3.543	61,0 2.402	49,0 1.929	59,0 2.323	M8x1	2,3 5.070	E930654031090M	20E9306M1	19MQL110S
	E9306540310120M1	03099165	HSK-A100	10,0 0.394	120,0 4.724	91,0 3.583	79,0 3.110	89,0 3.504	M8x1	2,7 5.950	E9306540310120M	20E9306M1	19MQL110L
	E9306540310160M1	03099166	HSK-A100	10,0 0.394	160,0 6.299	131,0 5.157	119,0 4.685	129,0 5.079	M8x1	2,8 6.170	E9306540310160M	20E9306M1	19MQL110L
CAT	E930654031295M1	03099167	HSK-A100	12,0 0.472	95,0 3.740	66,0 2.598	49,0 1.929	59,0 2.323	M10x1	2,6 5.730	E930654031295M	20E9306M1	19MQL112S
	E9306540312120M1	03099168	HSK-A100	12,0 0.472	120,0 4.724	91,0 3.583	74,0 2.913	84,0 3.307	M10x1	2,6 5.730	E9306540312120M	20E9306M1	19MQL112L
	E9306540312160M1	03099169	HSK-A100	12,0 0.472	160,0 6.299	131,0 5.157	114,0 4.488	124,0 4.882	M10x1	2,7 5.950	E9306540312160M	20E9306M1	19MQL112L
Combimaster	E930654031495M1	03099170	HSK-A100	14,0 0.551	95,0 3.740	66,0 2.598	49,0 1.929	59,0 2.323	M10x1	2,5 5.510	E930654031495M	20E9306M1	19MQL114S
	E9306540316100M1	03099171	HSK-A100	16,0 0.630	100,0 3.937	71,0 2.795	51,0 2.008	61,0 2.402	M10x1	2,4 5.290	E9306540316100M	20E9306M1	19MQL116S
	E9306540316130M1	03099172	HSK-A100	16,0 0.630	130,0 5.118	101,0 3.976	81,0 3.189	91,0 3.583	M10x1	2,8 6.170	E9306540316130M	20E9306M1	19MQL116L
Graflex	E9306540318100M1	03099174	HSK-A100	18,0 0.709	100,0 3.937	71,0 2.795	51,0 2.008	61,0 2.402	M10x1	2,6 5.730	E9306540318100M	20E9306M1	19MQL118S
	E9306540320105M1	03099175	HSK-A100	20,0 0.787	105,0 4.134	76,0 2.992	54,0 2.126	64,0 2.520	M10x1	2,6 5.730	E9306540320105M	20E9306M1	19MQL120S
	E9306540320130M1	03099176	HSK-A100	20,0 0.787	130,0 5.118	101,0 3.976	79,0 3.110	89,0 3.504	M10x1	2,9 6.390	E9306540320130M	20E9306M1	19MQL120L
Seco Capto™	E9306540320160M1	03099177	HSK-A100	20,0 0.787	160,0 6.299	131,0 5.157	109,0 4.291	119,0 4.685	M10x1	3,2 7.050	E9306540320160M	20E9306M1	19MQL120L
	E9306540325115M1	03099178	HSK-A100	25,0 0.984	115,0 4.528	86,0 3.386	58,0 2.283	68,0 2.677	M10x1	3,3 7.280	E9306540325115M	20E9306M1	19MQL125S
	E9306540325160M1	03099179	HSK-A100	25,0 0.984	160,0 6.299	131,0 5.157	103,0 4.055	113,0 4.449	M10x1	4,0 8.820	E9306540325160M	20E9306M1	19MQL125L
Others	E9306540332120M1	03099180	HSK-A100	32,0 1.260	120,0 4.724	91,0 3.583	59,0 2.323	69,0 2.717	M10x1	3,0 6.610	E9306540332120M	20E9306M1	19MQL132S
Operating & setting accessories													
Shrinkfit													

Reinforced type
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- * Holder without thread for a stop screw
- ** Holder without threaded holes for balancing screw
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	LSC	BD1	BD2	BD3	OAL	LFN	LF	RL	TDZ	BHTA°	*	**	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch							kg lbs
E930456000670	02845449	HSK-A63	6,0 0.236	70,0 2.756	44,0 1.732	—	37,5 1.476	22,0 0.866	24,0 0.945	30,9 1.217	—	102,0 4.016	—	—	12,0 0.472	—	4,5	*		1	G2.5	0,9 1.980
E9304560006130	02845469	HSK-A63	6,0 0.236	130,0 5.118	104,0 4.094	52,0 2.047	37,5 1.476	22,0 0.866	24,0 0.945	32,2 1.267	52,5 2.067	162,0 6.378	94,0 3.701	104,0 4.094	12,0 0.472	M5x0.8	4,5			1	G2.5	1,6 3.530
E9304560006160	02845477	HSK-A63	6,0 0.236	160,0 6.299	134,0 5.276	52,0 2.047	37,5 1.476	22,0 0.866	24,0 0.945	32,2 1.267	52,5 2.067	192,0 7.559	124,0 4.882	134,0 5.276	12,0 0.472	M5x0.8	4,5			1	G2.5	1,9 4.190
E930456000870	02845450	HSK-A63	8,0 0.315	70,0 2.756	44,0 1.732	—	37,5 1.476	26,0 1.024	24,0 0.945	32,2 1.267	—	102,0 4.016	34,0 1.339	44,0 1.732	12,0 0.472	M6x1	4,5	*		1	G2.5	0,9 1.980
E9304560008130	02845470	HSK-A63	8,0 0.315	130,0 5.118	104,0 4.094	52,0 2.047	37,5 1.476	26,0 1.024	24,0 0.945	32,2 1.267	52,5 2.067	162,0 6.378	94,0 3.701	104,0 4.094	12,0 0.472	M6x1	4,5			1	G2.5	1,6 3.530
E930456001070	02845451	HSK-A63	10,0 0.394	70,0 2.756	44,0 1.732	—	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	—	102,0 4.016	29,0 1.142	39,0 1.535	13,5 0.531	M8x1	4,5	*		1	G2.5	0,85 1.870
E9304560010130	02845471	HSK-A63	10,0 0.394	130,0 5.118	104,0 4.094	52,0 2.047	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	52,5 2.067	162,0 6.378	89,0 3.504	99,0 3.898	13,5 0.531	M8x1	4,5			1	G2.5	1,6 3.530
E9304560010160	02845479	HSK-A63	10,0 0.394	160,0 6.299	134,0 5.276	52,0 2.047	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	52,5 2.067	192,0 7.559	119,0 4.685	129,0 5.079	13,5 0.531	M8x1	4,5			1	G2.5	1,95 4.300
E930456001270	02845452	HSK-A63	12,0 0.472	70,0 2.756	44,0 1.732	—	46,0 1.811	34,0 1.339	27,0 1.063	35,2 1.386	—	102,0 4.016	24,0 0.945	36,0 1.417	13,5 0.531	M10x1	4,5	*		1	G2.5	0,9 1.980
E9304560012130	02845472	HSK-A63	12,0 0.472	130,0 5.118	104,0 4.094	52,0 2.047	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	52,5 2.067	162,0 6.378	84,0 3.307	94,0 3.701	13,5 0.531	M10x1	4,5			1	G2.5	1,6 3.530
E9304560012160	02845480	HSK-A63	12,0 0.472	160,0 6.299	134,0 5.276	52,0 2.047	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	52,5 2.067	192,0 7.559	114,0 4.488	124,0 4.882	13,5 0.531	M10x1	4,5			1	G2.5	2,0 4.410
E930456001675	02845453	HSK-A63	16,0 0.630	75,0 2.953	49,0 1.929	—	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	—	107,0 4.213	26,0 1.024	36,0 1.417	17,0 0.669	M12x1	4,5	*		1	G2.5	1,0 2.200
E9304560016130	02845473	HSK-A63	16,0 0.630	130,0 5.118	104,0 4.094	58,0 2.283	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	52,5 2.067	162,0 6.378	81,0 3.189	91,0 3.583	17,0 0.669	M12x1	4,5			1	G2.5	1,8 3.970
E930456002075	02845454	HSK-A63	20,0 0.787	75,0 2.953	49,0 1.929	—	50,5 1.988	41,0 1.614	44,0 1.732	53,1 2.092	—	107,0 4.213	24,0 0.945	34,0 1.339	21,5 0.846	M16x1	4,5	*		1	G2.5	1,2 2.650
E9304560020130	02845474	HSK-A63	20,0 0.787	130,0 5.118	104,0 4.094	58,0 2.283	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	52,5 2.067	162,0 6.378	79,0 3.110	89,0 3.504	21,5 0.846	M16x1	4,5			1	G2.5	2,2 4.850
E930456002585	02845456	HSK-A63	25,0 0.984	85,0 3.346	59,0 2.323	—	58,5 2.303	47,0 1.850	48,0 1.890	57,1 2.249	52,5 2.067	117,0 4.606	28,0 1.102	38,0 1.496	25,0 0.984	M16x1	4,5	*	**	1	G2.5	1,4 3.090
E930456003285	02845457	HSK-A63	32,0 1.260	85,0 3.346	59,0 2.323	—	61,0 2.402	51,0 2.008	48,0 1.890	57,1 2.249	52,5 2.067	117,0 4.606	24,0 0.945	34,0 1.339	25,0 0.984	M16x1	4,5	*	**	1	G2.5	1,3 2.870
E9306560006160	02845493	HSK-A100	6,0 0.236	160,0 6.299	131,0 5.157	52,0 2.047	37,5 1.476	22,0 0.866	24,0 0.945	32,2 1.267	87,5 3.445	210,0 8.268	124,0 4.882	134,0 5.276	12,0 0.472	M5x0.8	4,5			1	G2.5	4,4 9.700
E9306560008160	02845494	HSK-A100	8,0 0.315	160,0 6.299	131,0 5.157	52,0 2.047	37,5 1.476	26,0 1.024	24,0 0.945	32,2 1.267	87,5 3.445	210,0 8.268	124,0 4.882	134,0 5.276	12,0 0.472	M6x1	4,5			1	G2.5	4,4 9.700
E930656001090	02845486	HSK-A100	10,0 0.394	90,0 3.543	61,0 2.402	—	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	—	140,0 5.512	49,0 1.929	59,0 2.323	13,5 0.531	M8x1	4,5			1	G2.5	2,4 5.290
E9306560010160	02845495	HSK-A100	10,0 0.394	160,0 6.299	131,0 5.157	52,0 2.047	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	87,5 3.445	210,0 8.268	119,0 4.685	129,0 5.079	13,5 0.531	M8x1	4,5			1	G2.5	4,5 9.920

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Accessories

For	Balancing screws
-----	------------------



All 90ZQ01

Spare Parts, included in delivery

For	Sealing plugs
-----	---------------



6/ 0.236 90AI03 19BDR05165

6/ 0.236 (.....670) 90AI03

8/ 0.315	90A103	19BDR06165
----------	--------	------------

8/ 0.315 (.....870) 90AI03

10/0394	90A103	19BDR08165
---------	--------	------------

10/0304 (070)	00A103
----------------	--------

12/ 0.133	00A103	10PDE
-----------	--------	-------

12/0.472	50A100	1955
12/0.472 (0.570)	50A100	

12/ 0.472 (.....210)	90A103	
----------------------	--------	--

16/ 0.630	90A103	19BDR
-----------	--------	-------


16/ 0.630 (.....675)	90A103	-
----------------------	--------	---

20/ 0.787-32/ 1.260	90Al04	19BDR
---------------------	--------	-------

20/ 0.787-32/ 1.260 (.....075, ...285, ...585) 90AI04

Reinforced type
– Inch

HSK-A/ ISO 12164-1-A



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- * Holder without thread for a stop screw
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	LSC	BD1	BD2	BD3	OAL	LFN	LF	RL	TDZ	BHTA°	*	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch						lbs
E93045600050275	02904841	HSK-A63	0.500	2.750	1.726	–	1.811	1.339	1.063	1.385	–	4.010	0.939	1.333	0.531	–	4,5	*	1	G2.5	1.980
E93045600062300	02904842	HSK-A63	0.625	3.000	1.976	–	1.988	1.535	1.299	1.659	–	4.260	1.071	1.465	0.669	–	4,5	*	1	G2.5	2.200
E93045600075300	02904843	HSK-A63	0.750	3.000	1.976	–	1.988	1.614	1.732	2.092	–	4.260	0.992	1.386	0.846	M16x1	4,5	*	1	G2.5	2.870
E93065600075412	02904844	HSK-A100	0.750	4.125	2.983	–	2.067	1.614	1.732	2.092	–	6.094	2.117	2.511	0.846	M16x1	4,5		1	G2.5	6.610
E93065600100450	02904845	HSK-A100	1.000	4.500	3.358	2.283	2.303	1.850	1.890	2.249	3.445	6.469	2.256	2.650	0.984	M16x1	4,5		1	G2.5	8.600
E93065600125450	02904846	HSK-A100	1.250	4.500	3.358	2.283	2.461	2.008	1.890	2.249	3.445	6.469	2.098	2.492	0.984	M16x1	4,5		1	G2.5	8.160

Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery


For	Sealing plugs	Stop screw
		
HSK-A63	90AI03	–
HSK-A63, DCBN = 0.750	90AI04	–
HSK-A100	90AI04	19BDR16165

Reinforced type
– Metric/ Inch


HSK-A/ ISO12164-1-HSK-A



Design 1



Design 2



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	LB2	CDBP	LSC	BD1	BD2	BD3	OAL	LFN	LF	TDZ	BHTA°	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
HSKA125-SFR16-120-F6	03252951	HSK-A125	16,0 0.630	120,0 4.724	91,0 3.583	75,0 2.953	–	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	–	183,0 7.205	71,0 2.795	81,0 3.189	M12x1	4,5	1	1	PB	4,1 9.040
HSKA125-SFR16-160-F6	03252952	HSK-A125	16,0 0.630	160,0 6.299	131,0 5.157	75,0 2.953	112,74 4.439	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	47,84 1.883	223,0 8.780	111,0 4.370	121,0 4.764	M12x1	4,5	2	1	PB	4,6 10.140
HSKA125-SFR16-200-F6	03252953	HSK-A125	16,0 0.630	200,0 7.874	171,0 6.732	75,0 2.953	152,74 6.013	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	54,84 2.159	263,0 10.354	151,0 5.945	161,0 6.339	M12x1	4,5	2	1	PB	5,3 11.680
HSKA125-SFR20-120-F6	03252954	HSK-A125	20,0 0.787	120,0 4.724	91,0 3.583	80,0 3.150	–	52,5 2.067	41,0 1.614	44,0 1.732	53,0 2.087	–	183,0 7.205	69,0 2.717	79,0 3.110	M16x1	4,5	1	1	PB	4,5 9.920
HSKA125-SFR20-160-F6	03252955	HSK-A125	20,0 0.787	160,0 6.299	131,0 5.157	80,0 3.150	112,74 4.439	52,5 2.067	41,0 1.614	44,0 1.732	53,0 2.087	57,97 2.282	223,0 8.780	109,0 4.291	119,0 4.685	M16x1	4,5	2	1	PB	5,4 11.900
HSKA125-SFR20-200-F6	03252956	HSK-A125	20,0 0.787	200,0 7.874	171,0 6.732	80,0 3.150	152,74 6.013	52,5 2.067	41,0 1.614	44,0 1.732	53,0 2.087	64,96 2.557	263,0 10.354	149,0 5.866	159,0 6.260	M16x1	4,5	2	1	PB	6,3 13.890
HSKA125-SFR25-120-F6	03252957	HSK-A125	25,0 0.984	120,0 4.724	91,0 3.583	85,0 3.346	–	58,5 2.303	47,0 1.850	48,0 1.890	57,0 2.244	–	183,0 7.205	63,0 2.480	73,0 2.874	M16x1	4,5	1	1	PB	4,6 10.140

Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery


For	Sealing plugs	Stop screw
		
16/ 0.630	90AI03	19BDR12165
20/ 0.787-25/ 0.984	90AI04	19BDR16165

Reinforced type
– Inch


HSK-A/ ISO12164-1-HSK-A



Design 1



Design 2



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- * Holder without thread for a stop screw
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-																		RFID hole	Balanc- ing	Weight
			DCBX	LPR	LB	LB1	LB2	CBDP	LSC	BD1	BD2	BD3	OAL	LFN	LF	TDZ	BHTA°	*	Design				
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch				lbs			
HSKA125-SFR0.625-4.000	03229695	HSK-A125	0.750	4.000	2.858	—	—	1.988	1.535	1.299	1.659	—	6.480	2.071	2.465	M12x1	4,5	1	1	PB	8.600		
HSKA125-SFR0.625-6.250-F6	03252958	HSK-A125	0.750	6.250	5.108	2.953	4.389	1.988	1.535	1.299	1.654	1.875	8.730	4.321	4.715	M12x1	4,5	2	1	PB	10.360		
HSKA125-SFR0.750-4.000	03229697	HSK-A125	0.750	4.000	2.858	—	—	2.067	1.614	1.732	2.092	—	6.480	1.992	2.386	M16x1	4,5	*	1	1	PB	9.920	
HSKA125-SFR0.750-6.250-F6	03252959	HSK-A125	0.750	6.250	5.108	3.150	4.389	2.067	1.614	1.732	2.087	2.274	8.730	4.242	4.636	M16x1	4,5	2	1	PB	11.680		
HSKA125-SFR1.000-4.500	03229699	HSK-A125	1.000	4.500	3.358	2.283	—	2.303	1.850	1.890	2.249	4.350	6.980	2.256	2.650	M16x1	4,5	1	1	PB	12.570		
HSKA125-SFR1.000-6.250-F6	03252960	HSK-A125	1.000	6.250	5.108	3.346	4.389	2.303	1.850	1.890	2.244	2.396	8.730	4.006	4.400	M16x1	4,5	2	1	PB	12.350		
HSKA125-SFR1.250-4.750-F6	03252961	HSK-A125	1.250	4.750	3.608	3.346	—	2.461	2.008	1.890	2.244	—	7.230	2.348	2.742	M16x1	4,5	1	1	PB	10.140		

Accessories


For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Stop screw
		
...-SFR0.625	90AI04	19BDR12165
...-SFR0.750 - ...-SFR1.250	90AI04	19BDR16165
...-SFR0.750 -4.000	90AI04	–

Mold and Die type
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



–Run-out ≤3 µm
–For Shrinkfit extensions, see page(s) 357–358
–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	LSC	BD1	BD2	OAL	BHTA°	BHTA1°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E930258010370	00039384	HSK-A40	3,0 0.118	70,0 2.756	50,0 1.969	50,0 1.969	–	13,0 0.512	9,0 0.354	16,0 0.630	90,0 3.543	3,0	5,0	0	G2.5	0,3 0.660
E9302580103100	00047886	HSK-A40	3,0 0.118	100,0 3.937	80,0 3.150	25,0 0.984	–	13,0 0.512	9,0 0.354	21,2 0.836	120,0 4.724	3,0	5,0	0	G2.5	0,4 0.880
E930258010470	00039386	HSK-A40	4,0 0.157	70,0 2.756	50,0 1.969	25,0 0.984	–	15,0 0.591	10,0 0.394	17,0 0.669	90,0 3.543	3,0	5,0	0	G2.5	0,3 0.660
E930258010670	00039402	HSK-A40	6,0 0.236	70,0 2.756	50,0 1.969	50,0 1.969	40,0 1.575	26,0 1.024	12,0 0.472	18,5 0.728	90,0 3.543	3,0	5,0	0	G2.5	0,3 0.660
E9304580103100	00096470	HSK-A63	3,0 0.118	100,0 3.937	74,0 2.913	25,0 0.984	–	13,0 0.512	9,0 0.354	20,2 0.795	132,0 5.197	3,0	5,0	1	G2.5	0,8 1.760
E9304580103140	00096471	HSK-A63	3,0 0.118	140,0 5.512	114,0 4.488	25,0 0.984	–	13,0 0.512	9,0 0.354	27,2 1.071	172,0 6.772	3,0	5,0	1	G2.5	0,9 1.980
E9304580104100	00096472	HSK-A63	4,0 0.157	100,0 3.937	74,0 2.913	25,0 0.984	–	15,0 0.591	10,0 0.394	21,2 0.834	132,0 5.197	3,0	5,0	1	G2.5	0,8 1.760
E9304580104140	00096473	HSK-A63	4,0 0.157	140,0 5.512	114,0 4.488	25,0 0.984	–	15,0 0.591	10,0 0.394	28,2 1.110	172,0 6.772	3,0	5,0	1	G2.5	0,9 1.980
E9304580105100	00096474	HSK-A63	5,0 0.197	100,0 3.937	74,0 2.913	25,0 0.984	–	18,0 0.709	11,0 0.433	22,2 0.874	132,0 5.197	3,0	5,0	1	G2.5	0,8 1.760
E9304580105140	00096475	HSK-A63	5,0 0.197	140,0 5.512	114,0 4.488	25,0 0.984	–	18,0 0.709	11,0 0.433	29,2 1.149	172,0 6.772	3,0	5,0	1	G2.5	0,9 1.980
E9304580106100	00096476	HSK-A63	6,0 0.236	100,0 3.937	74,0 2.913	32,0 1.260	40,0 1.575	26,0 1.024	12,0 0.472	22,7 0.894	132,0 5.197	3,0	5,0	1	G2.5	0,8 1.760
E9304580106140	00096477	HSK-A63	6,0 0.236	140,0 5.512	114,0 4.488	32,0 1.260	40,0 1.575	26,0 1.024	12,0 0.472	29,7 1.169	172,0 6.772	3,0	5,0	1	G2.5	1,0 2.200
E9304580108100	00096478	HSK-A63	8,0 0.315	100,0 3.937	74,0 2.913	36,0 1.417	44,0 1.732	30,0 1.181	16,0 0.630	26,4 1.040	132,0 5.197	3,0	5,0	1	G2.5	0,9 1.980
E9304580108140	00096479	HSK-A63	8,0 0.315	140,0 5.512	114,0 4.488	36,0 1.417	44,0 1.732	30,0 1.181	16,0 0.630	33,4 1.316	172,0 6.772	3,0	5,0	1	G2.5	1,1 2.430
E9304580110120	00096480	HSK-A63	10,0 0.394	120,0 4.724	94,0 3.701	38,0 1.496	45,0 1.772	32,0 1.260	18,0 0.709	31,8 1.251	152,0 5.984	3,0	5,0	1	G2.5	1,0 2.200
E9304580110160	00096482	HSK-A63	10,0 0.394	160,0 6.299	134,0 5.276	38,0 1.496	45,0 1.772	32,0 1.260	18,0 0.709	38,8 1.527	192,0 7.559	3,0	5,0	1	G2.5	1,3 2.870
E9304580112130	00096764	HSK-A63	12,0 0.472	130,0 5.118	104,0 4.094	40,0 1.575	46,0 1.811	34,0 1.339	20,0 0.787	35,4 1.393	162,0 6.378	3,0	5,0	1	G2.5	1,1 2.430
E9304580112170	00096484	HSK-A63	12,0 0.472	170,0 6.693	144,0 5.669	40,0 1.575	46,0 1.811	34,0 1.339	20,0 0.787	42,4 1.669	202,0 7.953	3,0	5,0	1	G2.5	1,5 3.310
E9304580114180	00096487	HSK-A63	14,0 0.551	180,0 7.087	154,0 6.063	40,0 1.575	48,0 1.890	34,0 1.339	22,0 0.866	46,1 1.817	212,0 8.346	3,0	5,0	1	G2.5	1,7 3.750
E9304580116150	00099665	HSK-A63	16,0 0.630	150,0 5.906	124,0 4.882	45,0 1.772	52,0 2.047	38,0 1.496	24,0 0.945	42,5 1.675	182,0 7.165	3,0	5,0	1	G2.5	1,4 3.090
E9304580116190	00099666	HSK-A63	16,0 0.630	190,0 7.480	164,0 6.457	45,0 1.772	52,0 2.047	38,0 1.496	24,0 0.945	49,5 1.950	222,0 8.740	3,0	5,0	1	G2.5	1,9 4.190
E9306580106160	00096461	HSK-A100	6,0 0.236	160,0 6.299	131,0 5.157	131,0 5.157	40,0 1.575	26,0 1.024	12,0 0.472	32,7 1.286	210,0 8.268	3,0	5,0	1	G2.5	2,3 5.070

Designation	Item number	CTMS	DCBN- DCBX	LPR	LB	LB1	CBDP	LSC	BD1	BD2	OAL	BHTA°	BHTA1°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E9306580108160	00096462	HSK-A100	8,0 0.315	160,0 6.299	131,0 5.157	36,0 1.417	44,0 1.732	30,0 1.181	16,0 0.630	36,4 1.433	210,0 8.268	3,0	5,0	1	G2.5	2,5 5.510
E9306580110180	00096463	HSK-A100	10,0 0.394	180,0 7.087	151,0 5.945	38,0 1.496	45,0 1.772	32,0 1.260	18,0 0.709	41,8 1.644	230,0 9.055	3,0	5,0	1	G2.5	2,7 5.950
E9306580112180	00096464	HSK-A100	12,0 0.472	180,0 7.087	151,0 5.945	40,0 1.575	46,0 1.811	34,0 1.339	20,0 0.787	43,6 1.717	230,0 9.055	3,0	5,0	1	G2.5	2,76 6.080
E9306580114180	00096465	HSK-A100	14,0 0.551	180,0 7.087	151,0 5.945	151,0 5.945	48,0 1.890	34,0 1.339	22,0 0.866	45,6 1.796	230,0 9.055	3,0	5,0	1	G2.5	2,9 6.390
E9306580116200	00096468	HSK-A100	16,0 0.630	200,0 7.874	171,0 6.732	45,0 1.772	52,0 2.047	38,0 1.496	24,0 0.945	50,8 1.999	250,0 9.843	3,0	5,0	1	G2.5	3,24 7.140

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

– Metric/ Inch




- Run-out 3 µm maximum at 3 x ØDCBN-DCBX
- Suffix « H » at end of the description: designed with 4 threaded holes for balancing screws
- For ER HP collets type 5672, see page(s) 389, 390, 391-397
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For stop screws, see instructions at www.secotools.com
- * Holder prepared for MQL1 screws (see accessories)
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	Chuck & Collet Size	LPR	BD2	RL	BD1	OAL	LB	*	RFID hole	Balancing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
HSKA32-ERHP11R-040	10359285	HSK-A32	1,0 0.039	7,0 0.276	HP 11R	40,0 1.575	16,0 0.630	–	16,0 0.630	56,0 2.205	20,0 0.787		0	G2.5	0,2 0.440
HSKA32-ERHP16R-050	10359286	HSK-A32	1,0 0.039	10,0 0.394	HP 16R	50,0 1.969	22,0 0.866	–	22,0 0.866	66,0 2.598	30,0 1.181		0	G2.5	0,2 0.440
HSKA32-ERHP16R-100	10359287	HSK-A32	1,0 0.039	10,0 0.394	HP 16R	100,0 3.937	22,0 0.866	–	22,0 0.866	116,0 4.567	80,0 3.150		0	G2.5	0,3 0.660
HSKA40-ERHP11R-060	10359288	HSK-A40	1,0 0.039	7,0 0.276	HP 11R	60,0 2.362	16,0 0.630	–	16,0 0.630	80,0 3.150	40,0 1.575		0	G2.5	0,3 0.660
HSKA40-ERHP11R-130	10359289	HSK-A40	1,0 0.039	7,0 0.276	HP 11R	130,0 5.118	16,0 0.630	–	16,0 0.630	150,0 5.906	110,0 4.331		0	G2.5	0,4 0.880
HSKA40-ERHP16-060	10359290	HSK-A40	1,0 0.039	10,0 0.394	HP 16	60,0 2.362	30,0 1.181	–	30,0 1.181	80,0 3.150	40,0 1.575		0	G2.5	0,4 0.880
HSKA40-ERHP16-100	10359291	HSK-A40	1,0 0.039	10,0 0.394	HP 16	100,0 3.937	30,0 1.181	–	30,0 1.181	120,0 4.724	80,0 3.150		0	G2.5	0,6 1.320
HSKA50-ERHP16-060	10359292	HSK-A50	1,0 0.039	10,0 0.394	HP 16	60,0 2.362	30,0 1.181	–	30,0 1.181	85,0 3.346	34,0 1.339		1	G2.5	0,5 1.100
HSKA50-ERHP25-060	10359293	HSK-A50	1,0 0.039	16,0 0.630	HP 25	60,0 2.362	40,0 1.575	–	40,0 1.575	85,0 3.346	34,0 1.339		1	G2.5	0,6 1.320
HSKA50-ERHP32-070	10359294	HSK-A50	2,0 0.079	20,0 0.787	HP 32	70,0 2.756	41,5 1.634	–	50,0 1.969	95,0 3.740	44,0 1.732		1	G2.5	0,7 1.540
HSKA63-ERHP11R-070	10359295	HSK-A63	1,0 0.039	7,0 0.276	HP 11R	70,0 2.756	16,0 0.630	–	16,0 0.630	102,0 4.016	44,0 1.732		1	G2.5	0,7 1.540
HSKA63-ERHP11R-100	10359296	HSK-A63	1,0 0.039	7,0 0.276	HP 11R	100,0 3.937	16,0 0.630	–	16,0 0.630	132,0 5.197	74,0 2.913		1	G2.5	0,8 1.760
HSKA63-ERHP11R-130	10359297	HSK-A63	1,0 0.039	7,0 0.276	HP 11R	130,0 5.118	16,0 0.630	–	16,0 0.630	162,0 6.378	104,0 4.094		1	G2.5	0,8 1.760
HSKA63-ERHP11R-160	10359298	HSK-A63	1,0 0.039	7,0 0.276	HP 11R	160,0 6.299	16,0 0.630	–	16,0 0.630	192,0 7.559	134,0 5.276		1	G2.5	0,9 1.980
HSKA63-ERHP16-055-H	10359299	HSK-A63	1,0 0.039	10,0 0.394	HP 16	55,0 2.165	30,0 1.181	24,0 0.945	30,0 1.181	87,0 3.425	29,0 1.142		1	G2.5	0,8 1.760
HSKA63-ERHP16-100-H	10359300	HSK-A63	1,0 0.039	10,0 0.394	HP 16	100,0 3.937	30,0 1.181	24,0 0.945	30,0 1.181	132,0 5.197	74,0 2.913	*	1	G2.5	1,0 2.200
HSKA63-ERHP16R-100-H	10359301	HSK-A63	1,0 0.039	10,0 0.394	HP 16R	100,0 3.937	22,0 0.866	22,5 0.886	22,0 0.866	132,0 5.197	74,0 2.913	*	1	G2.5	0,8 1.760
HSKA63-ERHP16-130-H	10359302	HSK-A63	1,0 0.039	10,0 0.394	HP 16	130,0 5.118	30,0 1.181	24,0 0.945	30,0 1.181	162,0 6.378	104,0 4.094	*	1	G2.5	1,2 2.650
HSKA63-ERHP16R-130-H	10359303	HSK-A63	1,0 0.039	10,0 0.394	HP 16R	130,0 5.118	22,0 0.866	22,5 0.886	22,0 0.866	162,0 6.378	104,0 4.094	*	1	G2.5	0,9 1.980
HSKA63-ERHP16-160-H	10359304	HSK-A63	1,0 0.039	10,0 0.394	HP 16	160,0 6.299	30,0 1.181	24,0 0.945	30,0 1.181	192,0 7.559	134,0 5.276	*	1	G2.5	1,3 2.870

Designation	Item number	CTMS	DCBN	DCBX	Chuck & Collet Size	LPR	BD2	RL	BD1	OAL	LB	*	RFID hole	Balancing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
HSKA63-ERHP16R-160-H	10359305	HSK-A63	1,0 0.039	10,0 0.394	HP 16R	160,0 6.299	22,0 0.866	22,5 0.886	22,0 0.866	192,0 7.559	134,0 5.276	*	1	G2.5	1,0 2.200
HSKA63-ERHP16-200	10359306	HSK-A63	1,0 0.039	10,0 0.394	HP 16	200,0 7.874	30,0 1.181	–	30,0 1.181	232,0 9.134	174,0 6.850	*	1	G2.5	1,5 3.310
HSKA63-ERHP20-060-H	10359307	HSK-A63	1,0 0.039	13,0 0.512	HP 20	60,0 2.362	32,0 1.260	22,5 0.886	32,0 1.260	92,0 3.622	34,0 1.339		1	G2.5	0,8 1.760
HSKA63-ERHP20-100-H	10359308	HSK-A63	1,0 0.039	13,0 0.512	HP 20	100,0 3.937	32,0 1.260	22,5 0.886	32,0 1.260	132,0 5.197	74,0 2.913	*	1	G2.5	1,0 2.200
HSKA63-ERHP25-060-H	10359309	HSK-A63	1,0 0.039	16,0 0.630	HP 25	60,0 2.362	40,0 1.575	26,0 1.024	40,0 1.575	92,0 3.622	34,0 1.339		1	G2.5	0,9 1.980
HSKA63-ERHP25-100-H	10359310	HSK-A63	1,0 0.039	16,0 0.630	HP 25	100,0 3.937	40,0 1.575	17,0 0.669	40,0 1.575	132,0 5.197	74,0 2.913	*	1	G2.5	1,2 2.650
HSKA63-ERHP25-130-H	10359311	HSK-A63	1,0 0.039	16,0 0.630	HP 25	130,0 5.118	40,0 1.575	17,0 0.669	40,0 1.575	162,0 6.378	104,0 4.094	*	1	G2.5	1,5 3.310
HSKA63-ERHP25-160-H	10359312	HSK-A63	1,0 0.039	16,0 0.630	HP 25	160,0 6.299	40,0 1.575	17,0 0.669	40,0 1.575	192,0 7.559	134,0 5.276	*	1	G2.5	1,8 3.970
HSKA63-ERHP25-200	10359313	HSK-A63	1,0 0.039	16,0 0.630	HP 25	200,0 7.874	40,0 1.575	–	40,0 1.575	232,0 9.134	174,0 6.850	*	1	G2.5	2,2 4.850
HSKA63-ERHP32-070-H	10359314	HSK-A63	2,0 0.079	20,0 0.787	HP 32	70,0 2.756	50,0 1.969	22,0 0.866	50,0 1.969	102,0 4.016	44,0 1.732		1	G2.5	1,1 2.430
HSKA63-ERHP32-100-H	10359315	HSK-A63	2,0 0.079	20,0 0.787	HP 32	100,0 3.937	50,0 1.969	22,0 0.866	50,0 1.969	132,0 5.197	74,0 2.913	*	1	G2.5	1,5 3.310
HSKA63-ERHP32-130-H	10359316	HSK-A63	2,0 0.079	20,0 0.787	HP 32	130,0 5.118	50,0 1.969	22,0 0.866	50,0 1.969	162,0 6.378	104,0 4.094	*	1	G2.5	1,9 4.190
HSKA63-ERHP32-160-H	10359317	HSK-A63	2,0 0.079	20,0 0.787	HP 32	160,0 6.299	50,0 1.969	22,0 0.866	50,0 1.969	192,0 7.559	134,0 5.276	*	1	G2.5	2,4 5.290
HSKA63-ERHP32-200	10359318	HSK-A63	2,0 0.079	20,0 0.787	HP 32	200,0 7.874	50,0 1.969	–	50,0 1.969	232,0 9.134	174,0 6.850	*	1	G2.5	3,0 6.610
HSKA100-ERHP25-100	10359319	HSK-A100	1,0 0.039	16,0 0.630	HP 25	100,0 3.937	40,0 1.575	–	40,0 1.575	150,0 5.906	71,0 2.795	*	1	G2.5	2,6 5.730
HSKA100-ERHP25-160	10359320	HSK-A100	1,0 0.039	16,0 0.630	HP 25	160,0 6.299	40,0 1.575	–	40,0 1.575	210,0 8.268	131,0 5.157	*	1	G2.5	3,1 6.830
HSKA100-ERHP32-100	10359321	HSK-A100	2,0 0.079	20,0 0.787	HP 32	100,0 3.937	50,0 1.969	–	50,0 1.969	150,0 5.906	71,0 2.795	*	1	G2.5	2,8 6.170
HSKA100-ERHP32-160	10359322	HSK-A100	2,0 0.079	20,0 0.787	HP 32	160,0 6.299	50,0 1.969	–	50,0 1.969	210,0 8.268	131,0 5.157	*	1	G2.5	3,7 8.160
HSKA100-ERHP32-200	10359323	HSK-A100	2,0 0.079	20,0 0.787	HP 32	200,0 7.874	50,0 1.969	–	50,0 1.969	250,0 9.843	171,0 6.732	*	1	G2.5	4,3 9.480

Accessories

For	Key	Socket	Torque key
			
ERHP11R	03LME0912140	03ER016	03DYE003025
ERHP16R	03LME0912140	03ER022	03DYE010050
ERHP16	03LME1418260	03ER030B	03DYE010100B
ERHP20	03LME1418260	03ER032B	03DYE010100B
ERHP25	03LME1418260	03ER040	03DYE010100B
ERHP32	03LME1418370	03ER050	03DYE040200

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories


Shrinkfit

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery	
	For	Nut
		
HSK-A	ERHP11R	08B567211RC
	ERHP16R	08B567216RC
	ERHP16	08B567216C
	ERHP20	08B567220C
	ERHP25	08B567225C
HSK-E	ERHP32	08B567232C
DIN		
BT JIS		
CAT		
Combimaster		
Graflex		
Seco Capto™		
Others		
Operating & setting accessories		
Shrinkfit		

Conventional type
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A




- Run-out $\leq 3 \mu\text{m}$
- For reduction sleeves, see page(s) 381, 382
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
HSKA63-HC06-070	10137261	HSK-A63	6,0 0.236	70,0 2.756	44,05 1.734	24,0 0.945	38,5 1.516	50,0 1.969	26,0 1.024	101,9 4.012	33,0 1.299	43,0 1.693	M5	20,0	1	G2.5	1,0 2.200
HSKA63-HC08-070	10137262	HSK-A63	8,0 0.315	70,0 2.756	44,05 1.734	25,0 0.984	38,5 1.516	50,0 1.969	28,0 1.102	101,9 4.012	33,0 1.299	43,0 1.693	M6	20,0	1	G2.5	1,0 2.200
HSKA63-HC10-080	10137263	HSK-A63	10,0 0.394	80,0 3.150	54,05 2.128	35,0 1.378	42,5 1.673	50,0 1.969	30,0 1.181	111,9 4.406	39,0 1.535	49,0 1.929	M8x1	20,0	1	G2.5	1,1 2.430
HSKA63-HC12-085	10137264	HSK-A63	12,0 0.472	85,0 3.346	59,05 2.325	40,0 1.575	47,5 1.870	50,0 1.969	32,0 1.260	116,9 4.602	39,0 1.535	49,0 1.929	M10x1	20,0	1	G2.5	1,1 2.430
HSKA63-HC14-085	10137265	HSK-A63	14,0 0.551	85,0 3.346	59,05 2.325	40,0 1.575	47,5 1.870	50,0 1.969	34,0 1.339	116,9 4.602	39,0 1.535	49,0 1.929	M10x1	20,0	1	G2.5	1,1 2.430
HSKA63-HC16-090	10137266	HSK-A63	16,0 0.630	90,0 3.543	64,05 2.522	46,0 1.811	50,5 1.988	50,0 1.969	38,0 1.496	121,9 4.799	41,0 1.614	51,0 2.008	M12x1	20,0	1	G2.5	1,2 2.650
HSKA63-HC20-090	10137267	HSK-A63	20,0 0.787	90,0 3.543	64,05 2.522	48,0 1.890	52,5 2.067	50,0 1.969	42,0 1.654	121,9 4.799	39,0 1.535	49,0 1.929	M16x1	20,0	1	G2.5	1,3 2.870
HSKA63-HC25-120	10137268	HSK-A63	25,0 0.984	120,0 4.724	94,05 3.703	–	58,5 2.303	–	57,0 2.244	151,9 5.980	63,0 2.480	73,0 2.874	M16x1	–	1	G2.5	2,1 4.630
HSKA63-HC32-125	10137269	HSK-A63	32,0 1.260	125,0 4.921	99,05 3.900	82,8 3.260	62,5 2.461	50,0 1.969	62,0 2.441	156,9 6.177	64,0 2.520	74,0 2.913	M16x1	–	1	G2.5	2,4 5.290
HSKA100-HC12-095	10137270	HSK-A100	12,0 0.472	95,0 3.740	66,05 2.600	47,0 1.850	47,5 1.870	50,3 1.978	32,0 1.260	144,9 5.705	49,0 1.929	59,0 2.323	M10x1	20,0	1	G2.5	2,5 5.510
HSKA100-HC16-100	10137271	HSK-A100	16,0 0.630	100,0 3.937	71,05 2.797	53,0 2.087	50,5 1.988	50,3 1.978	38,0 1.496	149,9 5.902	51,0 2.008	61,0 2.402	M12x1	20,0	1	G2.5	2,6 5.730
HSKA100-HC20-105	10137272	HSK-A100	20,0 0.787	105,0 4.134	76,05 2.994	59,0 2.323	52,5 2.067	50,3 1.978	42,0 1.654	154,9 6.098	54,0 2.126	64,0 2.520	M16x1	20,0	1	G2.5	2,7 5.950
HSKA100-HC25-110	10137273	HSK-A100	25,0 0.984	110,0 4.331	81,05 3.191	62,0 2.441	58,5 2.303	63,3 2.490	57,0 2.244	159,9 6.295	53,0 2.087	63,0 2.480	M16x1	20,0	1	G2.5	3,4 7.500
HSKA100-HC32-110	10137274	HSK-A100	32,0 1.260	110,0 4.331	81,05 3.191	62,0 2.441	62,5 2.461	75,3 2.963	64,0 2.520	159,9 6.295	49,0 1.929	59,0 2.323	M16x1	20,0	1	G2.5	3,7 8.160

Accessories

For	Key
HSKA63, DCBN = 6-20	H05-4
HSKA63, DCBN = 25-32	03MS06L
HSKA100, DCBN = 12-20	H05-4
HSKA100, DCBN = 25-32	03MS06L



Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit


Reinforced type
– Metric/ Inch



- Run-out $\leq 3 \mu\text{m}$
- For reduction sleeves, see page(s) 381, 382
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15


Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balan-cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
HSKA50-HCR20-094	10137148	HSK-A50	20,0 0.787	94,0 3.701	68,05 2.679	51,8 2.039	52,5 2.067	40,3 1.585	42,0 1.654	118,9 4.681	41,5 1.634	41,5 1.634	–	–	1	G2.5	1,0 2.200
HSKA63-HCR12-080	10137125	HSK-A63	12,0 0.472	80,0 3.150	54,05 2.128	36,5 1.437	47,5 1.870	52,5 2.067	42,0 1.654	111,9 4.406	34,0 1.339	44,0 1.732	M8x1	20,0	1	G2.5	1,3 2.870
HSKA63-HCR20-080	10137126	HSK-A63	20,0 0.787	80,0 3.150	54,05 2.128	–	52,5 2.067	–	52,5 2.067	111,9 4.406	29,0 1.142	39,0 1.535	M8x1	–	1	G2.5	1,4 3.090
HSKA100-HCR20-090	10137127	HSK-A100	20,0 0.787	90,0 3.543	61,05 2.404	–	52,5 2.067	–	52,5 2.067	139,9 5.508	39,0 1.535	49,0 1.929	M8x1	–	1	G2.5	2,8 6.170
HSKA100-HCR32-100	10137128	HSK-A100	32,0 1.260	100,0 3.937	71,05 2.797	–	62,5 2.461	–	72,0 2.835	149,9 5.902	39,0 1.535	49,0 1.929	M8x1	–	1	G2.5	3,7 8.160

Accessories

For	Key
	
HSKA50	H05-4
HSKA63	H05-4
HSKA100-HCR20	H05-4
HSKA100-HCR32	03MS06L

Slim type
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



- Run-out $\leq 3 \mu\text{m}$
- For reduction sleeves, see page(s) 381, 382
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	BHTA1°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
HSKA63-HCS06-145	10137328	HSK-A63	6,0 0.236	145,0 5.709	119,0 4.685	90,0 3.543	37,0 1.457	50,0 1.969	20,0 0.787	177,0 6.969	108,0 4.252	118,0 4.646	M5x0.8	30,0	3,0	1	G2.5	1,4 3.090
HSKA63-HCS08-145	10137329	HSK-A63	8,0 0.315	145,0 5.709	119,0 4.685	90,0 3.543	37,0 1.457	50,0 1.969	22,0 0.866	177,0 6.969	108,0 4.252	118,0 4.646	M6x1	30,0	3,0	1	G2.5	1,5 3.310
HSKA63-HCS10-145	10137330	HSK-A63	10,0 0.394	145,0 5.709	119,0 4.685	90,0 3.543	42,0 1.654	50,0 1.969	24,0 0.945	177,0 6.969	103,0 4.055	113,0 4.449	M8x1	30,0	3,0	1	G2.5	1,5 3.310
HSKA63-HCS12-145	10137331	HSK-A63	12,0 0.472	145,0 5.709	119,0 4.685	90,0 3.543	49,0 1.929	50,0 1.969	25,0 0.984	177,0 6.969	98,0 3.858	108,0 4.252	M10x1	30,0	3,0	1	G2.5	1,5 3.310
HSKA63-HCS16-145	10137332	HSK-A63	16,0 0.630	145,0 5.709	119,0 4.685	90,0 3.543	51,0 2.008	50,0 1.969	32,0 1.260	177,0 6.969	93,0 3.661	103,0 4.055	M12x1	30,0	3,0	1	G2.5	1,8 3.970
HSKA63-HCS20-145	10137333	HSK-A63	20,0 0.787	145,0 5.709	119,0 4.685	90,0 3.543	53,0 2.087	50,0 1.969	34,0 1.339	177,0 6.969	93,0 3.661	103,0 4.055	M16x1	30,0	3,0	1	G2.5	1,8 3.970
HSKA100-HCS06-150	10137334	HSK-A100	6,0 0.236	150,0 5.906	121,0 4.764	90,0 3.543	37,0 1.457	50,0 1.969	20,0 0.787	200,0 7.874	113,0 4.449	123,0 4.843	M5x0.8	30,0	3,0	1	G2.5	2,8 6.170
HSKA100-HCS08-150	10137335	HSK-A100	8,0 0.315	150,0 5.906	121,0 4.764	90,0 3.543	37,0 1.457	50,0 1.969	22,0 0.866	200,0 7.874	113,0 4.449	123,0 4.843	M6x1	30,0	3,0	1	G2.5	2,9 6.390
HSKA100-HCS10-150	10137336	HSK-A100	10,0 0.394	150,0 5.906	121,0 4.764	90,0 3.543	42,5 1.673	50,0 1.969	24,0 0.945	200,0 7.874	108,0 4.252	118,0 4.646	M8x1	30,0	3,0	1	G2.5	2,9 6.390
HSKA100-HCS12-150	10137337	HSK-A100	12,0 0.472	150,0 5.906	121,0 4.764	90,0 3.543	48,0 1.890	50,0 1.969	25,0 0.984	200,0 7.874	103,0 4.055	113,0 4.449	M10x1	30,0	3,0	1	G2.5	2,9 6.390
HSKA100-HCS16-150	10137338	HSK-A100	16,0 0.630	150,0 5.906	121,0 4.764	90,0 3.543	52,0 2.047	50,0 1.969	32,0 1.260	200,0 7.874	98,0 3.858	108,0 4.252	M12x1	30,0	3,0	1	G2.5	3,1 6.830
HSKA100-HCS20-150	10137339	HSK-A100	20,0 0.787	150,0 5.906	121,0 4.764	90,0 3.543	52,0 2.047	50,0 1.969	34,0 1.339	200,0 7.874	100,0 3.937	110,0 4.331	M16x1	30,0	3,0	1	G2.5	3,2 7.050

Accessories

For	Key
	
All	H05-4

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

– Metric/ Inch




- For reduction sleeves, see page(s) 385–386
- For ‘Stop screws for through coolant’, see page(s) 387–388
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	OAL	LPR	LB	CBDP	BD1	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
HSKA63-PMC20-085	03211188	HSK-A63	20,0 0.787	117,0 4.606	85,0 3.346	59,0 2.323	60,0 2.362	49,0 1.929	1	PB	1,3 2.870
HSKA63-PMC32-105	03211189	HSK-A63	32,0 1.260	137,0 5.394	105,0 4.134	79,0 3.110	80,0 3.150	67,0 2.638	1	PB	2,0 4.410
HSKA100-PMC20-095	03211190	HSK-A100	20,0 0.787	145,0 5.709	95,0 3.740	66,0 2.598	60,0 2.362	49,0 1.929	1	PB	2,8 6.170
HSKA100-PMC32-110	03211191	HSK-A100	32,0 1.260	160,0 6.299	110,0 4.331	81,0 3.189	80,0 3.150	68,0 2.677	1	PB	3,7 8.160


Accessories

For	Spanner
	
20/ 0.787	03BPMC20
32/ 1.260	03BPMC32

Spare Parts, included in delivery

For	Extractor for reduction sleeves
	
All	03EXTPMC


– Inch



- For reduction sleeves, see page(s) 385–386
- For ‘Stop screws for through coolant’, see page(s) 387–388
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	OAL	LPR	LB	CBDP	BD1	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch			lbs
HSKA63-PMC0.750-3.500	03211210	HSK-A63	0.750	4.760	3.500	2.476	2.362	1.929	1	PB	3.090
HSKA63-PMC1.250-4.250	03211211	HSK-A63	1.250	5.510	4.250	3.226	3.150	2.638	1	PB	4.630
HSKA100-PMC0.750-3.750	03211212	HSK-A100	0.750	5.719	3.750	2.608	2.362	1.929	1	PB	6.170
HSKA100-PMC1.250-4.500	03211213	HSK-A100	1.250	6.469	4.500	3.358	3.150	2.677	1	PB	8.380

Accessories

For	Spanner	Stop screw (K)
		
HSKA100-PMC0.750-3.750	03BPMC32	–
HSKA100-PMC1.250-4.500	03BPMC32	19BPMC317505H
HSKA63-PMC0.750-3.500	03BPMC20	–
HSKA63-PMC1.250-4.250	03BPMC32	19BPMC317505H

Spare Parts, included in delivery


For	Extractor for reduction sleeves
	
All	03EXTPMC

ISO 15488
– Metric/ Inch


HSK-A/ ISO12164-1-HSK-A



Design 1



Design 2




–Run-out 15 µm/ .0006" maximum at 3 x ØDCBN-DCBX
–For ER extensions and ER collets, see page(s) 362, 363, 399, 400, 401, 402
–For ER sealing rings, see page(s) 410, 411
–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD3	BD2	BD1	OAL	LB	LB1	LFN	LF	Design	RFID hole	Balancing	Weight																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																																											
																			mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm</

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	CTWS	LPR mm inch	BD3 mm inch	BD2 mm inch	BD1 mm inch	OAL mm inch	LB mm inch	LB1 mm inch	LFN mm inch	LF mm inch	Design	RFID hole	Balan- cing	Weight kg lbs
HSKA125-ER25-160	03229639	HSK-A125	1,0 0.039	16,0 0.630	ER 25	160,0 6.299	–	42,0 1.654	42,0 1.654	223,0 8.780	131,0 5.157	–	91,0 3.583	122,0 4.803	1	1	PB	4,6 10.140
HSKA125-ER25-200-VF6	03240290	HSK-A125	1,0 0.039	16,0 0.630	ER 25	200,0 7.874	72,7 2.861	42,0 1.654	42,0 1.654	263,0 10.354	171,0 6.732	84,0 3.307	131,0 5.157	162,0 6.378	2	1	PB	5,7 12.570
HSKA125-ER32-120	03229641	HSK-A125	2,0 0.079	20,0 0.787	ER 32	120,0 4.724	–	50,0 1.969	50,0 1.969	183,0 7.205	91,0 3.583	–	60,0 2.362	80,0 3.150	1	1	PB	4,3 9.480
HSKA125-ER32-160	03229642	HSK-A125	2,0 0.079	20,0 0.787	ER 32	160,0 6.299	–	50,0 1.969	50,0 1.969	223,0 8.780	131,0 5.157	–	92,0 3.622	120,0 4.724	1	1	PB	4,9 10.800
HSKA125-ER32-200-VF6	03240291	HSK-A125	2,0 0.079	20,0 0.787	ER 32	200,0 7.874	75,0 2.954	50,0 1.969	50,0 1.969	263,0 10.354	171,0 6.732	100,0 3.937	132,0 5.197	160,0 6.299	2	1	PB	6,1 13.450

Accessories

For	Seal nut	Spanner
		
ER 16	08B587516IC	03B587516UM
ER 20	–	03B587520UM
ER 25	08B587525IC	03B587525
ER 32	08B587532IC	03B587532
ER 40	08B587540IC	03B587540

Spare Parts, included in delivery

For	Nut	Stop screw
		
HSKA40-ER16	08B587516UM	–
HSKA40-ER25	08B587525X	–
HSKA50-ER32	08B587532X	–
HSKA63-ER16	08B587516UM	19LRC1020
HSKA63-ER20	08B587520UM	19LRC1225
HSKA63-ER25	08B587525X	19LRC1225
HSKA63-ER32	08B587532X	19LRC1225
HSKA63-ER40	08B587540X	19LRC1225
HSKA100-ER25	08B587525X	19LRC1225
HSKA100-ER32	08B587532X	19LRC1225
HSKA100-ER40	08B587540X	19LRC1225
HSKA125-ER25	08B587525X	19B58718
HSKA125-ER32	08B587532X	19B58722

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

– Metric/ Inch



- Run-out 40 µm maximum at 2,5 x ØDCBN-DCBX
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15


Designation	Item number	CTMS	DCBN	DCBX	OAL	LPR	LB	BD1	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
E9304508513	75041587	HSK-A63	1,0 0.039	13,0 0.512	142,0 5.591	110,0 4.331	84,0 3.307	43,0 1.693	1	PB	1,2 2.650
E9306508516	75041588	HSK-A100	2,5 0.098	16,0 0.630	184,0 7.244	134,0 5.276	105,0 4.134	56,0 2.205	1	PB	3,3 7.280

For synchronized tapping, with micro-compensation
– Metric/ Inch


HSK-A/ ISO12164-1-HSK-A



Design 1





Design 2



- Maximum coolant pressure 80 bar/ 1160 psi
- For ER tapping collets with square drive, see page(s) 407, 408–409
- For TCER 5867 sealing rings, see page(s) 410, 411
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCBN	DCBX	LPR	LB	LB1	BD	BD1	OAL	SW	Design	RFID hole	Balan- cing	Weight
						mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
E9304586720108	02926954	HSK-A63	ER 20	M4	M12	103,1 4.059	77,2 3.039	35,3 1.390	35,0 1.378	33,7 1.327	135,0 5.315	22,0 0.866	1	0	–	1,1 2.430
E9304586725128	02926955	HSK-A63	ER 25	M8	M20	122,5 4.823	96,5 3.799	37,1 1.461	44,0 1.732	42,0 1.654	154,4 6.079	28,0 1.102	2	0	–	1,4 3.090
E9304586740160	02926956	HSK-A63	ER 40	M16	M33	154,5 6.083	128,6 5.063	46,6 1.835	62,0 2.441	62,7 2.469	186,4 7.339	39,6 1.559	2	0	–	2,9 6.390
E9306586720115	02926952	HSK-A100	ER 20	M4	M12	109,6 4.315	80,7 3.177	35,3 1.390	35,0 1.378	33,7 1.327	159,5 6.280	22,0 0.866	1	0	–	2,5 5.510
E9306586725134	02926953	HSK-A100	ER 25	M8	M20	129,0 5.079	100,0 3.937	37,1 1.461	44,0 1.732	42,0 1.654	178,9 7.043	28,0 1.102	2	0	–	2,8 6.170
E9306586740163	02926951	HSK-A100	ER 40	M16	M33	158,0 6.220	129,1 5.083	46,6 1.835	62,0 2.441	62,7 2.469	207,9 8.185	39,6 1.559	2	0	–	4,2 9.260

Accessories

For	Locking key	Seal nut	Spanner
			
ER 20	5680092-04	5533051-02	03B587520UM
ER 25	5680092-05	5533051-03	03B587525
ER 40	5680092-06	5533051-05	03B587540

Spare Parts, included in delivery

For	Nut
	
ER 20	5533050-08
ER 25	5533050-02
ER 40	5533050-04

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

– Metric/ Inch




–The cylindrical front part is hardened to 120–130 daN/mm², allowing machining
 –For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
 –For ISO attribute explanation, see page 15

Designation	Item number	CTMS	LPR	SRR	BD	OAL	CNDP	LB	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
E9302502340150	00007486	HSK-A40	150,0 5.906	8,0 0.315	40,0 1.575	178,0 7.008	36,0 1.417	130,0 5.118	0	PB	1,6 3.530
E9304502363250	75041753	HSK-A63	250,0 9.843	8,0 0.315	63,0 2.480	290,0 11.417	54,0 2.126	224,0 8.819	1	PB	6,2 13.670
E9306502363250	75041755	HSK-A100	250,0 9.843	8,0 0.315	63,0 2.480	308,0 12.126	78,5 3.091	221,0 8.701	1	PB	7,6 16.760
E9306502395250	75041756	HSK-A100	250,0 9.843	8,0 0.315	95,0 3.740	308,0 12.126	78,5 3.091	221,0 8.701	1	PB	14,0 30.860

– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



- Diameter, length values and measurement positions are laser engraved on each test bar
- With protective case and measurement report
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	LPR	LB	BD	OAL	RFID hole	Balan- cing	Weight
			mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>			kg <i>lbs</i>
E930458640250	00083582	HSK-A63	250,0 9.843	224,0 8.819	40,0 1.575	282,0 11.102	1	–	2,9 6.390
E930658650320	00083021	HSK-A100	320,0 12.598	291,0 11.457	50,0 1.969	370,0 14.567	1	–	6,4 14.110

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit




HSK-E

Seco allows you to get the most out of both your machine and tools by offering a comprehensive range of tool holders to connect them. **HSK - E** is designed for high spindles speed therefore there is no slots on the flange, it's completely cylindrical.

The range covers all standard workpiece side connections, as well Seco's unique connections.

- Shrinkfit holders
- High precision collet chucks
- ER collet chucks




Machine side catalogue designation	Hole for RFID carrier*	d_1	d_2	d_3_{max}	d_4	d_7	d_8	f_1	f_2	f_3	l_1	l_2
		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
HSK-E32	No*	32 1.260	24 0.945	26 1.024	26,5 1.043	17 0.669	21 0.827	20 0.787	35 1.378	16 0.630	16 0.630	3,2 0.126
HSK-E40	No*	40 1.575	30 1.181	34 1.339	34,8 1.370	21 0.827	25,5 1.004	20 0.787	35 1.378	16 0.630	20 0.787	4 0.157
HSK-E50	No*	50 1.969	38 1.496	42 1.654	43 1.693	26 1.024	32 1.260	26 1.024	42 1.654	18 0.709	25 0.984	5 0.197

Note: These machine side dimensions are applied to all the holders shown in the Product pages.

For HSK sealing plugs, coolant tubes and tube spanners, see chapter Operating & setting accessories.

* No hole for RFID carriers. If required, hole can be machined and a RFID carrier can be fitted on request, please enquire.

DIN type
– Metric/ Inch



–Run-out $\leq 3 \mu\text{m}$
 –Delivered with one stop screw
 –For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
 –For Shrinkfit extensions, see page(s) 357–358
 –For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					
E934256030350	02752956	HSK-E40	3,0 0.118	50,0 1.969	30,0 1.181	31,0 1.220	13,0 0.512	15,0 0.591	20,0 0.787	70,0 2.756	20,5 0.807	37,0 1.457	10,5 0.413	–	4,5	0	G2.5	0,3 0.660
E934256030450	02752957	HSK-E40	4,0 0.157	50,0 1.969	30,0 1.181	31,0 1.220	15,0 0.591	15,0 0.591	20,0 0.787	70,0 2.756	20,5 0.807	35,0 1.378	10,5 0.413	M5x0.8	4,5	0	G2.5	0,3 0.660
E934256030650	02752959	HSK-E40	6,0 0.236	50,0 1.969	30,0 1.181	31,0 1.220	22,0 0.866	21,0 0.827	27,0 1.063	70,0 2.756	20,5 0.807	28,0 1.102	10,5 0.413	M5x0.8	4,5	0	G2.5	0,3 0.660
E934256030670	02752960	HSK-E40	6,0 0.236	70,0 2.756	50,0 1.969	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	90,0 3.543	34,0 1.339	44,0 1.732	10,5 0.413	M5x0.8	4,5	0	G2.5	0,4 0.880
E934256030870	02752964	HSK-E40	8,0 0.315	70,0 2.756	50,0 1.969	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	90,0 3.543	34,0 1.339	44,0 1.732	10,5 0.413	M6x1	4,5	0	G2.5	0,36 0.790
E934256031055	02752966	HSK-E40	10,0 0.394	55,0 2.165	35,0 1.378	36,0 1.417	31,0 1.220	24,0 0.945	32,0 1.260	75,0 2.953	20,5 0.807	24,0 0.945	13,0 0.512	M8x1	4,5	0	G2.5	0,4 0.880
E934256031260	02752969	HSK-E40	12,0 0.472	60,0 2.362	40,0 1.575	41,0 1.614	34,0 1.339	24,0 0.945	32,0 1.260	80,0 3.150	20,5 0.807	26,0 1.024	13,0 0.512	M10x1	4,5	0	G2.5	0,4 0.880
E934256031665	02752973	HSK-E40	16,0 0.630	65,0 2.559	45,0 1.772	46,0 1.811	39,0 1.535	27,0 1.063	34,0 1.339	85,0 3.346	20,5 0.807	26,0 1.024	14,0 0.551	–	4,5	0	G2.5	0,4 0.880
E934356030355	02752979	HSK-E50	3,0 0.118	55,0 2.165	29,0 1.142	31,0 1.220	13,0 0.512	15,0 0.591	20,0 0.787	80,0 3.150	25,5 1.004	42,0 1.654	10,5 0.413	–	4,5	0	G2.5	0,5 1.100
E934356030455	02752980	HSK-E50	4,0 0.157	55,0 2.165	29,0 1.142	31,0 1.220	15,0 0.591	15,0 0.591	20,0 0.787	80,0 3.150	25,5 1.004	40,0 1.575	10,5 0.413	–	4,5	0	G2.5	0,5 1.100
E934356030655	02752981	HSK-E50	6,0 0.236	55,0 2.165	29,0 1.142	32,0 1.260	22,0 0.866	21,0 0.827	27,0 1.063	80,0 3.150	24,5 0.965	33,0 1.299	10,5 0.413	–	4,5	0	G2.5	0,5 1.100
E934356030855	02752983	HSK-E50	8,0 0.315	55,0 2.165	29,0 1.142	32,0 1.260	22,0 0.866	21,0 0.827	27,0 1.063	80,0 3.150	24,5 0.965	33,0 1.299	10,5 0.413	–	4,5	0	G2.5	0,5 1.100
E934356031060	02752985	HSK-E50	10,0 0.394	60,0 2.362	34,0 1.339	37,0 1.457	31,0 1.220	24,0 0.945	32,0 1.260	85,0 3.346	24,5 0.965	29,0 1.142	13,0 0.512	M8x1	4,5	0	G2.5	0,6 1.320
E934356031265	02752987	HSK-E50	12,0 0.472	65,0 2.559	39,0 1.535	42,0 1.654	34,0 1.339	24,0 0.945	32,0 1.260	90,0 3.543	24,5 0.965	31,0 1.220	13,0 0.512	M10x1	4,5	0	G2.5	0,6 1.320
E934356031290	02752988	HSK-E50	12,0 0.472	90,0 3.543	64,0 2.520	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	115,0 4.528	44,0 1.732	54,0 2.126	13,0 0.512	M10x1	4,5	0	G2.5	0,7 1.540
E934356031670	02752989	HSK-E50	16,0 0.630	70,0 2.756	44,0 1.732	47,0 1.850	39,0 1.535	27,0 1.063	34,0 1.339	95,0 3.740	24,5 0.965	31,0 1.220	14,0 0.551	–	4,5	0	G2.5	0,6 1.320

Accessories

For	Balancing screws
	
E934256030670	90ZQ01
E934256030870	90ZQ01
E934356031290	90ZQ01

Spare Parts, included in delivery

For	Stop screw
	
E934256030670	19BDR05165
E934256030870	19BDR06165
E934356031290	19BDR10165

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Mold and Die type
– Metric/ Inch


HSK-E



–Run-out $\leq 3 \mu\text{m}$
–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For Shrinkfit extensions, see page(s) 357-358
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	LSC	BD1	BD2	OAL	BHTA°	BHTA1°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E934258010360	02418319	HSK-E40	3,0 0.118	60,0 2.362	40,0 1.575	–	–	13,0 0.512	9,0 0.354	13,2 0.519	80,0 3.150	3,0	–	0	G2.5	0,3 0.660
E9342580103100	00048013	HSK-E40	3,0 0.118	100,0 3.937	80,0 3.150	25,0 0.984	–	13,0 0.512	9,0 0.354	21,2 0.836	120,0 4.724	3,0	5,0	0	G2.5	0,4 0.880
E934258010460	02418320	HSK-E40	4,0 0.157	60,0 2.362	40,0 1.575	–	–	15,0 0.591	10,0 0.394	14,2 0.559	80,0 3.150	3,0	–	0	G2.5	0,24 0.530
E9342580104100	00047774	HSK-E40	4,0 0.157	100,0 3.937	80,0 3.150	25,0 0.984	–	15,0 0.591	10,0 0.394	22,2 0.876	120,0 4.724	3,0	5,0	0	G2.5	0,4 0.880
E934258010660	02418323	HSK-E40	6,0 0.236	60,0 2.362	40,0 1.575	–	40,0 1.575	26,0 1.024	12,0 0.472	16,2 0.638	80,0 3.150	3,0	–	0	G2.5	0,25 0.550
E9342580106100	00047778	HSK-E40	6,0 0.236	100,0 3.937	80,0 3.150	32,0 1.260	40,0 1.575	26,0 1.024	12,0 0.472	23,8 0.935	120,0 4.724	3,0	5,0	0	G2.5	0,4 0.880
E934258010860	02418324	HSK-E40	8,0 0.315	60,0 2.362	40,0 1.575	–	42,0 1.654	30,0 1.181	16,0 0.630	20,2 0.795	80,0 3.150	3,0	–	0	G2.5	0,3 0.660
E934258011060	02418325	HSK-E40	10,0 0.394	60,0 2.362	40,0 1.575	40,0 1.575	42,0 1.654	32,0 1.260	18,0 0.709	22,2 0.874	80,0 3.150	3,0	–	0	G2.5	0,3 0.660
E9343580103100	00047797	HSK-E50	3,0 0.118	100,0 3.937	74,0 2.913	25,0 0.984	–	13,0 0.512	9,0 0.354	20,2 0.795	125,0 4.921	3,0	5,0	0	G2.5	0,5 1.100
E9343580104100	00047799	HSK-E50	4,0 0.157	100,0 3.937	74,0 2.913	25,0 0.984	–	15,0 0.591	10,0 0.394	21,2 0.834	125,0 4.921	3,0	5,0	0	G2.5	0,6 1.320
E9343580106100	00047807	HSK-E50	6,0 0.236	100,0 3.937	74,0 2.913	32,0 1.260	40,0 1.575	26,0 1.024	12,0 0.472	22,7 0.894	125,0 4.921	3,0	5,0	0	G2.5	0,6 1.320
E9343580108100	00047812	HSK-E50	8,0 0.315	100,0 3.937	74,0 2.913	36,0 1.417	44,0 1.732	30,0 1.181	16,0 0.630	26,4 1.040	125,0 4.921	3,0	5,0	0	G2.5	0,6 1.320

– Metric/ Inch



- Run-out 3 µm maximum at 3 x ØDCBN-DCBX
- Suffix « H » at end of the description: designed with 4 threaded holes for balancing screws
- For ER HP collets type 5672, see page(s) 389, 390, 391-397
- For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
- For stop screws, see instructions at www.secotools.com
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	CTWS	LPR mm inch	BD2 mm inch	RL mm inch	BD1 mm inch	OAL mm inch	LB mm inch	RFID hole	Balan- cing	Weight kg lbs
HSKE25-ERHP08R-035	10359325	HSK-E25	1,0 0.039	5,0 0.197	HP 08R	35,0 1.378	10,0 0.394	–	10,0 0.394	48,0 1.890	25,0 0.984	0	G2.5	0,1 0.220
HSKE25-ERHP11R-035	10359326	HSK-E25	1,0 0.039	7,0 0.276	HP 11R	35,0 1.378	16,0 0.630	–	16,0 0.630	48,0 1.890	25,0 0.984	0	G2.5	0,1 0.220
HSKE25-ERHP16R-045	10359327	HSK-E25	1,0 0.039	10,0 0.394	HP 16R	45,0 1.772	19,5 0.768	–	22,0 0.866	58,0 2.283	35,0 1.378	0	G2.5	0,1 0.220
HSKE32-ERHP08R-050	10359328	HSK-E32	1,0 0.039	5,0 0.197	HP 08R	50,0 1.969	10,0 0.394	–	10,0 0.394	66,0 2.598	30,0 1.181	0	G2.5	0,2 0.440
HSKE32-ERHP11R-050	10359329	HSK-E32	1,0 0.039	7,0 0.276	HP 11R	50,0 1.969	16,0 0.630	–	16,0 0.630	66,0 2.598	30,0 1.181	0	G2.5	0,2 0.440
HSKE32-ERHP16R-055	10359330	HSK-E32	1,0 0.039	10,0 0.394	HP 16R	55,0 2.165	22,0 0.866	–	22,0 0.866	71,0 2.795	35,0 1.378	0	G2.5	0,2 0.440
HSKE32-ERHP16R-100	10359331	HSK-E32	1,0 0.039	10,0 0.394	HP 16R	100,0 3.937	22,0 0.866	–	22,0 0.866	116,0 4.567	80,0 3.150	0	G2.5	0,4 0.880
HSKE40-ERHP08R-050	10359332	HSK-E40	1,0 0.039	5,0 0.197	HP 08R	50,0 1.969	10,0 0.394	–	10,0 0.394	70,0 2.756	30,0 1.181	0	G2.5	0,3 0.660
HSKE40-ERHP11R-050-V	10359333	HSK-E40	1,0 0.039	7,0 0.276	HP 11R	50,0 1.969	17,9 0.704	–	16,0 0.630	70,0 2.756	30,0 1.181	0	G2.5	0,3 0.660
HSKE40-ERHP11R-130-V	10359334	HSK-E40	1,0 0.039	7,0 0.276	HP 11R	130,0 5.118	30,5 1.199	–	16,0 0.630	150,0 5.906	110,0 4.331	0	G2.5	0,6 1.320
HSKE40-ERHP16-060	10359335	HSK-E40	1,0 0.039	10,0 0.394	HP 16	60,0 2.362	30,0 1.181	–	30,0 1.181	80,0 3.150	40,0 1.575	0	G2.5	0,4 0.880
HSKE40-ERHP16-130-H	10359336	HSK-E40	1,0 0.039	10,0 0.394	HP 16	130,0 5.118	30,0 1.181	12,0 0.472	30,0 1.181	150,0 5.906	110,0 4.331	0	G2.5	0,8 1.760
HSKE40-ERHP20-060	10359337	HSK-E40	1,0 0.039	13,0 0.512	HP 20	60,0 2.362	32,0 1.260	–	32,0 1.260	80,0 3.150	40,0 1.575	0	G2.5	0,4 0.880
HSKE40-ERHP25-070	10359338	HSK-E40	1,0 0.039	16,0 0.630	HP 25	70,0 2.756	40,0 1.575	–	40,0 1.575	90,0 3.543	50,0 1.969	0	G2.5	0,5 1.100
HSKE50-ERHP16-060-H	10359339	HSK-E50	1,0 0.039	10,0 0.394	HP 16	60,0 2.362	30,0 1.181	19,5 0.768	30,0 1.181	85,0 3.346	34,0 1.339	0	G2.5	0,6 1.320
HSKE50-ERHP25-070-H	10359340	HSK-E50	1,0 0.039	16,0 0.630	HP 25	70,0 2.756	40,0 1.575	17,0 0.669	40,0 1.575	95,0 3.740	44,0 1.732	0	G2.5	0,7 1.540

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Accessories

Guide	Accessories			
	For	Key	Socket	Torque key
				
HSK-A	ERHP08R	—	03ERB010	03DYE003025
	ERHP11R	03LME0912140	03ER016	03DYE003025
	ERHP16R	03LME0912140	03ER022	03DYE010050
	ERHP16	03LME1418260	03ER030B	03DYE010100B
HSK-E	ERHP20	03LME1418260	03ER032B	03DYE010100B
	ERHP25	03LME1418260	03ER040	03DYE010100B

Spare Parts, included in delivery

DIN	For		Nut
			
BT JIS	ERHP08R		08B567208RC
	ERHP11R		08B567211RC
	ERHP16R		08B567216RC
	ERHP16		08B567216C
CAT	ERHP20		08B567220C
	ERHP25		08B567225C

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit




DIN

Seco range of rotating holders allow you to get the most out of both your machine and tool by offering a comprehensive array of solutions to connect them. The range covers all standard workpiece side connections, as well as unique connections. Machine side connections are included for most of the norms, including **DIN 69871**.

- Steadyline, vibration damping shell mill holders
- Shell mill holders, with through coolant channels
- Milling cutter holders, flange mounting
- Disc mill holders
- Side lock holders, Weldon
- Shrinkfit holders
- High precision collet chucks
- Hydraulics chucks and Power milling chucks
- ER collet chucks
- Drill chucks and Tapping chucks
- Taper adapters SA
- Greenstock blanks and Control bars

DIN 69871-A/AD/B (ISO 7388-1-A/AD/AF) and CAT-A/AD/B (ISO 7388-1-U/UD/UF)



**** DIN40 ADB/CAT 40 and DIN50 ADB/CAT50
with sealing dowel**

**** DIN40 ADB/CAT 40 and DIN50 ADB/CAT50
with sealing screw**

Machine side catalogue designation	Through coolant Form	Hole for RFID carrier*	d ₁	d ₃ max	d ₄	d ₅	l ₁ -0.2/0	d ₇ ^{6H}	d ₂ ^{H7}	d ₉	e ₁	l ₅	l ₆	b	j
			mm inch	mm inch	mm inch	mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
DIN30	A/AD	No*	31,75 1.250	45 1.772	44,3 1.744	50 1.969	47,8 1.882	M12	13 0.512	—	—	16,4 0.646	19 0.748	16,1 0.634	15 0.591
DIN40	A/AD	*	44,45 1.750	50 1.969	56,25 2.215	63,55 2.502	68,4 2.693	M16	17 0.669	—	—	22,8 0.898	25 0.984	16,1 0.634	18,5 0.728
DIN40 AD / CAT40	A/AD	*	44,45 1.750	44,45 1.750	56,25 2.215	63,55 2.502	68,4 2.693	M16	17 0.669	—	—	22,8 0.898	25 0.984	16,1 0.634	18,5 0.728
DIN40 ADB / CAT40	A/AD/B	*	44,45 1.750	44,45 1.750	56,25 2.215	63,55 2.502	68,4 2.693	M16	17 0.669	4 0.157	27 1.063	22,8 0.898	25 0.984	16,1 0.634	18,5 0.728
DIN40 ADB	A/AD/B	*	44,45 1.750	50 1.969	56,25 2.215	63,55 2.502	68,4 2.693	M16	17 0.669	4 0.157	27 1.063	22,8 0.898	25 0.984	16,1 0.634	18,5 0.728
DIN45	A/AD	*	57,15 2.250	63 2.480	75 2.953	82,55 3.250	82,7 3.256	M20	21 0.827	—	—	29,1 1.146	31,3 1.232	19,3 0.760	24 0.945
DIN50	A/AD	*	69,85 2.750	80 3.150	91,25 3.593	97,5 3.839	101,75 4.006	M24	25 0.984	—	—	35,5 1.398	37,7 1.484	25,7 1.012	30 1.181
DIN50 AD / CAT50	A/AD	*	69,85 2.750	69,85 2.750	91,25 3.593	97,5 3.839	101,75 4.006	M24	25 0.984	—	—	35,5 1.398	37,7 1.484	25,7 1.012	30 1.181
DIN50 ADB / CAT50	A/AD/B	*	69,85 2.750	69,85 2.750	91,25 3.593	97,5 3.839	101,75 4.006	M24	25 0.984	6 0.236	42 1.654	35,5 1.398	37,7 1.484	25,7 1.012	30 1.181
DIN50 ADB	A/AD/B	*	69,85 2.750	80 3.150	91,25 3.593	97,5 3.839	101,75 4.006	M24	25 0.984	6 0.236	42 1.654	35,5 1.398	37,7 1.484	25,7 1.012	30 1.181

Note: These machine side dimensions are applied to all the holders shown in the Product pages.

* In order to know if a hole for RFID carrier exists, see 'RFID hole' column in Product pages:

1= hole for RFID carrier available, if required a carrier can be fitted on request, please enquire.

0= hole for RFID carrier not available, if required hole can be machined and a carrier can be fitted on request, please enquire.


DIN/ CAT (Combined) indicate these holders of the DIN 69871 range feature the fixed diameter d3 of the ANSI B5 50/CAT norm (full ANSICAT conformity restricted by timing notch inclusion and metric pull-stud thread).

Steadyline®, vibration damping
– Metric/ Inch


DIN 69871-ADB



Design 1



Design 2




– DMM 40 mm / 1.575", includes 4 threaded holes for M12 screws on the bearing face $\varnothing 66,7$ mm / 2.626" according to DIN 6357
– For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant


Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	BD1	OAL	LB	LSC	Design	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E347155522210	02675749	DIN50 ADB	22,0 0.866	210,0 8.268	48,0 1.890	48,0 1.890	330,75 13.022	190,9 7.516	19,0 0.748	1	–	1	PB	5,36 11.820
E3471555622260	02675750	DIN50 ADB	22,0 0.866	260,0 10.236	48,0 1.890	66,0 2.598	380,7 14.988	241,0 9.488	19,0 0.748	2	2,0	1	PB	7,52 16.580
E347155527260	02675751	DIN50 ADB	27,0 1.063	260,0 10.236	60,0 2.362	60,0 2.362	382,75 15.069	240,9 9.484	21,0 0.827	1	–	1	PB	8,52 18.780
E3471555627320	02675752	DIN50 ADB	27,0 1.063	320,0 12.598	60,0 2.362	79,3 3.122	442,75 17.431	300,9 11.846	21,0 0.827	2	1,7	1	PB	12,26 27.030
E347155532330	02706263	DIN50 ADB	32,0 1.260	330,0 12.992	78,0 3.071	78,0 3.071	455,75 17.943	310,9 12.240	24,0 0.945	1	–	1	PB	14,96 32.980
E347155540350	02753471	DIN50 ADB	40,0 1.575	350,0 13.780	89,0 3.504	89,0 3.504	478,75 18.848	330,9 13.028	27,0 1.063	1	–	1	PB	20,4 44.970

Accessories

For	Bolt, through coolant	Spanner
		
DIN50/ 22/ 0.866	5802210L	5812210
DIN50/ 27/ 1.063	5802712L	5812712
DIN50/ 32/ 1.260	5803216L	5813216
DIN50/ 40/ 1.575	5804020L	5814020

Spare Parts, included in delivery

For	Bolt	Screw	Sealing Screws	Tenon
				
DIN50/ 22/ 0.866	5802210	950D0416	950A0606	16C2101111
DIN50/ 27/ 1.063	5802712	950D0516	950A0606	16C2121214A
DIN50/ 32/ 1.260	5803216	950D0516	950A0606	16C2141421A
DIN50/ 40/ 1.575	5804020	950D0616	950A0606	16C2161621A

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

With through coolant channels – ISO 3937
– Metric/ Inch




–DMM 40 mm / 1.575", includes 4 threaded holes for M12 screws on the bearing face Ø66,7 mm / 2.626" according to DIN 6357
–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant


Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
DIN40ADB-SM16-035-L1	10007162	DIN40 ADB	16,0 0.630	35,0 1.378	38,0 1.496	120,4 4.740	15,9 0.626	17,0 0.669	1	G6.3	1,0 2.200
DIN40ADB-SM16-100-L1	10007163	DIN40 ADB	16,0 0.630	100,0 3.937	38,0 1.496	185,4 7.299	80,9 3.185	17,0 0.669	1	G6.3	1,6 3.530
DIN40ADB-SM22-035-L1	10007164	DIN40 ADB	22,0 0.866	35,0 1.378	48,0 1.890	122,4 4.819	15,9 0.626	19,0 0.748	1	G6.3	1,1 2.430
DIN40ADB-SM22-100-L1	10007167	DIN40 ADB	22,0 0.866	100,0 3.937	48,0 1.890	187,4 7.378	80,9 3.185	19,0 0.748	1	G6.3	2,0 4.410
DIN40ADB-SM27-045-L1	10007169	DIN40 ADB	27,0 1.063	45,0 1.772	60,0 2.362	134,4 5.291	25,9 1.020	21,0 0.827	1	G6.3	1,4 3.090
DIN40ADB-SM27-100-L1	10007171	DIN40 ADB	27,0 1.063	100,0 3.937	60,0 2.362	189,4 7.457	80,9 3.185	21,0 0.827	1	G6.3	2,6 5.730
DIN40ADB-SM32-050-L1	10007172	DIN40 ADB	32,0 1.260	50,0 1.969	78,0 3.071	142,4 5.606	30,9 1.217	24,0 0.945	1	G6.3	1,8 3.970
DIN40ADB-SM40-050-L1	10007174	DIN40 ADB	40,0 1.575	50,0 1.969	89,0 3.504	145,4 5.724	30,9 1.217	27,0 1.063	1	G6.3	2,0 4.410
DIN50ADB-SM16-100-L1	10007177	DIN50 ADB	16,0 0.630	100,0 3.937	38,0 1.496	218,75 8.612	80,9 3.185	17,0 0.669	1	G6.3	3,3 7.280
DIN50ADB-SM22-035-L1	10007178	DIN50 ADB	22,0 0.866	35,0 1.378	48,0 1.890	155,75 6.132	15,9 0.626	19,0 0.748	1	G6.3	2,8 6.170
DIN50ADB-SM22-100-L1	10007179	DIN50 ADB	22,0 0.866	100,0 3.937	48,0 1.890	220,75 8.691	80,9 3.185	19,0 0.748	1	G6.3	3,7 8.160
DIN50ADB-SM22-160-L1	10007180	DIN50 ADB	22,0 0.866	160,0 6.299	48,0 1.890	280,75 11.053	140,9 5.547	19,0 0.748	1	G6.3	4,6 10.140
DIN50ADB-SM27-040-L1	10007181	DIN50 ADB	27,0 1.063	40,0 1.575	60,0 2.362	162,75 6.407	20,9 0.823	21,0 0.827	1	G6.3	3,1 6.830
DIN50ADB-SM27-100-L1	10007182	DIN50 ADB	27,0 1.063	100,0 3.937	60,0 2.362	222,75 8.770	80,9 3.185	21,0 0.827	1	G6.3	4,4 9.700
DIN50ADB-SM27-160-L1	10007183	DIN50 ADB	27,0 1.063	160,0 6.299	60,0 2.362	282,75 11.132	140,9 5.547	21,0 0.827	1	G6.3	5,7 12.570
DIN50ADB-SM32-050-L1	10007184	DIN50 ADB	32,0 1.260	50,0 1.969	78,0 3.071	175,75 6.919	30,9 1.217	24,0 0.945	1	G6.3	3,8 8.380
DIN50ADB-SM32-100-L1	10007185	DIN50 ADB	32,0 1.260	100,0 3.937	78,0 3.071	225,75 8.888	80,9 3.185	24,0 0.945	1	G6.3	5,7 12.570
DIN50ADB-SM32-160-L1	10007186	DIN50 ADB	32,0 1.260	160,0 6.299	78,0 3.071	285,75 11.250	140,9 5.547	24,0 0.945	1	G6.3	7,9 17.420
DIN50ADB-SM40-050-L1	10007187	DIN50 ADB	40,0 1.575	50,0 1.969	89,0 3.504	178,75 7.037	30,9 1.217	27,0 1.063	1	G6.3	4,1 9.040
DIN50ADB-SM40-100-L1	10007188	DIN50 ADB	40,0 1.575	100,0 3.937	89,0 3.504	228,75 9.006	80,9 3.185	27,0 1.063	1	G6.3	6,5 14.330
DIN50ADB-SM40-160-L1	10007189	DIN50 ADB	40,0 1.575	160,0 6.299	89,0 3.504	288,75 11.368	140,9 5.547	27,0 1.063	1	G6.3	9,3 20.500

Accessories

For	Bolt, through coolant	Spanner
		
DIN40/ 16/ 0.630	5801608L	5811608
DIN40/ 22/ 0.866	5802210L	5812210
DIN40/ 27/ 1.063	5802712L	5812712
DIN40/ 32/ 1.260	5803216L	5813216
DIN40/ 40/ 1.575	5804020L	5814020
DIN50/ 16/ 0.630	5801608L	5811608
DIN50/ 22/ 0.866	5802210L	5812210
DIN50/ 27/ 1.063	5802712L	5812712
DIN50/ 32/ 1.260	5803216L	5813216
DIN50/ 40/ 1.575	5804020L	5814020

Spare Parts, included in delivery

For	Bolt	Plug	Screw	Tenon
				
DIN40/ 16/ 0.630	5801608	950AIE0404	950D0312	16C716A
DIN40/ 22/ 0.866	5802210	950AIE0404	950D0412	16C722A
DIN40/ 27/ 1.063	5802712	950AIE0404	950D0515	16C727A
DIN40/ 32/ 1.260	5803216	950AIE0404	950D0615	16C732A
DIN40/ 40/ 1.575	5804020	950AIE0404	950D0615	16C740A
DIN50/ 16/ 0.630	5801608	950AIE0505	950D0312	16C716A
DIN50/ 22/ 0.866	5802210	950AIE0505	950D0412	16C722A
DIN50/ 27/ 1.063	5802712	950AIE0505	950D0515	16C727A
DIN50/ 32/ 1.260	5803216	950AIE0505	950D0615	16C732A
DIN50/ 40/ 1.575	5804020	950AIE0505	950D0615	16C740A

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Small face with through coolant channels – ISO 3937 – Metric/ Inch

DIN 69871-ADB




–Small workpiece side diameter BD according to ISO 3937, suitable for Seco disc mill cutters Type B
–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
DIN40ADB-SM22-044-F3L1	10007165	DIN40 ADB	22,0 0.866	44,0 1.732	40,0 1.575	131,4 5.173	24,9 0.980	19,0 0.748	1	G6.3	1,1 2.430
DIN40ADB-SM22-100-F3L1	10007166	DIN40 ADB	22,0 0.866	100,0 3.937	40,0 1.575	187,4 7.378	80,9 3.185	19,0 0.748	1	G6.3	1,7 3.750
DIN40ADB-SM27-044-F3L1	10007175	DIN40 ADB	27,0 1.063	44,0 1.732	48,0 1.890	133,4 5.252	24,9 0.980	21,0 0.827	1	G6.3	1,3 2.870
DIN40ADB-SM27-100-F3L1	10007170	DIN40 ADB	27,0 1.063	100,0 3.937	48,0 1.890	189,4 7.457	80,9 3.185	21,0 0.827	1	G6.3	2,0 4.410
DIN40ADB-SM32-060-F3L1	10007176	DIN40 ADB	32,0 1.260	60,0 2.362	58,0 2.283	152,4 6.000	40,9 1.610	24,0 0.945	1	G6.3	1,6 3.530
DIN40ADB-SM40-060-F3L1	10007173	DIN40 ADB	40,0 1.575	60,0 2.362	70,0 2.756	155,4 6.118	40,9 1.610	27,0 1.063	1	G6.3	2,1 4.630
DIN50ADB-SM22-044-F3L1	03301599	DIN50 ADB	22,0 0.866	44,0 1.732	40,0 1.575	164,75 6.486	24,9 0.980	19,0 0.748	1	G6.3	2,8 6.170
DIN50ADB-SM22-100-F3L1	03301600	DIN50 ADB	22,0 0.866	100,0 3.937	40,0 1.575	220,75 8.691	80,9 3.185	19,0 0.748	1	G6.3	3,4 7.500
DIN50ADB-SM22-160-F3L1	03301601	DIN50 ADB	22,0 0.866	160,0 6.299	40,0 1.575	280,75 11.053	140,9 5.547	19,0 0.748	1	G6.3	3,9 8.600
DIN50ADB-SM27-044-F3L1	10007147	DIN50 ADB	27,0 1.063	44,0 1.732	48,0 1.890	166,75 6.565	24,9 0.980	27,0 1.063	1	G6.3	2,8 6.170
DIN50ADB-SM27-100-F3L1	03301602	DIN50 ADB	27,0 1.063	100,0 3.937	48,0 1.890	222,75 8.770	80,9 3.185	21,0 0.827	1	G6.3	3,8 8.380
DIN50ADB-SM27-160-F3L1	03301603	DIN50 ADB	27,0 1.063	160,0 6.299	48,0 1.890	282,75 11.132	140,9 5.547	21,0 0.827	1	G6.3	4,6 10.140
DIN50ADB-SM32-044-F3L1	10007161	DIN50 ADB	32,0 1.260	44,0 1.732	58,0 2.283	169,75 6.683	24,9 0.980	27,0 1.063	1	G6.3	3,2 7.050
DIN50ADB-SM32-100-F3L1	03301604	DIN50 ADB	32,0 1.260	100,0 3.937	58,0 2.283	225,75 8.888	80,9 3.185	24,0 0.945	1	G6.3	4,4 9.700
DIN50ADB-SM32-160-F3L1	03301605	DIN50 ADB	32,0 1.260	160,0 6.299	58,0 2.283	285,75 11.250	140,9 5.547	24,0 0.945	1	G6.3	5,5 12.130
DIN50ADB-SM40-044-F3L1	10007168	DIN50 ADB	40,0 1.575	44,0 1.732	70,0 2.756	172,75 6.801	24,9 0.980	27,0 1.063	1	G6.3	3,6 7.940
DIN50ADB-SM40-100-F3L1	03301606	DIN50 ADB	40,0 1.575	100,0 3.937	70,0 2.756	228,75 9.006	80,9 3.185	27,0 1.063	1	G6.3	5,2 11.460
DIN50ADB-SM40-160-F3L1	03301607	DIN50 ADB	40,0 1.575	160,0 6.299	70,0 2.756	288,75 11.368	140,9 5.547	27,0 1.063	1	G6.3	6,9 15.210

Accessories

For	Bolt, through coolant	Spanner
		
DIN40/ 22/ 0.866	5802210L	5812210
DIN40/ 27/ 1.063	5802712L	5812712
DIN40/ 32/ 1.260	5803216L	5813216
DIN40/ 40/ 1.575	5804020L	5814020
DIN50/ 22/ 0.866	5802210L	5812210
DIN50/ 22/ 0.866 (-044)	5802210L	5812210
DIN50/ 27/ 1.063	5802712L	5812712
DIN50/ 27/ 1.063 (-044)	5802712L	5812712
DIN50/ 32/ 1.260	5803216L	5813216
DIN50/ 40/ 1.575	5804020L	5814020

Spare Parts, included in delivery

For	Bolt	Plug	Screw	Tenon
				
DIN40/ 22/ 0.866	5802210	950AIE0404	950D0410	16C722
DIN40/ 27/ 1.063	5802712	950AIE0404	950D0512	16C727
DIN40/ 32/ 1.260	5803216	950AIE0404	950D0612	16C732
DIN40/ 40/ 1.575	5804020	950AIE0404	950D0615	16C740
DIN50/ 22/ 0.866	5802210	950AIE0505	950D0410	16C722
DIN50/ 22/ 0.866 (-044)	5802210	950AIE0505	950D0410	16C727
DIN50/ 27/ 1.063	5802712	950AIE0505	950D0512	16C727
DIN50/ 27/ 1.063 (-044)	5802712	950AIE0505	950D0515	16C727A
DIN50/ 32/ 1.260	5803216	950AIE0505	950D0616	16C732
DIN50/ 40/ 1.575	5804020	950AIE0505	950D0616	16C740

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

Flange mounting – DIN 6357/ DIN 2079
– Metric/ Inch



–For ISO attribute explanation, see page 15


Spare parts:
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LSC	DBC	TDZ	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
DIN50AD-SMF40-070	03301611	DIN50 AD	40,0 1.575	70,0 2.756	89,0 3.504	201,75 7.943	30,0 1.181	66,7 2.626	M12	1	G6.3	4,9 10.800
DIN50AD-SMF60-070	03301612	DIN50 AD	60,0 2.362	70,0 2.756	129,0 5.079	211,75 8.337	40,0 1.575	101,6 4.000	M16	1	G6.3	7,4 16.310

Spare Parts, included in delivery

For	Screw	Tenon
		
DIN50AD-SMF40-070	950D0616	16C34040
DIN50AD-SMF60-070	950D1225	16C35060

– Metric/ Inch




– Best suited for Seco disc mill cutters Type A
– For ISO attribute explanation, see page 15

Spare parts:
1 = Slide rod
2 = Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	FLGT	LSCN	LSCX	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
E446956572265	02602691	DIN40 AD	22,0 0.866	65,0 2.559	35,0 1.378	133,4 5.252	45,9 1.807	4,0 0.157	0,0 0.0	12,0 0.472	1	PB	1,2 2.650
E446956572765	02602693	DIN40 AD	27,0 1.063	65,0 2.559	42,0 1.654	133,4 5.252	45,9 1.807	5,0 0.197	0,0 0.0	15,0 0.591	1	PB	1,4 3.090
E446956573290	02602694	DIN40 AD	32,0 1.260	90,0 3.543	48,0 1.890	158,4 6.236	70,9 2.791	6,0 0.236	0,0 0.0	24,0 0.945	1	PB	1,9 4.190
E4471565740100	02602697	DIN50 AD	40,0 1.575	100,0 3.937	58,0 2.283	201,7 7.941	80,9 3.185	7,0 0.276	0,0 0.0	30,0 1.181	1	PB	4,4 9.700
E4471565750160	02602699	DIN50 AD	50,0 1.969	160,0 6.299	72,0 2.835	261,7 10.303	140,9 5.547	8,0 0.315	0,0 0.0	32,0 1.260	1	PB	7,06 15.560

Spare Parts, included in delivery

For	Screw	Slide rod
		
22/ 0.866	19C565722	565722
27/ 1.063	19C565727	565727
32/ 1.260	950D1690	565732
40/ 1.575	19C565740	565740
50/ 1.969	19C565750	565750

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories


Shrinkfit

DIN 1835 Form B/ DIN 6535 Form HB
– Metric/ Inch


DIN 69871-ADB



Design 1



Design 2



–Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
–With 2 coolant channels for front lubrication which can be sealed with included screws
–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
DIN40ADB-EM06-050-L1	10007238	DIN40 ADB	6,0 0.236	50,0 1.969	30,9 1.217	35,0 1.378	25,0 0.984	118,4 4.661	32,0 1.260	1	1	G6.3	0,9 1.980
DIN40ADB-EM06-120-L1	10007239	DIN40 ADB	6,0 0.236	120,0 4.724	100,9 3.972	35,0 1.378	25,0 0.984	188,4 7.417	102,0 4.016	1	1	G6.3	1,1 2.430
DIN40ADB-EM08-050-L1	10007240	DIN40 ADB	8,0 0.315	50,0 1.969	30,9 1.217	35,0 1.378	28,0 1.102	118,4 4.661	32,0 1.260	1	1	G6.3	0,9 1.980
DIN40ADB-EM08-120-L1	10325542	DIN40 ADB	8,0 0.315	120,0 4.724	100,9 3.972	35,3 1.390	28,0 1.102	188,4 7.417	102,0 4.016	1	1	G6.3	1,3 2.870
DIN40ADB-EM10-050-L1	10007241	DIN40 ADB	10,0 0.394	50,0 1.969	30,9 1.217	36,0 1.417	35,0 1.378	118,4 4.661	30,0 1.181	1	1	G6.3	1,0 2.200
DIN40ADB-EM10-120-L1	10325543	DIN40 ADB	10,0 0.394	120,0 4.724	100,9 3.972	35,7 1.406	35,0 1.378	188,4 7.417	100,0 3.937	1	1	G6.3	1,5 3.310
DIN40ADB-EM12-050-L1	10007242	DIN40 ADB	12,0 0.472	50,0 1.969	30,9 1.217	41,0 1.614	42,0 1.654	118,4 4.661	27,5 1.083	1	1	G6.3	1,1 2.430
DIN40ADB-EM12-120-L1	10325544	DIN40 ADB	12,0 0.472	120,0 4.724	100,9 3.972	41,0 1.614	42,0 1.654	188,4 7.417	97,5 3.839	1	1	G6.3	1,8 3.970
DIN40ADB-EM14-050-L1	10007243	DIN40 ADB	14,0 0.551	50,0 1.969	30,9 1.217	41,0 1.614	44,0 1.732	118,4 4.661	27,5 1.083	1	1	G6.3	1,1 2.430
DIN40ADB-EM16-063-L1	10007244	DIN40 ADB	16,0 0.630	63,0 2.480	43,9 1.728	44,0 1.732	48,0 1.890	131,4 5.173	39,0 1.535	1	1	G6.3	1,3 2.870
DIN40ADB-EM16-120-L1	10007245	DIN40 ADB	16,0 0.630	120,0 4.724	100,9 3.972	44,0 1.732	48,0 1.890	188,4 7.417	96,0 3.780	1	1	G6.3	2,1 4.630
DIN40ADB-EM18-063-L1	10007246	DIN40 ADB	18,0 0.709	63,0 2.480	43,9 1.728	44,0 1.732	50,0 1.969	131,4 5.173	39,0 1.535	1	1	G6.3	1,3 2.870
DIN40ADB-EM20-063-L1	10007248	DIN40 ADB	20,0 0.787	63,0 2.480	43,9 1.728	46,0 1.811	52,0 2.047	131,4 5.173	38,0 1.496	1	1	G6.3	1,4 3.090
DIN40ADB-EM20-120-L1	10007249	DIN40 ADB	20,0 0.787	120,0 4.724	100,9 3.972	46,0 1.811	52,0 2.047	188,4 7.417	95,0 3.740	1	1	G6.3	2,3 5.070
DIN40ADB-EM25-100-L1	10007251	DIN40 ADB	25,0 0.984	100,0 3.937	80,9 3.185	54,0 2.126	63,0 2.480	168,4 6.630	76,0 2.992	2	1	G6.3	2,2 4.850
DIN40ADB-EM32-100-L1	10007253	DIN40 ADB	32,0 1.260	100,0 3.937	80,9 3.185	58,0 2.283	72,0 2.835	168,4 6.630	76,0 2.992	2	1	G6.3	2,5 5.510
DIN50ADB-EM06-063-L1	10007254	DIN50 ADB	6,0 0.236	63,0 2.480	43,9 1.728	35,0 1.378	25,0 0.984	164,75 6.486	45,0 1.772	1	1	G6.3	2,7 5.950
DIN50ADB-EM06-120-L1	03301716	DIN50 ADB	6,0 0.236	120,0 4.724	100,9 3.972	35,0 1.378	25,0 0.984	221,75 8.730	102,0 4.016	1	1	G6.3	2,9 6.390
DIN50ADB-EM08-063-L1	10007255	DIN50 ADB	8,0 0.315	63,0 2.480	43,9 1.728	35,0 1.378	28,0 1.102	164,75 6.486	45,0 1.772	1	1	G6.3	2,7 5.950
DIN50ADB-EM08-120-L1	10007256	DIN50 ADB	8,0 0.315	120,0 4.724	100,9 3.972	35,0 1.378	28,0 1.102	221,75 8.730	102,0 4.016	1	1	G6.3	3,0 6.610
DIN50ADB-EM10-063-L1	10007257	DIN50 ADB	10,0 0.394	63,0 2.480	43,9 1.728	36,0 1.417	35,0 1.378	164,75 6.486	43,0 1.693	1	1	G6.3	2,8 6.170
DIN50ADB-EM10-120-L1	10007258	DIN50 ADB	10,0 0.394	120,0 4.724	100,9 3.972	36,0 1.417	35,0 1.378	221,75 8.730	100,0 3.937	1	1	G6.3	3,0 6.610

Designation	Item number	CTMS	DCBN- DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
DIN50ADB-EM12-063-L1	10007259	DIN50 ADB	12,0 0.472	63,0 2.480	43,9 1.728	41,0 1.614	42,0 1.654	164,75 6.486	40,5 1.594	1	1	G6.3	2,9 6.390
DIN50ADB-EM12-120-L1	10007260	DIN50 ADB	12,0 0.472	120,0 4.724	100,9 3.972	41,0 1.614	42,0 1.654	221,75 8.730	97,5 3.839	1	1	G6.3	3,5 7.720
DIN50ADB-EM14-063-L1	10007261	DIN50 ADB	14,0 0.551	63,0 2.480	43,9 1.728	41,0 1.614	44,0 1.732	164,75 6.486	40,5 1.594	1	1	G6.3	2,9 6.390
DIN50ADB-EM16-063-L1	10007262	DIN50 ADB	16,0 0.630	63,0 2.480	43,9 1.728	44,0 1.732	48,0 1.890	164,75 6.486	39,0 1.535	1	1	G6.3	3,0 6.610
DIN50ADB-EM16-120-L1	10007263	DIN50 ADB	16,0 0.630	120,0 4.724	100,9 3.972	44,0 1.732	48,0 1.890	221,75 8.730	96,0 3.780	1	1	G6.3	3,7 8.160
DIN50ADB-EM16-160-L1	10007264	DIN50 ADB	16,0 0.630	160,0 6.299	140,9 5.547	44,0 1.732	48,0 1.890	261,75 10.305	136,0 5.354	1	1	G6.3	4,2 9.260
DIN50ADB-EM18-063-L1	10007265	DIN50 ADB	18,0 0.709	63,0 2.480	43,9 1.728	44,0 1.732	50,0 1.969	164,75 6.486	39,0 1.535	1	1	G6.3	3,1 6.830
DIN50ADB-EM20-063-L1	10007266	DIN50 ADB	20,0 0.787	63,0 2.480	43,9 1.728	46,0 1.811	52,0 2.047	164,75 6.486	38,0 1.496	1	1	G6.3	3,1 6.830
DIN50ADB-EM20-120-L1	10007267	DIN50 ADB	20,0 0.787	120,0 4.724	100,9 3.972	46,0 1.811	52,0 2.047	221,75 8.730	95,0 3.740	1	1	G6.3	3,9 8.600
DIN50ADB-EM25-080-L1	10007268	DIN50 ADB	25,0 0.984	80,0 3.150	60,9 2.398	54,0 2.126	65,0 2.559	181,75 7.156	56,0 2.205	2	1	G6.3	3,8 8.380
DIN50ADB-EM25-120-L1	10007269	DIN50 ADB	25,0 0.984	120,0 4.724	100,9 3.972	54,0 2.126	65,0 2.559	221,75 8.730	96,0 3.780	2	1	G6.3	4,7 10.360
DIN50ADB-EM32-100-L1	10007270	DIN50 ADB	32,0 1.260	100,0 3.937	80,9 3.185	58,0 2.283	72,0 2.835	201,75 7.943	76,0 2.992	2	1	G6.3	4,5 9.920
DIN50ADB-EM40-120-L1	10007271	DIN50 ADB	40,0 1.575	120,0 4.724	100,9 3.972	68,0 2.677	80,0 3.150	221,75 8.730	90,0 3.543	2	1	G6.3	5,6 12.350
DIN50ADB-EM50-130-L1	10007272	DIN50 ADB	50,0 1.969	130,0 5.118	110,9 4.366	78,0 3.071	100,0 3.937	231,75 9.124	95,0 3.740	2	1	G6.3	7,3 16.090

Spare Parts, included in delivery


For	Coolant screw	Locking screw	Plug
			
DIN40/ 10/ 0.394	950A0304	951C1012	950AIE0404
DIN40/ 10/ 0.394	950A0304	951C1012	-
DIN40/ 12/ 0.472	950A0304	951C1216	950AIE0404
DIN40/ 12/ 0.472	950A0304	951C1216	-
DIN40/ 14/ 0.551	950A0304	951C1216	950AIE0404
DIN40/ 16/ 0.630-18/ 0.709	950A0304	951C1416	950AIE0404
DIN40/ 20/ 0.787	950A0304	951C1616	950AIE0404
DIN40/ 25/ 0.984	950A0304	951C1820	950AIE0404
DIN40/ 32/ 1.260	950A0304	951C2020	950AIE0404
DIN40/ 6/ 0.236	950A0304	951C0610	950AIE0404
DIN40/ 8/ 0.315	950A0304	951C0810	950AIE0404
DIN40/ 8/ 0.315	950A0304	951C0810	-
DIN50/ 10/ 0.394	950A0304	951C1012	950AIE0505
DIN50/ 12/ 0.472	950A0304	951C1216	950AIE0505
DIN50/ 14/ 0.551	950A0304	951C1216	950AIE0505
DIN50/ 16/ 0.630-18/ 0.709	950A0304	951C1416	950AIE0505
DIN50/ 20/ 0.787	950A0304	951C1616	950AIE0505
DIN50/ 25/ 0.984	950A0304	951C1820	950AIE0505
DIN50/ 32/ 1.260-40/ 1.575	950A0304	951C2020	950AIE0505
DIN50/ 50/ 1.969	950A0304	951C2425	950AIE0505
DIN50/ 6/ 0.236	950A0304	951C0610	950AIE0505
DIN50/ 8/ 0.315	950A0304	951C0810	950AIE0505

Short type
– Metric/ Inch


DIN 69871-ADB



Design 1



Design 2



–Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
–With 2 coolant channels for front lubrication which can be sealed with included screws
–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw
2 = Locking screw, reduced


Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
DIN40ADB-EM20-035-F5L1	10007247	DIN40 ADB	20,0 0.787	35,0 1.378	15,9 0.626	46,0 1.811	50,0 1.969	103,4 4.071	10,0 0.394	1	1	G6.3	0,9 1.980
DIN40ADB-EM25-060-F5L1	10007250	DIN40 ADB	25,0 0.984	60,0 2.362	40,9 1.610	54,0 2.126	50,0 1.969	128,4 5.055	36,0 1.417	2	1	G6.3	1,2 2.650
DIN40ADB-EM32-075-F5L1	10007252	DIN40 ADB	32,0 1.260	75,0 2.953	55,9 2.201	58,0 2.283	72,0 2.835	143,4 5.646	51,0 2.008	2	1	G6.3	1,7 3.750
DIN50ADB-EM25-060-F5L1	03301717	DIN50 ADB	25,0 0.984	60,0 2.362	40,9 1.610	55,0 2.165	65,0 2.559	161,75 6.368	36,5 1.437	2	0	G6.3	3,3 7.280
DIN50ADB-EM32-060-F5L1	03301718	DIN50 ADB	32,0 1.260	60,0 2.362	40,9 1.610	58,0 2.283	72,0 2.835	161,75 6.368	36,0 1.417	2	0	G6.3	3,4 7.500

Spare Parts, included in delivery

For	Coolant screw	Locking screw	Locking screw, reduced	Plug
				
DIN40ADB-EM20-035-F5L1	950A0304	951C1614	–	950AIE0404
DIN40ADB-EM25-060-F5L1	950A0304	951C1814	950A1410	950AIE0404
DIN40ADB-EM32-075-F5L1	950A0304	951C2020	950A1410	950AIE0404
DIN50ADB-EM25-060-F5L1	950A0304	951C1820	950A1416	950AIE0505
DIN50ADB-EM32-060-F5L1	950A0304	951C2020	950A1416	950AIE0505

DIN type
– Metric/ Inch

DIN 69871-ADB



- Run-out $\leq 3 \mu\text{m}$
- Delivered with one stop screw
- For Shrinkfit extensions, see page(s) 357-358
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E346956030680	02752997	DIN40 ADB	6,0 0.236	80,0 3.150	60,9 2.398	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	148,4 5.843	44,0 1.732	54,0 2.126	10,5 0.413	M5x0.8	4,5	1	G2.5	1,1 2.430
E3469560306120	02752994	DIN40 ADB	6,0 0.236	120,0 4.724	100,9 3.972	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	188,4 7.417	84,0 3.307	94,0 3.701	10,5 0.413	M5x0.8	4,5	1	G2.5	1,2 2.650
E3469560306160	02752996	DIN40 ADB	6,0 0.236	160,0 6.299	140,9 5.547	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	228,4 8.992	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	G2.5	1,4 3.090
E346956030880	02753002	DIN40 ADB	8,0 0.315	80,0 3.150	60,9 2.398	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	148,4 5.843	44,0 1.732	54,0 2.126	10,5 0.413	M6x1	4,5	1	G2.5	1,0 2.200
E3469560308120	02752999	DIN40 ADB	8,0 0.315	120,0 4.724	100,9 3.972	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	188,4 7.417	84,0 3.307	94,0 3.701	10,5 0.413	M6x1	4,5	1	G2.5	1,2 2.650
E3469560308160	02753001	DIN40 ADB	8,0 0.315	160,0 6.299	140,9 5.547	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	228,4 8.992	124,0 4.882	134,0 5.276	10,5 0.413	M6x1	4,5	1	G2.5	1,4 3.090
E346956031080	02753006	DIN40 ADB	10,0 0.394	80,0 3.150	60,9 2.398	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	148,4 5.843	39,0 1.535	49,0 1.929	13,0 0.512	M8x1	4,5	1	G2.5	1,1 2.430
E3469560310120	02753003	DIN40 ADB	10,0 0.394	120,0 4.724	100,9 3.972	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	188,4 7.417	79,0 3.110	89,0 3.504	13,0 0.512	M8x1	4,5	1	G2.5	1,4 3.090
E3469560310160	02753004	DIN40 ADB	10,0 0.394	160,0 6.299	140,9 5.547	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	228,4 8.992	119,0 4.685	129,0 5.079	13,0 0.512	M8x1	4,5	1	G2.5	1,6 3.530
E346956031280	02753009	DIN40 ADB	12,0 0.472	80,0 3.150	60,9 2.398	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	148,4 5.843	34,0 1.339	44,0 1.732	13,0 0.512	M10x1	4,5	1	G2.5	1,1 2.430
E3469560312120	02753007	DIN40 ADB	12,0 0.472	120,0 4.724	100,9 3.972	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	188,4 7.417	74,0 2.913	84,0 3.307	13,0 0.512	M10x1	4,5	1	G2.5	1,3 2.870
E3469560312160	02753008	DIN40 ADB	12,0 0.472	160,0 6.299	140,9 5.547	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	228,4 8.992	114,0 4.488	124,0 4.882	13,0 0.512	M10x1	4,5	1	G2.5	1,6 3.530
E346956031480	02753012	DIN40 ADB	14,0 0.551	80,0 3.150	60,9 2.398	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	148,4 5.843	34,0 1.339	44,0 1.732	14,0 0.551	M10x1	4,5	1	G2.5	1,1 2.430
E3469560314120	02753010	DIN40 ADB	14,0 0.551	120,0 4.724	100,9 3.972	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	188,4 7.417	74,0 2.913	84,0 3.307	14,0 0.551	M10x1	4,5	1	G2.5	1,4 3.090
E346956031680	02753015	DIN40 ADB	16,0 0.630	80,0 3.150	60,9 2.398	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	148,4 5.843	31,0 1.220	41,0 1.614	14,0 0.551	M12x1	4,5	1	G2.5	1,1 2.430
E3469560316120	02753013	DIN40 ADB	16,0 0.630	120,0 4.724	100,9 3.972	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	188,4 7.417	71,0 2.795	81,0 3.189	14,0 0.551	M12x1	4,5	1	G2.5	1,4 3.090
E3469560316160	02753014	DIN40 ADB	16,0 0.630	160,0 6.299	140,9 5.547	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	228,4 8.992	111,0 4.370	121,0 4.764	14,0 0.551	M12x1	4,5	1	G2.5	1,6 3.530
E346956031880	02753018	DIN40 ADB	18,0 0.709	80,0 3.150	60,9 2.398	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	148,4 5.843	31,0 1.220	41,0 1.614	18,0 0.709	M12x1	4,5	1	G2.5	1,3 2.870
E346956032080	02753021	DIN40 ADB	20,0 0.787	80,0 3.150	60,9 2.398	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	148,4 5.843	29,0 1.142	39,0 1.535	18,0 0.709	M16x1	4,5	1	G2.5	1,2 2.650
E3469560320120	02753019	DIN40 ADB	20,0 0.787	120,0 4.724	100,9 3.972	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	188,4 7.417	69,0 2.717	79,0 3.110	18,0 0.709	M16x1	4,5	1	G2.5	1,6 3.530
E3469560325100	02753022	DIN40 ADB	25,0 0.984	100,0 3.937	80,9 3.185	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	168,4 6.630	43,0 1.693	53,0 2.087	23,5 0.925	M16x1	4,5	1	G2.5	1,8 3.970
E347156030680	02753023	DIN50 ADB	6,0 0.236	80,0 3.150	60,9 2.398	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	181,75 7.156	44,0 1.732	54,0 2.126	10,5 0.413	M5x0.8	4,5	1	G2.5	2,8 6.170

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating & setting accessories

Shrinkfit

Guide	Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
HSK-A	E3471560306160	02753024	DIN50 ADB	6,0 0.236	160,0 6.299	140,9 5.547	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	261,75 10.305	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	G2.5	3,05 6.720
	E347156030880	02753025	DIN50 ADB	8,0 0.315	80,0 3.150	60,9 2.398	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	181,75 7.156	44,0 1.732	54,0 2.126	10,5 0.413	M6x1	4,5	1	G2.5	2,8 6.170
	E3471560308160	02753026	DIN50 ADB	8,0 0.315	160,0 6.299	140,9 5.547	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	261,75 10.305	124,0 4.882	134,0 5.276	10,5 0.413	M6x1	4,5	1	G2.5	3,1 6.830
HSK-E	E347156031080	02753027	DIN50 ADB	10,0 0.394	80,0 3.150	60,9 2.398	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	181,75 7.156	39,0 1.535	49,0 1.929	13,0 0.512	M8x1	4,5	1	G2.5	2,9 6.390
	E3471560310160	02753028	DIN50 ADB	10,0 0.394	160,0 6.299	140,9 5.547	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	261,75 10.305	119,0 4.685	129,0 5.079	13,0 0.512	M8x1	4,5	1	G2.5	3,3 7.280
	E347156031280	02753029	DIN50 ADB	12,0 0.472	80,0 3.150	60,9 2.398	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	181,75 7.156	34,0 1.339	44,0 1.732	13,0 0.512	M10x1	4,5	1	G2.5	2,9 6.390
DIN	E3471560312160	02753030	DIN50 ADB	12,0 0.472	160,0 6.299	140,9 5.547	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	261,75 10.305	114,0 4.488	124,0 4.882	13,0 0.512	M10x1	4,5	1	G2.5	3,25 7.170
	E347156031480	02753031	DIN50 ADB	14,0 0.551	80,0 3.150	60,9 2.398	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	181,75 7.156	34,0 1.339	44,0 1.732	14,0 0.551	M10x1	4,5	1	G2.5	2,9 6.390
	E347156031680	02753032	DIN50 ADB	16,0 0.630	80,0 3.150	60,9 2.398	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	181,75 7.156	31,0 1.220	41,0 1.614	14,0 0.551	M12x1	4,5	1	G2.5	2,9 6.390
BT JIS	E3471560316160	02753033	DIN50 ADB	16,0 0.630	160,0 6.299	140,9 5.547	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	261,75 10.305	111,0 4.370	121,0 4.764	14,0 0.551	M12x1	4,5	1	G2.5	3,4 7.500
	E347156031880	02753035	DIN50 ADB	18,0 0.709	80,0 3.150	60,9 2.398	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	181,75 7.156	31,0 1.220	41,0 1.614	18,0 0.709	M12x1	4,5	1	G2.5	3,0 6.610
	E347156032080	02753037	DIN50 ADB	20,0 0.787	80,0 3.150	60,9 2.398	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	181,75 7.156	29,0 1.142	39,0 1.535	18,0 0.709	M16x1	4,5	1	G2.5	3,0 6.610
CAT	E3471560320160	02753039	DIN50 ADB	20,0 0.787	160,0 6.299	140,9 5.547	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	261,75 10.305	109,0 4.291	119,0 4.685	18,0 0.709	M16x1	4,5	1	G2.5	3,8 8.380
	E347156032590	02753040	DIN50 ADB	25,0 0.984	90,0 3.543	70,9 2.791	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	191,75 7.549	33,0 1.299	43,0 1.693	23,5 0.925	M16x1	4,5	1	G2.5	3,4 7.500
	E3471560325160	02753041	DIN50 ADB	25,0 0.984	160,0 6.299	140,9 5.547	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	261,75 10.305	103,0 4.055	113,0 4.449	23,5 0.925	M16x1	4,5	1	G2.5	4,47 9.850
Combimaster	E347156033290	02753042	DIN50 ADB	32,0 1.260	90,0 3.543	70,9 2.791	62,5 2.461	51,0 2.008	44,0 1.732	53,0 2.087	191,75 7.549	29,0 1.142	39,0 1.535	23,5 0.925	M16x1	4,5	1	G2.5	3,3 7.280
Accessories																			
Combimaster	For																		
	Balancing screws																		
Graflex																			
	All90ZQ01																		
Spare Parts, included in delivery																			
Seco Capto™	For																		
	Sealing Screws																		
Others																			
	Stop screw																		
Operating & setting accessories																			
Shrinkfit																			

Reinforced type
– Metric/ Inch

DIN 69871-ADB



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- * Holder without threaded holes for balancing screw
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-	LPR	LB	LB1	CBDP	LSC	BD1	BD2	BD3	OAL	LFN	LF	RL	TDZ	BHTA°	*	RFID hole	Balan- cing	Weight
			DCBX																		
E346956001065	02845510	DIN40 ADB	10,0 0.394	65,0 2.559	45,9 1.807	—	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	—	133,4 5.252	24,0 0.945	34,0 1.339	13,5 0.531	M8x1	4,5	1	G2.5	1,1 2.430	
E3469560010130	02845521	DIN40 ADB	10,0 0.394	130,0 5.118	110,9 4.366	52,0 2.047	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	49,5 1.949	198,4 7.811	89,0 3.504	99,0 3.898	13,5 0.531	M8x1	4,5	1	G2.5	1,8 3.970	
E346956001265	02845511	DIN40 ADB	12,0 0.472	65,0 2.559	45,9 1.807	—	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	—	133,4 5.252	19,0 0.748	29,0 1.142	13,5 0.531	M10x1	4,5	1	G2.5	1,1 2.430	
E3469560012130	02845522	DIN40 ADB	12,0 0.472	130,0 5.118	110,9 4.366	52,0 2.047	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	49,5 1.949	198,4 7.811	84,0 3.307	94,0 3.701	13,5 0.531	M10x1	4,5	1	G2.5	1,8 3.970	
E346956001665	02845512	DIN40 ADB	16,0 0.630	65,0 2.559	45,9 1.807	—	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	—	133,4 5.252	16,0 0.630	26,0 1.024	17,0 0.669	M12x1	4,5	1	G2.5	1,1 2.430	
E3469560016130	02845523	DIN40 ADB	16,0 0.630	130,0 5.118	110,9 4.366	58,0 2.283	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	49,5 1.949	198,4 7.811	81,0 3.189	91,0 3.583	17,0 0.669	M12x1	4,5	1	G2.5	1,9 4.190	
E346956002065	02845513	DIN40 ADB	20,0 0.787	65,0 2.559	45,9 1.807	—	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	49,5 1.949	133,4 5.252	14,0 0.551	24,0 0.945	21,5 0.846	M16x1	4,5	*	1	G2.5	1,3 2.870
E3469560020130	02845524	DIN40 ADB	20,0 0.787	130,0 5.118	110,9 4.366	—	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	49,5 1.949	198,4 7.811	79,0 3.110	89,0 3.504	21,5 0.846	M16x1	4,5	1	G2.5	2,4 5.290	
E3471560006160	02845544	DIN50 ADB	6,0 0.236	160,0 6.299	140,9 5.547	—	37,5 1.476	22,0 0.866	24,0 0.945	32,2 1.267	79,5 3.130	261,75 10.305	124,0 4.882	134,0 5.276	12,0 0.472	M5x0.8	4,5	1	G2.5	4,9 10.800	
E3471560008160	02845545	DIN50 ADB	8,0 0.315	160,0 6.299	140,9 5.547	52,0 2.047	37,5 1.476	26,0 1.024	24,0 0.945	32,2 1.267	79,5 3.130	261,75 10.305	124,0 4.882	134,0 5.276	12,0 0.472	M6x1	4,5	1	G2.5	4,9 10.800	
E3471560010160	02845546	DIN50 ADB	10,0 0.394	160,0 6.299	140,9 5.547	52,0 2.047	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	79,5 3.130	261,75 10.305	119,0 4.685	129,0 5.079	13,5 0.531	M8x1	4,5	1	G2.5	5,0 11.020	
E347156001280	02845537	DIN50 ADB	12,0 0.472	80,0 3.150	60,9 2.398	—	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	—	181,75 7.156	34,0 1.339	44,0 1.732	13,5 0.531	M10x1	4,5	1	G2.5	3,0 6.610	
E3471560012160	02845547	DIN50 ADB	12,0 0.472	160,0 6.299	140,9 5.547	181,0 7.126	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	79,5 3.130	261,75 10.305	114,0 4.488	124,0 4.882	13,5 0.531	M10x1	4,5	1	G2.5	5,0 11.020	
E3471560012200	02845554	DIN50 ADB	12,0 0.472	200,0 7.874	180,9 7.122	52,0 2.047	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	79,5 3.130	301,75 11.880	154,0 6.063	164,0 6.457	13,5 0.531	M10x1	4,5	1	G2.5	5,75 12.680	
E347156001680	02845538	DIN50 ADB	16,0 0.630	80,0 3.150	60,9 2.398	—	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	—	181,75 7.156	31,0 1.220	41,0 1.614	17,0 0.669	M12x1	4,5	1	G2.5	3,1 6.830	
E3471560016160	02845548	DIN50 ADB	16,0 0.630	160,0 6.299	140,9 5.547	58,0 2.283	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	79,5 3.130	261,75 10.305	111,0 4.370	121,0 4.764	17,0 0.669	M12x1	4,5	1	G2.5	5,2 11.460	
E3471560016200	02845555	DIN50 ADB	16,0 0.630	200,0 7.874	180,9 7.122	58,0 2.283	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	79,5 3.130	301,75 11.880	151,0 5.945	161,0 6.339	17,0 0.669	M12x1	4,5	1	G2.5	6,0 13.230	
E347156002080	02845539	DIN50 ADB	20,0 0.787	80,0 3.150	60,9 2.398	—	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	—	181,75 7.156	29,0 1.142	39,0 1.535	21,5 0.846	M16x1	4,5	1	G2.5	3,4 7.500	
E347156002590	02845540	DIN50 ADB	25,0 0.984	90,0 3.543	70,9 2.791	—	58,5 2.303	47,0 1.850	48,0 1.890	57,1 2.249	—	191,75 7.549	33,0 1.299	43,0 1.693	25,0 0.984	M16x1	4,5	1	G2.5	3,6 7.940	
E347156003290	02845541	DIN50 ADB	32,0 1.260	90,0 3.543	70,9 2.791	—	62,5 2.461	51,0 2.008	48,0 1.890	57,1 2.249	—	191,75 7.549	29,0 1.142	39,0 1.535	25,0 0.984	M16x1	4,5	1	G2.5	3,4 7.500	

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Accessories

For Balancing screws



All 90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Sealing Screws	Stop screw
			
DIN40/ 10/ 0.394	90AI03	950A0406	19BDR08165
DIN40/ 12/ 0.472	90AI03	950A0406	19BDR10165
DIN40/ 16/ 0.630	90AI03	950A0406	19BDR12165
DIN40/ 20/ 0.787-25/ 0.984	90AI04	950A0406	19BDR16165
DIN50/ 10/ 0.394	90AI03	950A0606	19BDR08165
DIN50/ 12/ 0.472	90AI03	950A0606	19BDR10165
DIN50/ 16/ 0.630	90AI03	950A0606	19BDR12165
DIN50/ 20/ 0.787-32/ 1.260	90AI04	950A0606	19BDR16165
DIN50/ 6/ 0.236	90AI03	950A0606	19BDR05165
DIN50/ 8/ 0.315	90AI03	950A0606	19BDR06165

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Mold and Die type
– Metric/ Inch

DIN/CAT (Combined)



– Run-out $\leq 3 \mu\text{m}$
– For Shrinkfit extensions, see page(s) 357-358
– For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	LSC	BD1	BD2	OAL	BHTA°	BHTA1°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E347658010380	00034443	DIN40 ADB/ CAT40	3,0 0.118	80,0 3.150	60,9 2.398	25,0 0.984	–	13,0 0.512	9,0 0.354	15,1 0.595	148,4 5.843	3,0	5,0	1	G2.5	1,0 2.200
E3476580103140	00047866	DIN40 ADB/ CAT40	3,0 0.118	140,0 5.512	120,9 4.760	25,0 0.984	–	13,0 0.512	9,0 0.354	25,6 1.009	208,4 8.205	3,0	5,0	1	G2.5	1,12 2.470
E347658010480	00034446	DIN40 ADB/ CAT40	4,0 0.157	80,0 3.150	60,9 2.398	25,0 0.984	–	15,0 0.591	10,0 0.394	16,1 0.635	148,4 5.843	3,0	5,0	1	G2.5	1,0 2.200
E3476580104140	00048122	DIN40 ADB/ CAT40	4,0 0.157	140,0 5.512	120,9 4.760	25,0 0.984	–	15,0 0.591	10,0 0.394	26,6 1.048	208,4 8.205	3,0	5,0	1	G2.5	1,2 2.650
E347658010680	00034448	DIN40 ADB/ CAT40	6,0 0.236	80,0 3.150	60,9 2.398	–	40,0 1.575	26,0 1.024	12,0 0.472	16,7 0.658	148,4 5.843	3,0	–	1	G2.5	1,1 2.430
E3476580106140	00048125	DIN40 ADB/ CAT40	6,0 0.236	140,0 5.512	120,9 4.760	32,0 1.260	40,0 1.575	26,0 1.024	12,0 0.472	28,1 1.107	208,4 8.205	3,0	5,0	1	G2.5	1,2 2.650
E347658010880	00034449	DIN40 ADB/ CAT40	8,0 0.315	80,0 3.150	60,9 2.398	–	44,0 1.732	30,0 1.181	16,0 0.630	20,7 0.816	148,4 5.843	3,0	–	1	G2.5	1,1 2.430
E3476580108140	00048139	DIN40 ADB/ CAT40	8,0 0.315	140,0 5.512	120,9 4.760	36,0 1.417	44,0 1.732	30,0 1.181	16,0 0.630	31,8 1.254	208,4 8.205	3,0	5,0	1	G2.5	1,3 2.870
E347658011080	00034450	DIN40 ADB/ CAT40	10,0 0.394	80,0 3.150	60,9 2.398	–	45,0 1.772	32,0 1.260	18,0 0.709	22,7 0.894	148,4 5.843	3,0	–	1	G2.5	1,1 2.430
E3476580110160	00048163	DIN40 ADB/ CAT40	10,0 0.394	160,0 6.299	140,9 5.547	38,0 1.496	45,0 1.772	32,0 1.260	18,0 0.709	37,2 1.465	228,4 8.992	3,0	5,0	1	G2.5	1,5 3.310
E347658011280	00034452	DIN40 ADB/ CAT40	12,0 0.472	80,0 3.150	60,9 2.398	–	46,0 1.811	34,0 1.339	20,0 0.787	24,7 0.973	148,4 5.843	3,0	–	1	G2.5	1,1 2.430

Spare Parts, included in delivery

For	Sealing Screws
	
DIN40	950A0406

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit


– Metric/ Inch



- Run-out 3 µm maximum at 3 x ØDCBN-DCBX
- For ER HP collets type 5672, see page(s) 389, 390, 391-397
- For stop screws, see instructions at www.secotools.com
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	RFID hole	Balan- cing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
DIN40AD-ERHP16-070	10359039	DIN40 AD	1,0 0.039	10,0 0.394	HP 16	70,4 2.772	30,0 1.181	30,0 1.181	138,8 5.465	51,3 2.020	1	G2.5	1,1 2.430
DIN40AD-ERHP16-100	10359040	DIN40 AD	1,0 0.039	10,0 0.394	HP 16	100,4 3.953	30,0 1.181	30,0 1.181	168,8 6.646	81,3 3.201	1	G2.5	1,2 2.650
DIN40AD-ERHP25-070	10359041	DIN40 AD	1,0 0.039	16,0 0.630	HP 25	70,4 2.772	40,0 1.575	40,0 1.575	138,8 5.465	51,3 2.020	1	G2.5	1,1 2.430
DIN40AD-ERHP25-100	10359042	DIN40 AD	1,0 0.039	16,0 0.630	HP 25	100,4 3.953	40,0 1.575	40,0 1.575	168,8 6.646	81,3 3.201	1	G2.5	1,4 3.090
DIN40AD-ERHP25-160	10359043	DIN40 AD	1,0 0.039	16,0 0.630	HP 25	160,7 6.327	40,0 1.575	40,0 1.575	229,1 9.020	141,6 5.575	1	G2.5	1,9 4.190
DIN40AD-ERHP32-070	10359044	DIN40 AD	2,0 0.079	20,0 0.787	HP 32	70,2 2.764	50,0 1.969	50,0 1.969	138,6 5.457	51,1 2.012	1	G2.5	1,3 2.870
DIN40AD-ERHP32-100	10359045	DIN40 AD	2,0 0.079	20,0 0.787	HP 32	100,2 3.945	50,0 1.969	50,0 1.969	168,6 6.638	81,1 3.193	1	G2.5	1,6 3.530
DIN40AD-ERHP32-160	10359046	DIN40 AD	2,0 0.079	20,0 0.787	HP 32	160,2 6.307	50,0 1.969	50,0 1.969	228,6 9.000	141,1 5.555	1	G2.5	2,4 5.290
DIN50AD-ERHP25-070	10359047	DIN50 AD	1,0 0.039	16,0 0.630	HP 25	69,8 2.748	40,0 1.575	40,0 1.575	171,6 6.756	50,7 1.996	1	G2.5	3,0 6.610
DIN50AD-ERHP32-070	10359048	DIN50 AD	2,0 0.079	20,0 0.787	HP 32	70,0 2.756	50,0 1.969	50,0 1.969	171,8 6.764	50,9 2.004	1	G2.5	3,1 6.830
DIN50AD-ERHP32-160	10359049	DIN50 AD	2,0 0.079	20,0 0.787	HP 32	160,0 6.299	50,0 1.969	50,0 1.969	261,8 10.307	140,9 5.547	1	G2.5	4,3 9.480

Accessories

For	Key	Socket	Torque key
ERHP16			
ERHP25	03LME1418260	03ER030B	03DYE010100B
ERHP32	03LME1418260	03ER040	03DYE010100B
	03LME1418370	03ER050	03DYE040200

Spare Parts, included in delivery

For	Nut
	
ERHP16	08B567216C
ERHP25	08B567225C
ERHP32	08B567232C

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

Conventional type
– Metric/ Inch




–Run-out $\leq 3 \mu\text{m}$
–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
DIN40ADB-HC06-080	10137275	DIN40 ADB	6,0 0.236	80,5 3.169	61,45 2.419	29,5 1.161	38,5 1.516	49,3 1.939	26,0 1.024	148,75 5.856	43,5 1.713	53,5 2.106	M5	20,0	1	G2.5	1,2 2.650
DIN40ADB-HC08-080	10137276	DIN40 ADB	8,0 0.315	80,5 3.169	61,45 2.419	30,0 1.181	38,5 1.516	49,3 1.939	28,0 1.102	148,75 5.856	43,5 1.713	53,5 2.106	M6	20,0	1	G2.5	1,4 3.090
DIN40ADB-HC10-080	10137277	DIN40 ADB	10,0 0.394	80,5 3.169	61,45 2.419	31,0 1.220	42,5 1.673	49,3 1.939	30,0 1.181	148,75 5.856	39,5 1.555	49,5 1.949	M8x1	20,0	1	G2.5	1,4 3.090
DIN40ADB-HC12-080	10137278	DIN40 ADB	12,0 0.472	80,5 3.169	61,45 2.419	31,5 1.240	47,5 1.870	49,3 1.939	32,0 1.260	148,75 5.856	34,5 1.358	44,5 1.752	M10x1	20,0	1	G2.5	1,4 3.090
DIN40ADB-HC16-080	10137279	DIN40 ADB	16,0 0.630	80,5 3.169	61,45 2.419	33,0 1.299	50,5 1.988	49,3 1.939	38,0 1.496	148,75 5.856	31,5 1.240	41,5 1.634	M12x1	20,0	1	G2.5	1,4 3.090
DIN40ADB-HC20-080	10138581	DIN40 ADB	20,0 0.787	80,5 3.169	61,45 2.419	34,0 1.339	52,5 2.067	49,3 1.939	42,0 1.654	148,75 5.856	29,5 1.161	39,5 1.555	M16x1	20,0	1	G2.5	1,4 3.090
DIN50ADB-HC12-080	10137280	DIN50 ADB	12,0 0.472	80,5 3.169	61,45 2.419	31,5 1.240	47,5 1.870	49,3 1.939	32,0 1.260	182,1 7.169	34,5 1.358	44,5 1.752	M10x1	20,0	1	G2.5	3,0 6.610
DIN50ADB-HC20-080	10138582	DIN50 ADB	20,0 0.787	80,5 3.169	61,45 2.419	34,0 1.339	52,5 2.067	49,3 1.939	42,0 1.654	182,1 7.169	29,5 1.161	39,5 1.555	M16x1	20,0	1	G2.5	3,2 7.050
DIN50ADB-HC32-103	10138583	DIN50 ADB	32,0 1.260	103,2 4.063	84,15 3.313	62,5 2.461	62,5 2.461	70,3 2.766	64,0 2.520	204,8 8.063	42,2 1.661	52,2 2.055	M16x1	20,0	1	G2.5	4,4 9.700


Accessories

For	Key
DIN40	H05-4
DIN50, DCBN = 12-20	H05-4
DIN50, DCBN = 32	03MS06L



Reinforced type
– Metric/ Inch

DIN 69871-ADB



- Run-out $\leq 3 \mu\text{m}$
- For reduction sleeves, see page(s) 381, 382
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
DIN40ADB-HCR12-050	10137129	DIN40 ADB	12,0 0.472	50,0 1.969	31,0 1.220	–	47,5 1.870	–	42,0 1.654	118,25 4.656	4,0 0.157	14,0 0.551	M8x1	–	0	G2.5	1,1 2.430
DIN40ADB-HCR20-064	10137130	DIN40 ADB	20,0 0.787	64,5 2.539	45,45 1.789	–	52,5 2.067	–	49,25 1.939	132,75 5.226	13,5 0.531	23,5 0.925	M8x1	–	0	G2.5	1,3 2.870
DIN50ADB-HCR20-064	10137131	DIN50 ADB	20,0 0.787	64,5 2.539	45,5 1.791	–	52,5 2.067	–	49,25 1.939	166,0 6.535	13,5 0.531	23,5 0.925	M8x1	–	0	G2.5	3,1 6.830
DIN50ADB-HCR32-081	10137132	DIN50 ADB	32,0 1.260	81,0 3.189	61,95 2.439	–	62,5 2.461	–	72,0 2.835	182,6 7.189	20,0 0.787	30,0 1.181	M8x1	–	0	G2.5	4,1 9.040

Accessories

For	Key
	
DIN40	H05-4
DIN50, DCBN = 20	H05-4
DIN50, DCBN = 32	03MS06L

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating &
setting acces-
series

Shrinkfit


– Metric/ Inch



Design 1



Design 2



–For reduction sleeves, see page(s) 385–386
 –For ‘Stop screws for through coolant’, see page(s) 387–388
 –For ISO attribute explanation, see page 15

Spare parts:
 1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	OAL	LPR	LB	CBDP	BD1	LFN	LF	KWW	TDZ	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
DIN40AD-PMC20-060	10185650	DIN40 AD	20,0 0.787	128,4 5.055	60,0 2.362	40,9 1.610	63,0 2.480	49,0 1.929	-3,0 -0.118	2,0 0.079	8,0	M16	1	1	PB	1,2 2.650
DIN40AD-PMC32-095	10185649	DIN40 AD	32,0 1.260	163,4 6.433	95,0 3.740	75,9 2.988	80,0 3.150	67,0 2.638	15,0 0.591	20,0 0.787	8,0	M16	2	1	PB	2,1 4.630
DIN50AD-PMC20-080	10185648	DIN50 AD	20,0 0.787	181,8 7.157	80,0 3.150	60,9 2.398	63,0 2.480	49,0 1.929	17,0 0.669	22,0 0.866	8,0	M16	1	1	PB	3,2 7.050
DIN50AD-PMC32-075	10185645	DIN50 AD	32,0 1.260	176,8 6.961	75,0 2.953	55,9 2.201	90,0 3.543	68,0 2.677	-15,0 -0.591	-10,0 -0.394	8,0	M16	1	1	PB	3,6 7.940

Accessories


For	Spanner
	
DIN40AD-PMC20	19BPMC2002A
DIN50AD-PMC20	03BPMC20
-PMC32	03BPMC32

Spare Parts, included in delivery

For	Extractor for reduction sleeves	Stop screw
		
All	03EXTPMC	19BEPMC01

ISO 15488
– Metric/ Inch

DIN 69871-AD



–Run-out 15 µm/ .0006" maximum at 3 x ØDCBN-DCBX
–For ER extensions and ER collets, see page(s) 362, 363, 399, 400, 401, 402
–For ER sealing rings, see page(s) 410, 411
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	Chuck & Collet Size	LPR	BD2	BD1	OAL	LB	LFN	LF	RFID hole	Balan- cing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
DIN40AD-ER16-070	10229603	DIN40 AD	0,5 0.020	10,0 0.394	ER 16	70,0 2.756	28,0 1.102	28,0 1.102	138,4 5.449	50,9 2.004	25,0 0.984	40,0 1.575	1	G6.3	1,0 2.200
DIN40AD-ER16-120	10229604	DIN40 AD	0,5 0.020	10,0 0.394	ER 16	120,0 4.724	28,0 1.102	28,0 1.102	188,4 7.417	100,9 3.972	75,0 2.953	90,0 3.543	1	G6.3	1,2 2.650
DIN40AD-ER20-070	10229605	DIN40 AD	1,0 0.039	13,0 0.512	ER 20	70,0 2.756	34,0 1.339	34,0 1.339	138,4 5.449	50,9 2.004	20,0 0.787	40,0 1.575	1	G6.3	1,1 2.430
DIN40AD-ER20-120	10229606	DIN40 AD	1,0 0.039	13,0 0.512	ER 20	120,0 4.724	34,0 1.339	34,0 1.339	188,4 7.417	100,9 3.972	70,0 2.756	90,0 3.543	1	G6.3	1,4 3.090
DIN40AD-ER25-070	10229607	DIN40 AD	1,0 0.039	16,0 0.630	ER 25	70,0 2.756	42,0 1.654	42,0 1.654	138,4 5.449	50,9 2.004	5,0 0.197	25,0 0.984	1	G6.3	1,1 2.430
DIN40AD-ER25-120	10229608	DIN40 AD	1,0 0.039	16,0 0.630	ER 25	120,0 4.724	42,0 1.654	42,0 1.654	188,4 7.417	100,9 3.972	55,0 2.165	75,0 2.953	1	G6.3	1,6 3.530
DIN40AD-ER32-070	10229609	DIN40 AD	2,0 0.079	20,0 0.787	ER 32	70,0 2.756	50,0 1.969	50,0 1.969	138,4 5.449	50,9 2.004	5,0 0.197	25,0 0.984	1	G6.3	1,2 2.650
DIN40AD-ER32-120	10229610	DIN40 AD	2,0 0.079	20,0 0.787	ER 32	120,0 4.724	50,0 1.969	50,0 1.969	188,4 7.417	100,9 3.972	55,0 2.165	75,0 2.953	1	G6.3	1,7 3.750
DIN40AD-ER40-070	10229611	DIN40 AD	3,0 0.118	26,0 1.024	ER 40	70,0 2.756	63,0 2.480	63,0 2.480	138,4 5.449	50,9 2.004	-5,0 -0.197	15,0 0.591	1	G6.3	1,3 2.870
DIN50AD-ER16-075	10229612	DIN50 AD	0,5 0.020	10,0 0.394	ER 16	75,0 2.953	28,0 1.102	28,0 1.102	176,75 6.959	55,9 2.201	30,0 1.181	45,0 1.772	1	G6.3	2,9 6.390
DIN50AD-ER16-120	10229613	DIN50 AD	0,5 0.020	10,0 0.394	ER 16	120,0 4.724	28,0 1.102	28,0 1.102	221,75 8.730	100,9 3.972	75,0 2.953	90,0 3.543	1	G6.3	3,2 7.050
DIN50AD-ER20-075	10229614	DIN50 AD	1,0 0.039	13,0 0.512	ER 20	75,0 2.953	34,0 1.339	34,0 1.339	176,75 6.959	55,9 2.201	25,0 0.984	45,0 1.772	1	G6.3	2,8 6.170
DIN50AD-ER20-120	10229615	DIN50 AD	1,0 0.039	13,0 0.512	ER 20	120,0 4.724	34,0 1.339	34,0 1.339	221,75 8.730	100,9 3.972	70,0 2.756	90,0 3.543	1	G6.3	3,1 6.830
DIN50AD-ER25-090	10229616	DIN50 AD	1,0 0.039	16,0 0.630	ER 25	90,0 3.543	42,0 1.654	42,0 1.654	191,75 7.549	70,9 2.791	25,0 0.984	45,0 1.772	1	G6.3	3,2 7.050
DIN50AD-ER25-120	10229617	DIN50 AD	1,0 0.039	16,0 0.630	ER 25	120,0 4.724	42,0 1.654	42,0 1.654	221,75 8.730	100,9 3.972	55,0 2.165	75,0 2.953	1	G6.3	3,4 7.500
DIN50AD-ER32-090	10229618	DIN50 AD	2,0 0.079	20,0 0.787	ER 32	90,0 3.543	50,0 1.969	50,0 1.969	191,75 7.549	70,9 2.791	25,0 0.984	45,0 1.772	1	G6.3	3,3 7.280
DIN50AD-ER32-120	10229619	DIN50 AD	2,0 0.079	20,0 0.787	ER 32	120,0 4.724	50,0 1.969	50,0 1.969	221,75 8.730	100,9 3.972	55,0 2.165	75,0 2.953	1	G6.3	3,7 8.160
DIN50AD-ER32-160	10229620	DIN50 AD	2,0 0.079	20,0 0.787	ER 32	160,0 6.299	50,0 1.969	50,0 1.969	261,75 10.305	140,9 5.547	95,0 3.740	115,0 4.528	1	G6.3	4,2 9.260
DIN50AD-ER40-100	10229621	DIN50 AD	3,0 0.118	26,0 1.024	ER 40	100,0 3.937	63,0 2.480	63,0 2.480	201,75 7.943	80,9 3.185	25,0 0.984	45,0 1.772	1	G6.3	3,8 8.380

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Grafix


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Accessories

Guide	Accessories		
	For	Seal nut	Spanner
			
HSK-A	ER16	08B587516IC	03B587516UM
	ER20	-	03B587520UM
	ER25	08B587525IC	03B587525
	ER32	08B587532IC	03B587532
	ER40	08B587540IC	03B587540
HSK-E	Spare Parts, included in delivery		
	For	Nut	Stop screw
			
DIN	ER16	08B587516UM	19LRC1020
	ER20	08B587520UM	19LRC1225
	ER25	08B587525X	19LRC1225
	ER32	08B587532X	19LRC1225
	ER40	08B587540X	19LRC1225
BT JIS			

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

– Metric/ Inch



–Run-out 40 µm maximum at 2,5 x ØDCBN-DCBX
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	OAL mm inch	LPR mm inch	LB mm inch	BD1 mm inch	RFID hole	Balancing	Weight kg lbs
E3469508513	00048223	DIN40 ADB	1,0 0.039	13,0 0.512	164,4 6.472	96,0 3.780	77,0 3.031	43,0 1.693	1	PB	1,24 2.730
E3471508516	00099664	DIN50 ADB	2,5 0.098	16,0 0.630	213,7 8.413	112,0 4.409	93,0 3.661	56,0 2.205	1	PB	3,68 8.110

Spare Parts, included in delivery


For	Sealing Screws
E3469508513	950A0406
E3471508516	950A0606




For synchronized tapping, with micro-compensation
– Metric/ Inch



Design 1




Design 2



- Maximum coolant pressure 80 bar/ 1160 psi
- For ER tapping collets with square drive, see page(s) 407, 408–409
- For TCER 5867 sealing rings, see page(s) 410, 411
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCBN	DCBX	LPR	LB	LB1	BD	BD1	OAL	SW	Design	RFID hole	Balan- cing	Weight
						mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
E4469586720102	02926979	DIN40 AD	ER 20	M4	M12	97,2 3.827	78,2 3.079	35,3 1.390	35,0 1.378	33,7 1.327	165,45 6.514	22,0 0.866	1	0	–	1,3 2.870
E4469586725122	02926980	DIN40 AD	ER 25	M8	M20	116,6 4.591	97,5 3.839	37,1 1.461	44,0 1.732	42,0 1.654	184,85 7.278	28,0 1.102	2	0	–	1,6 3.530
E4471586720106	02926981	DIN50 AD	ER 20	M4	M12	101,2 3.984	82,2 3.236	35,3 1.390	35,0 1.378	33,7 1.327	202,8 7.984	22,0 0.866	1	0	–	3,0 6.610
E4471586725126	02926982	DIN50 AD	ER 25	M8	M20	120,6 4.748	101,5 3.996	37,1 1.461	44,0 1.732	42,0 1.654	222,2 8.748	28,0 1.102	2	0	–	3,4 7.500
E4471586740155	02926983	DIN50 AD	ER 40	M16	M33	149,6 5.890	130,6 5.142	46,6 1.835	62,0 2.441	62,7 2.469	251,2 9.890	39,0 1.535	2	0	–	4,8 10.580

Accessories


For	Locking key	Seal nut	Spanner
			
ER 20	5680092-04	5533051-02	03B587520UM
ER 25	5680092-05	5533051-03	03B587525
ER 40	5680092-06	5533051-05	03B587540

Spare Parts, included in delivery

For	Nut
	
ER 20	5533050-08
ER 25	5533050-02
ER 40	5533050-04

SA – DIN 69871-BT
– Metric/ Inch

DIN 69871-A




– Direct run-out 5 µm maximum
– For ISO attribute explanation, see page 15

Spare parts:
1 = Screw
2 = Ring
3 = Balls
4 = Screw
5 = Washer

Designation	Item number	CTMS	CTWS	LPR	LB	BD	OAL	TDZ	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch				kg lbs
E44715434070T	75040732	DIN50 A	40 DIN 69871 BT	70,0 2.756	51,0 2.008	70,0 2.756	179,7 2.756	M16	1	PB	3,66 8.070
E447154350120T	75040733	DIN50 A	50 DIN 69871 BT	120,0 4.724	–	98,0 3.858	234,2 4.724	M24	1	PB	6,2 13.670

Spare Parts, included in delivery

For	Plug	Ring	Screw	Washer
				
E44715434070T	950A0505	02B54240	950E1670	15B54240
E447154350120T	950A0806	02B54250	19B172490	–

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

– Metric/ Inch



–The cylindrical front part is hardened to 120–130 daN/mm², allowing machining
 –For ISO attribute explanation, see page 15


Designation	Item number	CTMS	LPR	LB	SRR	BD	CND	OAL	CNDP	RFID hole	Balan- cing	Weight
			mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>			kg <i>lbs</i>
E3469502363250	02503167	DIN40 ADB	250,0 9.843	230,9 9.091	8,0 0.315	63,0 2.480	10,0 0.394	326,4 12.850	85,0 3.346	1	PB	6,48 14.290
E3471502363315	02503168	DIN50 ADB	315,0 12.402	295,9 11.650	8,0 0.315	63,0 2.480	8,0 0.315	424,75 16.722	120,0 4.724	1	PB	10,04 22.130
E3471502395315	02503169	DIN50 ADB	315,0 12.402	295,9 11.650	8,0 0.315	95,0 3.740	20,5 0.807	424,75 16.722	130,0 5.118	1	PB	19,0 41.890

Spare Parts, included in delivery

For	Sealing Screws
DIN40	950A0406
DIN50	950A0606



– Metric/ Inch



- Diameter, length values and measurement positions are laser engraved on each test bar
- DIN50 also suitable for BT50 spindles
- With protective case and measurement report
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	LPR	BD	OAL	RFID hole	Balancing	Weight
			mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>			kg <i>lbs</i>
E446958640330	75041806	DIN40 A	330,0 12.992	40,0 1.575	398,4 15.685	1	–	2,7 5.950
E447158650330	75041808	DIN50 A	330,0 12.992	50,0 1.969	431,7 16.996	1	–	6,8 14.990

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit




BT

Seco range of rotating holders allow you to get the most out of both your machine and tool by offering a comprehensive array of solutions to connect them. The range covers all standard workpiece side connections, as well Seco's unique connections

- Steadyline, vibration damping shell mill holders
- Shell mill holders, with through coolant channels
- Milling cutter holders, flange mounting
- Disc mill holders
- Side lock holders, Weldon
- Shrinkfit holders
- High precision collet chucks
- Hydraulics chucks and Power milling chucks
- ER collet chucks
- Drill chucks and Tapping chucks
- Taper adapters SA
- Greenstock blanks and Control bars

JIS B 6339 with coolant through A/AD/B from DIN (ISO 7388-2-J/JD/JF)



Machine side catalogue designation	Through coolant Form	Hole for RFID carrier*	d ₁	d ₂	d ₄	d ₅ ****	d ₇	d ₉	e ₁	u	l ₁	l ₆	l ₉	b	y
			mm inch	mm inch	mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
BT30	A/AD	No***	31,75 1.250	12,5 0.492	38 1.496	46 1.811	M12	—	—	22 0.866	48,4 1.906	16,3 0.642	11 0.433	16,1 0.634	2 0.079
BT40	A/AD	***	44,45 1.750	17 0.669	53 2.087	63 2.480	M16	—	—	27 1.063	65,4 2.575	22,5 0.886	14,5 0.571	16,1 0.634	2 0.079
BT40 ADB	A/AD/B	***	44,45 1.750	17 0.669	53 2.087	63 2.480	M16	4 0.157	27 1.063	27 1.063	65,4 2.575	22,5 0.886	14,5 0.571	16,1 0.634	2 0.079
BT50	A/AD	***	69,85 2.750	25 0.984	85 3.346	100 3.937	M24	—	—	38 1.496	101,8 4.008	35,4 1.394	20,5 0.807	25,7 1.012	3 0.118
BT50 ADB	A/AD/B	***	69,85 2.750	25 0.984	85 3.346	100 3.937	M24	6 0.236	42 1.654	38 1.496	101,8 4.008	35,4 1.394	20,5 0.807	25,7 1.012	3 0.118

Note: These machine side dimensions are applied to all the holders shown in the Product pages.

The B through coolant design of ADB holders is made according to DIN 69871-B.

* BT holders with a front end diameter in excess of diameter d₅, are produced with a flange clearance length: BT30 = Ø 45 mm x 3 mm; BT40 = Ø 62 mm x 8 mm; BT50 = Ø 98 mm x 12 mm. This is compatible with the BT JIS norm which permits free dimensions on workpiece side.

*** In order to know if a hole for RFID carrier exists, see 'RFID hole' column in Product pages:

1= hole for RFID carrier available, if required a carrier can be fitted on request, please enquire.

0= hole for RFID carrier not available, if required hole can be machined and a carrier can be fitted on request, please enquire.

Steadyline®, vibration damping
– Metric/ Inch

BT JIS B 6339-ADB

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories


Shrinkfit



Design 1 (5555)



Design 2 (5556)




–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant


Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	BD1	OAL	LB	LSC	Design	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E3414555522210	02675756	BT40 ADB	22,0 0.866	210,0 8.268	48,0 1.890	48,0 1.890	294,4 11.591	183,0 7.205	19,0 0.748	1	–	1	PB	3,78 8.330
E3416555522210	02675760	BT50 ADB	22,0 0.866	210,0 8.268	48,0 1.890	48,0 1.890	330,8 13.024	172,0 6.772	19,0 0.748	1	–	1	PB	6,08 13.400
E3416555622260	02671860	BT50 ADB	22,0 0.866	260,0 10.236	48,0 1.890	64,0 2.520	380,8 14.992	222,0 8.740	19,0 0.748	2	1,9	1	PB	7,9 17.420
E3416555527260	02675761	BT50 ADB	27,0 1.063	260,0 10.236	60,0 2.362	60,0 2.362	382,8 15.071	222,0 8.740	21,0 0.827	1	–	1	PB	9,06 19.970
E3416555627320	02675762	BT50 ADB	27,0 1.063	320,0 12.598	60,0 2.362	80,0 3.150	442,8 17.433	282,0 11.102	21,0 0.827	2	1,9	1	PB	12,64 27.870
E341655532330	02706265	BT50 ADB	32,0 1.260	330,0 12.992	78,0 3.071	78,0 3.071	455,8 17.945	292,0 11.496	24,0 0.945	1	–	1	PB	15,34 33.820

Accessories


For	Bolt, through coolant	Spanner
		
BT40/ 22	5802210L	5812210
BT50/ 22	5802210L	5812210
BT50/ 27	5802712L	5812712
BT50/ 32	5803216L	5813216

Spare Parts, included in delivery

For	Bolt	Screw	Sealing Screws	Tenon
				
BT40/ 22	5802210	950D0416	950A0406	16C2101111
BT50/ 22	5802210	950D0416	950A0606	16C2101111
BT50/ 27	5802712	950D0516	950A0606	16C2121214A
BT50/ 32	5803216	950D0516	950A0606	16C2141421A

With through coolant channels – ISO 3937
– Metric/ Inch

BT JIS B 6339-ADB



– DMM 40 mm / 1.575", includes 4 threaded holes for M12 screws on the bearing face $\varnothing 66,7$ mm / 2.626" according to DIN 6357
– For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT40ADB-SM16-045-L1	10007139	BT40 ADB	16,0 0.630	45,0 1.772	38,0 1.496	127,4 5.016	18,0 0.709	17,0 0.669	1	G6.3	1,2 2.650
BT40ADB-SM16-100-L1	10007140	BT40 ADB	16,0 0.630	100,0 3.937	38,0 1.496	182,4 7.181	73,0 2.874	17,0 0.669	1	G6.3	1,7 3.750
BT40ADB-SM22-045-L1	10007141	BT40 ADB	22,0 0.866	45,0 1.772	48,0 1.890	129,4 5.094	18,0 0.709	19,0 0.748	1	G6.3	1,3 2.870
BT40ADB-SM22-100-L1	10007142	BT40 ADB	22,0 0.866	100,0 3.937	48,0 1.890	184,4 7.260	73,0 2.874	19,0 0.748	1	G6.3	2,0 4.410
BT40ADB-SM27-045-L1	10007143	BT40 ADB	27,0 1.063	45,0 1.772	60,0 2.362	131,4 5.173	18,0 0.709	21,0 0.827	1	G6.3	1,5 3.310
BT40ADB-SM27-100-L1	10007144	BT40 ADB	27,0 1.063	100,0 3.937	60,0 2.362	186,4 7.339	73,0 2.874	21,0 0.827	1	G6.3	2,7 5.950
BT40ADB-SM32-050-L1	10007145	BT40 ADB	32,0 1.260	50,0 1.969	78,0 3.071	139,4 5.488	23,0 0.906	24,0 0.945	1	G6.3	1,8 3.970
BT40ADB-SM40-050-L1	10007146	BT40 ADB	40,0 1.575	50,0 1.969	89,0 3.504	142,4 5.606	23,0 0.906	27,0 1.063	1	G6.3	2,1 4.630
BT50ADB-SM16-100-L1	10007148	BT50 ADB	16,0 0.630	100,0 3.937	38,0 1.496	218,8 8.614	62,0 2.441	17,0 0.669	1	G6.3	4,1 9.040
BT50ADB-SM22-055-L1	10007149	BT50 ADB	22,0 0.866	55,0 2.165	48,0 1.890	175,8 6.921	17,0 0.669	19,0 0.748	1	G6.3	3,8 8.380
BT50ADB-SM22-100-L1	10007150	BT50 ADB	22,0 0.866	100,0 3.937	48,0 1.890	220,8 8.693	62,0 2.441	19,0 0.748	1	G6.3	4,5 9.920
BT50ADB-SM22-160-L1	10007151	BT50 ADB	22,0 0.866	160,0 6.299	48,0 1.890	280,8 11.055	122,0 4.803	19,0 0.748	1	G6.3	5,3 11.680
BT50ADB-SM27-055-L1	10007152	BT50 ADB	27,0 1.063	55,0 2.165	60,0 2.362	177,8 7.000	17,0 0.669	21,0 0.827	1	G6.3	4,0 8.820
BT50ADB-SM27-100-L1	10007153	BT50 ADB	27,0 1.063	100,0 3.937	60,0 2.362	222,8 8.772	62,0 2.441	21,0 0.827	1	G6.3	5,0 11.020
BT50ADB-SM27-160-L1	10007154	BT50 ADB	27,0 1.063	160,0 6.299	60,0 2.362	282,8 11.134	122,0 4.803	21,0 0.827	1	G6.3	6,3 13.890
BT50ADB-SM32-055-L1	10007155	BT50 ADB	32,0 1.260	55,0 2.165	78,0 3.071	180,8 7.118	17,0 0.669	24,0 0.945	1	G6.3	4,3 9.480
BT50ADB-SM32-100-L1	10007156	BT50 ADB	32,0 1.260	100,0 3.937	78,0 3.071	225,8 8.890	62,0 2.441	24,0 0.945	1	G6.3	6,0 13.230
BT50ADB-SM32-160-L1	10007157	BT50 ADB	32,0 1.260	160,0 6.299	78,0 3.071	285,8 11.252	122,0 4.803	24,0 0.945	1	G6.3	8,2 18.080
BT50ADB-SM40-055-L1	10007158	BT50 ADB	40,0 1.575	55,0 2.165	89,0 3.504	183,8 7.236	17,0 0.669	27,0 1.063	1	G6.3	4,6 10.140
BT50ADB-SM40-100-L1	10007159	BT50 ADB	40,0 1.575	100,0 3.937	89,0 3.504	228,8 9.008	62,0 2.441	27,0 1.063	1	G6.3	6,7 14.770
BT50ADB-SM40-160-L1	10007160	BT50 ADB	40,0 1.575	160,0 6.299	89,0 3.504	288,8 11.370	122,0 4.803	27,0 1.063	1	G6.3	9,2 20.280

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Grafex

Seco Capto™

Others


Operating & setting accessories

Shrinkfit

secotools.com

With through coolant channels – ISO 3937
– Inch

BT JIS B 6339-AD




–For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch			lbs
BT40AD-SM0.750-1.750-L1	03301687	BT40 AD	0.750	1.750	1.750	5.013	0.687	0.688	1	G6.3	2.650
BT40AD-SM1.000-1.750-L1	03301684	BT40 AD	1.000	1.750	2.250	5.013	0.687	0.688	1	G6.3	3.090
BT50AD-SM0.750-2.250-L1	03301680	BT50 AD	0.750	2.250	1.750	6.946	0.754	0.688	1	G6.3	8.380

Spare Parts, included in delivery

For	Bolt	Plug	Screw	Tenon
				
BT40/ 0.750	58271905	950AIE0404	950DNC012031	16C71905
BT40/ 1.000	58272540	950AIE0404	950DNC016037	16C72540
BT50/ 0.750	58271905	950AIE0505	950DNC012031	16C71905

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

Small face with through coolant channels – ISO 3937
– Metric/ Inch



–Small workpiece side diameter BD according to ISO 3937, suitable for Seco disc mill cutters Type B
–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT30AD-SM22-040-F3L1	03301665	BT30 AD	22,0 0.866	40,0 1.575	40,0 1.575	107,4 4.228	18,0 0.709	19,0 0.748	0	G6.3	0,6 1.320
BT30AD-SM22-100-F3L1	03301666	BT30 AD	22,0 0.866	100,0 3.937	40,0 1.575	167,4 6.591	78,0 3.071	19,0 0.748	0	G6.3	1,2 2.650
BT30AD-SM27-040-F3L1	03301667	BT30 AD	27,0 1.063	40,0 1.575	48,0 1.890	109,4 4.307	18,0 0.709	21,0 0.827	0	G6.3	0,8 1.760
BT30AD-SM27-100-F3L1	03301668	BT30 AD	27,0 1.063	100,0 3.937	48,0 1.890	169,4 6.669	78,0 3.071	21,0 0.827	0	G6.3	1,6 3.530


Accessories

For	Bolt, through coolant	Spanner
22	5802210L	5812210
27	5802712L	5812712

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
22	5802210	950D0410	16C722
27	5802712	950D0512	16C727

Small face with through coolant channels – ISO 3937
 – Metric/ Inch

BT JIS B 6339-AD


– Small workpiece side diameter BD according to ISO 3937, suitable for Seco disc mill cutters Type B
 – For ISO attribute explanation, see page 15

Accessories:
 4 = Bolt, through coolant

Spare parts:
 1 = Bolt
 2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT40ADB-SM22-052-F3L1	03301654	BT40 ADB	22,0 0.866	52,0 2.047	40,0 1.575	136,4 5.370	25,0 0.984	19,0 0.748	1	G6.3	1,3 2.870
BT40ADB-SM22-100-F3L1	03301655	BT40 ADB	22,0 0.866	100,0 3.937	40,0 1.575	184,4 7.260	73,0 2.874	19,0 0.748	1	G6.3	1,8 3.970
BT40ADB-SM27-052-F3L1	03301656	BT40 ADB	27,0 1.063	52,0 2.047	48,0 1.890	138,4 5.449	25,0 0.984	21,0 0.827	1	G6.3	1,4 3.090
BT40ADB-SM27-100-F3L1	03301657	BT40 ADB	27,0 1.063	100,0 3.937	48,0 1.890	186,4 7.339	73,0 2.874	21,0 0.827	1	G6.3	2,1 4.630
BT40ADB-SM32-052-F3L1	03301659	BT40 ADB	32,0 1.260	52,0 2.047	58,0 2.283	141,4 5.567	25,0 0.984	24,0 0.945	1	G6.3	1,7 3.750
BT40ADB-SM40-060-F3L1	03301660	BT40 ADB	40,0 1.575	60,0 2.362	70,0 2.756	152,4 6.000	33,0 1.299	27,0 1.063	1	G6.3	2,2 4.850
BT50ADB-SM22-063-F3L1	03301630	BT50 ADB	22,0 0.866	63,0 2.480	40,0 1.575	183,8 7.236	25,0 0.984	19,0 0.748	1	G6.3	3,8 8.380
BT50ADB-SM22-100-F3L1	03301631	BT50 ADB	22,0 0.866	100,0 3.937	40,0 1.575	220,8 8.693	62,0 2.441	19,0 0.748	1	G6.3	4,2 9.260
BT50ADB-SM22-160-F3L1	03301632	BT50 ADB	22,0 0.866	160,0 6.299	40,0 1.575	280,8 11.055	122,0 4.803	19,0 0.748	1	G6.3	4,8 10.580
BT50ADB-SM27-063-F3L1	03301634	BT50 ADB	27,0 1.063	63,0 2.480	48,0 1.890	185,8 7.315	25,0 0.984	21,0 0.827	1	G6.3	3,9 8.600
BT50ADB-SM27-100-F3L1	03301635	BT50 ADB	27,0 1.063	100,0 3.937	48,0 1.890	222,8 8.772	62,0 2.441	21,0 0.827	1	G6.3	4,5 9.920
BT50ADB-SM27-160-F3L1	03301636	BT50 ADB	27,0 1.063	160,0 6.299	48,0 1.890	282,8 11.134	122,0 4.803	21,0 0.827	1	G6.3	5,3 11.680
BT50ADB-SM32-063-F3L1	03301637	BT50 ADB	32,0 1.260	63,0 2.480	58,0 2.283	188,8 7.433	25,0 0.984	24,0 0.945	1	G6.3	4,2 9.260
BT50ADB-SM32-100-F3L1	03301638	BT50 ADB	32,0 1.260	100,0 3.937	58,0 2.283	225,8 8.890	62,0 2.441	24,0 0.945	1	G6.3	4,9 10.800
BT50ADB-SM32-160-F3L1	03301639	BT50 ADB	32,0 1.260	160,0 6.299	58,0 2.283	285,8 11.252	122,0 4.803	24,0 0.945	1	G6.3	6,1 13.450
BT50ADB-SM40-063-F3L1	03301640	BT50 ADB	40,0 1.575	63,0 2.480	70,0 2.756	191,8 7.551	25,0 0.984	27,0 1.063	1	G6.3	4,5 9.920
BT50ADB-SM40-160-F3L1	03301642	BT50 ADB	40,0 1.575	160,0 6.299	70,0 2.756	288,8 11.370	122,0 4.803	27,0 1.063	1	G6.3	7,3 16.090

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Accessories

Guide	Accessories		
	For	Bolt, through coolant	Spanner
			
HSK-A	BT40/ 22	5802210L	5812210
	BT40/ 27	5802712L	5812712
	BT40/ 32	5803216L	5813216
	BT40/ 40	5804020L	5814020
HSK-E	BT50/ 22	5802210L	5812210
	BT50/ 27	5802712L	5812712
	BT50/ 32	5803216L	5813216
	BT50/ 40	5804020L	5814020

Spare Parts, included in delivery

DIN	Spare Parts, included in delivery				
	For	Bolt	Plug	Screw	Tenon
					
BT JIS	BT40/ 22	5802210	950AIE0404	950D0410	16C722
	BT40/ 27	5802712	950AIE0404	950D0512	16C727
	BT40/ 32	5803216	950AIE0404	950D0616	16C732
	BT40/ 40	5804020	950AIE0404	950D0616	16C740
CAT	BT50/ 22	5802210	950AIE0505	950D0410	16C722
	BT50/ 27	5802712	950AIE0505	950D0512	16C727
	BT50/ 32	5803216	950AIE0505	950D0616	16C732
	BT50/ 40	5804020	950AIE0505	950D0616	16C740

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

Flange mounting – DIN 6357/ DIN 2079
– Metric/ Inch

BT JIS B 6339-AD



–For ISO attribute explanation, see page 15

Spare parts:
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LSC	DBC	TDZ	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
BT50AD-SMF40-070	03301643	BT50 AD	40,0 1.575	70,0 2.756	89,0 3.504	201,8 7.945	30,0 1.181	66,7 2.626	M12	1	G6.3	5,3 11.680
BT50AD-SMF60-080	03301644	BT50 AD	60,0 2.362	80,0 3.150	129,0 5.079	221,8 8.732	40,0 1.575	101,6 4.000	M16	1	G6.3	8,0 17.640

Spare Parts, included in delivery

For	Screw	Tenon
		
BT50AD-SMF40-070	950D0616	16C34040
BT50AD-SMF60-080	950D1225	16C35060

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

– Metric/ Inch




–Best suited for Seco disc mill cutters Type A
–For ISO attribute explanation, see page 15

Spare parts:
1 = Slide rod
2 = Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	FLGT	LSCN	LSCX	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
E404156573290	02602705	BT40 A	32,0 1.260	90,0 3.543	48,0 1.890	155,4 6.118	63,0 2.480	6,0 0.236	0,0 0.0	24,0 0.945	1	PB	1,91 4.210
E5766565740120	02602710	BT50 A	40,0 1.575	120,0 4.724	58,0 2.283	221,8 8.732	82,0 3.228	7,0 0.276	0,0 0.0	30,0 1.181	1	PB	5,4 11.900
E5766565750145	02602712	BT50 A	50,0 1.969	145,0 5.709	72,0 2.835	246,8 9.717	107,0 4.213	8,0 0.315	0,0 0.0	32,0 1.260	1	PB	7,04 15.520

Spare Parts, included in delivery


For	Screw	Slide rod
		
E404156573290	950D1690	565732
E5766565740120	19C565740	565740
E5766565750145	19C565750	565750

DIN 1835 Form B/ DIN 6535 Form HB
– Metric/ Inch


BT JIS B 6339-ADB



Design 1



Design 2



– Weldon $\varnothing$ DCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
– With 2 coolant channels for front lubrication which can be sealed with included screws
– For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
BT40ADB-EM06-050-L1	10007206	BT40 ADB	6,0 0.236	50,0 1.969	23,0 0.906	35,0 1.378	25,0 0.984	115,4 4.543	32,0 1.260	1	1	G6.3	1,1 2.430
BT40ADB-EM06-120-L1	10007207	BT40 ADB	6,0 0.236	120,0 4.724	93,0 3.661	35,0 1.378	25,0 0.984	185,4 7.299	102,0 4.016	1	1	G6.3	1,2 2.650
BT40ADB-EM08-050-L1	10007208	BT40 ADB	8,0 0.315	50,0 1.969	23,0 0.906	35,0 1.378	28,0 1.102	115,4 4.543	32,0 1.260	1	1	G6.3	1,1 2.430
BT40ADB-EM08-120-L1	10325536	BT40 ADB	8,0 0.315	120,0 4.724	93,0 3.661	34,8 1.370	28,0 1.102	185,4 7.299	102,0 4.016	1	1	G6.3	1,5 3.310
BT40ADB-EM10-063-L1	10007209	BT40 ADB	10,0 0.394	63,0 2.480	36,0 1.417	36,0 1.417	35,0 1.378	128,4 5.055	43,0 1.693	1	1	G6.3	1,2 2.650
BT40ADB-EM10-120-L1	10325537	BT40 ADB	10,0 0.394	120,0 4.724	93,0 3.661	35,7 1.406	35,0 1.378	185,4 7.299	100,0 3.937	1	1	G6.3	1,7 3.750
BT40ADB-EM12-063-L1	10007210	BT40 ADB	12,0 0.472	63,0 2.480	36,0 1.417	41,0 1.614	42,0 1.654	128,4 5.055	40,5 1.594	1	1	G6.3	1,3 2.870
BT40ADB-EM12-120-L1	10007211	BT40 ADB	12,0 0.472	120,0 4.724	93,0 3.661	41,0 1.614	42,0 1.654	185,4 7.299	97,5 3.839	1	1	G6.3	1,9 4.190
BT40ADB-EM14-063-L1	10007212	BT40 ADB	14,0 0.551	63,0 2.480	36,0 1.417	41,0 1.614	44,0 1.732	128,4 5.055	40,5 1.594	1	1	G6.3	1,3 2.870
BT40ADB-EM16-063-L1	10007213	BT40 ADB	16,0 0.630	63,0 2.480	36,0 1.417	44,0 1.732	48,0 1.890	128,4 5.055	39,0 1.535	1	1	G6.3	1,4 3.090
BT40ADB-EM16-120-L1	10007214	BT40 ADB	16,0 0.630	120,0 4.724	93,0 3.661	44,0 1.732	48,0 1.890	185,4 7.299	96,0 3.780	1	1	G6.3	2,1 4.630
BT40ADB-EM18-063-L1	10007215	BT40 ADB	18,0 0.709	63,0 2.480	36,0 1.417	44,0 1.732	50,0 1.969	128,4 5.055	39,0 1.535	1	1	G6.3	1,4 3.090
BT40ADB-EM20-063-L1	10007216	BT40 ADB	20,0 0.787	63,0 2.480	36,0 1.417	46,0 1.811	52,0 2.047	128,4 5.055	38,0 1.496	1	1	G6.3	1,4 3.090
BT40ADB-EM20-120-L1	10007217	BT40 ADB	20,0 0.787	120,0 4.724	93,0 3.661	46,0 1.811	52,0 2.047	185,4 7.299	95,0 3.740	1	1	G6.3	2,3 5.070
BT40ADB-EM25-090-L1	10007219	BT40 ADB	25,0 0.984	90,0 3.543	63,0 2.480	54,0 2.126	63,0 2.480	155,4 6.118	66,0 2.598	2	1	G6.3	2,2 4.850
BT40ADB-EM25-160-L1	10325538	BT40 ADB	25,0 0.984	160,0 6.299	137,0 5.394	54,0 2.126	63,0 2.480	225,4 8.874	136,0 5.354	2	1	G6.3	3,8 8.380
BT40ADB-EM32-100-L1	10007221	BT40 ADB	32,0 1.260	100,0 3.937	73,0 2.874	58,0 2.283	72,0 2.835	165,4 6.512	76,0 2.992	2	1	G6.3	2,7 5.950
BT40ADB-EM32-160-L1	10325539	BT40 ADB	32,0 1.260	160,0 6.299	137,0 5.394	57,0 2.244	72,0 2.835	225,4 8.874	136,0 5.354	2	1	G6.3	4,6 10.140
BT50ADB-EM12-080-L1	10007222	BT50 ADB	12,0 0.472	80,0 3.150	42,0 1.654	41,0 1.614	42,0 1.654	181,8 7.157	57,5 2.264	1	1	G6.3	3,9 8.600
BT50ADB-EM12-120-L1	10325540	BT50 ADB	12,0 0.472	120,0 4.724	82,0 3.228	40,9 1.610	42,0 1.654	221,8 8.732	97,5 3.839	1	1	G6.3	4,2 9.260
BT50ADB-EM14-080-L1	10007223	BT50 ADB	14,0 0.551	80,0 3.150	42,0 1.654	41,0 1.614	44,0 1.732	181,8 7.157	57,5 2.264	1	1	G6.3	3,9 8.600
BT50ADB-EM16-080-L1	10007224	BT50 ADB	16,0 0.630	80,0 3.150	42,0 1.654	44,0 1.732	48,0 1.890	181,8 7.157	56,0 2.205	1	1	G6.3	4,0 8.820

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Grafix

Seco Capto™

Others

Operating & setting accessories

Shrinkfit


Guide														
	Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balan- cing	Weight
HSK-A				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
	BT50ADB-EM16-120-L1	10007225	BT50 ADB	16,0 0.630	120,0 4.724	82,0 3.228	44,0 1.732	48,0 1.890	221,8 8.732	96,0 3.780	1	1	G6.3	4,5 9.920
	BT50ADB-EM18-080-L1	10007226	BT50 ADB	18,0 0.709	80,0 3.150	42,0 1.654	44,0 1.732	50,0 1.969	181,8 7.157	56,0 2.205	1	1	G6.3	4,0 8.820
	BT50ADB-EM20-080-L1	10007227	BT50 ADB	20,0 0.787	80,0 3.150	42,0 1.654	46,0 1.811	52,0 2.047	181,8 7.157	55,0 2.165	1	1	G6.3	4,0 8.820
HSK-E	BT50ADB-EM20-120-L1	10007228	BT50 ADB	20,0 0.787	120,0 4.724	82,0 3.228	46,0 1.811	52,0 2.047	221,8 8.732	95,0 3.740	1	1	G6.3	4,6 10.140
	BT50ADB-EM25-100-L1	10007229	BT50 ADB	25,0 0.984	100,0 3.937	62,0 2.441	54,0 2.126	65,0 2.559	201,8 7.945	76,0 2.992	2	1	G6.3	4,8 10.580
	BT50ADB-EM25-120-L1	10007230	BT50 ADB	25,0 0.984	120,0 4.724	82,0 3.228	54,0 2.126	65,0 2.559	221,8 8.732	96,0 3.780	2	1	G6.3	5,2 11.460
DIN	BT50ADB-EM32-105-L1	10007232	BT50 ADB	32,0 1.260	105,0 4.134	67,0 2.638	58,0 2.283	72,0 2.835	206,8 8.142	81,0 3.189	2	1	G6.3	5,1 11.240
	BT50ADB-EM32-160-L1	10325541	BT50 ADB	32,0 1.260	160,0 6.299	122,0 4.803	58,0 2.283	72,0 2.835	261,8 10.307	136,0 5.354	2	1	G6.3	7,0 15.430
	BT50ADB-EM40-120-L1	10007233	BT50 ADB	40,0 1.575	120,0 4.724	82,0 3.228	68,0 2.677	80,0 3.150	221,8 8.732	90,0 3.543	2	1	G6.3	5,8 12.790
	BT50ADB-EM50-130-L1	10007234	BT50 ADB	50,0 1.969	130,0 5.118	92,0 3.622	78,0 3.071	100,0 3.937	231,8 9.126	95,0 3.740	2	1	G6.3	7,5 16.530
BT JIS	Spare Parts, included in delivery													
	For	Coolant screw				Locking screw				Plug				
CAT														
	BT40/ 10	950A0304				951C1012				950AIE0404				
Combimaster	BT40/ 10	950A0304				951C1012				–				
	BT40/ 12-14	950A0304				951C1216				950AIE0404				
	BT40/ 16-18	950A0304				951C1416				950AIE0404				
	BT40/ 20	950A0304				951C1616				950AIE0404				
	BT40/ 25	950A0304				951C1820				950AIE0404				
	BT40/ 25	950A0304				951C1820				–				
	BT40/ 32	950A0304				951C2020				950AIE0404				
Graflex	BT40/ 32	950A0304				951C2020				–				
	BT40/ 6	950A0304				951C0610				950AIE0404				
	BT40/ 8	950A0304				951C0810				950AIE0404				
Seco Capto™	BT40/ 8	950A0304				951C0810				–				
	BT50/ 12-14	950A0304				951C1216				950AIE0505				
	BT50/ 12-14	950A0304				951C1216				–				
	BT50/ 16-18	950A0304				951C1416				950AIE0505				
	BT50/ 20	950A0304				951C1616				950AIE0505				
Others	BT50/ 25	950A0304				951C1820				950AIE0505				
	BT50/ 32-40	950A0304				951C2020				950AIE0505				
	BT50/ 32-40	950A0304				951C2020				–				
Operating & setting acces- sories	BT50/ 50	950A0304				951C2425				950AIE0505				
Shrinkfit														

DIN 1835 Form B/ DIN 6535 Form HB
– Inch


BT JIS B 6339-AD



Design 1



Design 2



– With 2 coolant channels for front lubrication which can be sealed with included screws
– For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw


Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch				lbs
BT40AD-EM0.375-2.500-L1	03301757	BT40 AD	0.375	2.500	1.437	1.500	1.000	5.075	1.750	1	1	G6.3	2.430
BT40AD-EM0.500-2.500-L1	03301758	BT40 AD	0.500	2.500	1.437	1.620	1.250	5.075	1.630	1	1	G6.3	2.650
BT40AD-EM0.750-2.500-L1	03301759	BT40 AD	0.750	2.500	1.437	2.000	1.750	5.075	1.500	1	1	G6.3	2.870
BT40AD-EM1.000-4.000-L1	03301760	BT40 AD	1.000	4.000	2.937	2.250	2.000	6.575	2.880	2	1	G6.3	3.970
BT40AD-EM1.250-4.000-L1	03301761	BT40 AD	1.250	4.000	2.937	2.250	2.500	6.575	2.880	2	1	G6.3	5.070
BT50AD-EM1.250-4.000-L1	03301755	BT50 AD	1.250	4.000	2.504	2.250	2.500	8.008	2.880	2	1	G6.3	10.140
BT50AD-EM1.500-4.500-L1	03301756	BT50 AD	1.500	4.500	3.012	2.620	2.750	8.508	3.000	2	1	G6.3	11.020

Spare Parts, included in delivery

For	Coolant screw	Locking screw
		
0.375	950A0304	951CNF037031
0.500	950A0304	951CNF043037
0.750	950A0304	951CNF062050
1.000-1.500	950A0304	951CNF075068

Short type
– Metric/ Inch

BT JIS B 6339-ADB



–Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
–With 2 coolant channels for front lubrication which can be sealed with included screws
–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw
2 = Locking screw, reduced

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	TDZ1	TDZ2	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BT40ADB-EM25-060-F5L1	10007218	BT40 ADB	25,0 0.984	60,0 2.362	33,0 1.299	54,0 2.126	62,0 2.441	125,4 4.937	36,0 1.417	M18x2	M14	0	G6.3	1,5 3.310
BT40ADB-EM32-065-F5L1	10007220	BT40 ADB	32,0 1.260	65,0 2.559	38,0 1.496	58,0 2.283	62,0 2.441	130,4 5.134	41,0 1.614	M20x2	M14	0	G6.3	1,5 3.310
BT50ADB-EM25-044-F5L1	03301733	BT50 ADB	25,0 0.984	44,0 1.732	6,0 0.236	54,0 2.126	57,0 2.244	145,8 5.740	20,5 0.807	M18x2	M14	0	G6.3	3,4 7.500

Spare Parts, included in delivery

For	Coolant screw	Locking screw	Locking screw, reduced	Plug
				
BT40ADB-EM25-060-F5L1	950A0304	951C1817	950A1410	950AIE0404
BT40ADB-EM32-065-F5L1	950A0304	951C2014	951C1407	950AIE0404
BT50ADB-EM25-044-F5L1	950A0304	951C1820	–	950AIE0505

DIN type
– Metric/ Inch

BT JIS B 6339-AD

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster


Graflex

Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit



–Run-out $\leq 3 \mu\text{m}$
–Delivered with one stop screw
–For Shrinkfit extensions, see page(s) 357-358
–For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw


Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E404056030680	02753111	BT30 AD	6,0 0.236	80,0 3.150	58,0 2.283	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	128,4 5.055	44,0 1.732	54,0 2.126	10,5 0.413	M5x0.8	4,5	0	G2.5	0,6 1.320
E404056030880	02753112	BT30 AD	8,0 0.315	80,0 3.150	58,0 2.283	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	128,4 5.055	44,0 1.732	54,0 2.126	10,5 0.413	M6x1	4,5	0	G2.5	0,6 1.320
E404056031080	02753113	BT30 AD	10,0 0.394	80,0 3.150	58,0 2.283	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	128,4 5.055	39,0 1.535	49,0 1.929	13,0 0.512	M8x1	4,5	0	G2.5	0,7 1.540
E404056031280	02753114	BT30 AD	12,0 0.472	80,0 3.150	58,0 2.283	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	128,4 5.055	34,0 1.339	44,0 1.732	13,0 0.512	M10x1	4,5	0	G2.5	0,7 1.540

Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Stop screw
	
E404056030680	19BDR05165
E404056030880	19BDR06165
E404056031080	19BDR08165
E404056031280	19BDR10165

DIN type
- Metric/ Inch


—Run-out $\leq 3 \mu\text{m}$
 —Delivered with one stop screw
 —For Shrinkfit extensions, see page(s) 357-358
 —For ISO attribute explanation, see page 15

Spare parts:
 1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E341456030690	02753045	BT40 ADB	6,0 0.236	90,0 3.543	63,0 2.480	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	155,4 6.118	54,0 2.126	64,0 2.520	10,5 0.413	M5x0.8	4,5	1	G2.5	1,2 2.650
E3414560306120	02753043	BT40 ADB	6,0 0.236	120,0 4.724	93,0 3.661	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	185,4 7.299	84,0 3.307	94,0 3.701	10,5 0.413	M5x0.8	4,5	1	G2.5	1,4 3.090
E3414560306160	02753044	BT40 ADB	6,0 0.236	160,0 6.299	133,0 5.236	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	225,4 8.874	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	G2.5	1,5 3.310
E341456030890	02753048	BT40 ADB	8,0 0.315	90,0 3.543	63,0 2.480	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	155,4 6.118	54,0 2.126	64,0 2.520	10,5 0.413	M6x1	4,5	1	G2.5	1,2 2.650
E3414560308120	02753046	BT40 ADB	8,0 0.315	120,0 4.724	93,0 3.661	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	185,4 7.299	84,0 3.307	94,0 3.701	10,5 0.413	M6x1	4,5	1	G2.5	1,3 2.870
E3414560308160	02753047	BT40 ADB	8,0 0.315	160,0 6.299	133,0 5.236	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	225,4 8.874	124,0 4.882	134,0 5.276	10,5 0.413	M6x1	4,5	1	G2.5	1,5 3.310
E341456031090	02753051	BT40 ADB	10,0 0.394	90,0 3.543	63,0 2.480	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	155,4 6.118	49,0 1.929	59,0 2.323	13,0 0.512	M8x1	4,5	1	G2.5	1,3 2.870
E3414560310120	02753049	BT40 ADB	10,0 0.394	120,0 4.724	93,0 3.661	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	185,4 7.299	79,0 3.110	89,0 3.504	13,0 0.512	M8x1	4,5	1	G2.5	1,5 3.310
E3414560310160	02753050	BT40 ADB	10,0 0.394	160,0 6.299	133,0 5.236	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	225,4 8.874	119,0 4.685	129,0 5.079	13,0 0.512	M8x1	4,5	1	G2.5	1,7 3.750
E341456031290	02753054	BT40 ADB	12,0 0.472	90,0 3.543	63,0 2.480	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	155,4 6.118	44,0 1.732	54,0 2.126	13,0 0.512	M10x1	4,5	1	G2.5	1,3 2.870
E3414560312120	02753052	BT40 ADB	12,0 0.472	120,0 4.724	93,0 3.661	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	185,4 7.299	74,0 2.913	84,0 3.307	13,0 0.512	M10x1	4,5	1	G2.5	1,4 3.090
E3414560312160	02753053	BT40 ADB	12,0 0.472	160,0 6.299	133,0 5.236	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	225,4 8.874	114,0 4.488	124,0 4.882	13,0 0.512	M10x1	4,5	1	G2.5	1,7 3.750
E341456031490	02753057	BT40 ADB	14,0 0.551	90,0 3.543	63,0 2.480	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	155,4 6.118	44,0 1.732	54,0 2.126	14,0 0.551	M10x1	4,5	1	G2.5	1,3 2.870
E3414560314120	02753056	BT40 ADB	14,0 0.551	120,0 4.724	93,0 3.661	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	185,4 7.299	74,0 2.913	84,0 3.307	14,0 0.551	M10x1	4,5	1	G2.5	1,5 3.310
E341456031690	02753060	BT40 ADB	16,0 0.630	90,0 3.543	63,0 2.480	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	155,4 6.118	41,0 1.614	51,0 2.008	14,0 0.551	M12x1	4,5	1	G2.5	1,3 2.870
E3414560316120	02753058	BT40 ADB	16,0 0.630	120,0 4.724	93,0 3.661	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	185,4 7.299	71,0 2.795	81,0 3.189	14,0 0.551	M12x1	4,5	1	G2.5	1,5 3.310
E3414560316160	02753059	BT40 ADB	16,0 0.630	160,0 6.299	133,0 5.236	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	225,4 8.874	111,0 4.370	121,0 4.764	14,0 0.551	M12x1	4,5	1	G2.5	1,8 3.970
E341456031890	02753062	BT40 ADB	18,0 0.709	90,0 3.543	63,0 2.480	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	155,4 6.118	41,0 1.614	51,0 2.008	18,0 0.709	M12x1	4,5	1	G2.5	1,4 3.090
E341456032090	02753064	BT40 ADB	20,0 0.787	90,0 3.543	63,0 2.480	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	155,4 6.118	39,0 1.535	49,0 1.929	18,0 0.709	M16x1	4,5	1	G2.5	1,4 3.090
E3414560320120	02753063	BT40 ADB	20,0 0.787	120,0 4.724	93,0 3.661	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	185,4 7.299	69,0 2.717	79,0 3.110	18,0 0.709	M16x1	4,5	1	G2.5	1,7 3.750
E3414560325100	02753065	BT40 ADB	25,0 0.984	100,0 3.937	73,0 2.874	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	165,4 6.512	43,0 1.693	53,0 2.087	23,5 0.925	M16x1	4,5	1	G2.5	1,8 3.970
E3416560306100	02753092	BT50 ADB	6,0 0.236	100,0 3.937	62,0 2.441	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	201,8 7.945	64,0 2.520	74,0 2.913	10,5 0.413	M5x0.8	4,5	1	G2.5	3,8 8.380

Designation	Item number	CTMS	DCBN- DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E3416560306160	02753093	BT50 ADB	6,0 0.236	160,0 6.299	122,0 4.803	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	261,8 10.307	124,0 4.882	134,0 5.276	10,5 0.413	M5x0.8	4,5	1	G2.5	4,0 8.820
E3416560308100	02753094	BT50 ADB	8,0 0.315	100,0 3.937	62,0 2.441	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	201,8 7.945	64,0 2.520	74,0 2.913	10,5 0.413	M6x1	4,5	1	G2.5	3,8 8.380
E3416560308160	02753095	BT50 ADB	8,0 0.315	160,0 6.299	122,0 4.803	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	261,8 10.307	124,0 4.882	134,0 5.276	10,5 0.413	M6x1	4,5	1	G2.5	4,0 8.820
E3416560310100	02753096	BT50 ADB	10,0 0.394	100,0 3.937	62,0 2.441	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	201,8 7.945	59,0 2.323	69,0 2.717	13,0 0.512	M8x1	4,5	1	G2.5	3,9 8.600
E3416560310160	02753097	BT50 ADB	10,0 0.394	160,0 6.299	122,0 4.803	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	261,8 10.307	119,0 4.685	129,0 5.079	13,0 0.512	M8x1	4,5	1	G2.5	4,2 9.260
E3416560312100	02753098	BT50 ADB	12,0 0.472	100,0 3.937	62,0 2.441	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	201,8 7.945	54,0 2.126	64,0 2.520	13,0 0.512	M10x1	4,5	1	G2.5	3,8 8.380
E3416560312160	02753099	BT50 ADB	12,0 0.472	160,0 6.299	122,0 4.803	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	261,8 10.307	114,0 4.488	124,0 4.882	13,0 0.512	M10x1	4,5	1	G2.5	4,2 9.260
E3416560314100	02753100	BT50 ADB	14,0 0.551	100,0 3.937	62,0 2.441	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	201,8 7.945	54,0 2.126	64,0 2.520	14,0 0.551	M10x1	4,5	1	G2.5	3,9 8.600
E3416560316100	02753101	BT50 ADB	16,0 0.630	100,0 3.937	62,0 2.441	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	201,8 7.945	51,0 2.008	61,0 2.402	14,0 0.551	M12x1	4,5	1	G2.5	3,9 8.600
E3416560316160	02753102	BT50 ADB	16,0 0.630	160,0 6.299	122,0 4.803	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	261,8 10.307	111,0 4.370	121,0 4.764	14,0 0.551	M12x1	4,5	1	G2.5	4,3 9.480
E3416560318100	02753103	BT50 ADB	18,0 0.709	100,0 3.937	62,0 2.441	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	201,8 7.945	51,0 2.008	61,0 2.402	18,0 0.709	M12x1	4,5	1	G2.5	4,0 8.820
E3416560320100	02753104	BT50 ADB	20,0 0.787	100,0 3.937	62,0 2.441	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	201,8 7.945	49,0 1.929	59,0 2.323	18,0 0.709	M16x1	4,5	1	G2.5	3,9 8.600
E3416560320160	02753105	BT50 ADB	20,0 0.787	160,0 6.299	122,0 4.803	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	261,8 10.307	109,0 4.291	119,0 4.685	18,0 0.709	M16x1	4,5	1	G2.5	4,6 10.140
E3416560325110	02753106	BT50 ADB	25,0 0.984	110,0 4.331	72,0 2.835	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	211,8 8.339	53,0 2.087	63,0 2.480	23,5 0.925	M16x1	4,5	1	G2.5	4,4 9.700
E3416560325160	02753107	BT50 ADB	25,0 0.984	160,0 6.299	122,0 4.803	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	261,8 10.307	103,0 4.055	113,0 4.449	23,5 0.925	M16x1	4,5	1	G2.5	5,2 11.460
E3416560332110	02753108	BT50 ADB	32,0 1.260	110,0 4.331	72,0 2.835	62,5 2.461	51,0 2.008	44,0 1.732	53,0 2.087	211,8 8.339	49,0 1.929	59,0 2.323	23,5 0.925	M16x1	4,5	1	G2.5	4,2 9.260

Accessories

For	Balancing screws
-----	------------------




All	90ZQ01
-----	--------

Spare Parts, included in delivery

For	Sealing Screws	Stop screw
		
BT40	6/ 0.236	950A0406
BT40	8/ 0.315	950A0406
BT40	10/ 0.394	950A0406
BT40	12/ 0.472-14/ 0.551	950A0406
BT40	16/ 0.630-18/ 0.709	950A0406
BT40	20/ 0.787-25/ 0.984	950A0406
BT40	32/ 1.260	950A0606
BT50	6/ 0.236	950A0606
BT50	8/ 0.315	950A0606
BT50	10/ 0.394	950A0606
BT50	12/ 0.472-14/ 0.551	950A0606
BT50	16/ 0.630-18/ 0.709	950A0606
BT50	20/ 0.787-25/ 0.984	950A0606

DIN type
– Inch



–Run-out $\leq 3 \mu\text{m}$
 –Delivered with one stop screw
 –For Shrinkfit extensions, see page(s) 357–358
 –For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw


Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch					lbs
E3414560302590	02753317	BT40 ADB	0.250	3.543	2.480	1.476	0.866	0.827	1.063	6.118	2.126	2.520	0.413	M5x0.8	4,5	1	G2.5	2.650
E34145603025120	02753316	BT40 ADB	0.250	4.724	3.661	1.476	0.866	0.827	1.063	7.299	3.307	3.701	0.413	M5x0.8	4,5	1	G2.5	2.870
E3414560303790	02753319	BT40 ADB	0.375	3.543	2.480	1.673	1.220	0.945	1.260	6.118	1.929	2.323	0.512	M8x1	4,5	1	G2.5	2.870
E3414560305090	02753321	BT40 ADB	0.500	3.543	2.480	1.791	1.339	0.945	1.260	6.118	1.811	2.205	0.512	M10x1	4,5	1	G2.5	2.870
E34145603050120	02753320	BT40 ADB	0.500	4.724	3.661	1.791	1.339	0.945	1.260	7.299	2.992	3.386	0.512	M10x1	4,5	1	G2.5	3.090
E3414560306290	02753323	BT40 ADB	0.625	3.543	2.480	1.988	1.535	1.063	1.339	6.118	1.614	2.008	0.551	M12x1	4,5	1	G2.5	2.870
E34145603062120	02753322	BT40 ADB	0.625	4.724	3.661	1.988	1.535	1.063	1.339	7.299	2.795	3.189	0.551	M12x1	4,5	1	G2.5	3.310
E3414560307590	02753325	BT40 ADB	0.750	3.543	2.480	2.067	1.614	1.299	1.654	6.118	1.535	1.929	0.709	M16x1	4,5	1	G2.5	3.090
E34145603100100	02753326	BT40 ADB	1.000	3.937	2.874	2.303	1.850	1.732	2.087	6.512	1.693	2.087	0.925	M16x1	4,5	1	G2.5	3.970

Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Sealing Screws	Stop screw
		
0.250	950A0406	19BDR05165
0.375	950A0406	19BDR06165
0.500	950A0406	19BDR08165
0.625	950A0406	19BDR10165
0.750/1.000	950A0406	19BDR12165

Reinforced type
– Metric/ Inch
BT JIS B 6339-ADB


- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- For ISO attribute explanation, see page 15

Spare parts:
 1 = Stop screw
 2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR*	LB	LB1	CBDP	LSC	BD1	BD2	BD3	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E3414560006130	02845565	BT40 ADB	6,0 0.236	130,0 5.118	103,0 4.055	52,0 2.047	37,5 1.476	22,0 0.866	24,0 0.945	32,2 1.267	61,5 2.421	195,4 7.693	94,0 3.701	104,0 4.094	12,0 0.472	M5x0.8	4,5	1	G2.5	2,0 4.410
E3414560008130	02845566	BT40 ADB	8,0 0.315	130,0 5.118	103,0 4.055	52,0 2.047	37,5 1.476	26,0 1.024	24,0 0.945	32,2 1.267	61,5 2.421	195,4 7.693	94,0 3.701	104,0 4.094	12,0 0.472	M6x1	4,5	1	G2.5	2,0 4.410
E341456001070	02845559	BT40 ADB	10,0 0.394	70,0 2.756	43,0 1.693	—	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	—	135,4 5.331	29,0 1.142	39,0 1.535	13,5 0.531	M8x1	4,5	1	G2.5	1,2 2.650
E3414560010130	02845567	BT40 ADB	10,0 0.394	130,0 5.118	103,0 4.055	52,0 2.047	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	61,5 2.421	195,4 7.693	89,0 3.504	99,0 3.898	13,5 0.531	M8x1	4,5	1	G2.5	2,1 4.630
E341456001270	02845560	BT40 ADB	12,0 0.472	70,0 2.756	43,0 1.693	—	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	—	135,4 5.331	24,0 0.945	34,0 1.339	13,5 0.531	M10x1	4,5	1	G2.5	1,2 2.650
E3414560012130	02845568	BT40 ADB	12,0 0.472	130,0 5.118	103,0 4.055	103,0 4.055	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	61,5 2.421	195,4 7.693	84,0 3.307	94,0 3.701	13,5 0.531	M10x1	4,5	1	G2.5	2,1 4.630
E341456001675	02845561	BT40 ADB	16,0 0.630	75,0 2.953	48,0 1.890	—	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	—	140,4 5.528	26,0 1.024	36,0 1.417	17,0 0.669	M12x1	4,5	1	G2.5	1,3 2.870
E3414560016130	02845569	BT40 ADB	16,0 0.630	130,0 5.118	103,0 4.055	58,0 2.283	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	61,5 2.421	195,4 7.693	81,0 3.189	91,0 3.583	17,0 0.669	M12x1	4,5	1	G2.5	2,2 4.850
E341456002075	02845562	BT40 ADB	20,0 0.787	75,0 2.953	48,0 1.890	—	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	—	140,4 5.528	24,0 0.945	34,0 1.339	21,5 0.846	M16x1	4,5	1	G2.5	1,5 3.310
E3416560006160	02845588	BT50 ADB	6,0 0.236	160,0 6.299	122,0 4.803	52,0 2.047	37,5 1.476	22,0 0.866	24,0 0.945	32,2 1.267	97,5 3.839	261,8 10.307	124,0 4.882	134,0 5.276	12,0 0.472	M5x0.8	4,5	1	G2.5	6,2 13.670
E3416560008160	02845589	BT50 ADB	8,0 0.315	160,0 6.299	122,0 4.803	122,0 4.803	37,5 1.476	26,0 1.024	24,0 0.945	32,2 1.267	97,5 3.839	261,8 10.307	124,0 4.882	134,0 5.276	12,0 0.472	M6x1	4,5	1	G2.5	6,2 13.670
E3416560010100	02845582	BT50 ADB	10,0 0.394	100,0 3.937	62,0 2.441	—	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	—	201,8 7.945	59,0 2.323	69,0 2.717	13,5 0.531	M8x1	4,5	1	G2.5	4,0 8.820
E3416560010160	02845590	BT50 ADB	10,0 0.394	160,0 6.299	122,0 4.803	52,0 2.047	42,5 1.673	31,0 1.220	27,0 1.063	35,2 1.385	97,5 3.839	261,8 10.307	119,0 4.685	129,0 5.079	13,5 0.531	M8x1	4,5	1	G2.5	6,2 13.670
E3416560012100	02845583	BT50 ADB	12,0 0.472	100,0 3.937	62,0 2.441	—	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	—	201,8 7.945	54,0 2.126	64,0 2.520	13,5 0.531	M10x1	4,5	1	G2.5	4,0 8.820
E3416560012160	02845591	BT50 ADB	12,0 0.472	160,0 6.299	122,0 4.803	52,0 2.047	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	97,5 3.839	261,8 10.307	114,0 4.488	124,0 4.882	13,5 0.531	M10x1	4,5	1	G2.5	6,2 13.670
E3416560016100	02845584	BT50 ADB	16,0 0.630	100,0 3.937	62,0 2.441	—	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	—	201,8 7.945	51,0 2.008	61,0 2.402	17,0 0.669	M12x1	4,5	1	G2.5	4,1 9.040
E3416560016160	02845592	BT50 ADB	16,0 0.630	160,0 6.299	122,0 4.803	58,0 2.283	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	97,5 3.839	261,8 10.307	111,0 4.370	121,0 4.764	17,0 0.669	M12x1	4,5	1	G2.5	6,3 13.890
E3416560020100	02845585	BT50 ADB	20,0 0.787	100,0 3.937	62,0 2.441	—	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	—	201,8 7.945	49,0 1.929	59,0 2.323	21,5 0.846	M16x1	4,5	1	G2.5	4,3 9.480
E3416560020160	02845593	BT50 ADB	20,0 0.787	160,0 6.299	122,0 4.803	58,0 2.283	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	97,5 3.839	261,8 10.307	109,0 4.291	119,0 4.685	21,5 0.846	M16x1	4,5	1	G2.5	6,8 14.990
E3416560025100	02845586	BT50 ADB	25,0 0.984	100,0 3.937	62,0 2.441	—	58,5 2.303	47,0 1.850	48,0 1.890	57,1 2.249	—	201,8 7.945	43,0 1.693	53,0 2.087	25,0 0.984	M16x1	4,5	1	G2.5	4,46 9.830
E3416560025160	02845594	BT50 ADB	25,0 0.984	160,0 6.299	122,0 4.803	—	58,5 2.303	47,0 1.850	48,0 1.890	57,1 2.249	97,5 3.839	261,8 10.307	103,0 4.055	113,0 4.449	25,0 0.984	M16x1	4,5	1	G2.5	7,0 15.430
E3416560032105	02845587	BT50 ADB	32,0 1.260	105,0 4.134	67,0 2.638	—	62,5 2.461	51,0 2.008	48,0 1.890	57,1 2.249	—	206,8 8.142	44,0 1.732	54,0 2.126	25,0 0.984	M16x1	4,5	1	G2.5	4,4 9.700

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

 Operating &
setting acces-
series

Shrinkfit

Accessories

For Balancing screws




All 90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Sealing Screws	Stop screw
			
BT40 6/ 0.236	90AI03	950A0406	19BDR05165
BT40 8/ 0.315	90AI03	950A0406	19BDR06165
BT40 10/ 0.394	90AI03	950A0406	19BDR08165
BT40 12/ 0.472	90AI03	950A0406	19BDR10165
BT40 16/ 0.630	90AI03	950A0406	19BDR12165
BT40 20/ 0.787-25/ 0.984	90AI04	950A0406	19BDR16165
BT50 6/ 0.236	90AI03	950A0606	19BDR05165
BT50 8/ 0.315	90AI03	950A0606	19BDR06165
BT50 10/ 0.394	90AI03	950A0606	19BDR08165
BT50 12/ 0.472	90AI03	950A0606	19BDR10165
BT50 16/ 0.630	90AI03	950A0606	19BDR12165
BT50 20/ 0.787-32/ 1.260	90AI04	950A0606	19BDR16165

Mold and Die type
– Metric/ Inch

BT JIS B 6339-ADB



– Run-out $\leq 3 \mu\text{m}$
– For Shrinkfit extensions, see page(s) 357–358
– For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LB1	LSC	BD1	BD2	OAL	BHTA°	BHTA1°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E341458010390	00034385	BT40 ADB	3,0 0.118	90,0 3.543	63,0 2.480	–	25,0 0.984	13,0 0.512	9,0 0.354	18,3 0.719	155,4 6.118	3,0	5,0	1	G2.5	0,99 2.180
E3414580103140	00096374	BT40 ADB	3,0 0.118	140,0 5.512	113,0 4.449	–	25,0 0.984	13,0 0.512	9,0 0.354	27,0 1.064	205,4 8.087	3,0	5,0	1	G2.5	1,2 2.650
E341458010490	00034386	BT40 ADB	4,0 0.157	90,0 3.543	63,0 2.480	–	25,0 0.984	15,0 0.591	10,0 0.394	19,3 0.759	155,4 6.118	3,0	5,0	1	G2.5	1,0 2.200
E3414580104140	00096375	BT40 ADB	4,0 0.157	140,0 5.512	113,0 4.449	–	25,0 0.984	15,0 0.591	10,0 0.394	28,0 1.103	205,4 8.087	3,0	5,0	1	G2.5	1,2 2.650
E3414580105140	00096376	BT40 ADB	5,0 0.197	140,0 5.512	113,0 4.449	–	25,0 0.984	18,0 0.709	11,0 0.433	29,0 1.142	205,4 8.087	3,0	5,0	1	G2.5	1,2 2.650
E341458010690	00034388	BT40 ADB	6,0 0.236	90,0 3.543	63,0 2.480	40,0 1.575	32,0 1.260	26,0 1.024	12,0 0.472	20,8 0.818	155,4 6.118	3,0	5,0	1	G2.5	1,01 2.230
E3414580106140	00096377	BT40 ADB	6,0 0.236	140,0 5.512	113,0 4.449	40,0 1.575	32,0 1.260	26,0 1.024	12,0 0.472	29,5 1.162	205,4 8.087	3,0	5,0	1	G2.5	1,2 2.650
E341458010890	00034389	BT40 ADB	8,0 0.315	90,0 3.543	63,0 2.480	44,0 1.732	36,0 1.417	30,0 1.181	16,0 0.630	24,5 0.964	155,4 6.118	3,0	5,0	1	G2.5	1,05 2.310
E3414580108140	00096378	BT40 ADB	8,0 0.315	140,0 5.512	113,0 4.449	44,0 1.732	36,0 1.417	30,0 1.181	16,0 0.630	33,2 1.309	205,4 8.087	3,0	5,0	1	G2.5	1,3 2.870
E341458011090	00034390	BT40 ADB	10,0 0.394	90,0 3.543	63,0 2.480	45,0 1.772	38,0 1.496	32,0 1.260	18,0 0.709	26,4 1.038	155,4 6.118	3,0	5,0	1	G2.5	1,1 2.430
E3414580110160	00096379	BT40 ADB	10,0 0.394	160,0 6.299	133,0 5.236	45,0 1.772	38,0 1.496	32,0 1.260	18,0 0.709	38,6 1.520	225,4 8.874	3,0	5,0	1	G2.5	1,5 3.310
E341458011290	00034391	BT40 ADB	12,0 0.472	90,0 3.543	63,0 2.480	46,0 1.811	40,0 1.575	34,0 1.339	20,0 0.787	28,2 1.111	155,4 6.118	3,0	5,0	1	G2.5	1,1 2.430

Spare Parts, included in delivery

For	Sealing Screws
	
All	950A0406

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Grafix


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

– Metric/ Inch




–Run-out 3 µm maximum at 3 x ØDCBN-DCBX
 –For ER HP collets type 5672, see page(s) 389, 390, 391-397
 –For stop screws, see instructions at www.secotools.com
 –For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	RFID hole	Balancing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT30AD-ERHP08R-075	10358795	BT30 AD	1,0 0.039	5,0 0.197	HP 08R	75,0 2.953	10,0 0.394	10,0 0.394	123,4 4.858	53,0 2.087	0	G2.5	0,5 1.100
BT30AD-ERHP11R-050	10358796	BT30 AD	1,0 0.039	7,0 0.276	HP 11R	50,2 1.976	16,0 0.630	16,0 0.630	98,6 3.882	28,2 1.110	0	G2.5	0,5 1.100
BT30AD-ERHP11R-100	10358797	BT30 AD	1,0 0.039	7,0 0.276	HP 11R	100,2 3.945	16,0 0.630	16,0 0.630	148,6 5.850	78,2 3.079	0	G2.5	0,5 1.100
BT30AD-ERHP11R-130-V	10358798	BT30 AD	1,0 0.039	7,0 0.276	HP 11R	130,2 5.126	33,6 1.323	16,0 0.630	178,6 7.031	108,2 4.260	0	G2.5	0,8 1.760
BT30AD-ERHP16-050	10358800	BT30 AD	1,0 0.039	10,0 0.394	HP 16	50,6 1.992	30,0 1.181	30,0 1.181	99,0 3.898	28,6 1.126	0	G2.5	0,5 1.100
BT30AD-ERHP16-100	10358801	BT30 AD	1,0 0.039	10,0 0.394	HP 16	100,6 3.961	30,0 1.181	30,0 1.181	149,0 5.866	78,6 3.094	0	G2.5	0,8 1.760
BT30AD-ERHP16-120	10358802	BT30 AD	1,0 0.039	10,0 0.394	HP 16	120,1 4.728	30,0 1.181	30,0 1.181	168,5 6.634	98,1 3.862	0	G2.5	0,9 1.980
BT30AD-ERHP20-060	10358803	BT30 AD	1,0 0.039	13,0 0.512	HP 20	60,0 2.362	32,0 1.260	32,0 1.260	108,4 4.268	38,0 1.496	0	G2.5	0,6 1.320
BT30AD-ERHP20-120	10358804	BT30 AD	1,0 0.039	13,0 0.512	HP 20	120,0 4.724	32,0 1.260	32,0 1.260	168,4 6.630	98,0 3.858	0	G2.5	0,9 1.980
BT30AD-ERHP25-060	10358805	BT30 AD	1,0 0.039	16,0 0.630	HP 25	60,0 2.362	40,0 1.575	40,0 1.575	108,4 4.268	38,0 1.496	0	G2.5	0,6 1.320
BT30AD-ERHP25-120	10358806	BT30 AD	1,0 0.039	16,0 0.630	HP 25	120,0 4.724	40,0 1.575	40,0 1.575	168,4 6.630	98,0 3.858	0	G2.5	1,1 2.430
BT40AD-ERHP11R-100	10358807	BT40 AD	1,0 0.039	7,0 0.276	HP 11R	100,2 3.945	16,0 0.630	16,0 0.630	165,6 6.520	73,2 2.882	1	G2.5	1,1 2.430
BT40AD-ERHP11R-120	10358808	BT40 AD	1,0 0.039	7,0 0.276	HP 11R	120,2 4.732	16,0 0.630	16,0 0.630	185,6 7.307	93,2 3.669	1	G2.5	1,1 2.430
BT40AD-ERHP16-075	10358809	BT40 AD	1,0 0.039	10,0 0.394	HP 16	75,0 2.953	30,0 1.181	30,0 1.181	140,4 5.528	48,0 1.890	1	G2.5	1,2 2.650
BT40AD-ERHP16-120	10358810	BT40 AD	1,0 0.039	10,0 0.394	HP 16	120,0 4.724	30,0 1.181	30,0 1.181	185,4 7.299	93,0 3.661	1	G2.5	1,4 3.090
BT40AD-ERHP16-165	10358811	BT40 AD	1,0 0.039	10,0 0.394	HP 16	165,0 6.496	30,0 1.181	30,0 1.181	230,4 9.071	138,0 5.433	1	G2.5	1,6 3.530
BT40AD-ERHP20-075	10358812	BT40 AD	1,0 0.039	13,0 0.512	HP 20	75,1 2.957	32,0 1.260	32,0 1.260	140,5 5.531	48,1 1.894	1	G2.5	1,2 2.650
BT40AD-ERHP20-120	10358813	BT40 AD	1,0 0.039	13,0 0.512	HP 20	120,1 4.728	32,0 1.260	32,0 1.260	185,5 7.303	93,1 3.665	1	G2.5	1,4 3.090
BT40AD-ERHP25-075	10358814	BT40 AD	1,0 0.039	16,0 0.630	HP 25	75,0 2.953	40,0 1.575	40,0 1.575	140,4 5.528	48,0 1.890	1	G2.5	1,3 2.870
BT40AD-ERHP25-120	10358815	BT40 AD	1,0 0.039	16,0 0.630	HP 25	120,2 4.732	40,0 1.575	40,0 1.575	185,6 7.307	93,2 3.669	1	G2.5	1,7 3.750
BT40AD-ERHP25-165	10358816	BT40 AD	1,0 0.039	16,0 0.630	HP 25	165,2 6.504	40,0 1.575	40,0 1.575	230,6 9.079	138,2 5.441	1	G2.5	2,0 4.410
BT40AD-ERHP25-200	10358817	BT40 AD	1,0 0.039	16,0 0.630	HP 25	200,0 7.874	40,0 1.575	40,0 1.575	265,4 10.449	173,0 6.811	1	G2.5	2,3 5.070

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	CTWS	LPR mm inch	BD2 mm inch	BD1 mm inch	OAL mm inch	LB mm inch	RFID hole	Balan- cing	Weight kg lbs
BT40AD-ERHP32-075	10358818	BT40 AD	2,0 0.079	20,0 0.787	HP 32	74,8 2.945	50,0 1.969	50,0 1.969	140,2 5.520	47,8 1.882	1	G2.5	1,4 3.090
BT40AD-ERHP32-120	10358819	BT40 AD	2,0 0.079	20,0 0.787	HP 32	120,0 4.724	50,0 1.969	50,0 1.969	185,4 7.299	93,0 3.661	1	G2.5	2,0 4.410
BT40AD-ERHP32-165	10358820	BT40 AD	2,0 0.079	20,0 0.787	HP 32	165,0 6.496	50,0 1.969	50,0 1.969	230,4 9.071	138,0 5.433	1	G2.5	2,6 5.730
BT50AD-ERHP25-105	10358821	BT50 AD	1,0 0.039	16,0 0.630	HP 25	105,0 4.134	40,0 1.575	40,0 1.575	206,8 8.142	67,0 2.638	1	G2.5	4,0 8.820
BT50AD-ERHP32-105	10358822	BT50 AD	2,0 0.079	20,0 0.787	HP 32	105,0 4.134	50,0 1.969	50,0 1.969	206,8 8.142	67,0 2.638	1	G2.5	4,2 9.260
BT50AD-ERHP32-165	10358823	BT50 AD	2,0 0.079	20,0 0.787	HP 32	165,0 6.496	50,0 1.969	50,0 1.969	266,8 10.504	127,0 5.000	1	G2.5	5,0 11.020

Accessories

For	Key	Socket	Torque key
			
ERHP08R	—	03ERB010	03DYE003025
ERHP11R	03LME0912140	03ER016	03DYE003025
ERHP16	03LME1418260	03ER030B	03DYE010100B
ERHP20	03LME1418260	03ER032B	03DYE010100B
ERHP25	03LME1418260	03ER040	03DYE010100B
ERHP32	03LME1418370	03ER050	03DYE040200

Spare Parts, included in delivery

For	Nut
	
ERHP08R	08B567208RC
ERHP11R	08B567211RC
ERHP16	08B567216C
ERHP20	08B567220C
ERHP25	08B567225C
ERHP32	08B567232C

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

Conventional type
– Metric/ Inch



–Run-out $\leq 3 \mu\text{m}$
–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BT40ADB-HC06-090	10137297	BT40 ADB	6,0 0.236	90,0 3.543	63,0 2.480	43,0 1.693	38,5 1.516	44,5 1.752	26,05 1.026	155,4 6.118	53,0 2.087	63,0 2.480	M5	20,0	1	G2.5	1,4 3.090
BT40ADB-HC08-090	10137298	BT40 ADB	8,0 0.315	90,0 3.543	63,0 2.480	44,5 1.752	38,5 1.516	44,5 1.752	28,0 1.102	155,4 6.118	53,0 2.087	63,0 2.480	M6x1	20,0	1	G2.5	1,4 3.090
BT40ADB-HC10-090	10137299	BT40 ADB	10,0 0.394	90,0 3.543	63,0 2.480	44,5 1.752	42,5 1.673	44,5 1.752	30,0 1.181	155,4 6.118	49,0 1.929	59,0 2.323	M8x1	20,0	1	G2.5	1,4 3.090
BT40ADB-HC12-090	10137300	BT40 ADB	12,0 0.472	90,0 3.543	63,0 2.480	44,5 1.752	47,5 1.870	44,5 1.752	32,0 1.260	155,4 6.118	44,0 1.732	54,0 2.126	M10x1	20,0	1	G2.5	1,4 3.090
BT40ADB-HC16-090	10137301	BT40 ADB	16,0 0.630	90,0 3.543	63,0 2.480	47,5 1.870	50,5 1.988	44,5 1.752	38,0 1.496	155,4 6.118	41,0 1.614	51,0 2.008	M12x1	20,0	1	G2.5	1,5 3.310
BT40ADB-HC20-090	10137302	BT40 ADB	20,0 0.787	90,0 3.543	63,0 2.480	47,5 1.870	52,5 2.067	44,5 1.752	42,0 1.654	155,4 6.118	39,0 1.535	49,0 1.929	M16x1	20,0	1	G2.5	1,5 3.310
BT50ADB-HC20-090	10137303	BT50 ADB	20,0 0.787	90,0 3.543	52,0 2.047	34,0 1.339	52,5 2.067	49,3 1.939	42,0 1.654	191,8 7.551	39,0 1.535	49,0 1.929	M16x1	20,0	1	G2.5	3,9 8.600
BT50ADB-HC32-120	10137304	BT50 ADB	32,0 1.260	120,0 4.724	82,0 3.228	62,5 2.461	62,5 2.461	70,3 2.766	64,0 2.520	221,8 8.732	59,0 2.323	69,0 2.717	M16x1	20,0	1	G2.5	5,2 11.460


Accessories

For	Key
BT40	H05-4
BT50, DCBN = 20	H05-4
BT50, DCBN = 32	03MS06L



Reinforced type
– Metric/ Inch

BT JIS B 6339-AD/ADB



–Run-out $\leq 3 \mu\text{m}$
–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BT30AD-HCR12-069	10137136	BT30 AD	12,0 0.472	69,0 2.717	47,0 1.850	32,0 1.260	47,5 1.870	44,5 1.752	42,0 1.654	117,4 4.622	23,0 0.906	33,0 1.299	M8x1	20,0	0	G2.5	0,9 1.980
BT30AD-HCR20-090	10137137	BT30 AD	20,0 0.787	90,0 3.543	68,0 2.677	50,0 1.969	52,5 2.067	44,5 1.752	42,0 1.654	138,4 5.449	39,0 1.535	49,0 1.929	M8x1	20,0	0	G2.5	1,0 2.200
BT40ADB-HCR12-058	10137140	BT40 ADB	12,0 0.472	58,0 2.283	31,0 1.220	–	47,5 1.870	–	42,0 1.654	123,4 4.858	12,0 0.472	22,0 0.866	M8x1	–	0	G2.5	1,2 2.650
BT40ADB-HCR20-072	10137141	BT40 ADB	20,0 0.787	72,5 2.854	45,5 1.791	–	52,5 2.067	–	49,25 1.939	137,9 5.429	21,5 0.846	31,5 1.240	M8x1	–	0	G2.5	1,5 3.310
BT50ADB-HCR20-083	10137144	BT50 ADB	20,0 0.787	83,5 3.287	45,5 1.791	–	52,5 2.067	–	49,25 1.939	185,3 7.295	32,5 1.280	42,5 1.673	M8x1	–	0	G2.5	4,1 9.040
BT50ADB-HCR32-090	10137145	BT50 ADB	32,0 1.260	90,0 3.543	52,0 2.047	–	62,5 2.461	–	72,0 2.835	191,8 7.551	29,0 1.142	39,0 1.535	M8x1	–	0	G2.5	4,7 10.360

Accessories

For	Key
	
BT30	H05-4
BT40	H05-4
BT50, DCBN = 20	H05-4
BT50, DCBN = 32	03MS06L

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Slim type
– Metric/ Inch




–Run-out $\leq 3 \mu\text{m}$
–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	BHTA1°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
BT40ADB-HCS06-150	10137340	BT40 ADB	6,0 0.236	150,0 5.906	123,0 4.843	100,0 3.937	37,0 1.457	44,5 1.752	20,0 0.787	215,4 8.480	113,0 4.449	123,0 4.843	M5x0.8	30,0	3,0	1	G2.5	1,6 3.530
BT40ADB-HCS08-150	10137341	BT40 ADB	8,0 0.315	150,0 5.906	123,0 4.843	100,0 3.937	37,0 1.457	44,5 1.752	22,0 0.866	215,4 8.480	113,0 4.449	123,0 4.843	M6x1	30,0	3,0	1	G2.5	1,7 3.750
BT40ADB-HCS10-150	10137342	BT40 ADB	10,0 0.394	150,0 5.906	123,0 4.843	100,0 3.937	42,0 1.654	44,5 1.752	24,0 0.945	215,4 8.480	110,0 4.331	120,0 4.724	M8x1	30,0	3,0	1	G2.5	1,7 3.750
BT40ADB-HCS12-150	10137343	BT40 ADB	12,0 0.472	150,0 5.906	123,0 4.843	100,0 3.937	47,0 1.850	44,5 1.752	25,0 0.984	215,4 8.480	105,0 4.134	115,0 4.528	M10x1	30,0	3,0	1	G2.5	1,7 3.750
BT40ADB-HCS16-150	10137344	BT40 ADB	16,0 0.630	150,0 5.906	123,0 4.843	100,0 3.937	52,0 2.047	44,5 1.752	32,0 1.260	215,4 8.480	100,0 3.937	110,0 4.331	M12x1	30,0	3,0	1	G2.5	2,0 4.410
BT40ADB-HCS20-150	10137345	BT40 ADB	20,0 0.787	150,0 5.906	123,0 4.843	–	52,0 2.047	46,9 1.846	34,0 1.339	215,4 8.480	100,0 3.937	110,0 4.331	M16x1	–	3,0	1	G2.5	2,0 4.410

Accessories

For	Key
	
All	03MS04C

– Metric/ Inch



–For reduction sleeves, see page(s) 385-386
–For ‘Stop screws for through coolant’, see page(s) 387-388
–For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	OAL	LPR	LB	CBDP	BD1	LFN	LF	KWW	TDZ	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BT40AD-PMC20-065	10185657	BT40 AD	20,0 0.787	130,4 5.134	65,0 2.559	38,5 1.516	62,0 2.441	49,0 1.929	0,0 0	7,0 0.276	8,0	M16	1	PB	1,4 3.090
BT40AD-PMC32-090	10185651	BT40 AD	32,0 1.260	155,4 6.118	90,0 3.543	75,9 2.988	80,0 3.150	67,0 2.638	10,0 0.394	15,0 0.591	8,0	M16	1	PB	2,1 4.630
BT50AD-PMC20-085	10185659	BT50 AD	20,0 0.787	186,8 7.354	85,0 3.346	47,0 1.850	63,0 2.480	49,0 1.929	22,0 0.866	27,0 1.063	8,0	M16	1	PB	4,0 8.820
BT50AD-PMC32-095	10185652	BT50 AD	32,0 1.260	196,8 7.748	95,0 3.740	57,0 2.244	90,0 3.543	67,0 2.638	5,0 0.197	10,0 0.394	8,0	M16	1	PB	4,5 9.920


Accessories

For	Spanner
	
-PMC20	03BPMC20
-PMC32	03BPMC32

Spare Parts, included in delivery

For	Extractor for reduction sleeves	Stop screw
		
-PMC20	03EXTPMC	19BEPMC01
-PMC32	03EXTPMC	19BEPMC01

ISO 15488
– Metric/ Inch




–Run-out 15 µm/ .0006" maximum at 3 x ØDCBN-DCBX
–For ER extensions and ER collets, see page(s) 362, 363, 399, 400, 401, 402
–For ER sealing rings, see page(s) 410, 411
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	LFN	LF	RFID hole	Balan- cing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT30AD-ER11-075	10229622	BT30 AD	0,5 0.020	7,0 0.276	ER 11	75,0 2.953	19,0 0.748	19,0 0.748	123,4 4.858	53,0 2.087	30,0 1.181	50,0 1.969	0	G6.3	0,5 1.100
BT30AD-ER16-060	10229623	BT30 AD	0,5 0.020	10,0 0.394	ER 16	60,0 2.362	28,0 1.102	28,0 1.102	108,4 4.268	38,0 1.496	15,0,0 0.0.591	30,0 1.181	0	G6.3	0,5 1.100
BT30AD-ER20-060	10229624	BT30 AD	1,0 0.039	13,0 0.512	ER 20	60,0 2.362	34,0 1.339	34,0 1.339	108,4 4.268	38,0 1.496	10,0 0.0.394	30,0 1.181	0	G6.3	0,6 1.320
BT30AD-ER25-065	10229625	BT30 AD	1,0 0.039	16,0 0.630	ER 25	65,0 2.559	42,0 1.654	42,0 1.654	113,4 4.465	43,0 1.693	15,0,0 0.0.591	35,0 1.378	0	G6.3	0,7 1.540
BT40AD-ER16-070	10229669	BT40 AD	0,5 0.020	10,0 0.394	ER 16	70,0 2.756	28,0 1.102	28,0 1.102	135,4 5.331	43,0 1.693	25,0,0 0.0.984	40,0 1.575	1	G6.3	1,1 2.430
BT40AD-ER16-120	10229670	BT40 AD	0,5 0.020	10,0 0.394	ER 16	120,0 4.724	28,0 1.102	28,0 1.102	185,4 7.299	93,0 3.661	75,0,0 2.953	90,0 3.543	1	G6.3	1,3 2.870
BT40AD-ER20-070	10229671	BT40 AD	1,0 0.039	13,0 0.512	ER 20	70,0 2.756	34,0 1.339	34,0 1.339	135,4 5.331	43,0 1.693	20,0 0.0.787	40,0 1.575	1	G6.3	1,2 2.650
BT40AD-ER20-120	10229672	BT40 AD	1,0 0.039	13,0 0.512	ER 20	120,0 4.724	34,0 1.339	34,0 1.339	185,4 7.299	93,0 3.661	70,0 2.756	90,0 3.543	1	G6.3	1,5 3.310
BT40AD-ER25-070	10229673	BT40 AD	1,0 0.039	16,0 0.630	ER 25	70,0 2.756	42,0 1.654	42,0 1.654	135,4 5.331	43,0 1.693	5,0,0 0.0.197	25,0 0.984	1	G6.3	1,2 2.650
BT40AD-ER25-120	10229674	BT40 AD	1,0 0.039	16,0 0.630	ER 25	120,0 4.724	42,0 1.654	42,0 1.654	185,4 7.299	93,0 3.661	55,0,0 2.165	75,0 2.953	1	G6.3	1,7 3.750
BT40AD-ER25-160	10229675	BT40 AD	1,0 0.039	16,0 0.630	ER 25	160,0 6.299	42,0 1.654	42,0 1.654	225,4 8.874	133,0 5.236	95,0,0 3.740,0	115,0 4.528	1	G6.3	2,1 4.630
BT40AD-ER32-070	10229676	BT40 AD	2,0 0.079	20,0 0.787	ER 32	70,0 2.756	50,0 1.969	50,0 1.969	135,4 5.331	43,0 1.693	5,0,0 0.0.197	25,0 0.984	1	G6.3	1,3 2.870
BT40AD-ER32-120	10229677	BT40 AD	2,0 0.079	20,0 0.787	ER 32	120,0 4.724	50,0 1.969	50,0 1.969	185,4 7.299	93,0 3.661	55,0,0 2.165	75,0 2.953	1	G6.3	2,0 4.410
BT40AD-ER32-160	10229678	BT40 AD	2,0 0.079	20,0 0.787	ER 32	160,0 6.299	50,0 1.969	50,0 1.969	225,4 8.874	133,0 5.236	95,0,0 3.740,0	115,0 4.528	1	G6.3	2,6 5.730
BT40AD-ER40-075	10229679	BT40 AD	3,0 0.118	26,0 1.024	ER 40	75,0 2.953	50,0 1.969	63,0 2.480	140,4 5.528	48,0 1.890	20,0 0.0.787	20,0 0.787	1	G6.3	1,4 3.090
BT40AD-ER40-100	10229680	BT40 AD	3,0 0.118	26,0 1.024	ER 40	100,0 3.937	50,0 1.969	63,0 2.480	164,4 6.472	73,0 2.874	25,0,0 0.0.984	45,0 1.772	1	G6.3	1,8 3.970
BT50AD-ER16-100	10229681	BT50 AD	0,5 0.020	10,0 0.394	ER 16	100,0 3.937	28,0 1.102	28,0 1.102	201,8 7.945	62,0 2.441	55,0,0 2.165	70,0 2.756	1	G6.3	4,0 8.820
BT50AD-ER16-120	10229682	BT50 AD	0,5 0.020	10,0 0.394	ER 16	120,0 4.724	28,0 1.102	28,0 1.102	221,8 8.732	82,0 3.228	75,0,0 2.953	90,0 3.543	1	G6.3	3,9 8.600
BT50AD-ER20-100	10229683	BT50 AD	1,0 0.039	13,0 0.512	ER 20	100,0 3.937	34,0 1.339	34,0 1.339	201,8 7.945	62,0 2.441	50,0 1.969	70,0 2.756	1	G6.3	4,1 9.040
BT50AD-ER20-120	10229757	BT50 AD	1,0 0.039	13,0 0.512	ER 20	120,0 4.724	34,0 1.339	34,0 1.339	221,8 8.732	82,0 3.228	70,0 2.756	90,0 3.543	1	G6.3	4,2 9.260
BT50AD-ER25-100	10229684	BT50 AD	1,0 0.039	16,0 0.630	ER 25	100,0 3.937	42,0 1.654	42,0 1.654	201,8 7.945	62,0 2.441	35,0,0 1.378	55,0 2.165	1	G6.3	4,0 8.820
BT50AD-ER25-120	10229685	BT50 AD	1,0 0.039	16,0 0.630	ER 25	120,0 4.724	42,0 1.654	42,0 1.654	221,8 8.732	82,0 3.228	55,0,0 2.165	75,0 2.953	1	G6.3	4,2 9.260

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	CTWS	LPR mm inch	BD2 mm inch	BD1 mm inch	OAL mm inch	LB mm inch	LFN mm inch	LF mm inch	RFID hole	Balan- cing	Weight kg lbs
BT50AD-ER32-100	10229686	BT50 AD	2,0 0.079	20,0 0.787	ER 32	100,0 3.937	50,0 1.969	50,0 1.969	201,8 7.945	62,0 2.441	35,0,0 1.378	55,0 2.165	1	G6.3	4,1 9.040
BT50AD-ER32-120	10229687	BT50 AD	2,0 0.079	20,0 0.787	ER 32	120,0 4.724	50,0 1.969	50,0 1.969	221,8 8.732	82,0 3.228	55,0,0 2.165	75,0 2.953	1	G6.3	4,4 9.700
BT50AD-ER32-160	10229688	BT50 AD	2,0 0.079	20,0 0.787	ER 32	160,0 6.299	50,0 1.969	50,0 1.969	261,8 10.307	122,0 4.803	95,0,0 3.740,0	115,0 4.528	1	G6.3	5,2 11.460
BT50AD-ER40-100	10229689	BT50 AD	3,0 0.118	26,0 1.024	ER 40	100,0 3.937	63,0 2.480	63,0 2.480	201,8 7.945	62,0 2.441	25,0,0 0.0.984	45,0 1.772	1	G6.3	4,3 9.480

Accessories

For	Seal nut	Spanner
		
ER11	—	03B587511UM
ER16	08B587516IC	03B587516UM
ER20	—	03B587520UM
ER25	08B587525IC	03B587525
ER32	08B587532IC	03B587532
ER40	08B587540IC	03B587540

Spare Parts, included in delivery

For	Nut	Stop screw
		
ER11	08B587511UM	19LRC1225
ER16	08B587516UM	19LRC1020
ER20	08B587520UM	19LRC1225
ER25	08B587525X	19LRC1225
ER32	08B587532X	19LRC1225
ER40	08B587540X	19LRC1225

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

– Metric/ Inch



—Run-out 40 µm maximum at 2,5 x ØDCBN-DCBX
—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	OAL	LPR	LB	BD1	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
E3414508513	00048215	BT40 ADB	1,0 0.039	13,0 0.512	169,4 6.669	104,0 4.094	77,0 3.031	43,0 1.693	1	PB	1,4 3.090
E3416508516	00048218	BT50 ADB	2,5 0.098	16,0 0.630	232,8 9.165	131,0 5.157	93,0 3.661	56,0 2.205	1	PB	4,66 10.270

Spare Parts, included in delivery

For	Sealing Screws
E3414508513	950A0406
E3416508516	950A0606




For synchronized tapping, with micro-compensation
– Metric/ Inch


BT JIS B 6339-AD



Design 1





Design 2



- Maximum coolant pressure 80 bar/ 1160 psi
- For ER tapping collets with square drive, see page(s) 407, 408–409
- For TCER 5867 sealing rings, see page(s) 410, 411
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCBN	DCBX	LPR	LB	LB1	BD	BD1	OAL	SW	Design	RFID hole	Balancing	Weight
						mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
E404058671182	02926971	BT30 AD	ER 11	M2	M5	82,0 3.228	60,0 2.362	24,1 0.949	23,5 0.925	18,7 0.736	130,4 5.134	12,7 0.500	1	0	–	0,6 1.320
E4040586720105	02926972	BT30 AD	ER 20	M4	M12	100,2 3.945	78,2 3.079	35,3 1.390	35,0 1.378	33,7 1.327	148,6 5.850	22,0 0.866	1	0	–	0,9 1.980
E4040586725125	02926973	BT30 AD	ER 25	M8	M20	119,6 4.709	97,6 3.843	37,1 1.461	44,0 1.732	42,0 1.654	168,0 6.614	28,0 1.102	2	0	–	1,2 2.650
E4041586720110	02926974	BT40 AD	ER 20	M4	M12	105,2 4.142	78,2 3.079	35,3 1.390	35,0 1.378	33,7 1.327	170,6 6.717	22,0 0.866	1	0	–	1,4 3.090
E4041586725130	02926975	BT40 AD	ER 25	M8	M20	124,6 4.906	97,6 3.843	37,1 1.461	44,0 1.732	42,0 1.654	190,0 7.480	28,0 1.102	2	0	–	1,8 3.970
E5766586720125	02926976	BT50 AD	ER 20	M4	M12	120,2 4.732	82,2 3.236	35,3 1.390	35,0 1.378	33,7 1.327	222,0 8.740	22,0 0.866	1	0	–	3,9 8.600
E5766586725145	02926977	BT50 AD	ER 25	M8	M20	139,6 5.496	101,6 4.000	37,1 1.461	44,0 1.732	42,0 1.654	241,4 9.504	28,0 1.102	2	0	–	4,3 9.480
E5766586740174	02926978	BT50 AD	ER 40	M16	M33	168,6 6.638	130,6 5.142	46,6 1.835	62,0 2.441	62,7 2.469	270,4 10.646	39,6 1.559	2	0	–	5,8 12.790


Accessories

For	Locking key	Seal nut	Spanner
			
ER 11	5680092-03	–	03B587511UM
ER 20	5680092-04	5533051-02	03B587520UM
ER 25	5680092-05	5533051-03	03B587525
ER 40	5680092-06	5533051-05	03B587540

Spare Parts, included in delivery

For	Nut
	
ER 11	5533050-07
ER 20	5533050-08
ER 25	5533050-02
ER 40	5533050-04

SA – DIN 69871-BT
– Metric/ Inch




—Direct run-out 5 µm maximum
—For ISO attribute explanation, see page 15


Spare parts:
1 = Plug
2 = Ring
3 = Balls
4 = Screw
5 = Washer

Designation	Item number	CTMS	CTWS	LPR	LB	BD	OAL	TDZ	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch				kg lbs
E57665434070T	00041981	BT50 A	DIN40 BT40	70,0 2.756	32,0 1.260	70,0 2.756	179,8 2.756	M16	1	PB	4,1 9.040

Spare Parts, included in delivery

For	Plug	Ring	Screw	Washer
				
E57665434070T	950A0505	02B54240	950E1670	15B54240

– Metric/ Inch



–The cylindrical front part is hardened to 120–130 daN/mm², allowing machining
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	LPR	LB	SRR	BD	CND	OAL	CNDP	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
E3414502363250	02503289	BT40 ADB	250,0 9.843	215,0 8.465	8,0 0.315	63,0 2.480	13,5 0.531	323,4 12.732	85,0 3.346	1	PB	6,58 14.510
E3416502363315	02503290	BT50 ADB	315,0 12.402	277,0 10.906	8,0 0.315	63,0 2.480	20,5 0.807	424,8 16.724	130,0 5.118	1	PB	10,42 22.970
E3416502395315	02503291	BT50 ADB	315,0 12.402	277,0 10.906	8,0 0.315	95,0 3.740	20,5 0.807	424,8 16.724	130,0 5.118	1	PB	20,0 44.090

Spare Parts, included in delivery

For	Sealing Screws
	
BT40	950A0406
BT50	950A0606

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

– Metric/ Inch



–Diameter, length values and measurement positions are laser engraved on each test bar
–With protective case and measurement report
–**Note:** For BT50, use suitable DIN50 Control bars (E447158650330)
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	LPR	BD	OAL	RFID hole	Balan- cing	Weight
			mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>			kg <i>lbs</i>
E404158640330	75041810	BT40 A	330.0 12.992	40.0 1.575	395.4 15.567	1	-	3.64 8.020

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit



BT TF

Seco range of rotating holders allow you to get the most out of both your machine and tool by offering a comprehensive array of solutions to connect them. The range covers all standard workpiece side connections, as well Seco's unique connections. BT JIS TF brings a better accuracy and is ideal for long tools.

- Steadyline, vibration damping shell mill holders
- Shell mill holders, with through coolant channels
- Side lock holders, Weldon
- Shrinkfit holders
- High precision collet chucks
- Power milling chucks
- ER collet chucks

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster


Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit



BT40 TF and 50 ADB with sealing dowel

BT40 TF and 50 ADB with sealing screw

Machine side catalogue designation	Through coolant Form	Hole for RFID carrier***	d ₁	d ₂	d ₄	d ₅ ****	d ₇	d ₉	e ₁	u	l ₁	l ₆	l ₉	b	y
			mm inch	mm inch	mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
BT30 TF AD	A/AD	No	31,75 1.250	12,5 0.492	38 1.496	46 1.811	M12	—	—	22 0.866	48,4 1.906	16,3 0.642	11 0.433	16,1 0.634	1 0.039
BT40 TF ADB	A/AD/B	Yes***	44,45 1.750	17 0.669	53 2.087	63 2.480	M16	4 0.157	27 1.063	27 1.063	65,4 2.575	22,5 0.886	14,5 0.571	16,1 0.634	1 0.039
BT50 TF ADB	A/AD/B	Yes***	69,85 2.750	25 0.984	85 3.346	100 3.937	M24	6 0.236	42 1.654	38 1.496	101,8 4.008	35,4 1.394	20,5 0.807	25,7 1.012	1,5 0.059

Note: These machine side dimensions are applied to all the holders shown in the Product pages.

* BT with Taper-Face tooling machine sides are:

– conform to the JIS B 6339 (ISO 7388-2) norm.

– except that they have a larger flange towards machine side, with tight tolerances: this achieves taper and face contacts on machine spindles with Taper-Face dimensions. Taper-Face tooling is also usable on standard spindles, but in that case a gap remains between spindle and flange faces.

*** In order to know if a hole for RFID carrier exists, see 'RFID hole' column in Product pages:

1= hole for RFID carrier available, if required a carrier can be fitted on request, please enquire.


0= hole for RFID carrier not available, if required hole can be machined and a carrier can be fitted on request, please enquire.

**** BT holders with a front end diameter in excess of diameter d₅, are produced with a flange clearance length: BT30 = Ø 45 mm x 3 mm;

BT40 = Ø 62 mm x 8 mm; BT50 = Ø 98 mm x 12 mm. This is compatible with the BT JIS norm which permits free dimensions on workpiece side.

Steadyline®, vibration damping
– Metric/ Inch

BT Taper-Face-ADB




–DMM 40 mm / 1.575", includes 4 threaded holes on the bearing face according to DIN 6357
–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	Max. RPM	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
E3216555540350	02926043	BT50 TF ADB	40,0 1.575	350,0 13.780	89,0 3.504	478,8 18.850	312,0 12.283	27,0 1.063	3000	1	PB	20,7 45.640

Accessories

For	Bolt, through coolant	Spanner
		
E3216555540350	5804020L	5814020

Spare Parts, included in delivery

For	Bolt	Screw	Sealing Screws	Tenon
				
E3216555540350	5804020	950D0616	950A0606	16C2161621A

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

With through coolant channels – ISO 3937
– Metric/ Inch

BT Taper-Face-AD




–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant


Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT30TFAD-SM16-040-L1	03301661	BT30 TF AD	16,0 0.630	40,0 1.575	38,0 1.496	105,4 4.150	18,0 0.709	17,0 0.669	1	G6.3	0,6 1.320
BT30TFAD-SM22-040-L1	03301662	BT30 TF AD	22,0 0.866	40,0 1.575	48,0 1.890	107,4 4.228	18,0 0.709	19,0 0.748	1	G6.3	0,7 1.540
BT30TFAD-SM27-040-L1	03301663	BT30 TF AD	27,0 1.063	40,0 1.575	60,0 2.362	109,4 4.307	18,0 0.709	21,0 0.827	1	G6.3	0,9 1.980

Accessories


For	Bolt, through coolant	Spanner
		
BT30TFAD-SM16-040-L1	5801608L	5811608
BT30TFAD-SM22-040-L1	5802210L	5812210
BT30TFAD-SM27-040-L1	5802712L	5812712

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
			
BT30TFAD-SM16-040-L1	5801608	950D0312	16C716A
BT30TFAD-SM22-040-L1	5802210	950D0416	16C722A
BT30TFAD-SM27-040-L1	5802712	950D0512	16C727A

Small face with through coolant channels
– Inch

BT Taper-Face-AD




–For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch			lbs
BT30TFAD-SM0.750-2.000-L1	03301686	BT30 TF AD	0.750	2.000	1.750	4.594	1.134	0.688	1	G6.3	1.760

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
			
BT30TFAD-SM0.750-2.000-L1	58271905	950DNC012031	16C71905

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
sories

Shrinkfit

With through coolant channels – ISO 3937
– Metric/ Inch

BT Taper-Face-ADB




–DMM 40 mm / 1.575", includes 4 threaded holes on the bearing face according to DIN 6357
–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant


Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT40TFADB-SM16-050-L1	03301645	BT40 TF ADB	16,0 0.630	50,0 1.969	38,0 1.496	132,4 5.213	23,0 0.906	17,0 0.669	1	G6.3	1,2 2.650
BT40TFADB-SM22-045-L1	03301648	BT40 TF ADB	22,0 0.866	45,0 1.772	48,0 1.890	129,4 5.094	18,0 0.709	19,0 0.748	1	G6.3	1,3 2.870
BT40TFADB-SM27-045-L1	03301651	BT40 TF ADB	27,0 1.063	45,0 1.772	60,0 2.362	131,4 5.173	18,0 0.709	21,0 0.827	1	G6.3	1,5 3.310
BT40TFADB-SM32-050-L1	03301652	BT40 TF ADB	32,0 1.260	50,0 1.969	78,0 3.071	139,4 5.488	23,0 0.906	24,0 0.945	1	G6.3	1,9 4.190
BT40TFADB-SM40-050-L1	03301653	BT40 TF ADB	40,0 1.575	50,0 1.969	89,0 3.504	142,4 5.606	23,0 0.906	27,0 1.063	1	G6.3	2,1 4.630
BT50TFADB-SM22-055-L1	03301620	BT50 TF ADB	22,0 0.866	55,0 2.165	48,0 1.890	175,8 6.921	17,0 0.669	19,0 0.748	1	G6.3	3,8 8.380
BT50TFADB-SM27-055-L1	03301623	BT50 TF ADB	27,0 1.063	55,0 2.165	60,0 2.362	177,8 7.000	17,0 0.669	21,0 0.827	1	G6.3	4,0 8.820
BT50TFADB-SM32-055-L1	03301626	BT50 TF ADB	32,0 1.260	55,0 2.165	78,0 3.071	180,8 7.118	17,0 0.669	24,0 0.945	1	G6.3	4,4 9.700
BT50TFADB-SM40-055-L1	03301629	BT50 TF ADB	40,0 1.575	55,0 2.165	89,0 3.504	183,8 7.236	17,0 0.669	27,0 1.063	1	G6.3	4,6 10.140

Accessories

For	Bolt, through coolant	Spanner
		
BT40/ 16/ 0.630	5801608L	5811608
BT40/ 22/ 0.866	5802210L	5812210
BT40/ 27/ 1.063	5802712L	5812712
BT40/ 32/ 1.260	5803216L	5813216
BT40/ 40/ 1.575	5804020L	5814020
BT50/ 22/ 0.866	5802210L	5812210
BT50/ 27/ 1.063	5802712L	5812712
BT50/ 32/ 1.260	5803216L	5813216
BT50/ 40/ 1.575	5804020L	5814020

Spare Parts, included in delivery

For	Bolt	Plug	Screw	Tenon
				
BT40/ 16/ 0.630	5801608	950AIE0404	950D0312	16C716A
BT40/ 22/ 0.866	5802210	950AIE0404	950D0416	16C722A
BT40/ 27/ 1.063	5802712	950AIE0404	950D0512	16C727A
BT40/ 32/ 1.260	5803216	950AIE0404	950D0616	16C732A
BT40/ 40/ 1.575	5804020	950AIE0404	950D0616	16C740A
BT50/ 22/ 0.866	5802210	950AIE0505	950D0416	16C722A
BT50/ 27/ 1.063	5802712	950AIE0505	950D0512	16C727A
BT50/ 32/ 1.260	5803216	950AIE0505	950D0616	16C732A
BT50/ 40/ 1.575	5804020	950AIE0505	950D0616	16C740A

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

Small face with through coolant channels – ISO 3937
– Metric/ Inch

BT Taper-Face-ADB




– Small workpiece side diameter BD according to ISO 3937, suitable for Seco disc mill cutters Type B
– For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT40TFADB-SM22-060-F3L1	03301646	BT40 TF ADB	22,0 0.866	60,0 2.362	40,0 1.575	144,4 5.685	33,0 1.299	19,0 0.748	1	G6.3	1,4 3.090
BT40TFADB-SM22-120-F3L1	03301647	BT40 TF ADB	22,0 0.866	120,0 4.724	40,0 1.575	204,4 8.047	93,0 3.661	19,0 0.748	1	G6.3	1,9 4.190
BT40TFADB-SM27-060-F3L1	03301649	BT40 TF ADB	27,0 1.063	60,0 2.362	48,0 1.890	146,4 5.764	33,0 1.299	21,0 0.827	1	G6.3	1,5 3.310
BT40TFADB-SM27-120-F3L1	03301650	BT40 TF ADB	27,0 1.063	120,0 4.724	48,0 1.890	206,4 8.126	93,0 3.661	21,0 0.827	1	G6.3	2,4 5.290
BT50TFADB-SM22-075-F3L1	03301618	BT50 TF ADB	22,0 0.866	75,0 2.953	40,0 1.575	195,8 7.709	37,0 1.457	19,0 0.748	1	G6.3	4,0 8.820
BT50TFADB-SM22-120-F3L1	03301619	BT50 TF ADB	22,0 0.866	120,0 4.724	40,0 1.575	240,8 9.480	82,0 3.228	19,0 0.748	1	G6.3	4,4 9.700
BT50TFADB-SM27-075-F3L1	03301621	BT50 TF ADB	27,0 1.063	75,0 2.953	48,0 1.890	197,8 7.787	37,0 1.457	21,0 0.827	1	G6.3	4,3 9.480
BT50TFADB-SM27-120-F3L1	03301622	BT50 TF ADB	27,0 1.063	120,0 4.724	48,0 1.890	242,8 9.559	82,0 3.228	21,0 0.827	1	G6.3	4,8 10.580
BT50TFADB-SM32-120-F3L1	03301625	BT50 TF ADB	32,0 1.260	120,0 4.724	58,0 2.283	245,8 9.677	82,0 3.228	24,0 0.945	1	G6.3	5,3 11.680

Accessories

For	Bolt, through coolant	Spanner
		
BT40/ 22	5802210L	5812210
BT40/ 27	5802712L	5812712
BT50/ 22	5802210L	5812210
BT50/ 27	5802712L	5812712
BT50/ 32	5803216L	5813216

Spare Parts, included in delivery

For	Bolt	Plug	Screw	Tenon
				
BT40/ 22	5802210	950AIE0404	950D0410	16C722
BT40/ 27	5802712	950AIE0404	950D0512	16C727
BT50/ 22	5802210	950AIE0505	950D0410	16C722
BT50/ 27	5802712	950AIE0505	950D0512	16C727
BT50/ 32	5803216	950AIE0505	950D0616	16C732

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

DIN 1835 Form B/ DIN 6535 Form HB
– Metric/ Inch


BT Taper-Face-AD



Design 1



Design 2



–Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
–With 2 coolant channels for front lubrication which can be sealed with included screws
–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw


Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
BT30AD-EM06-050-L1	10325530	BT30 AD	6,0 0.236	50,0 1.969	28,0 1.102	35,2 1.386	25,0 0.984	98,4 3.874	32,0 1.260	1	1	G6.3	0,5 1.100
BT30AD-EM08-050-L1	10325531	BT30 AD	8,0 0.315	50,0 1.969	28,0 1.102	34,8 1.370	28,0 1.102	98,4 3.874	32,0 1.260	1	1	G6.3	0,5 1.100
BT30AD-EM10-050-L1	10325532	BT30 AD	10,0 0.394	50,0 1.969	28,0 1.102	36,0 1.417	35,0 1.378	98,4 3.874	30,0 1.181	1	1	G6.3	0,6 1.320
BT30TFAD-EM10-065-L1	03301728	BT30 TF AD	10,0 0.394	65,0 2.559	43,0 1.693	36,0 1.417	35,0 1.378	113,4 4.465	45,0 1.772	1	1	G6.3	0,7 1.540
BT30AD-EM12-055-L1	10325533	BT30 AD	12,0 0.472	55,0 2.165	33,0 1.299	41,0 1.614	42,0 1.654	103,4 4.071	32,5 1.280	1	1	G6.3	0,7 1.540
BT30TFAD-EM12-065-L1	03301729	BT30 TF AD	12,0 0.472	65,0 2.559	43,0 1.693	41,0 1.614	42,0 1.654	113,4 4.465	42,5 1.673	1	1	G6.3	0,8 1.760
BT30TFAD-EM16-060-L1	03301730	BT30 TF AD	16,0 0.630	60,0 2.362	35,0 1.378	44,0 1.732	48,0 1.890	108,4 4.268	36,0 1.417	1	1	G6.3	0,8 1.760
BT30AD-EM16-063-L1	10325534	BT30 AD	16,0 0.630	63,0 2.480	44,0 1.732	44,0 1.732	48,0 1.890	111,4 4.386	39,0 1.535	1	1	G6.3	0,9 1.980
BT30TFAD-EM20-065-L1	03301731	BT30 TF AD	20,0 0.787	66,0 2.598	43,0 1.693	46,0 1.811	52,0 2.047	113,4 4.465	40,0 1.575	1	1	G6.3	0,9 1.980
BT30AD-EM20-063-L1	10325535	BT30 AD	20,0 0.787	63,0 2.480	44,0 1.732	46,0 1.811	52,0 2.047	111,4 4.386	38,0 1.496	1	1	G6.3	0,9 1.980
BT30TFAD-EM25-090-L1	03301732	BT30 TF AD	25,0 0.984	90,0 3.543	68,0 2.677	54,0 2.126	63,0 2.480	138,4 5.449	66,0 2.598	2	1	G6.3	1,7 3.750
BT30TFAD-EM32-095-L1	10007235	BT30 TF AD	32,0 1.260	95,0 3.740	73,0 2.874	58,0 2.283	72,0 2.835	143,4 5.646	71,0 2.795	2	0	G6.3	2,2 4.850

Spare Parts, included in delivery

Others	For DCBN-DCBX	Coolant screw	Locking screw
			
Operating & setting accessories	6 / 0.236	950A0304	951C0610
	8 / 0.315	950A0304	951C0810
	10 / 0.394	950A0304	951C1012
	12 / 0.472	950A0304	951C1216
	16 / 0.630	950A0304	951C1416
Shrinkfit	20 / 0.787	950A0304	951C1616
	25 / 0.984	950A0304	951C1820
	32 / 1.260	950A0304	951C2020

DIN 1835 Form B/ DIN 6535 Form HB
– Inch

BT Taper-Face-AD



– With 2 coolant channels for front lubrication which can be sealed with included screws
– For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch	inch			lbs
BT30TFAD-EM0.500-2.500-L1	03301749	BT30 TF AD	0.500	2.500	1.634	1.620	1.250	4.406	1.630	1	G6.3	1.320

Spare Parts, included in delivery

For	Coolant screw	Locking screw
		
BT30TFAD-EM0.500-2.500-L1	950A0304	951CNF043037

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

DIN 1835 Form B/ DIN 6535 Form HB
– Metric/ Inch


BT Taper-Face-ADB



Design 1



Design 2



–Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
–With 2 coolant channels for front lubrication which can be sealed with included screws
–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
BT40TFADB-EM16-065-L1	03301722	BT40 TF ADB	16,0 0.630	65,0 2.559	38,0 1.496	44,0 1.732	48,0 1.890	130,4 5.134	41,0 1.614	1	1	G6.3	1,4 3.090
BT40TFADB-EM20-065-L1	03301723	BT40 TF ADB	20,0 0.787	65,0 2.559	38,0 1.496	46,0 1.811	52,0 2.047	130,4 5.134	40,0 1.575	1	1	G6.3	1,4 3.090
BT40TFADB-EM25-090-L1	03301724	BT40 TF ADB	25,0 0.984	90,0 3.543	63,0 2.480	54,0 2.126	63,0 2.480	155,4 6.118	66,0 2.598	2	1	G6.3	2,2 4.850
BT40TFADB-EM32-100-L1	10007236	BT40 TF ADB	32,0 1.260	100,0 3.937	73,0 2.874	58,0 2.283	72,0 2.835	165,4 6.512	76,0 2.992	2	1	G6.3	2,7 5.950
BT40TFADB-EM40-110-L1	03301725	BT40 TF ADB	40,0 1.575	110,0 4.331	75,0 2.953	68,0 2.677	80,0 3.150	175,4 6.906	80,0 3.150	2	1	G6.3	3,2 7.050
BT50TFADB-EM25-100-L1	03301719	BT50 TF ADB	25,0 0.984	100,0 3.937	62,0 2.441	54,0 2.126	63,0 2.480	201,8 7.945	76,0 2.992	2	1	G6.3	4,8 10.580
BT50TFADB-EM32-105-L1	10007237	BT50 TF ADB	32,0 1.260	105,0 4.134	67,0 2.638	58,0 2.283	72,0 2.835	206,8 8.142	81,0 3.189	2	1	G6.3	5,1 11.240
BT50TFADB-EM40-115-L1	03301720	BT50 TF ADB	40,0 1.575	115,0 4.528	77,0 3.031	68,0 2.677	80,0 3.150	216,8 8.535	85,0 3.346	2	1	G6.3	5,7 12.570
BT50TFADB-EM50-130-L1	03301721	BT50 TF ADB	50,0 1.969	130,0 5.118	92,0 3.622	78,0 3.071	100,0 3.937	231,8 9.126	95,0 3.740	2	1	G6.3	7,4 16.310

Spare Parts, included in delivery

For	Coolant screw	Locking screw	Plug
			
BT40/ 16/ 0.630	950A0304	951C1416	950AIE0404
BT40/ 20/ 0.787	950A0304	951C1616	950AIE0404
BT40/ 25/ 0.984	950A0304	951C1820	950AIE0404
BT40/ 32/ 1.260-40/ 1.575	950A0304	951C2020	950AIE0404
BT50/ 25/ 0.984	950A0304	951C1820	950AIE0505
BT50/ 32/ 1.260-40/ 1.575	950A0304	951C2020	950AIE0505
BT50/ 50/ 1.969	950A0304	951C2425	950AIE0505

DIN type
– Metric/ Inch

BT Taper-Face-AD

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster


Graflex

Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit



- Run-out $\leq 3 \mu\text{m}$
- Delivered with one stop screw
- For Shrinkfit extensions, see page(s) 357-358
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E400256030680	02998719	BT30 TF AD	6,0 0.236	80,0 3.150	58,0 2.283	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	128,4 5.055	44,0 1.732	54,0 2.126	10,5 0.413	M5x0.8	4,5	0	G2.5	0,6 1.320
E400256030880	02998720	BT30 TF AD	8,0 0.315	80,0 3.150	58,0 2.283	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	128,4 5.055	44,0 1.732	54,0 2.126	10,5 0.413	M6x1	4,5	0	G2.5	0,6 1.320
E400256031080	02998721	BT30 TF AD	10,0 0.394	80,0 3.150	58,0 2.283	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	128,4 5.055	39,0 1.535	49,0 1.929	13,0 0.512	M8x1	4,5	0	G2.5	0,7 1.540
E400256031280	02998722	BT30 TF AD	12,0 0.472	80,0 3.150	58,0 2.283	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	128,4 5.055	34,0 1.339	44,0 1.732	13,0 0.512	M10x1	4,5	0	G2.5	0,7 1.540


Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Stop screw
	
E400256030680	19BDR05165
E400256030880	19BDR06165
E400256031080	19BDR08165
E400256031280	19BDR10165

DIN type
– Inch



–Run-out $\leq 3 \mu\text{m}$
 –Delivered with one stop screw
 –For Shrinkfit extensions, see page(s) 357–358
 –For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch					lbs
E40025603025315	02998693	BT30 TF AD	0.250	3.150	2.283	1.476	0.866	0.827	1.063	5.055	1.732	2.126	0.413	M5x0.8	4,5	0	G2.5	1.320
E40025603037315	02998694	BT30 TF AD	0.375	3.150	2.283	1.673	1.220	0.945	1.260	5.055	1.535	1.929	0.512	M8x1	4,5	0	G2.5	1.540
E40025603050315	02998695	BT30 TF AD	0.500	3.150	2.283	1.791	1.339	0.945	1.260	5.055	1.417	1.811	0.512	M10x1	4,5	0	G2.5	1.540

Accessories


For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Stop screw
	
E40025603025315	19BDR05165
E40025603037315	19BDR08165
E40025603050315	19BDR10165

Reinforced type
– Metric/ Inch

BT Taper-Face-ADB



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	LSC	BD1	BD2	BD3	OAL	LFN	LF	RL	TDZ	BHTA*	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E321456001270	02904803	BT40 TF ADB	12,0 0.472	70,0 2.756	43,0 1.693	–	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	–	135,4 5.331	24,0 0.945	34,0 1.339	13,5 0.531	M10x1	4,5	1	G2.5	1,2 2.650
E321456001675	02904804	BT40 TF ADB	16,0 0.630	75,0 2.953	48,0 1.890	–	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	–	140,4 5.528	26,0 1.024	36,0 1.417	17,0 0.669	M12x1	4,5	1	G2.5	1,3 2.870
E321456002075	02904805	BT40 TF ADB	20,0 0.787	75,0 2.953	48,0 1.890	–	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	–	140,4 5.528	24,0 0.945	34,0 1.339	21,5 0.846	M16x1	4,5	1	G2.5	1,5 3.310
E321456002585	02904806	BT40 TF ADB	25,0 0.984	85,0 3.346	58,0 2.283	–	58,5 2.303	47,0 1.850	48,0 1.890	57,1 2.249	–	150,4 5.921	28,0 1.102	38,0 1.496	25,0 0.984	M16x1	4,5	1	G2.5	1,7 3.750
E3216560012100	02904815	BT50 TF ADB	12,0 0.472	100,0 3.937	62,0 2.441	–	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	–	201,8 7.945	54,0 2.126	64,0 2.520	13,5 0.531	M10x1	4,5	1	G2.5	4,1 9.040
E3216560016100	02904816	BT50 TF ADB	16,0 0.630	100,0 3.937	62,0 2.441	–	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	–	201,8 7.945	51,0 2.008	61,0 2.402	17,0 0.669	M12x1	4,5	1	G2.5	4,2 9.260
E3216560020100	02904817	BT50 TF ADB	20,0 0.787	100,0 3.937	62,0 2.441	–	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	–	201,8 7.945	49,0 1.929	59,0 2.323	21,5 0.846	M16x1	4,5	1	G2.5	4,5 9.920
E3216560025100	02904818	BT50 TF ADB	25,0 0.984	100,0 3.937	62,0 2.441	–	58,5 2.303	47,0 1.850	48,0 1.890	57,1 2.249	–	201,8 7.945	43,0 1.693	53,0 2.087	25,0 0.984	M16x1	4,5	1	G2.5	4,5 9.920
E3216560032105	02904819	BT50 TF ADB	32,0 1.260	105,0 4.134	67,0 2.638	–	62,5 2.461	51,0 2.008	48,0 1.890	57,1 2.249	–	206,8 8.142	44,0 1.732	54,0 2.126	25,0 0.984	M16x1	4,5	1	G2.5	4,5 9.920


Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Sealing Screws	Stop screw
			
BT40 TF/ 12	90AI03	950A0406	19BDR10165
BT40 TF/ 16	90AI03	950A0406	19BDR12165
BT40 TF/ 20-25	90AI04	950A0406	19BDR16165
BT50 TF/ 12	90AI03	950A0606	19BDR10165
BT50 TF/ 16	90AI03	950A0606	19BDR12165
BT50 TF/ 20-25	90AI04	950A0606	19BDR16165
BT50 TF/ 32	90AI04	950A0606	19BDR16165


– Metric/ Inch



–Run-out 3 µm maximum at 3 x ØDCBN-DCBX
 –For ER HP collets type 5672, see page(s) 389, 390, 391-397
 –For stop screws, see instructions at www.secotools.com
 –For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	RFID hole	Balancing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BT30TFAD-ERHP11R-105	10358829	BT30 TF AD	1,0 0.039	7,0 0.276	HP 11R	106,0 4.173	16,0 0.630	16,0 0.630	154,4 6.079	84,0 3.307	0	G2.5	0,5 1.100
BT30TFAD-ERHP16-060	10358830	BT30 TF AD	1,0 0.039	10,0 0.394	HP 16	61,0 2.402	30,0 1.181	30,0 1.181	109,4 4.307	39,0 1.535	0	G2.5	0,6 1.320
BT30TFAD-ERHP16-120	10358831	BT30 TF AD	1,0 0.039	10,0 0.394	HP 16	121,0 4.764	30,0 1.181	30,0 1.181	169,4 6.669	99,0 3.898	0	G2.5	0,9 1.980
BT40TFAD-ERHP16-075	10358832	BT40 TF AD	1,0 0.039	10,0 0.394	HP 16	76,0 2.992	30,0 1.181	30,0 1.181	141,5 5.571	49,1 1.933	1	G2.5	0,7 1.540
BT40TFAD-ERHP16-150	10358833	BT40 TF AD	1,0 0.039	10,0 0.394	HP 16	151,0 5.945	30,0 1.181	30,0 1.181	216,5 8.524	124,1 4.886	1	G2.5	0,8 1.760
BT30TFAD-ERHP20-075	10358834	BT30 TF AD	1,0 0.039	13,0 0.512	HP 20	76,0 2.992	32,0 1.260	32,0 1.260	124,4 4.898	54,0 2.126	0	G2.5	1,1 2.430
BT30TFAD-ERHP25-075	10358835	BT30 TF AD	1,0 0.039	16,0 0.630	HP 25	76,0 2.992	40,0 1.575	40,0 1.575	124,4 4.898	54,0 2.126	0	G2.5	1,2 2.650
BT30TFAD-ERHP25-120	10358836	BT30 TF AD	1,0 0.039	16,0 0.630	HP 25	121,0 4.764	40,0 1.575	40,0 1.575	169,4 6.669	99,0 3.898	0	G2.5	1,6 3.530
BT40TFAD-ERHP25-075	10358837	BT40 TF AD	1,0 0.039	16,0 0.630	HP 25	76,2 3.000	40,0 1.575	40,0 1.575	141,6 5.575	49,2 1.937	1	G2.5	1,3 2.870
BT40TFAD-ERHP25-165	10358838	BT40 TF AD	1,0 0.039	16,0 0.630	HP 25	166,2 6.543	40,0 1.575	40,0 1.575	231,6 9.118	139,2 5.480	1	G2.5	2,1 4.630
BT50TFAD-ERHP25-105	10358839	BT50 TF AD	1,0 0.039	16,0 0.630	HP 25	106,5 4.193	40,0 1.575	40,0 1.575	208,3 8.201	68,5 2.697	1	G2.5	1,4 3.090
BT40TFAD-ERHP32-075	10358840	BT40 TF AD	2,0 0.079	20,0 0.787	HP 32	76,0 2.992	50,0 1.969	50,0 1.969	141,4 5.567	49,0 1.929	1	G2.5	2,6 5.730
BT40TFAD-ERHP32-165	10358841	BT40 TF AD	2,0 0.079	20,0 0.787	HP 32	165,5 6.516	50,0 1.969	50,0 1.969	230,9 9.091	138,5 5.453	1	G2.5	4,1 9.040
BT50TFAD-ERHP32-105	10358842	BT50 TF AD	2,0 0.079	20,0 0.787	HP 32	106,5 4.193	50,0 1.969	50,0 1.969	208,3 8.201	68,5 2.697	1	G2.5	4,3 9.480
BT50TFAD-ERHP32-165	10358843	BT50 TF AD	2,0 0.079	20,0 0.787	HP 32	166,5 6.555	50,0 1.969	50,0 1.969	268,3 10.563	128,5 5.059	1	G2.5	5,1 11.240

Accessories

For	Key	Socket	Torque key
			
ERHP11R	03LME0912140	03ER016	03DYE003025
ERHP16	03LME1418260	03ER030B	03DYE010100B
ERHP20	03LME1418260	03ER032B	03DYE010100B
ERHP25	03LME1418260	03ER040	03DYE010100B
ERHP32	03LME1418370	03ER050	03DYE040200

Spare Parts, included in delivery

For	Nut
	
ERHP11R	08B567211RC
ERHP16	08B567216C
ERHP20	08B567220C
ERHP25	08B567225C
ERHP32	08B567232C

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Reinforced type
– Metric/ Inch



–Run-out $\leq 3 \mu\text{m}$
–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15


Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BT30TFAD-HCR12-069	10137138	BT30 TF AD	12,0 0.472	69,0 2.717	47,0 1.850	32,0 1.260	47,5 1.870	44,5 1.752	42,0 1.654	117,4 4.622	23,0 0.906	33,0 1.299	M8x1	20,0	0	G2.5	0,9 1.980
BT30TFAD-HCR20-090	10137139	BT30 TF AD	20,0 0.787	90,0 3.543	68,0 2.677	50,0 1.969	52,5 2.067	44,5 1.752	42,0 1.654	138,4 5.449	39,0 1.535	49,0 1.929	M8x1	20,0	0	G2.5	1,0 2.200
BT40TFADB-HCR12-058	10137142	BT40 TF ADB	12,0 0.472	58,0 2.283	31,0 1.220	–	47,5 1.870	–	42,0 1.654	123,4 4.858	12,0 0.472	22,0 0.866	M8x1	–	0	G2.5	1,2 2.650
BT40TFADB-HCR20-072	10137143	BT40 TF ADB	20,0 0.787	72,5 2.854	45,5 1.791	–	52,5 2.067	–	49,25 1.939	137,9 5.429	21,5 0.846	31,5 1.240	M8x1	–	0	G2.5	1,5 3.310

Accessories

For	Key
	
All	H05-4

Slim type
– Metric/ Inch


BT Taper-Face-ADB



- Run-out $\leq 3 \mu\text{m}$
- For reduction sleeves, see page(s) 381, 382
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	BHTA1°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
BT40TFADB-HCS06-150	10137346	BT40 TF ADB	6,0 0.236	150,0 5.906	123,0 4.843	100,0 3.937	37,0 1.457	44,5 1.752	20,0 0.787	215,4 8.480	113,0 4.449	123,0 4.843	M5x0.8	30,0	3,0	1	G2.5	1,6 3.530
BT40TFADB-HCS08-150	10137347	BT40 TF ADB	8,0 0.315	150,0 5.906	123,0 4.843	100,0 3.937	37,0 1.457	44,5 1.752	22,0 0.866	215,4 8.480	113,0 4.449	123,0 4.843	M6x1	30,0	3,0	1	G2.5	1,7 3.750
BT40TFADB-HCS10-150	10137348	BT40 TF ADB	10,0 0.394	150,0 5.906	123,0 4.843	100,0 3.937	42,0 1.654	44,5 1.752	24,0 0.945	215,4 8.480	110,0 4.331	120,0 4.724	M8x1	30,0	3,0	1	G2.5	1,7 3.750
BT40TFADB-HCS12-150	10137349	BT40 TF ADB	12,0 0.472	150,0 5.906	123,0 4.843	100,0 3.937	47,0 1.850	44,5 1.752	25,0 0.984	215,4 8.480	103,0 4.055	113,0 4.449	M10x1	30,0	3,0	1	G2.5	1,8 3.970
BT40TFADB-HCS16-150	10137350	BT40 TF ADB	16,0 0.630	150,0 5.906	123,0 4.843	100,0 3.937	52,0 2.047	44,5 1.752	32,0 1.260	215,4 8.480	100,0 3.937	110,0 4.331	M12x1	30,0	3,0	1	G2.5	2,0 4.410
BT40TFADB-HCS20-150	10137351	BT40 TF ADB	20,0 0.787	150,0 5.906	123,0 4.843	–	52,0 2.047	46,9 1.846	34,0 1.339	215,4 8.480	100,0 3.937	110,0 4.331	M16x1	–	3,0	1	G2.5	2,0 4.410

Accessories

For	Key
	
All	03MS04C

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating & setting accessories

Shrinkfit


– Metric/ Inch



Design 1



Design 2



–For reduction sleeves, see page(s) 385–386
–For ‘Stop screws for through coolant’, see page(s) 387–388
–For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	OAL	LPR	LB	CBDP	BD1	LFN	LF	KWW	TDZ	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
BT40TFADB-PMC20-065	03242413	BT40 TF ADB	20,0 0.787	128,4 5.055	65,0 2.559	36,5 1.437	63,0 2.480	65,0 2.559	2,0 0.079	7,0 0.276	8,0	M16	1	1	PB	1,4 3.090
BT40TFAD-PMC32-090	10185653	BT40 TF AD	32,0 1.260	155,4 6.118	90,0 3.543	63,0 2.480	80,0 3.150	67,0 2.638	10,0 0.394	15,0 0.591	8,0	M16	–	1	PB	2,1 4.630
BT50TFAD-PMC32-095	10185658	BT50 TF AD	32,0 1.260	196,8 7.748	95,0 3.740	57,0 2.244	90,0 3.543	67,0 2.638	5,0 0.197	10,0 0.394	8,0	M16	2	1	PB	4,6 10.140

Accessories


For	Spanner
-PMC20	03BPMC20
-PMC32	03BPMC32

Spare Parts, included in delivery

For	Extractor for reduction sleeves	Sealing Screws	Stop screw
-PMC20	03EXTPMC	950A0406	19BEPMC01
-PMC32	03EXTPMC	–	19BEPMC01

ISO 15488
– Metric/ Inch

BT Taper-Face-AD



–Run-out 15 µm/ .0006" maximum at 3 x ØDCBN-DCBX
–For ER extensions and ER collets, see page(s) 362, 363, 399, 400, 401, 402
–For ER sealing rings, see page(s) 410, 411
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	CTWS	LPR mm inch	BD2 mm inch	BD1 mm inch	OAL mm inch	LB mm inch	LFN mm inch	LF mm inch	RFID hole	Balan- cing	Weight kg lbs
BT40TFAD-ER16-070	10229690	BT40 TF AD	0,5 0.020	10,0 0.394	ER 16	70,0 2.756	28,0 1.102	28,0 1.102	134,5 5.295	43,0 1.693	25,0 0.984	40,0 1.575	1	G6.3	1,1 2.430
BT40TFAD-ER16-120	10229691	BT40 TF AD	0,5 0.020	10,0 0.394	ER 16	120,0 4.724	28,0 1.102	28,0 1.102	185,4 7.299	93,0 3.661	75,0 2.953	90,0 3.543	1	G6.3	1,4 3.090
BT40TFAD-ER25-070	10229692	BT40 TF AD	1,0 0.039	16,0 0.630	ER 25	70,0 2.756	42,0 1.654	42,0 1.654	134,5 5.295	43,0 1.693	5,0 0.197	25,0 0.984	1	G6.3	1,2 2.650
BT40TFAD-ER25-120	10229693	BT40 TF AD	1,0 0.039	16,0 0.630	ER 25	120,0 4.724	42,0 1.654	42,0 1.654	185,4 7.299	93,0 3.661	55,0 2.165	75,0 2.953	1	G6.3	1,7 3.750
BT40TFAD-ER32-070	10229694	BT40 TF AD	2,0 0.079	20,0 0.787	ER 32	70,0 2.756	50,0 1.969	50,0 1.969	135,0 5.315	43,0 1.693	5,0 0.197	25,0 0.984	1	G6.3	1,3 2.870
BT40TFAD-ER32-120	10229695	BT40 TF AD	2,0 0.079	20,0 0.787	ER 32	120,0 4.724	50,0 1.969	50,0 1.969	185,4 7.299	93,0 3.661	55,0 2.165	75,0 2.953	1	G6.3	2,1 4.630

Accessories

For	Seal nut	Spanner
		
ER16	08B587516IC	03B587516UM
ER25	08B587525IC	03B587525
ER32	08B587532IC	03B587532

Spare Parts, included in delivery

For	Nut	Stop screw
		
ER16	08B587516UM	19LRC1020
ER25	08B587525X	19LRC1225
ER32	08B587532X	19LRC1225




CAT

Seco range of rotating holders allow you to get the most out of both your machine and tool by offering a comprehensive array of solutions to connect them. The range covers all standard workpiece side connections, as well Seco's unique connections. Machine side connections are included for most of the norms, including **CAT-V**.

- Steadyline, vibration damping shell mill holders
- Shell mill holders, with through coolant channels
- Disc mill holders
- Side lock holders, Weldon
- Shrinkfit holders
- High precision collet chucks
- Hydraulic chucks and Power milling chucks
- ER collet chucks
- Tapping chucks

With through coolant channels
– Inch

CAT / ASME B5.50-1994-ADB



–DMM 2.500", includes 4 threaded holes for 5/8-11 UNC screws on the bearing face on Ø4"
–For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw (not removable)

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch			lbs
CAT40ADB-SM0.500-1.500-L1	03197127	CAT40 ADB	0.500	1.500	1.437	4.749	0.750	0.562	1	PB	2.200
CAT40ADB-SM0.750-1.500-L1	03197128	CAT40 ADB	0.750	1.500	1.750	4.874	0.750	0.687	1	PB	2.430
CAT40ADB-SM0.750-1.750-L1	03197129	CAT40 ADB	0.750	1.750	1.750	5.124	1.000	0.687	1	PB	2.650
CAT40ADB-SM0.750-4.000-L1	03197130	CAT40 ADB	0.750	4.000	1.750	7.374	3.250	0.687	1	PB	4.190
CAT40ADB-SM1.000-2.000-L1	03197131	CAT40 ADB	1.000	2.000	2.250	5.374	1.250	0.687	1	PB	3.310
CAT40ADB-SM1.000-2.250-L1	03197132	CAT40 ADB	1.000	2.250	2.250	5.624	1.500	0.687	1	PB	3.530
CAT40ADB-SM1.000-4.000-L1	03197133	CAT40 ADB	1.000	4.000	2.250	7.374	3.250	0.687	1	PB	4.850
CAT40ADB-SM1.250-2.250-L1	03197134	CAT40 ADB	1.250	2.250	2.750	5.624	1.500	0.687	1	PB	3.750
CAT40ADB-SM1.500-2.250-L1	03197136	CAT40 ADB	1.500	2.250	3.750	5.874	1.500	0.937	1	PB	5.950
CAT40ADB-SM1.500-4.000-L1	03197138	CAT40 ADB	1.500	4.000	3.750	7.624	3.250	0.937	1	PB	9.040
CAT50ADB-SM0.750-2.000-L1	03197141	CAT50 ADB	0.750	2.000	1.750	6.687	1.250	0.687	1	PB	7.280
CAT50ADB-SM0.750-3.500-L1	03197142	CAT50 ADB	0.750	3.500	1.750	8.187	2.750	0.687	1	PB	8.160
CAT50ADB-SM1.000-2.250-L1	03197145	CAT50 ADB	1.000	2.250	2.250	6.937	1.500	0.687	1	PB	8.160
CAT50ADB-SM1.000-4.000-L1	03197146	CAT50 ADB	1.000	4.000	2.250	8.687	3.250	0.687	1	PB	9.700
CAT50ADB-SM1.000-6.000-L1	03197147	CAT50 ADB	1.000	6.000	2.250	10.687	5.250	0.687	1	PB	11.900
CAT50ADB-SM1.250-1.500-L1	03197148	CAT50 ADB	1.250	1.500	2.750	6.187	0.750	0.687	1	PB	7.500
CAT50ADB-SM1.500-2.250-L1	03197150	CAT50 ADB	1.500	2.250	3.750	7.187	1.500	0.937	1	PB	10.140
CAT50ADB-SM1.500-4.000-L1	03197152	CAT50 ADB	1.500	4.000	3.750	8.937	3.250	0.937	1	PB	14.330
CAT50ADB-SM1.500-6.000-L1	03197153	CAT50 ADB	1.500	6.000	3.750	10.937	5.250	0.937	1	PB	17.200
CAT50ADB-SM2.000-2.400-L1	03197154	CAT50 ADB	2.000	2.400	4.874	7.337	1.650	0.937	1	PB	13.890
CAT50ADB-SM2.000-4.000-L1	03197156	CAT50 ADB	2.000	4.000	4.874	8.937	3.250	0.937	1	PB	18.740
CAT50ADB-SM2.500-2.400-L1	03197155	CAT50 ADB	2.500	2.400	4.874	7.525	1.650	1.125	1	PB	14.330

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others


Operating & setting accessories

Shrinkfit

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery			
	For	Bolt	Plug	Screw
				
HSK-A	CAT40ADB-SM0.500-1.500-L1	58281270	564301701	950DNF025050
	CAT40ADB-SM0.750-1.500-L1	58281905	564301701	950DNF037100
	CAT40ADB-SM0.750-1.750-L1	58281905	564301701	950DNF037100
	CAT40ADB-SM0.750-4.000-L1	58281905	564301701	950DNF037100
HSK-E	CAT40ADB-SM1.000-2.000-L1	58282540	564301701	950DNF050125
	CAT40ADB-SM1.000-2.250-L1	58282540	564301701	950DNF050125
	CAT40ADB-SM1.000-4.000-L1	58282540	564301701	950DNF050125
	CAT40ADB-SM1.250-2.250-L1	58283175	564301701	950DNF062125
DIN	CAT40ADB-SM1.500-2.250-L1	58283810	564301701	58283810A
	CAT40ADB-SM1.500-4.000-L1	58283810	564301701	58283810A
	CAT50ADB-SM0.750-2.000-L1	58281905	564301702	950DNF037100
	CAT50ADB-SM0.750-3.500-L1	58281905	564301702	950DNF037100
BT JIS	CAT50ADB-SM1.000-2.250-L1	58282540	564301702	950DNF050125
	CAT50ADB-SM1.000-4.000-L1	58282540	564301702	950DNF050125
	CAT50ADB-SM1.000-6.000-L1	58282540	564301702	950DNF050125
	CAT50ADB-SM1.250-1.500-L1	58283175	564301702	950DNF062125
CAT	CAT50ADB-SM1.500-2.250-L1	58283810	564301702	58283810A
	CAT50ADB-SM1.500-4.000-L1	58283810	564301702	58283810A
	CAT50ADB-SM1.500-6.000-L1	58283810	564301702	58283810A
	CAT50ADB-SM2.000-2.400-L1	58285080	564301702	-
	CAT50ADB-SM2.000-4.000-L1	58285080	564301702	-
	CAT50ADB-SM2.500-2.400-L1	58286350	564301702	950DNC062225
Combimaster				
Graflex				
Seco Capto™				
Others				
Operating & setting accessories				
Shrinkfit				

– Inch




– Best suited for Seco disc mill cutters Type A
– For ISO attribute explanation, see page 15

Spare parts:
1 = Slide rod
2 = Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	FLGT	LSCN	LSCX	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch			lbs
E25225657100350	02870716	CAT40 AD	1.000	3.500	1.654	6.193	2.748	0.197	0	0.591	1	PB	3.530
E25225657125475	02870717	CAT40 AD	1.250	4.750	1.969	7.443	3.998	0.236	0	0.945	1	PB	5.290
E25245657100350	02870718	CAT50 AD	1.000	3.500	1.654	7.506	2.748	0.197	0	0.591	1	PB	8.160
E25245657125475	02870719	CAT50 AD	1.250	4.750	1.969	8.756	3.998	0.236	0	0.945	1	PB	9.700
E25245657150600	02870720	CAT50 AD	1.500	6.000	2.244	10.006	5.248	0.276	0	1.181	1	PB	11.900
E25245657200625	02870721	CAT50 AD	2.000	6.250	2.835	10.256	5.500	0.315	0	1.260	1	PB	15.650

Spare Parts, included in delivery

For	Screw	Slide rod
		
1.000	950D1070	5657100
1.250	950D1270	5657125
1.500	950D16100	5657150
2.000	950D16120	5657200

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating &
setting acces-
series

Shrinkfit


– Metric/ Inch



Design 1



Design 2



–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
CAT40ADB-EM16-2.750	10008188	CAT40 ADB	16,0 0.630	69,85 2.750	50,8 2.000	47,0 1.850	48,0 1.890	138,1 5.437	45,85 1.805	1	1	PB	1,4 3.090
CAT40ADB-EM20-3.500	10008189	CAT40 ADB	20,0 0.787	88,9 3.500	69,85 2.750	49,0 1.929	52,0 2.047	157,15 6.187	63,9 2.516	1	1	PB	1,7 3.750
CAT40ADB-EM25-4.000	10008190	CAT40 ADB	25,0 0.984	101,6 4.000	82,55 3.250	54,0 2.126	65,0 2.559	169,85 6.687	77,6 3.055	2	1	PB	2,4 5.290
CAT40ADB-EM32-4.000	10008191	CAT40 ADB	32,0 1.260	101,6 4.000	82,55 3.250	58,0 2.283	72,0 2.835	101,6 4.000	77,6 3.055	2	1	PB	2,6 5.730
CAT50ADB-EM16-3.750	10008193	CAT50 ADB	16,0 0.630	95,25 3.750	76,2 3.000	49,0 1.929	48,0 1.890	196,85 7.750	71,25 2.805	1	1	PB	3,6 7.940
CAT50ADB-EM20-3.750	10008194	CAT50 ADB	20,0 0.787	95,25 3.750	76,2 3.000	51,0 2.008	52,0 2.047	196,85 7.750	70,25 2.766	1	1	PB	3,7 8.160
CAT50ADB-EM25-4.000	10008195	CAT50 ADB	25,0 0.984	101,6 4.000	82,55 3.250	54,0 2.126	54,0 2.126	203,2 8.000	77,6 3.055	2	1	PB	4,3 9.480
CAT50ADB-EM32-4.000	10008196	CAT50 ADB	32,0 1.260	101,6 4.000	82,55 3.250	60,0 2.362	72,0 2.835	203,2 8.000	77,6 3.055	2	1	PB	4,5 9.920
CAT50ADB-EM40-4.500	10008197	CAT50 ADB	40,0 1.575	114,3 4.500	95,25 3.750	70,0 2.756	80,0 3.150	215,9 8.500	84,3 3.319	2	1	PB	5,2 11.460


Spare Parts, included in delivery

For	Locking screw	Plug
		
CAT40ADB-EM16-2.750	951C1416	564301701
CAT40ADB-EM20-3.500	951C1616	564301701
CAT40ADB-EM25-4.000	951C1820	564301701
CAT40ADB-EM32-4.000	951C2020	564301701
CAT50ADB-EM16-3.750	951C1416	564301702
CAT50ADB-EM20-3.750	951C1616	564301702
CAT50ADB-EM25-4.000	951C1820	564301702
CAT50ADB-EM32-4.000	951C2020	564301702
CAT50ADB-EM40-4.500	951C2020	564301702


– Inch



Design 1



Design 2



–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch				lbs
CAT40ADB-EM0.250-2.500	03201497	CAT40 ADB	0.250	2.500	1.750	0.750	0.875	5.187	2.125	1	1	PB	2.430
CAT40ADB-EM0.375-2.000	03201499	CAT40 ADB	0.375	2.000	1.250	1.500	1.340	4.687	1.250	1	1	PB	2.650
CAT40ADB-EM0.500-1.750	03201501	CAT40 ADB	0.500	1.750	1.000	1.764	1.750	4.437	0.875	1	1	PB	2.430
CAT40ADB-EM0.500-2.620	03201503	CAT40 ADB	0.500	2.620	1.870	1.764	1.250	5.307	1.745	1	1	PB	2.650
CAT40ADB-EM0.625-1.750	03201504	CAT40 ADB	0.625	1.750	1.000	1.764	1.750	4.437	0.889	1	1	PB	2.200
CAT40ADB-EM0.625-2.500	03201505	CAT40 ADB	0.625	2.500	1.750	1.890	1.875	5.187	1.562	1	1	PB	2.870
CAT40ADB-EM0.750-1.750	03201507	CAT40 ADB	0.750	1.750	1.000	2.000	1.750	4.437	0.875	1	1	PB	2.200
CAT40ADB-EM0.750-2.500	03201508	CAT40 ADB	0.750	2.500	1.750	2.000	2.000	5.187	1.500	1	1	PB	2.870
CAT40ADB-EM0.750-3.500	03201509	CAT40 ADB	0.750	3.500	2.750	2.000	1.750	6.187	2.500	1	1	PB	7.280
CAT40ADB-EM1.000-1.750	03201510	CAT40 ADB	1.000	1.750	1.000	2.000	1.900	4.437	0.625	1	1	PB	2.200
CAT40ADB-EM1.000-4.000	03201511	CAT40 ADB	1.000	4.000	3.250	2.750	2.000	6.687	2.875	2	1	PB	3.750
CAT40ADB-EM1.250-4.000	03201512	CAT40 ADB	1.250	4.000	3.250	3.250	2.500	6.687	2.875	2	1	PB	4.410
CAT40ADB-EM1.500-4.000	03201513	CAT40 ADB	1.500	4.000	3.250	2.375	2.628	6.687	2.875	2	1	PB	4.630
CAT50ADB-EM0.375-2.500	03201515	CAT50 ADB	0.375	2.500	1.750	1.500	1.000	6.500	1.750	1	1	PB	6.830
CAT50ADB-EM0.500-2.620	03201516	CAT50 ADB	0.500	2.620	1.875	1.750	1.250	6.625	1.775	1	1	PB	6.830
CAT50ADB-EM0.625-3.750	03201518	CAT50 ADB	0.625	2.500	3.000	1.880	1.500	7.750	2.812	1	1	PB	7.720
CAT50ADB-EM0.750-2.500	03201521	CAT50 ADB	0.750	2.500	1.750	2.000	1.750	6.500	1.500	1	1	PB	7.050
CAT50ADB-EM0.750-3.750	03201522	CAT50 ADB	0.750	3.750	3.000	2.000	1.750	7.750	2.750	1	1	PB	8.380
CAT50ADB-EM1.000-1.620	03201524	CAT50 ADB	1.000	1.620	0.870	2.361	2.750	5.620	0.495	2	1	PB	6.610
CAT50ADB-EM1.000-4.000	03201526	CAT50 ADB	1.000	4.000	3.250	2.750	2.000	8.000	2.875	2	1	PB	8.380
CAT50ADB-EM1.000-6.000	03201527	CAT50 ADB	1.000	6.000	5.250	2.750	2.000	10.000	4.875	2	1	PB	10.140
CAT50ADB-EM1.250-4.000	03201528	CAT50 ADB	1.250	4.000	3.250	2.350	2.500	8.000	2.885	2	1	PB	9.260
CAT50ADB-EM1.500-2.620	03201530	CAT50 ADB	1.500	2.620	1.870	3.000	2.750	6.620	1.495	2	1	PB	7.500
CAT50ADB-EM1.500-4.000	03201531	CAT50 ADB	1.500	4.000	3.250	3.000	2.750	8.000	2.875	2	1	PB	9.260
CAT50ADB-EM1.500-6.000	03201533	CAT50 ADB	1.500	6.000	5.250	3.000	2.750	10.000	4.875	2	1	PB	11.680
CAT50ADB-EM2.000-5.620	03201534	CAT50 ADB	2.000	5.620	4.875	3.250	3.750	9.625	4.219	2	1	PB	16.530

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Grafix

Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Spare Parts, included in delivery

Guide	For	Locking screw	Locking screw, reduced	Plug
				
HSK-A	CAT40 / 0.250	951CNP025025	–	564301701
	CAT40 / 0.375	951CNP037031	–	564301701
	CAT40 / 0.500	951CNP043038	–	564301701
	CAT40 / 0.625	951CNP056044	–	564301701
HSK-E	CAT40 / 0.750	951CNP062050	–	564301701
	CAT40 / 1.000	951CNP075050	–	564301701
	CAT40 / 1.250-1.500	951CNP075062	–	564301701
	CAT50 / 0.375	951CNP037031	–	564301702
DIN	CAT50 / 0.500	951CNP043038	–	564301702
	CAT50 / 0.625	951CNP056044	–	564301702
	CAT50 / 0.750	951CNP062050	–	564301702
	CAT50 / 1.000	951CNP075050	–	564301702
BT / JIS	CAT50 / 1.250-1.500	951CNP075062	–	564301702
	CAT50 / 2.000	951CNS100087	–	564301702
	CAT50ADB-EM1.000-1.620	951CNP075050	951CNP062050	564301702

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
sories

Shrinkfit

DIN type
– Metric/ Inch

CAT / ASME B5.50-1994-ADB



- Run-out $\leq 3 \mu\text{m}$
- Delivered with one stop screw
- For Shrinkfit extensions, see page(s) 357-358
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E2502560306312	02753286	CAT40 ADB	6,0 0.236	79,38 3.125	60,28 2.373	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	147,78 5.818	43,38 1.708	53,38 2.102	10,5 0.413	M5x0.8	4,5	1	G2.5	1,2 2.650
E2502560308312	02753287	CAT40 ADB	8,0 0.315	79,38 3.125	60,28 2.373	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	147,78 5.818	43,38 1.708	53,38 2.102	10,5 0.413	M6x1	4,5	1	G2.5	1,2 2.650
E2502560310350	02753288	CAT40 ADB	10,0 0.394	88,9 3.500	69,8 2.748	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	157,3 6.193	47,9 1.886	57,9 2.280	13,0 0.512	M8x1	4,5	1	G2.5	1,3 2.870
E2502560312350	02753290	CAT40 ADB	12,0 0.472	88,9 3.500	69,8 2.748	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	157,3 6.193	42,9 1.689	52,9 2.083	13,0 0.512	M10x1	4,5	1	G2.5	1,2 2.650
E2502560314350	02753292	CAT40 ADB	14,0 0.551	88,9 3.500	69,8 2.748	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	157,3 6.193	42,9 1.689	52,9 2.083	14,0 0.551	M10x1	4,5	1	G2.5	1,3 2.870
E2502560316350	02753293	CAT40 ADB	16,0 0.630	88,9 3.500	69,8 2.748	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	157,3 6.193	39,9 1.571	49,9 1.965	14,0 0.551	M12x1	4,5	1	G2.5	1,3 2.870
E2502560318375	02753294	CAT40 ADB	18,0 0.709	95,25 3.750	76,15 2.998	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	163,65 6.443	46,25 1.821	56,25 2.215	18,0 0.709	M12x1	4,5	1	G2.5	1,4 3.090
E2502560320375	02753295	CAT40 ADB	20,0 0.787	95,25 3.750	76,15 2.998	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	163,65 6.443	44,25 1.742	54,25 2.136	18,0 0.709	M16x1	4,5	1	G2.5	1,4 3.090
E2502560325400	02753296	CAT40 ADB	25,0 0.984	101,6 4.000	82,5 3.248	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	170,0 6.693	44,6 1.756	54,6 2.150	23,5 0.925	M16x1	4,5	1	G2.5	1,7 3.750
E2504560306400	02753297	CAT50 ADB	6,0 0.236	101,6 4.000	82,5 3.248	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	203,35 8.006	65,6 2.583	75,6 2.976	10,5 0.413	M5x0.8	4,5	1	G2.5	3,3 7.280
E2504560308400	02753299	CAT50 ADB	8,0 0.315	101,6 4.000	82,5 3.248	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	203,35 8.006	65,6 2.583	75,6 2.976	10,5 0.413	M6x1	4,5	1	G2.5	3,3 7.280
E2504560310400	02753300	CAT50 ADB	10,0 0.394	101,6 4.000	82,5 3.248	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	203,35 8.006	60,6 2.386	70,6 2.780	13,0 0.512	M8x1	4,5	1	G2.5	3,4 7.500
E2504560312400	02753301	CAT50 ADB	12,0 0.472	101,6 4.000	82,5 3.248	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	203,35 8.006	55,6 2.189	65,6 2.583	13,0 0.512	M10x1	4,5	1	G2.5	3,3 7.280
E2504560314400	02753302	CAT50 ADB	14,0 0.551	101,6 4.000	82,5 3.248	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	203,35 8.006	55,6 2.189	65,6 2.583	14,0 0.551	M10x1	4,5	1	G2.5	3,4 7.500
E2504560316400	02753303	CAT50 ADB	16,0 0.630	101,6 4.000	82,5 3.248	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	203,35 8.006	52,6 2.071	62,6 2.465	14,0 0.551	M12x1	4,5	1	G2.5	3,4 7.500
E2504560318400	02753304	CAT50 ADB	18,0 0.709	101,6 4.000	82,5 3.248	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	203,35 8.006	52,6 2.071	62,6 2.465	18,0 0.709	M12x1	4,5	1	G2.5	3,5 7.720
E2504560320400	02753305	CAT50 ADB	20,0 0.787	101,6 4.000	82,5 3.248	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	203,35 8.006	50,6 1.992	60,6 2.386	18,0 0.709	M16x1	4,5	1	G2.5	3,5 7.720
E2504560325400	02753306	CAT50 ADB	25,0 0.984	101,6 4.000	82,5 3.248	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	203,35 8.006	44,6 1.756	54,6 2.150	23,5 0.925	M16x1	4,5	1	G2.5	3,8 8.380
E2504560332400	02753308	CAT50 ADB	32,0 1.260	101,6 4.000	82,5 3.248	62,5 2.461	51,0 2.008	44,0 1.732	53,0 2.087	203,35 8.006	40,6 1.598	50,6 1.992	23,5 0.925	M16x1	4,5	1	G2.5	3,6 7.940

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating & setting accessories

Shrinkfit

Accessories				
Guide	For			
	Balancing screws			
				
HSK-A	All90ZQ01			
Spare Parts, included in delivery				
HSK-E	For		Sealing Screws	Stop screw
				
DIN	CAT40	6/ 0.236	950A0406	19BDR05165
	CAT40	8/ 0.315	950A0406	19BDR06165
	CAT40	10/ 0.394	950A0406	19BDR08165
	CAT40	12/ 0.472-14/ 0.551	950A0406	19BDR10165
	CAT40	16/ 0.630-18/ 0.709	950A0406	19BDR12165
	CAT40	20/ 0.787-32/ 1.260	950A0406	19BDR16165
BT JIS	CAT50	6/ 0.236	950A0606	19BDR05165
	CAT50	8/ 0.315	950A0606	19BDR06165
	CAT50	10/ 0.394	950A0606	19BDR08165
	CAT50	12/ 0.472-14/ 0.551	950A0606	19BDR10165
	CAT50	16/ 0.630-18/ 0.709	950A0606	19BDR12165
	CAT50	20/ 0.787-32/ 1.260	950A0606	19BDR16165
CAT				
Combimaster				
Graflex				
Seco Capto™				
Others				
Operating & setting accessories				
Shrinkfit				

DIN type
– Inch

CAT / ASME B5.50-1994-ADB



- Run-out $\leq 3 \mu\text{m}$
- Delivered with one stop screw
- For Shrinkfit extensions, see page(s) 357-358
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch					lbs
E2502560302595	02753252	CAT40 ADB	0.250	3.740	2.988	1.476	0.866	0.827	1.063	6.433	2.323	2.717	0.413	M5x0.8	4,5	1	G2.5	2.650
E25025603025160	02753249	CAT40 ADB	0.250	6.299	5.547	1.476	0.866	0.827	1.063	8.992	4.882	5.276	0.413	M5x0.8	4,5	1	G2.5	3.310
E2502560303795	02753256	CAT40 ADB	0.375	3.740	2.988	1.673	1.220	0.945	1.260	6.433	2.126	2.520	0.512	M8x1	4,5	1	G2.5	2.870
E25025603037160	02753255	CAT40 ADB	0.375	6.299	5.547	1.673	1.220	0.945	1.260	8.992	4.685	5.079	0.512	M8x1	4,5	1	G2.5	3.750
E2502560305095	02753258	CAT40 ADB	0.500	3.740	2.988	1.791	1.339	0.945	1.260	6.433	2.008	2.402	0.512	M10x1	4,5	1	G2.5	2.870
E25025603050160	02753257	CAT40 ADB	0.500	6.299	5.547	1.791	1.339	0.945	1.260	8.992	4.567	4.961	0.512	M10x1	4,5	1	G2.5	3.530
E2502560306295	02753260	CAT40 ADB	0.625	3.740	2.988	1.988	1.535	1.063	1.339	6.433	1.811	2.205	0.551	M12x1	4,5	1	G2.5	2.870
E25025603062160	02753259	CAT40 ADB	0.625	6.299	5.547	1.988	1.535	1.063	1.339	8.992	4.370	4.764	0.551	M12x1	4,5	1	G2.5	3.750
E2502560307595	02753264	CAT40 ADB	0.750	3.740	2.988	2.067	1.614	1.299	1.654	6.433	1.732	2.126	0.709	M16x1	4,5	1	G2.5	3.090
E25025603075160	02753261	CAT40 ADB	0.750	6.299	5.547	2.067	1.614	1.299	1.654	8.992	4.291	4.685	0.709	M16x1	4,5	1	G2.5	4.190
E25025603100115	02753265	CAT40 ADB	1.000	4.528	3.776	2.303	1.850	1.732	2.087	7.220	2.283	2.677	0.925	M16x1	4,5	1	G2.5	4.190
E25045603025100	02753268	CAT50 ADB	0.250	3.937	3.185	1.476	0.866	0.827	1.063	7.943	2.520	2.913	0.413	M5x0.8	4,5	1	G2.5	7.280
E25045603025160	02753269	CAT50 ADB	0.250	6.299	5.547	1.476	0.866	0.827	1.063	10.305	4.882	5.276	0.413	M5x0.8	4,5	1	G2.5	7.720
E25045603037100	02753271	CAT50 ADB	0.375	3.937	3.185	1.673	1.220	0.945	1.260	7.943	2.323	2.717	0.512	M8x1	4,5	1	G2.5	7.500
E25045603037160	02753272	CAT50 ADB	0.375	6.299	5.547	1.673	1.220	0.945	1.260	10.305	4.685	5.079	0.512	M8x1	4,5	1	G2.5	8.160
E25045603050100	02753273	CAT50 ADB	0.500	3.937	3.185	1.791	1.339	0.945	1.260	7.943	2.205	2.598	0.512	M10x1	4,5	1	G2.5	7.280
E25045603050160	02753274	CAT50 ADB	0.500	6.299	5.547	1.791	1.339	0.945	1.260	10.305	4.567	4.961	0.512	M10x1	4,5	1	G2.5	8.160
E25045603062100	02753276	CAT50 ADB	0.625	3.937	3.185	1.988	1.535	1.063	1.339	7.943	2.008	2.402	0.551	M12x1	4,5	1	G2.5	7.500
E25045603062160	02753277	CAT50 ADB	0.625	6.299	5.547	1.988	1.535	1.063	1.339	10.305	4.370	4.764	0.551	M12x1	4,5	1	G2.5	8.160
E25045603075100	02753280	CAT50 ADB	0.750	3.937	3.185	2.067	1.614	1.299	1.654	7.943	1.929	2.323	0.709	M16x1	4,5	1	G2.5	7.720
E25045603075160	02753281	CAT50 ADB	0.750	6.299	5.547	2.067	1.614	1.299	1.654	10.305	4.291	4.685	0.709	M16x1	4,5	1	G2.5	9.040
E25045603100100	02753282	CAT50 ADB	1.000	3.947	3.195	2.303	1.850	1.732	2.087	7.953	1.703	2.096	0.925	M16x1	4,5	1	G2.5	8.380
E25045603100160	02753283	CAT50 ADB	1.000	6.299	5.547	2.303	1.850	1.732	2.087	10.305	4.055	4.449	0.925	M16x1	4,5	1	G2.5	10.360
E25045603125110	02753284	CAT50 ADB	1.250	4.331	3.579	2.461	2.008	1.732	2.087	8.337	1.929	2.323	0.925	M16x1	4,5	1	G2.5	8.160

Accessories

For	Balancing screws
	
All	90ZQ01

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories


Shrinkfit

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery		
	For	Sealing Screws	Stop screw
			
HSK-A	CAT40/ 0.250	950A0406	19BDR05165
	CAT40/ 0.375	950A0406	19BDR08165
	CAT40/ 0.500	950A0406	19BDR10165
	CAT40/ 0.625	950A0406	19BDR12165
HSK-E	CAT40/ 0.750-1.000	950A0406	19BDR16165
	CAT50/ 0.250	950A0606	19BDR05165
	CAT50/ 0.375	950A0606	19BDR08165
	CAT50/ 0.500	950A0606	19BDR10165
	CAT50/ 0.625	950A0606	19BDR12165
DIN	CAT50/ 0.750-1.250	950A0606	19BDR16165
BT JIS			
CAT			
Combimaster			
Graflex			
Seco Capto™			
Others			
Operating & setting accessories			
Shrinkfit			

Reinforced type
– Metric/ Inch

CAT / ASME B5.50-1994-ADB



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	LSC	BD1	BD2	BD3	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E250256001275	02904796	CAT40 ADB	12,0 0.472	75,0 2.953	55,9 2.201	40,0 1.575	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	44,45 1.750	143,4 5.646	29,0 1.142	39,0 1.535	13,5 0.531	M10x1	4,5	1	G2.5	1,2 2.650
E250256001680	02904797	CAT40 ADB	16,0 0.630	80,0 3.150	60,9 2.398	45,0 1.772	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	44,45 1.750	148,4 5.843	31,0 1.220	41,0 1.614	17,0 0.669	M12x1	4,5	1	G2.5	1,3 2.870
E250256002080	02904798	CAT40 ADB	20,0 0.787	80,0 3.150	60,9 2.398	45,0 1.772	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	44,45 1.750	148,4 5.843	29,0 1.142	39,0 1.535	21,5 0.846	M16x1	4,5	1	G2.5	1,5 3.310

Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Sealing Screws	Stop screw
			
E250256001275	90AI03	950A0406	19BDR10165
E250256001680	90AI03	950A0406	19BDR12165
E250256002080	90AI04	950A0406	19BDR16165

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Reinforced type – Inch

CAT / ASME B5.50-1994-ADB



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	LSC	BD1	BD2	BD3	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch					lbs
E25025600050287	02904855	CAT40 ADB	0.500	2.874	2.122	1.496	1.870	1.339	1.063	1.385	1.750	5.567	1.063	1.457	0.531	M10x1	4,5	1	G2.5	2.650
E25025600062300	02904856	CAT40 ADB	0.625	3.000	2.248	1.622	1.988	1.535	1.299	1.659	1.750	5.693	1.071	1.465	0.669	M12x1	4,5	1	G2.5	2.870
E25025600075312	02904857	CAT40 ADB	0.750	3.125	2.373	1.747	1.747	1.614	1.732	2.092	1.750	5.818	1.117	1.511	0.846	M16x1	4,5	1	G2.5	3.310
E25045600050325	02904858	CAT50 ADB	0.500	3.252	2.500	1.874	1.870	1.339	1.063	1.385	2.754	7.258	1.441	1.835	0.531	M10x1	4,5	1	G2.5	7.280
E25045600062325	02904859	CAT50 ADB	0.625	3.252	2.500	1.874	1.988	1.535	1.299	1.659	2.754	7.258	1.323	1.717	0.669	M12x1	4,5	1	G2.5	7.500
E25045600075350	02904860	CAT50 ADB	0.750	3.500	2.748	2.122	2.067	1.614	1.732	2.092	2.754	7.506	1.492	1.886	0.846	M16x1	4,5	1	G2.5	8.160
E25045600100400	02904861	CAT50 ADB	1.000	4.000	3.248	2.622	2.303	1.850	1.890	2.249	2.754	8.006	1.756	2.150	0.984	M16x1	4,5	1	G2.5	8.820
E25045600125400	02904862	CAT50 ADB	1.250	4.000	3.248	2.622	2.461	2.008	1.890	2.249	2.754	8.006	1.598	1.992	0.984	M16x1	4,5	1	G2.5	8.600


Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Sealing Screws	Stop screw
			
CAT40/ 0.500	90AI03	950A0406	19BDR10165
CAT40/ 0.625	90AI03	950A0406	19BDR12165
CAT40/ 0.750	90AI04	950A0406	19BDR16165
CAT50/ 0.500	90AI03	950A0606	19BDR10165
CAT50/0.625	90AI03	950A0606	19BDR12165
CAT50/ 0.750-1.250	90AI04	950A0606	19BDR16165


– Metric/ Inch



- Run-out 3 µm maximum at 3 x ØDCBN-DCBX
- For ER HP collets type 5672, see page(s) 389, 390, 391-397
- For stop screws, see instructions at www.secotools.com
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	BD1	BD2	OAL	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch			lbs
CAT40AD-ERHP11R-4.000	10358886	CAT40AD	0.039	4.000	2.622	0.630	0.630	6.693	1	G2.5	2.430
CAT40AD-ERHP16-2.500	10358887	CAT40AD	0.039	2.500	1.122	1.181	1.181	5.193	1	G2.5	2.430
CAT40AD-ERHP16-5.000	10358888	CAT40AD	0.039	5.000	3.622	1.181	1.181	7.693	1	G2.5	3.310
CAT40AD-ERHP16-6.000	10358889	CAT40AD	0.039	6.000	4.622	1.181	1.181	8.693	1	G2.5	3.530
CAT40AD-ERHP20-3.000	10358890	CAT40AD	0.039	3.000	1.622	1.260	1.260	5.693	1	G2.5	2.650
CAT40AD-ERHP20-4.000	10358891	CAT40AD	0.039	4.000	2.622	1.260	1.260	6.693	1	G2.5	2.870
CAT40AD-ERHP25-3.000	10358892	CAT40AD	0.039	3.000	1.622	1.575	1.575	5.693	1	G2.5	2.650
CAT40AD-ERHP25-4.000	10358893	CAT40AD	0.039	4.000	2.622	1.575	1.575	6.693	1	G2.5	3.310
CAT40AD-ERHP25-6.000	10358894	CAT40AD	0.039	6.000	4.622	1.575	1.575	8.693	1	G2.5	4.190
CAT40AD-ERHP32-3.000	10358895	CAT40AD	0.079	3.000	2.248	1.969	1.969	5.693	1	G2.5	2.870
CAT40AD-ERHP32-4.000	10358896	CAT40AD	0.079	4.000	3.248	1.969	1.969	6.693	1	G2.5	3.750
CAT40AD-ERHP32-6.000	10358897	CAT40AD	0.079	6.000	5.248	1.969	1.969	8.693	1	G2.5	5.290
CAT50AD-ERHP25-4.000	10358898	CAT50AD	0.039	4.000	2.622	1.575	1.575	8.006	1	G2.5	7.720
CAT50AD-ERHP32-4.000	10358899	CAT50AD	0.079	4.000	2.622	1.969	1.969	8.006	1	G2.5	8.160
CAT50AD-ERHP32-6.000	10358900	CAT50AD	0.079	6.000	4.622	1.969	1.969	10.006	1	G2.5	9.700

Accessories

For	Key	Socket	Torque key
			
ERHP11R	03LME0912140	03ER016	03DYE003025
ERHP16	03LME1418260	03ER030B	03DYE010100B
ERHP20	03LME1418260	03ER032B	03DYE010100B
ERHP25	03LME1418260	03ER040	03DYE010100B
ERHP32	03LME1418370	03ER050	03DYE040200

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories


Shrinkfit

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery	
	For	Nut
		
HSK-A	ERHP11R	08B567211RC
	ERHP16	08B567216C
	ERHP20	08B567220C
	ERHP25	08B567225C
	ERHP32	08B567232C
HSK-E		
DIN		
BT JIS		
CAT		
Combimaster		
Graflex		
Seco Capto™		
Others		
Operating & setting accessories		
Shrinkfit		

Conventional type
– Metric/ Inch

CAT / ASME B5.50-2009-ADB



– Run-out $\leq 3 \mu\text{m}$
– For reduction sleeves, see page(s) 381, 382
– For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
CAT40ADB-HC06-063	10137281	CAT40 ADB	6,0 0.236	63,5 2.500	44,45 1.750	24,56 0.967	38,5 1.516	44,5 1.750	26,0 1.024	131,75 5.187	26,5 1.043	36,5 1.437	M5	20,0	1	G2.5	1,2 2.650
CAT40ADB-HC08-063	10137282	CAT40 ADB	8,0 0.315	63,5 2.500	44,45 1.750	25,56 1.006	38,5 1.516	49,0 1.929	28,0 1.102	131,75 5.187	26,5 1.043	36,5 1.437	M5	20,0	1	G2.5	1,2 2.650
CAT40ADB-HC10-063	10137283	CAT40 ADB	10,0 0.394	63,5 2.500	44,45 1.750	27,56 1.085	42,5 1.673	49,0 1.929	30,0 1.181	131,75 5.187	22,5 0.886	32,5 1.280	M5	20,0	1	G2.5	1,2 2.650
CAT40ADB-HC12-063	10137284	CAT40 ADB	12,0 0.472	63,5 2.500	44,45 1.750	26,56 1.046	47,5 1.870	49,0 1.929	32,0 1.260	131,75 5.187	17,5 0.689	27,5 1.083	M10x1	20,0	1	G2.5	1,2 2.650
CAT40ADB-HC16-063	10137285	CAT40 ADB	16,0 0.630	63,5 2.500	44,45 1.750	27,56 1.085	51,0 2.008	49,0 1.929	38,0 1.496	131,75 5.187	14,5 0.571	24,5 0.965	M10x1	20,0	1	G2.5	1,2 2.650
CAT40ADB-HC20-063	10137286	CAT40 ADB	20,0 0.787	63,5 2.500	44,45 1.750	25,56 1.006	52,5 2.067	49,0 1.929	42,0 1.654	131,75 5.187	12,5 0.492	22,5 0.886	M10x1	20,0	1	G2.5	1,2 2.650
CAT50ADB-HC12-081	10137293	CAT50 ADB	12,0 0.472	81,0 3.189	61,95 2.439	40,0 1.575	47,5 1.870	49,0 1.929	32,0 1.260	182,6 7.189	35,0 1.378	45,0 1.772	M10x1	20,0	1	G2.5	3,1 6.830
CAT50ADB-HC20-081	10137294	CAT50 ADB	20,0 0.787	81,0 3.189	61,95 2.439	46,0 1.811	52,5 2.067	51,0 2.008	42,0 1.654	182,6 7.189	30,0 1.181	40,0 1.575	M10x1	20,0	1	G2.5	3,2 7.050
CAT50ADB-HC25-081	10137295	CAT50 ADB	25,0 0.984	81,0 3.189	61,95 2.439	36,0 1.417	58,5 2.303	68,0 2.677	48,0 1.890	182,6 7.189	24,0 0.945	34,0 1.339	M10x1	20,0	1	G2.5	3,6 7.940
CAT50ADB-HC32-081	10137296	CAT50 ADB	32,0 1.260	81,0 3.189	61,95 2.439	40,0 1.575	62,5 2.461	75,0 2.953	62,0 2.441	182,6 7.189	20,0 0.787	30,0 1.181	M10x1	20,0	1	G2.5	3,8 8.380

Accessories

For	Key
	
CAT40	H05-4
CAT50, DCBN = 12-25	H05-4
CAT50, DCBN = 32	03MS06L

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Conventional type – Inch



- Run-out $\leq 3 \mu\text{m}$
- For reduction sleeves, see page(s) 381, 382
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch					lbs
CAT40ADB-HCS0.500-5.906	10214923	CAT40 ADB	0.500	5.906	5.156	4.087	1.890	1.949	1.024	8.593	4.075	4.469	M10x1.0	30,0	1	G2.5	3.970
CAT40ADB-HCS0.625-5.906	10214924	CAT40 ADB	0.625	5.906	5.156	4.016	2.008	1.949	1.260	8.593	3.976	4.370	M12x1.0	30,0	1	G2.5	4.410
CAT40ADB-HCS0.750-5.906	10214925	CAT40 ADB	0.750	5.906	5.156	3.994	2.087	1.949	1.339	8.593	3.898	4.291	M16x1.0	30,0	1	G2.5	4.410
CAT50ADB-HCS0.500-5.906	10214926	CAT50 ADB	0.500	5.906	5.156	4.028	1.890	1.752	1.024	9.906	4.075	4.469	M10x1.0	30,0	1	G2.5	7.720
CAT50ADB-HCS0.625-5.906	10214927	CAT50 ADB	0.625	5.906	5.156	3.960	2.008	1.752	1.260	9.906	3.976	4.370	M12x1.0	30,0	1	G2.5	7.940
CAT50ADB-HCS0.750-5.906	10214928	CAT50 ADB	0.750	5.906	5.156	3.944	2.087	1.752	1.339	9.906	3.898	4.291	M16x1.0	–	1	G2.5	8.160

Accessories

For


Key



03MS04C

Reinforced type
– Metric/ Inch

CAT / ASME B5.50-2009-ADB



–Run-out $\leq 3 \mu\text{m}$
–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
CAT40ADB-HCR20-064	10137133	CAT40 ADB	20,0 0.787	64,5 2.539	45,45 1.789	–	52,5 2.067	–	49,25 1.939	132,75 5.226	13,5 0.531	23,5 0.925	M8x1	–	0	G2.5	1,3 2.870
CAT50ADB-HCR32-081	10137135	CAT50 ADB	32,0 1.260	81,0 3.189	61,95 2.439	–	62,5 2.461	–	72,0 2.835	182,6 7.189	20,0 0.787	30,0 1.181	M8x1	–	0	G2.5	4,0 8.820

Accessories

For	Key
	
CAT40ADB-HCR20-064	H05-4
CAT50ADB-HCR32-081	03MS06L

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating & setting accessories

Shrinkfit


– Inch



Design 1



Design 2




–For reduction sleeves, see page(s) 385–386
–For ‘Stop screws for through coolant’, see page(s) 387–388
–For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	OAL	LPR	LB	CDBP	BD1	BD2	LFN	LF	KWW	TDZ	Design	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch						lbs
CAT40AD-PMC0.750-3.000	10185660	CAT40 AD	0.750	5.693	3.000	2.248	2.480	1.929	1.760	0.520	0.717	8,0	UNF 5/8"-18	–	1	PB	3.090
CAT40AD-PMC1.250-4.250	10185646	CAT40 AD	1.250	6.945	4.250	3.496	3.150	2.638	1.760	1.102	1.299	8,0	UNF 5/8"	2	1	PB	5.070
CAT50ADB-PMC0.750-3.000	03211217	CAT50 ADB	0.750	7.006	3.000	1.560	2.480	1.929	2.750	0.520	0.717	8,0	UNF 5/8"	1	1	PB	7.720

Accessories


For	Spanner	Stop screw (J)
		
CAT40AD-PMC1.250-4.250	03BPMC32	–
CAT50ADB-PMC0.750-3.000	03BPMC20	19BPMC190506E
-PMC0.750	03BPMC20	–

Spare Parts, included in delivery

For	Extractor for reduction sleeves	Sealing Screws	Stop screw
			
CAT40AD-PMC1.250-4.250	03EXTPMC	–	19BEPMC02
CAT50ADB-PMC0.750-3.000	03EXTPMC	950A0606	19BEPMC02
-PMC0.750	03EXTPMC	–	19BEPMC02

ISO 15488
– Metric/ Inch

CAT / ASME B5.50-2009-ADB



- Run-out 15 µm/ .0006" maximum at 3 x ØDCBN-DCBX
- For ER extensions and ER collets, see page(s) 362, 363, 399, 400, 401, 402
- For ER sealing rings, see page(s) 410, 411
- CAT40ADB-ER16-2.000 following ASME B5.50-2009
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	CTWS	LPR mm inch	BD2 mm inch	BD1 mm inch	OAL mm inch	LB mm inch	LFN mm inch	LF mm inch	RFID hole	Balan- cing	Weight kg lbs
CAT40ADB-ER16-2.000	03201473	CAT40 ADB	0,5 0.020	10,0 0.394	ER 16	50,8 2.000	21,9 0.860	28,0 1.102	119,05 4.687	31,75 1.250	-4,2 -0.165	16,8 0.661	1	PB	1,0 2.200
CAT40ADB-ER16-4.000	03201474	CAT40 ADB	0,5 0.020	10,0 0.394	ER 16	101,6 4.000	27,6 1.087	28,0 1.102	169,85 6.687	82,55 3.250	11,6 0.457	67,6 2.661	1	PB	1,3 2.870
CAT40ADB-ER16-6.000	10229696	CAT40 ADB	0,5 0.020	10,0 0.394	ER 16	152,4 6.000	44,0 1.732	28,0 1.102	220,65 8.687	133,35 5.250	53,0 2.087	118,0 4.646	1	G6.3	1,6 3.530
CAT40ADB-ER20-2.000	10229697	CAT40 ADB	1,0 0.039	13,0 0.512	ER 20	50,8 2.000	25,0 0.984	34,0 1.339	119,05 4.687	31,75 1.250	-4,2 -0.165	10,8 0.425	1	G6.3	1,0 2.200
CAT40ADB-ER20-4.000	10229698	CAT40 ADB	1,0 0.039	13,0 0.512	ER 20	101,6 4.000	44,5 1.750	34,0 1.339	169,85 6.687	82,55 3.250	27,0 1.063	62,0 2.441	1	G6.3	1,3 2.870
CAT40ADB-ER20-6.000	10229699	CAT40 ADB	1,0 0.039	13,0 0.512	ER 20	152,4 6.000	44,5 1.750	34,0 1.339	220,65 8.687	133,35 5.250	78,0 3.071	113,0 4.449	1	G6.3	1,8 3.970
CAT40ADB-ER25-2.500	03201475	CAT40 ADB	1,0 0.039	16,0 0.630	ER 25	63,5 2.500	44,5 1.750	42,0 1.654	131,75 5.187	44,45 1.750	-11,5 -0.453	21,5 0.846	1	PB	1,1 2.430
CAT40ADB-ER25-4.000	03201476	CAT40 ADB	1,0 0.039	16,0 0.630	ER 25	101,6 4.000	41,6 1.638	42,0 1.654	169,85 6.687	82,55 3.250	1,6 0.063	59,6 2.346	1	PB	1,5 3.310
CAT40ADB-ER25-6.000	10229700	CAT40 ADB	1,0 0.039	16,0 0.630	ER 25	152,4 6.000	44,5 1.750	42,0 1.654	220,65 8.687	133,35 5.250	53,0 2.087	110,0 4.331	1	G6.3	2,0 4.410
CAT40ADB-ER32-3.000	03201477	CAT40 ADB	2,0 0.079	20,0 0.787	ER 32	76,2 3.000	44,5 1.750	50,0 1.969	144,45 5.687	57,15 2.250	-8,8 -0.346	27,2 1.071	1	PB	1,3 2.870
CAT40ADB-ER32-4.000	03201478	CAT40 ADB	2,0 0.079	20,0 0.787	ER 32	101,6 4.000	44,5 1.750	50,0 1.969	169,85 6.687	82,55 3.250	1,6 0.063	52,6 2.071	1	PB	1,3 2.870
CAT40ADB-ER32-6.000	10229701	CAT40 ADB	2,0 0.079	20,0 0.787	ER 32	152,4 6.000	44,5 1.750	50,0 1.969	220,65 8.687	133,35 5.250	50,0 1.969	103,0 4.055	1	G6.3	2,2 4.850
CAT40ADB-ER40-4.000	03201479	CAT40 ADB	3,0 0.118	26,0 1.024	ER 40	101,6 4.000	62,6 2.465	63,0 2.480	169,85 6.687	82,55 3.250	1,6 0.063	46,6 1.835	1	PB	1,8 3.970
CAT50ADB-ER16-4.000	03201480	CAT50 ADB	0,5 0.020	10,0 0.394	ER 16	101,6 4.000	27,6 1.087	28,0 1.102	203,2 8.000	82,55 3.250	1,6 0.063	61,6 2.425	1	PB	3,2 7.050
CAT50ADB-ER16-6.000	03201481	CAT50 ADB	0,5 0.020	10,0 0.394	ER 16	152,4 6.000	27,6 1.087	28,0 1.102	254,0 10.000	133,35 5.250	32,4 1.276	112,4 4.425	1	PB	3,7 8.160
CAT50ADB-ER20-4.000	10229702	CAT40 ADB	1,0 0.039	13,0 0.512	ER 20	101,6 4.000	69,9 2.750	34,0 1.339	203,2 8.000	82,55 3.250	2,0 0.079	61,0 2.402	1	G6.3	4,3 9.480
CAT50ADB-ER20-6.000	10229703	CAT50 ADB	1,0 0.039	13,0 0.512	ER 20	152,4 6.000	69,9 2.750	34,0 1.339	254,0 10.000	133,35 5.250	53,0 2.087	112,0 4.409	1	G6.3	3,9 8.600
CAT50ADB-ER25-4.000	03201482	CAT50 ADB	1,0 0.039	16,0 0.630	ER 25	101,6 4.000	41,6 1.638	42,0 1.654	203,2 8.000	82,55 3.250	1,6 0.063	59,6 2.346	1	PB	3,5 7.720
CAT50ADB-ER25-6.000	03201483	CAT50 ADB	1,0 0.039	16,0 0.630	ER 25	152,4 6.000	41,6 1.638	42,0 1.654	254,0 10.000	133,35 5.250	12,4 0.488	110,4 4.346	1	PB	3,9 8.600
CAT50ADB-ER32-4.000	03201484	CAT50 ADB	2,0 0.079	20,0 0.787	ER 32	101,6 4.000	49,6 1.953	50,0 1.969	203,2 8.000	82,55 3.250	-18,4 -0.724	50,6 1.992	1	PB	3,8 8.380
CAT50ADB-ER32-6.000	03201485	CAT50 ADB	2,0 0.079	20,0 0.787	ER 32	152,4 6.000	49,6 1.953	50,0 1.969	254,0 10.000	133,35 5.250	22,4 0.882	101,4 3.992	1	PB	4,3 9.480
CAT50ADB-ER40-4.000	03201486	CAT50 ADB	3,0 0.118	26,0 1.024	ER 40	101,6 4.000	62,6 2.465	63,0 2.480	203,2 8.000	82,55 3.250	-18,4 -0.724	46,6 1.835	1	PB	4,1 9.040

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others


Operating &
setting acces-
series

Shrinkfit

Accessories

Guide	Accessories		
	For	Seal nut	Spanner
			
HSK-A	CAT40/ ER16	08B587516IC	03B587516UM
	CAT40/ ER20	-	03B587520UM
	CAT40/ ER25	08B587525IC	03B587525
	CAT40/ ER32	08B587532IC	03B587532
HSK-E	CAT40/ ER40	08B587540IC	03B587540
	CAT50/ ER16	08B587516IC	03B587516UM
	CAT50/ ER20	-	03B587520UM
	CAT50/ ER25	08B587525IC	03B587525
	CAT50/ ER32	08B587532IC	03B587532
DIN	CAT50/ ER40	08B587540IC	03B587540

Spare Parts, included in delivery


BT / IIS	Spare Parts, included in delivery			
	For	Nut	Plug	Stop screw
				
CAT	CAT40/ ER16-2.000 / 4.000	5533050-06	564301701	19BS567510
	CAT40/ ER16-6.000	5533050-06	-	19BS567510
	CAT40/ ER20	5533050-08	-	19BS567512
	CAT40/ ER25-2.500 / 4.000	5533050-02	564301701	19BS567518
Combimaster	CAT40/ ER25-6.000	5533050-02	-	19BS567518
	CAT40/ ER32-3.000 / 4.000	5533050-03	564301701	19BS567522
	CAT40/ ER32-6.000	5533050-03	-	19BS567522
	CAT40/ ER40	5533050-04	564301701	19BS567528
Graflex	CAT50/ ER16	5533050-06	564301702	19BS567510
	CAT50/ ER20	5533050-08	-	19BS567512
	CAT50/ ER25	5533050-02	564301702	19BS567518
	CAT50/ ER32	5533050-03	564301702	19BS567522
Seco Capto™	CAT50/ ER40	5533050-04	564301702	19BS567528

For synchronized tapping, with micro-compensation
– Inch


CAT / ASME B5.50-2009-AD



Design 1





Design 2



- Maximum coolant pressure 80 bar/ 1160 psi
- For ER tapping collets with square drive, see page(s) 407, 408–409
- For TCER 5867 sealing rings, see page(s) 410, 411
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCBN	DCBX	LPR	LB	LB1	BD	BD1	OAL	SW	Design	RFID hole	Balan- cing	Weight
						inch	inch	inch	inch	inch	inch	inch				lbs
E2622586720102	03131168	CAT40 AD	ER 20	M4	M12	3.827	3.079	1.390	1.339	1.378	6.514	0.866	1	0	–	2.870
E2622586725122	03131169	CAT40 AD	ER 25	M8	M20	4.591	3.839	1.461	1.654	1.732	7.278	1.102	1	0	–	3.530
E2624586720106	03131170	CAT50 AD	ER 20	M4	M12	3.984	3.236	1.390	1.339	1.378	7.984	0.866	1	0	–	6.610
E2624586725126	03131171	CAT50 AD	ER 25	M8	M20	4.748	3.996	1.461	1.654	1.732	8.748	1.102	1	0	–	7.500
E2624586740155	03131172	CAT50 AD	ER 40	M16	M33	5.890	5.130	1.835	2.480	2.441	9.890	1.559	1	0	–	10.360

Accessories

For	Locking key	Seal nut	Spanner
			
ER 20	5680092-04	5533051-02	03B587520UM
ER 25	5680092-05	5533051-03	03B587525
ER 40	5680092-06	5533051-05	03B587540

Spare Parts, included in delivery

For	Nut
	
ER 20	5533050-08
ER 25	5533050-02
ER 40	5533050-04

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit



CAT TF

The Seco range of rotating holders allows you to get the most out of both your machine and tool by offering a comprehensive array of solutions to connect them. The range covers all standard workpiece side connections, as well as Seco's unique connections. **CAT-V TF** brings a better accuracy and is ideal for long tools.


- Steadyline, vibration damping shell mill holders
- Shell mill holders, with through coolant channels
- Side lock holders, Weldon
- Shrinkfit holders
- High precision collet chucks
- Power milling chucks
- ER collet chucks

Steadyline®, vibration damping
– Inch


CAT TF / ASME B5.50-2009-ADB



Design 1 (5555)



Design 2 (5556)




–For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	BD1	OAL	LB	LSC	Design	BHTA°	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch	inch					lbs
E26445556075900	02998686	CAT50 TF ADB	0.750	9.000	1.750	2.520	13.695	8.248	0.689	2	2,6	1	PB	14.550
E26445556100C00	02926888	CAT50 TF ADB	1.000	12.000	2.250	3.000	16.695	11.250	0.689	2	1,8	1	PB	24.030

Spare Parts, included in delivery

For	Bolt	Screw	Sealing Screws	Tenon
				
E26445556075900	58211905	950D0312	950A0606	16C2080712A
E26445556100C00	58212540	950D0416	950A0606	16C2091014A

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
sories

Shrinkfit

With through coolant channels
– Inch

CAT TF / ASME B5.50-2009-ADB




—For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw (not removable)

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch			lbs
CAT40TFADB-SM0.750-4.000-L1	10008257	CAT40 TF ADB	0.750	4.000	1.750	7.374	3.250	0.687	1	PB	4.190
CAT40TFADB-SM1.000-4.000-L1	10008258	CAT40 TF ADB	1.000	4.000	2.250	7.374	3.250	0.687	1	PB	5.950
CAT40TFADB-SM1.250-4.000-L1	10008260	CAT40 TF ADB	1.250	4.000	2.750	7.374	3.250	0.687	1	PB	7.280
CAT40TFADB-SM1.500-4.000-L1	10008261	CAT40 TF ADB	1.500	4.000	3.500	7.624	3.250	0.937	1	PB	10.580
CAT50TFADB-SM0.750-4.000-L1	10008262	CAT50 TF ADB	0.750	4.000	1.750	8.687	3.250	0.687	1	PB	7.940
CAT50TFADB-SM1.000-4.000-L1	10008263	CAT50 TF ADB	1.000	4.000	2.250	8.687	3.250	0.687	1	PB	9.920
CAT50TFADB-SM1.250-4.000-L1	10008264	CAT50 TF ADB	1.250	4.000	2.750	8.687	3.250	0.687	1	PB	11.460
CAT50TFADB-SM1.500-4.000-L1	10008265	CAT50 TF ADB	1.500	4.000	3.500	8.937	3.250	0.937	1	PB	15.210
CAT50TFADB-SM2.000-4.000-L1	10008266	CAT50 TF ADB	2.000	4.000	4.882	8.937	3.250	0.937	1	PB	22.050

Spare Parts, included in delivery


For	Bolt	Plug	Screw
			
CAT40TFADB-SM0.750-4.000-L1	58281905	564301701	950DNF037100
CAT40TFADB-SM1.000-4.000-L1	58282540	564301701	950DNF050125
CAT40TFADB-SM1.250-4.000-L1	58283175	564301701	950DNF062125
CAT40TFADB-SM1.500-4.000-L1	58283810	564301701	58283810A
CAT50TFADB-SM0.750-4.000-L1	58281905	564301702	950DNF037100
CAT50TFADB-SM1.000-4.000-L1	58282540	564301702	950DNF050125
CAT50TFADB-SM1.250-4.000-L1	58283175	564301702	950DNF062125
CAT50TFADB-SM1.500-4.000-L1	58283810	564301702	58283810A
CAT50TFADB-SM2.000-4.000-L1	58285080	564301702	—

DIN 1835 Form B/ DIN 6535 Form HB
– Inch


CAT TF / ASME B5.50-2009-ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LSC	BD	OAL	LFS	Design	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch				lbs
CAT40TFADB-EM0.500-2.620	10008198	CAT40 TF ADB	0.500	2.581	1.870	1.750	1.594	5.307	1.745	1	1	PB	2.650
CAT40TFADB-EM0.625-3.000	10008199	CAT40 TF ADB	0.625	3.000	2.250	1.870	1.850	5.687	2.062	1	1	PB	3.310
CAT40TFADB-EM0.750-3.000	10008200	CAT40 TF ADB	0.750	3.000	2.250	2.008	1.980	5.687	2.000	1	1	PB	3.530
CAT40TFADB-EM1.000-4.000	10008201	CAT40 TF ADB	1.000	4.000	3.250	2.244	2.480	6.687	2.875	2	1	PB	5.290
CAT40TFADB-EM1.250-4.000	10008202	CAT40 TF ADB	1.250	4.000	3.250	2.244	2.728	6.687	2.875	2	1	PB	5.730
CAT50TFADB-EM0.500-4.620	10008203	CAT50 TF ADB	0.500	4.620	3.870	1.750	1.594	8.620	3.745	1	1	PB	7.500
CAT50TFADB-EM0.625-5.750	10008204	CAT50 TF ADB	0.625	5.750	5.000	1.870	1.850	9.750	4.812	1	1	PB	8.820
CAT50TFADB-EM0.750-2.620	10008205	CAT50 TF ADB	0.750	2.620	1.870	2.000	1.980	6.620	1.620	1	1	PB	6.830
CAT50TFADB-EM0.750-4.000	10008206	CAT50 TF ADB	0.750	4.000	3.250	2.000	1.980	8.000	3.000	1	1	PB	7.940
CAT50TFADB-EM1.000-4.000	10008207	CAT50 TF ADB	1.000	4.000	3.368	2.244	2.480	8.000	2.875	2	1	PB	9.040
CAT50TFADB-EM1.250-4.000	10008208	CAT50 TF ADB	1.250	4.000	3.250	2.244	2.730	8.000	2.875	2	1	PB	9.700
CAT50TFADB-EM1.500-4.000	10008209	CAT50 TF ADB	1.500	4.000	3.250	2.618	3.480	8.000	2.500	2	1	PB	12.130
CAT50TFADB-EM2.000-5.620	10008210	CAT50 TF ADB	2.000	5.625	4.875	3.189	3.980	9.625	4.219	2	1	PB	18.520

Spare Parts, included in delivery

For	Locking screw	Plug
		
CAT40TFADB-EM0.500-2.620	951CNP043038	564301701
CAT40TFADB-EM0.625-3.000	951CNP056044	564301701
CAT40TFADB-EM0.750-3.000	951CNP062050	564301701
CAT40TFADB-EM1.000-4.000	951CNP075062	564301701
CAT40TFADB-EM1.250-4.000	951CNP075062	564301701
CAT50TFADB-EM0.500-4.620	951CNP043038	564301702
CAT50TFADB-EM0.625-5.750	951CNP056044	564301702
CAT50TFADB-EM0.750-2.620	951CNP062050	564301702
CAT50TFADB-EM0.750-4.000	951CNP062050	564301702
CAT50TFADB-EM1.000-4.000	951CNP075062	564301702
CAT50TFADB-EM1.250-4.000	951CNP075062	564301702
CAT50TFADB-EM1.500-4.000	951CNP075062	564301702
CAT50TFADB-EM2.000-5.620	951CNS100087	564301702

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

– Metric/ Inch



- Run-out $\leq 3 \mu\text{m}$
- Delivered with one stop screw
- For Shrinkfit extensions, see page(s) 357-358
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E264256030695	02998704	CAT40 TF ADB	6,0 0.236	95,0 3.740	75,9 2.988	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	163,4 6.433	59,0 2.323	69,0 2.717	10,5 0.413	M5x0.8	4,5	1	G2.5	1,2 2.650
E264256030895	02998705	CAT40 TF ADB	8,0 0.315	95,0 3.740	75,9 2.988	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	163,4 6.433	59,0 2.323	69,0 2.717	10,5 0.413	M6x1	4,5	1	G2.5	1,2 2.650
E264256031095	02998706	CAT40 TF ADB	10,0 0.394	95,0 3.740	75,9 2.988	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	163,4 6.433	54,0 2.126	64,0 2.520	13,0 0.512	M8x1	4,5	1	G2.5	1,3 2.870
E264256031295	02998707	CAT40 TF ADB	12,0 0.472	95,0 3.740	75,9 2.988	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	163,4 6.433	49,0 1.929	59,0 2.323	13,0 0.512	M10x1	4,5	1	G2.5	1,2 2.650
E264256031695	02998708	CAT40 TF ADB	16,0 0.630	95,0 3.740	75,9 2.988	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	163,4 6.433	46,0 1.811	56,0 2.205	14,0 0.551	M12x1	4,5	1	G2.5	1,3 2.870
E264256032095	02998709	CAT40 TF ADB	20,0 0.787	95,0 3.740	75,9 2.988	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	163,4 6.433	44,0 1.732	54,0 2.126	18,0 0.709	M16x1	4,5	1	G2.5	1,4 3.090

Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For		Sealing Screws	Stop screw
			
CAT40	6/ 0.236	950A0406	19BDR12165
CAT40	8/ 0.315	950A0406	19BDR08165
CAT40	10/ 0.394	950A0406	19BDR12165
CAT40	12/ 0.472	950A0406	19BDR05165
CAT40	16/ 0.630	950A0406	19BDR12165
CAT40	20/ 0.787	950A0406	19BDR16165

DIN type
– Inch

CAT TF / ASME B5.50-2009-ADB

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster


Graflex

Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit



- Run-out $\leq 3 \mu\text{m}$
- Delivered with one stop screw
- For Shrinkfit extensions, see page(s) 357-358
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch				lbs
E26425603025375	02999165	CAT40 TF ADB	0.250	3.750	2.998	1.476	0.866	0.827	1.063	6.443	2.333	2.726	0.413	M5x0.8	4,5	1	G2.5	2.650
E26425603037375	02999166	CAT40 TF ADB	0.375	3.750	2.998	1.673	1.220	0.945	1.260	6.443	2.136	2.530	0.512	M8x1	4,5	1	G2.5	2.870
E26425603050375	02999167	CAT40 TF ADB	0.500	3.750	2.998	1.791	1.339	0.945	1.260	6.443	2.018	2.411	0.512	M10x1	4,5	1	G2.5	2.650
E26445603037400	02998688	CAT50 TF ADB	0.375	4.000	3.248	1.673	1.220	0.945	1.260	8.006	2.386	2.780	0.512	M8x1	4,5	1	G2.5	6.830
E26445603050400	02998689	CAT50 TF ADB	0.500	4.000	3.248	1.791	1.339	0.945	1.260	8.006	2.268	2.661	0.512	M10x1	4,5	1	G2.5	6.830
E26445603062400	02998690	CAT50 TF ADB	0.625	4.000	3.248	1.988	1.535	1.063	1.339	8.006	2.071	2.465	0.551	M12x1	4,5	1	G2.5	6.830
E26445603075400	02998691	CAT50 TF ADB	0.750	4.000	3.248	2.067	1.614	1.299	1.654	8.006	1.992	2.386	0.709	M16x1	4,5	1	G2.5	7.050
E26445603100400	02998692	CAT50 TF ADB	1.000	4.000	3.248	2.303	1.850	1.732	2.087	8.006	1.756	2.150	0.925	M16x1	4,5	1	G2.5	8.160

Accessories


For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Sealing Screws	Stop screw
		
E26425603025375	950A0406	19BDR05165
E26425603037375	950A0406	19BDR08165
E26425603050375	950A0406	19BDR10165
E26445603037400	950A0606	19BDR08165
E26445603050400	950A0606	19BDR10165
E26445603062400	950A0606	19BDR12165
E26445603075400	950A0606	19BDR16165
E26445603100400	950A0606	19BDR16165

Reinforced type
– Inch

CAT TF / ASME B5.50-1994-ADB



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	LSC	BD1	BD2	BD3	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch					lbs
E25425600050287	02904847	CAT40 TF ADB	0.500	2.874	2.122	1.496	1.870	1.339	1.063	1.385	1.750	5.567	1.063	1.457	0.531	M10x1	4,5	1	G2.5	2.650
E25425600062300	02904848	CAT40 TF ADB	0.625	3.000	2.248	1.622	1.988	1.535	1.299	1.659	1.750	5.693	1.071	1.465	0.669	M12x1	4,5	1	G2.5	2.870
E25425600075312	02904849	CAT40 TF ADB	0.750	3.125	2.373	1.747	2.067	1.614	1.732	2.092	1.750	5.818	1.117	1.511	0.846	M16x1	4,5	1	G2.5	3.530


Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Sealing Screws	Stop screw
			
CAT40/ 0.500	90AI03	950A0406	19BDR10165
CAT40/ 0.625	90AI03	950A0406	19BDR12165
CAT40/ 0.750	90AI04	950A0406	19BDR16165


– Inch



- Run-out 3 µm maximum at 3 x ØDCBN-DCBX
- For ER HP collets type 5672, see page(s) 389, 390, 391-397
- For stop screws, see instructions at www.secotools.com
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	RFID hole	Balan- cing	Weight
			inch	inch		inch	inch	inch	inch	inch			lbs
CAT40TFAD-ERHP16-2.500	10358901	CAT40ADTF	0.039	0.394	HP 16	2.500	1.181	1.181	5.193	1.748	1	G2.5	2.430
CAT40TFAD-ERHP16-6.000	10358902	CAT40ADTF	0.039	0.394	HP 16	6.000	1.181	1.181	8.693	5.248	1	G2.5	3.310
CAT40TFAD-ERHP25-2.500	10358903	CAT40ADTF	0.039	0.630	HP 25	2.500	1.575	1.575	5.193	1.748	1	G2.5	2.430
CAT40TFADB-ERHP25-4.000	10190243	CAT40 TF ADB	0.039	0.630	HP 25	4.000	1.575	1.575	6.693	3.248	1	G2.5	3.090
CAT40TFAD-ERHP25-6.000	10358905	CAT40ADTF	0.039	0.630	HP 25	6.000	1.575	1.575	8.693	5.248	1	G2.5	4.190
CAT50TFAD-ERHP32-3.000	10358906	CAT50ADTF	0.079	0.787	HP 32	3.000	1.969	1.969	7.006	2.248	1	G2.5	7.050
CAT50TFAD-ERHP32-6.000	10358907	CAT50ADTF	0.079	0.787	HP 32	6.000	1.969	1.969	10.006	5.248	1	G2.5	9.260

Accessories

For	Key	Socket	Torque key
			
ERHP16	03LME1418260	03ER030B	03DYE010100B
ERHP25	03LME1418260	03ER040	03DYE010100B
ERHP32	03LME1418370	03ER050	03DYE040200

Spare Parts, included in delivery

For	Nut
	
ERHP16	08B567216C
ERHP25	08B567225C
ERHP32	08B567232C

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Conventional type
– Metric/ Inch

CAT TF / ASME B5.50-2009-ADB



–Run-out $\leq 3 \mu\text{m}$
–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15


Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
CAT40TFADB-HC06-080	10137287	CAT40 TF ADB	6,0 0.236	80,0 3.150	60,95 2.400	29,5 1.161	37,0 1.457	49,5 1.949	26,0 1.024	148,25 5.837	43,0 1.693	53,0 2.087	M5x0.8	30,0	1	G2.5	1,5 3.310
CAT40TFADB-HC08-080	10137288	CAT40 TF ADB	8,0 0.315	80,0 3.150	60,95 2.400	30,0 1.181	37,0 1.457	49,5 1.949	28,0 1.102	148,25 5.837	43,0 1.693	53,0 2.087	M6x1	30,0	1	G2.5	1,4 3.090
CAT40TFADB-HC10-080	10137289	CAT40 TF ADB	10,0 0.394	80,0 3.150	60,95 2.400	31,0 1.220	42,0 1.654	49,5 1.949	30,0 1.181	148,25 5.837	40,0 1.575	50,0 1.969	M8x1	30,0	1	G2.5	1,4 3.090
CAT40TFADB-HC12-080	10137290	CAT40 TF ADB	12,0 0.472	80,0 3.150	60,95 2.400	31,5 1.240	47,0 1.850	49,5 1.949	32,0 1.260	148,25 5.837	35,0 1.378	45,0 1.772	M10x1	30,0	1	G2.5	1,4 3.090
CAT40TFADB-HC16-080	10137291	CAT40 TF ADB	16,0 0.630	80,0 3.150	60,95 2.400	33,0 1.299	52,0 2.047	49,5 1.949	38,0 1.496	148,25 5.837	30,0 1.181	40,0 1.575	M12x1	30,0	1	G2.5	1,5 3.310
CAT40TFADB-HC20-080	10137292	CAT40 TF ADB	20,0 0.787	80,0 3.150	60,95 2.400	34,0 1.339	52,0 2.047	49,5 1.949	42,0 1.654	148,25 5.837	30,0 1.181	40,0 1.575	M16x1	30,0	1	G2.5	1,5 3.310

Accessories

For	Key
	
All	H05-4

Reinforced type
– Metric/ Inch

CAT TF / ASME B5.50-2009-ADB



–Run-out $\leq 3 \mu\text{m}$
–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
CAT40TFADB-HCR20-064	10137134	CAT40 TF ADB	20,0 0.787	64,5 2.539	45,45 1.789	–	52,5 2.067	–	49,25 1.939	132,75 5.226	13,5 0.531	23,5 0.925	M8x1	–	0	G2.5	1,3 2.870

Accessories

For	Key
	
CAT40TFADB-HCR20-064	H05-4

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating &
setting acces-
series

Shrinkfit


– Inch



Design 1



Design 2




–For reduction sleeves, see page(s) 385–386
–For ‘Stop screws for through coolant’, see page(s) 387–388
–For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	OAL	LPR	LB	CDBP	BD1	BD2	LFN	LF	KWW	TDZ	Design	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch						lbs
CAT40TFAD-PMC0.750-3.000	10185655	CAT40 TF AD	0.750	5.693	3.000	2.248	2.248	1.929	1.760	0.520	0.717	8,0	UNF 5/8"-18	2	1	PB	3.310
CAT40TFADB-PMC1.250-4.250	03211220	CAT40 TF ADB	1.250	6.943	4.250	1.560	3.540	2.638	1.750	1.100	1.297	8,0	UNF 5/8"	1	1	PB	5.070

Accessories


For	Spanner	Stop screw (K)
		
CAT40TFADB-PMC1.250-4.250	03BPMC32	19BPMC317506H
CAT40TFAD-PMC0.750-3.000	03BPMC20	–

Spare Parts, included in delivery

For	Extractor for reduction sleeves	Sealing Screws	Stop screw
			
CAT40TFADB-PMC1.250-4.250	03EXTPMC	950A0406	19BPMC02
CAT40TFAD-PMC0.750-3.000	03EXTPMC	–	19BPMC02

ISO 15488
– Metric/ Inch

CAT TF / ASME B5.50-2009-ADB



–Run-out 15 µm/ .0006" maximum at 3 x ØDCBN-DCBX
–For ER sealing rings, see page(s) 410, 411
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	LFN	LF	RFID hole	Balan- cing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
CAT40TFADB-ER16-4.000	10008238	CAT40 TF ADB	0,5 0.020	10,0 0.394	ER 16	101,6 4.000	27,6 1.087	28,0 1.102	169,85 6.687	82,55 3.250	11,6 0.457	67,6 2.661	1	PB	1,2 2.650
CAT40TFADB-ER25-4.000	10008239	CAT40 TF ADB	1,0 0.039	16,0 0.630	ER 25	101,6 4.000	41,6 1.638	42,0 1.654	169,85 6.687	82,55 3.250	1,6 0.063	59,6 2.346	1	PB	1,4 3.090
CAT40TFADB-ER32-4.000	10008240	CAT40 TF ADB	2,0 0.079	20,0 0.787	ER 32	101,6 4.000	49,6 1.953	50,0 1.969	169,85 6.687	82,55 3.250	1,6 0.063	52,6 2.071	1	PB	1,7 3.750
CAT50TFADB-ER16-4.000	10229704	CAT50 TF ADB	0,5 0.020	10,0 0.394	ER 16	101,6 4.000	27,6 1.087	28,0 1.102	203,2 8.000	82,55 3.250	11,6 0.457	67,6 2.661	1	G6.3	2,9 6.390
CAT50TFADB-ER20-4.000	10229705	CAT50 TF ADB	1,0 0.039	13,0 0.512	ER 20	101,6 4.000	33,6 1.323	34,0 1.339	203,2 8.000	82,55 3.250	1,6 0.063	61,6 2.425	1	G6.3	3,1 6.830
CAT50TFADB-ER20-6.000	10229706	CAT50 TF ADB	1,0 0.039	13,0 0.512	ER 20	152,4 6.000	33,6 1.323	34,0 1.339	254,0 10.000	133,35 5.250	52,4 2.063	112,4 4.425	1	G6.3	3,7 8.160
CAT50TFADB-ER32-4.000	10229707	CAT50 TF ADB	2,0 0.079	20,0 0.787	ER 32	101,6 4.000	49,6 1.953	50,0 1.969	203,2 8.000	82,55 3.250	1,6 0.063	53,6 2.110	1	G6.3	3,4 7.500
CAT50TFADB-ER32-6.000	10008241	CAT50 TF ADB	2,0 0.079	20,0 0.787	ER 32	152,4 6.000	49,6 1.953	50,0 1.969	254,0 10.000	133,35 5.250	52,4 2.063	104,4 4.110	1	PB	4,0 8.820
CAT50TFADB-ER40-4.000	10008242	CAT50 TF ADB	3,0 0.118	26,0 1.024	ER 40	101,6 4.000	62,6 2.465	63,0 2.480	203,2 8.000	82,55 3.250	-18,4 -0.724	46,6 1.835	1	PB	3,8 8.380

Accessories

For	Seal nut	Spanner
		
CAT40TFADB-ER16-4.000	08B587516IC	03B587516UM
CAT40TFADB-ER25-4.000	08B587525IC	03B587525
CAT40TFADB-ER32-4.000	08B587532IC	03B587532
CAT50TFADB-ER16-4.000	08B587516IC	03B587516UM
CAT50TFADB-ER20-4.000	–	03B587520UM
CAT50TFADB-ER20-6.000	–	03B587520UM
CAT50TFADB-ER32-4.000	08B587532IC	03B587532
CAT50TFADB-ER32-6.000	08B587532IC	03B587532
CAT50TFADB-ER40-4.000	08B587540IC	03B587540

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery		
	For	Nut	Plug
			
HSK-A	CAT40TFADB-ER16-4.000	5533050-06	564301701
	CAT40TFADB-ER25-4.000	5533050-02	564301701
	CAT40TFADB-ER32-4.000	5533050-03	564301701
HSK-E	CAT50TFADB-ER16-4.000	5533050-06	-
	CAT50TFADB-ER20-4.000	5533050-08	-
	CAT50TFADB-ER20-6.000	5533050-08	-
	CAT50TFADB-ER32-4.000	5533050-03	-
	CAT50TFADB-ER32-6.000	5533050-03	564301702
	CAT50TFADB-ER40-4.000	5533050-04	564301702
DIN			
BT JIS			
CAT			
Combimaster			
Graflex			
Seco Capto™			
Others			
Operating & setting accessories			
Shrinkfit			



Combimaster

Poorly designed holders can't provide the rigidity, stability or precision needed for optimized milling strategies and, subsequently, superior performance. Maximize these factors for fully secure milling processes with the expanded line of **Combimaster™** holders.

- Combimaster with different taper backends
- Shrinkfit holders
- Steadyline solutions
- Intermediates to cover extensions and reducers

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Machine side

Workpiece side



Machine side catalogue designation	Hole for RFID carrier*	L	L1	D	M	SW
		mm inch	mm inch	mm inch	mm inch	mm inch
M10	No	18,75 0.738	13 0.512	18,5 0.728	10 0.394	15 0.591
M12	No	21,75 0.856	15 0.591	23 0.906	12 0.472	19 0.748
M16	No	22,75 0.896	16 0.630	30 1.181	16 0.630	26 1.024
M20	No	27 1.063	18 0.709	36,5 1.437	20 0.787	32 1.260
M6	No	13,5 0.531	9 0.354	11 0.433	6 0.236	9 0.354
M8	No	17,75 0.699	11 0.433	13,5 0.531	8 0.315	11 0.433
Workpiece side catalogue designation	Hole for RFID carrier*			D	M	
				mm inch	mm inch	
M10	No			18,5 0.728	10 0.394	
M12	No			23 0.906	12 0.472	
M16	No			30 1.181	16 0.630	
M20	No			36,5 1.437	20 0.787	
M6	No			11 0.433	6 0.236	
M8	No			13,5 0.531	8 0.315	

Note: These machine side and workpiece side dimensions are applied to all the holders shown in the Product pages.


* No hole for RFID carriers

Steadyline®, vibration damping
– Metric/ Inch


HSK-A/ ISO12164-1-HSK-A



Design 1



Design 2



–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB3	LB1	BD	BD2	BD1	OAL	BHTA°	Design	Max. RPM	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
E9304K82012185	02904473	HSK-A63	M12	185,0 7.283	159,0 6.260	156,14 6.147	24,0 0.945	20,0 0.787	23,0 0.906	42,97 1.692	30,0 1.181	217,0 8.543	2,75	1	9000	1	PB	1,9 4.190
E9304K82016235	02904476	HSK-A63	M16	235,0 9.252	193,0 7.598	192,41 7.575	24,0 0.945	20,0 0.787	30,0 1.181	53,18 2.094	37,0 1.457	267,0 10.512	2,75	1	9000	1	PB	3,5 7.720
E9304K82116160	02904474	HSK-A63	M16	160,0 6.299	134,0 5.276	131,0 5.157	–	22,0 0.866	30,0 1.181	–	30,5 1.201	192,0 7.559	–	2	9000	1	PB	1,4 3.090
HSKA63-M20-160-K	03308049	HSK-A63	M20	160,0 6.299	134,0 5.276	131,0 5.157	–	31,0 1.220	36,5 1.437	–	37,0 1.457	192,0 7.559	–	2	9000	1	PB	2,1 4.630
E9306K82012235	02904477	HSK-A100	M12	235,0 9.252	206,0 8.110	201,24 7.923	24,0 0.945	20,0 0.787	23,0 0.906	47,48 1.869	30,0 1.181	285,0 11.220	2,75	1	6000	1	PB	4,0 8.820
E9306K82016235	02904479	HSK-A100	M16	235,0 9.252	206,0 8.110	201,24 7.923	24,0 0.945	20,0 0.787	30,0 1.181	54,48 2.145	37,0 1.457	285,0 11.220	2,75	1	8000	1	PB	4,78 10.540
E9306K82016285	02904480	HSK-A100	M16	285,0 11.220	256,0 10.079	251,24 9.891	24,0 0.945	20,0 0.787	30,0 1.181	59,29 2.334	37,0 1.457	335,0 13.189	2,75	1	9000	1	PB	5,86 12.920
E9306K82116185	02904478	HSK-A100	M16	185,0 7.283	156,0 6.142	151,0 5.945	–	22,0 0.866	30,0 1.181	–	30,5 1.201	235,0 9.252	–	2	8000	1	PB	2,91 6.420
E9306K82020285	03029803	HSK-A100	M20	285,0 11.220	256,0 10.079	251,24 9.891	29,0 1.142	24,5 0.965	36,5 1.437	66,81 2.630	45,0 1.772	335,0 13.189	2,75	1	6000	1	PB	7,2 15.870
HSKA100-M20-185-K	03308052	HSK-A100	M20	185,0 7.283	156,0 6.142	151,0 5.945	–	31,0 1.220	36,5 1.437	–	37,0 1.457	235,0 9.252	–	2	9000	1	PB	3,9 8.600

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Grafix

Seco Capto™

Others

Operating &
setting acces-
sories


Shrinkfit

HSK-A to Combimaster – Metric/ Inch


HSK-A/ ISO12164-1-HSK-A



Design 1



Design 2



–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

	Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balancing	Weight
					mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
BT JIS	E930458200660	02643801	HSK-A63	M6	60,0 2.362	34,0 1.339	25,0 0.984	10,0 0.394	11,0 0.433	14,5 0.571	11,7 0.461	92,0 3.622	5,3	1	1	G6.3	0,7 1.540
	E930458200860	02438495	HSK-A63	M8	60,0 2.362	34,0 1.339	25,0 0.984	10,0 0.394	13,5 0.531	18,5 0.728	15,7 0.618	92,0 3.622	5,3	1	1	G6.3	0,7 1.540
CAT	E930458200885	02438497	HSK-A63	M8	85,0 3.346	59,0 2.323	50,0 1.969	15,0 0.591	13,5 0.531	20,0 0.787	15,7 0.618	117,0 4.606	3,5	1	1	G6.3	0,8 1.760
	E930458201060	02444885	HSK-A63	M10	60,0 2.362	34,0 1.339	25,0 0.984	10,0 0.394	18,5 0.728	23,0 0.906	19,7 0.776	92,0 3.622	6,3	1	1	G6.3	0,8 1.760
	E930458201085	02444889	HSK-A63	M10	85,0 3.346	59,0 2.323	50,0 1.969	15,0 0.591	18,5 0.728	24,5 0.965	19,7 0.776	117,0 4.606	3,9	1	1	G6.3	0,8 1.760
Combimaster	E9304582010135	02438500	HSK-A63	M10	135,0 5.315	109,0 4.291	100,0 3.937	20,0 0.787	18,5 0.728	27,5 1.083	19,7 0.776	167,0 6.575	2,8	1	1	G6.3	1,0 2.200
	E930458211060	02444948	HSK-A63	M10	60,0 2.362	34,0 1.339	25,0 0.984	10,0 0.394	18,5 0.728	–	18,5 0.728	92,0 3.622	–	2	1	G6.3	0,7 1.540
	E930458201260	02444905	HSK-A63	M12	60,0 2.362	34,0 1.339	25,0 0.984	10,0 0.394	23,0 0.906	28,5 1.122	24,7 0.972	92,0 3.622	7,2	1	1	G6.3	0,8 1.760
Graflex	E930458201285	02444907	HSK-A63	M12	85,0 3.346	59,0 2.323	50,0 1.969	20,0 0.787	23,0 0.906	30,0 1.181	24,7 0.972	117,0 4.606	5,0	1	1	G6.3	0,9 1.980
	E9304582012110	02444894	HSK-A63	M12	110,0 4.331	84,0 3.307	75,0 2.953	25,0 0.984	23,0 0.906	31,5 1.240	24,7 0.972	142,0 5.591	3,9	1	1	G6.3	1,0 2.200
	E9304582012135	02444903	HSK-A63	M12	135,0 5.315	109,0 4.291	100,0 3.937	30,0 1.181	23,0 0.906	33,0 1.299	24,7 0.972	167,0 6.575	3,4	1	1	G6.3	1,2 2.650
Seco Capto™	E930458211260	02444950	HSK-A63	M12	60,0 2.362	34,0 1.339	25,0 0.984	10,0 0.394	23,0 0.906	–	23,5 0.925	92,0 3.622	–	2	1	G6.3	0,8 1.760
	E930458211285	02444953	HSK-A63	M12	85,0 3.346	59,0 2.323	50,0 1.969	20,0 0.787	23,0 0.906	–	23,5 0.925	117,0 4.606	–	2	1	G6.3	0,9 1.980
	E930458201660	02444942	HSK-A63	M16	60,0 2.362	34,0 1.339	25,0 0.984	10,0 0.394	30,0 1.181	35,5 1.398	31,7 1.248	92,0 3.622	6,9	1	1	G6.3	0,9 1.980
Others	E930458201685	02444944	HSK-A63	M16	85,0 3.346	59,0 2.323	50,0 1.969	20,0 0.787	30,0 1.181	37,0 1.457	31,7 1.248	117,0 4.606	5,0	1	1	G6.3	1,0 2.200
	E9304582016110	02444908	HSK-A63	M16	110,0 4.331	84,0 3.307	75,0 2.953	25,0 0.984	30,0 1.181	38,5 1.516	31,7 1.248	142,0 5.591	3,9	1	1	G6.3	1,2 2.650
	E9304582016135	02444910	HSK-A63	M16	135,0 5.315	109,0 4.291	100,0 3.937	30,0 1.181	30,0 1.181	40,0 1.575	31,7 1.248	167,0 6.575	3,4	1	1	G6.3	1,4 3.090
Operating & setting accessories	E9304582016185	02444912	HSK-A63	M16	185,0 7.283	159,0 6.260	150,0 5.906	35,0 1.378	30,0 1.181	50,0 1.969	31,7 1.248	217,0 8.543	4,5	1	1	G6.3	2,1 4.630
	E930458211685	02438506	HSK-A63	M16	85,0 3.346	59,0 2.323	50,0 1.969	20,0 0.787	30,0 1.181	–	30,5 1.201	117,0 4.606	–	2	1	G6.3	1,0 2.200
	E9304582116110	02438507	HSK-A63	M16	110,0 4.331	84,0 3.307	77,0 3.031	25,0 0.984	30,0 1.181	–	30,5 1.201	142,0 5.591	–	2	1	G6.3	1,1 2.430
Shrinkfit	E9304582116135	02438508	HSK-A63	M16	135,0 5.315	109,0 4.291	100,0 3.937	30,0 1.181	30,0 1.181	–	30,5 1.201	167,0 6.575	–	2	1	G6.3	1,2 2.650
	E930458202065	02971293	HSK-A63	M20	65,0 2.559	39,0 1.535	30,0 1.181	10,0 0.394	36,5 1.437	44,5 1.752	37,5 1.476	97,0 3.819	6,4	1	1	G6.3	1,0 2.200
	E9304582120110	02971294	HSK-A63	M20	110,0 4.331	84,0 3.307	75,0 2.953	25,0 0.984	36,5 1.437	–	37,0 1.457	142,0 5.591	–	2	1	G6.3	1,2 2.650

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
HSKA63-M20-085	03308047	HSK-A63	M20	85,0 3.346	59,0 2.323	50,0 1.969	20,0 0.787	36,5 1.437	–	37,0 1.457	117,0 4.606	–	2	1	PB	1,1 2.430
HSKA63-M20-135	03308048	HSK-A63	M20	135,0 5.315	109,0 4.291	100,0 3.937	30,0 1.181	36,5 1.437	–	37,0 1.457	167,0 6.575	–	2	1	G6.3	1,4 3.090
HSKA63-M20-185	03308050	HSK-A63	M20	185,0 7.283	159,0 6.260	150,0 5.906	35,0 1.378	36,5 1.437	–	37,0 1.457	217,0 8.543	–	2	1	G6.3	1,8 3.970
E930658201085	02445323	HSK-A100	M10	85,0 3.346	56,0 2.205	50,0 1.969	15,0 0.591	18,5 0.728	27,0 1.063	19,7 0.776	135,0 5.315	7,6	1	1	G6.3	2,2 4.850
E930658201285	02445356	HSK-A100	M12	85,0 3.346	56,0 2.205	50,0 1.969	20,0 0.787	23,0 0.906	35,0 1.378	24,7 0.972	135,0 5.315	9,7	1	1	G6.3	2,3 5.070
E9306582012110	02445326	HSK-A100	M12	110,0 4.331	81,0 3.189	75,0 2.953	25,0 0.984	23,0 0.906	38,0 1.496	24,7 0.972	160,0 6.299	7,6	1	1	G6.3	2,4 5.290
E9306582012135	02445329	HSK-A100	M12	135,0 5.315	106,0 4.173	100,0 3.937	30,0 1.181	23,0 0.906	41,0 1.614	24,7 0.972	185,0 7.283	6,6	1	1	G6.3	2,6 5.730
E9306582012185	02445333	HSK-A100	M12	185,0 7.283	156,0 6.142	150,0 5.906	30,0 1.181	23,0 0.906	42,5 1.673	24,7 0.972	235,0 9.252	4,2	1	1	G6.3	2,9 6.390
E930658201685	02445390	HSK-A100	M16	85,0 3.346	56,0 2.205	50,0 1.969	20,0 0.787	30,0 1.181	42,5 1.673	31,7 1.248	135,0 5.315	10,2	1	1	G6.3	2,4 5.290
E9306582016135	02445366	HSK-A100	M16	135,0 5.315	106,0 4.173	100,0 3.937	30,0 1.181	30,0 1.181	49,0 1.929	31,7 1.248	185,0 7.283	7,0	1	1	G6.3	2,9 6.390
E9306582016185	02445388	HSK-A100	M16	185,0 7.283	156,0 6.142	150,0 5.906	35,0 1.378	30,0 1.181	50,0 1.969	31,7 1.248	235,0 9.252	4,5	1	1	G6.3	3,4 7.500
E9306582016235	02445389	HSK-A100	M16	235,0 9.252	206,0 8.110	200,0 7.874	35,0 1.378	30,0 1.181	55,0 2.165	31,7 1.248	285,0 11.220	4,0	1	1	G6.3	4,1 9.040
E9306582020135	02928179	HSK-A100	M20	135,0 5.315	106,0 4.173	100,0 3.937	30,0 1.181	36,5 1.437	54,5 2.146	37,5 1.476	185,0 7.283	6,9	1	1	G6.3	3,1 6.830
HSKA100-M20-085	03308051	HSK-A100	M20	85,0 3.346	56,0 2.205	50,0 1.969	20,0 0.787	36,5 1.437	–	37,0 1.457	135,0 5.315	–	2	1	G6.3	2,4 5.290
HSKA125-M16-085	03229655	HSK-A125	M16	85,0 3.346	56,0 2.205	35,0 1.378	20,0 0.787	30,0 1.181	–	30,5 1.201	148,0 5.827	–	2	1	PB	3,6 7.940
HSKA125-M16-135	03229656	HSK-A125	M16	135,0 5.315	106,0 4.173	85,0 3.346	35,0 1.378	30,0 1.181	–	30,5 1.201	198,0 7.795	–	2	1	PB	3,9 8.600
HSKA125-M16-185-VF6	03240292	HSK-A125	M16	185,0 7.283	156,0 6.142	150,0 5.906	60,0 2.362	30,0 1.181	54,9 2.161	30,0 1.181	248,0 9.764	7,88	1	1	PB	4,6 10.140
HSKA125-M20-075	03229659	HSK-A125	M20	75,0 2.953	46,0 1.811	30,0 1.181	10,0 0.394	36,5 1.437	–	37,0 1.457	138,0 5.433	–	2	1	PB	3,7 8.160
HSKA125-M20-135	03229660	HSK-A125	M20	135,0 5.315	106,0 4.173	90,0 3.543	30,0 1.181	36,5 1.437	–	37,0 1.457	198,0 7.795	–	2	1	PB	4,1 9.040
HSKA125-M20-185-VF6	03240293	HSK-A125	M20	185,0 7.283	156,0 6.142	150,0 5.906	73,0 2.874	36,5 1.437	62,9 2.476	36,5 1.437	248,0 9.764	9,73	1	1	PB	5,0 11.020

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

Steadyline®, vibration damping
– Metric/ Inch


DIN 69871-ADB



Design 1



Design 2



—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	Max. RPM	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
E3469K82116160	02904486	DIN40 ADB	M16	160,0 6.299	140,9 5.547	137,9 5.429	22,0 0.866	30,0 1.181	—	30,5 1.201	228,4 8.992	—	2	9000	1	PB	1,7 3.750
E3471K82116185	02904490	DIN50 ADB	M16	185,0 7.283	165,9 6.531	160,9 6.335	22,0 0.866	30,0 1.181	—	30,5 1.201	286,75 11.289	—	2	8000	1	PB	3,5 7.720

Spare Parts, included in delivery

For	Sealing Screws
DIN40	950A0406
DIN50	950A0606




DIN 69871 to Combimaster
– Metric/ Inch


DIN 69871-ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
DIN40ADB-M20-060-V	03308039	DIN40 ADB	M20	60,0 2.362	40,9 1.610	25,0 0.984	10,0 0.394	36,5 1.437	44,0 1.732	37,0 1.457	128,4 5.055	12,23	1	1	G6.3	1,2 2.650
E346958212085	02971302	DIN40 ADB	M20	85,0 3.346	65,9 2.594	60,0 2.362	20,0 0.787	36,5 1.437	–	37,0 1.457	153,4 6.039	–	2	1	G6.3	1,2 2.650
DIN40ADB-M20-110	03308040	DIN40 ADB	M20	110,0 4.331	90,9 3.579	75,0 2.953	25,0 0.984	36,5 1.437	–	37,0 1.457	178,4 7.024	–	2	1	G6.3	1,4 3.090
DIN40ADB-M20-135	03308041	DIN40 ADB	M20	135,0 5.315	115,9 4.563	100,0 3.937	30,0 1.181	36,5 1.437	–	37,0 1.457	203,4 8.008	–	2	1	G6.3	1,6 3.530
DIN40ADB-M20-185	03308043	DIN40 ADB	M20	185,0 7.283	165,9 6.531	150,0 5.906	35,0 1.378	36,5 1.437	–	37,0 1.457	253,4 9.976	–	2	1	G6.3	2,0 4.410
E347158202095	02971303	DIN50 ADB	M20	95,0 3.740	75,9 2.988	65,0 2.559	25,0 0.984	36,5 1.437	50,5 1.988	37,5 1.476	196,75 7.746	9,3	1	1	G6.3	3,3 7.280
DIN50ADB-M20-145	03308044	DIN50 ADB	M20	145,0 5.709	125,9 4.957	100,0 3.937	30,0 1.181	36,5 1.437	–	37,0 1.457	246,75 9.715	–	2	1	G6.3	3,4 7.500
DIN50ADB-M20-295-V	03308046	DIN50 ADB	M20	295,0 11.614	275,9 10.862	250,0 9.843	35,0 1.378	36,5 1.437	68,0 2.677	37,0 1.457	396,75 15.620	4,06	1	1	G6.3	7,2 15.870

Spare Parts, included in delivery

For	Sealing Screws
	
DIN40	950A0406
DIN50	950A0606

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit

DIN/CAT (Combined) to Combimaster – Metric/ Inch

DIN/CAT (Combined)

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories


Shrinkfit



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E347658200660	02628844	DIN40 ADB/ CAT40	M6	60,0 2.362	41,0 1.614	25,0 0.984	10,0 0.394	11,0 0.433	14,5 0.571	11,7 0.461	128,4 5.055	5,3	1	1	G6.3	1,0 2.200
E347658200860	02438484	DIN40 ADB/ CAT40	M8	60,0 2.362	41,0 1.614	25,0 0.984	10,0 0.394	13,5 0.531	18,5 0.728	15,7 0.618	128,4 5.055	5,3	1	1	G6.3	1,0 2.200
E347658201040	02444577	DIN40 ADB/ CAT40	M10	40,0 1.575	21,0 0.827	5,0 0.197	5,0 0.197	18,5 0.728	–	19,7 0.776	108,4 4.268	6,8	1	1	G6.3	1,0 2.200
E347658201060	02444588	DIN40 ADB/ CAT40	M10	60,0 2.362	41,0 1.614	25,0 0.984	10,0 0.394	18,5 0.728	23,0 0.906	19,7 0.776	128,4 5.055	6,3	1	1	G6.3	1,1 2.430
E347658201085	02444594	DIN40 ADB/ CAT40	M10	85,0 3.346	66,0 2.598	50,0 1.969	15,0 0.591	18,5 0.728	24,5 0.965	19,7 0.776	153,4 6.039	3,9	1	1	G6.3	1,1 2.430
E3476582010135	02438487	DIN40 ADB/ CAT40	M10	135,0 5.315	116,0 4.567	100,0 3.937	20,0 0.787	18,5 0.728	27,5 1.083	19,7 0.776	203,4 8.008	2,8	1	1	G6.3	1,3 2.870
E347658211060	02444670	DIN40 ADB/ CAT40	M10	60,0 2.362	41,0 1.614	25,0 0.984	10,0 0.394	18,5 0.728	–	18,5 0.728	128,4 5.055	–	2	1	G6.3	1,0 2.200
E347658201240	02444621	DIN40 ADB/ CAT40	M12	40,0 1.575	21,0 0.827	5,0 0.197	5,0 0.197	23,0 0.906	24,7 0.972	24,7 0.972	108,4 4.268	9,6	1	1	G6.3	1,0 2.200
E347658201260	02444623	DIN40 ADB/ CAT40	M12	60,0 2.362	41,0 1.614	25,0 0.984	10,0 0.394	23,0 0.906	28,5 1.122	24,7 0.972	128,4 5.055	7,2	1	1	G6.3	1,1 2.430
E347658201285	02444637	DIN40 ADB/ CAT40	M12	85,0 3.346	66,0 2.598	50,0 1.969	20,0 0.787	23,0 0.906	30,0 1.181	24,7 0.972	153,4 6.039	5,0	1	1	G6.3	1,2 2.650
E3476582012110	02444600	DIN40 ADB/ CAT40	M12	110,0 4.331	91,0 3.583	75,0 2.953	25,0 0.984	23,0 0.906	31,5 1.240	24,7 0.972	178,4 7.024	3,9	1	1	G6.3	1,3 2.870
E3476582012185	02438489	DIN40 ADB/ CAT40	M12	185,0 7.283	166,0 6.535	150,0 5.906	30,0 1.181	23,0 0.906	42,5 1.673	24,7 0.972	253,4 9.976	4,2	1	1	G6.3	1,8 3.970
E347658211260	02444672	DIN40 ADB/ CAT40	M12	60,0 2.362	41,0 1.614	25,0 0.984	10,0 0.394	23,0 0.906	–	23,5 0.925	128,4 5.055	–	2	1	G6.3	1,1 2.430
E347658211285	02444673	DIN40 ADB/ CAT40	M12	85,0 3.346	66,0 2.598	50,0 1.969	20,0 0.787	23,0 0.906	–	23,5 0.925	153,4 6.039	–	2	1	G6.3	1,1 2.430
E347658201640	02444659	DIN40 ADB/ CAT40	M16	40,0 1.575	21,0 0.827	5,0 0.197	5,0 0.197	30,0 1.181	31,8 1.252	31,8 1.252	108,4 4.268	9,6	1	1	G6.3	1,0 2.200
E347658201660	02444662	DIN40 ADB/ CAT40	M16	60,0 2.362	41,0 1.614	25,0 0.984	10,0 0.394	30,0 1.181	35,5 1.398	31,7 1.248	128,4 5.055	7,2	1	1	G6.3	1,1 2.430
E347658201685	02444664	DIN40 ADB/ CAT40	M16	85,0 3.346	66,0 2.598	50,0 1.969	20,0 0.787	30,0 1.181	37,0 1.457	31,7 1.248	153,4 6.039	5,0	1	1	G6.3	1,3 2.870

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E3476582016110	02444650	DIN40 ADB/ CAT40	M16	110,0 4.331	91,0 3.583	75,0 2.953	25,0 0.984	30,0 1.181	38,5 1.516	31,7 1.248	178,4 7.024	3,9	1	1	G6.3	1,5 3.310
E3476582016135	02444652	DIN40 ADB/ CAT40	M16	135,0 5.315	116,0 4.567	100,0 3.937	30,0 1.181	30,0 1.181	40,5 1.594	31,7 1.248	203,4 8.008	3,6	1	1	G6.3	1,7 3.750
E3476582016185	02444656	DIN40 ADB/ CAT40	M16	185,0 7.283	166,0 6.535	150,0 5.906	35,0 1.378	30,0 1.181	43,5 1.713	31,7 1.248	253,4 9.976	2,9	1	1	G6.3	2,1 4.630
E347658211685	02438490	DIN40 ADB/ CAT40	M16	85,0 3.346	66,0 2.598	50,0 1.969	20,0 0.787	30,0 1.181	30,5 1.201	153,4 6.039	—	—	2	1	G6.3	1,2 2.650
E3476582116110	02438491	DIN40 ADB/ CAT40	M16	110,0 4.331	91,0 3.583	75,0 2.953	25,0 0.984	30,0 1.181	—	30,5 1.201	178,4 7.024	—	2	1	G6.3	1,4 3.090
E3476582116135	02438492	DIN40 ADB/ CAT40	M16	135,0 5.315	116,0 4.567	100,0 3.937	30,0 1.181	30,0 1.181	—	30,5 1.201	203,4 8.008	—	2	1	G6.3	1,5 3.310
E347858201295	02444754	DIN50 ADB/ CAT50	M12	95,0 3.740	76,0 2.992	50,0 1.969	20,0 0.787	23,0 0.906	35,0 1.378	24,7 0.972	196,7 7.744	9,7	1	1	G6.3	3,3 7.280
E3478582012145	02444725	DIN50 ADB/ CAT50	M12	145,0 5.709	126,0 4.961	100,0 3.937	30,0 1.181	23,0 0.906	41,0 1.614	24,7 0.972	246,7 9.713	6,6	1	1	G6.3	3,6 7.940
E3478582012195	02444726	DIN50 ADB/ CAT50	M12	195,0 7.677	176,0 6.929	150,0 5.906	30,0 1.181	23,0 0.906	42,5 1.673	24,7 0.972	296,7 11.681	4,2	1	1	G6.3	3,9 8.600
E3478582012245	02444732	DIN50 ADB/ CAT50	M12	245,0 9.646	226,0 8.898	200,0 7.874	30,0 1.181	23,0 0.906	47,5 1.870	24,7 0.972	346,7 13.650	3,8	1	1	G6.3	4,5 9.920
E347858201695	02444763	DIN50 ADB/ CAT50	M16	95,0 3.740	76,0 2.992	50,0 1.969	20,0 0.787	30,0 1.181	42,5 1.673	31,7 1.248	196,7 7.744	10,2	1	1	G6.3	3,4 7.500
E3478582016145	02444755	DIN50 ADB/ CAT50	M16	145,0 5.709	126,0 4.961	100,0 3.937	30,0 1.181	30,0 1.181	49,0 1.929	31,7 1.248	246,7 9.713	7,0	1	1	G6.3	3,9 8.600
E3478582016195	02444756	DIN50 ADB/ CAT50	M16	195,0 7.677	176,0 6.929	150,0 5.906	35,0 1.378	30,0 1.181	50,0 1.969	31,7 1.248	296,7 11.681	4,5	1	1	G6.3	4,4 9.700
E3478582016245	02444757	DIN50 ADB/ CAT50	M16	245,0 9.646	226,0 8.898	200,0 7.874	35,0 1.378	30,0 1.181	55,0 2.165	31,7 1.248	346,7 13.650	4,0	1	1	G6.3	5,1 11.240
E3478582016295	02444759	DIN50 ADB/ CAT50	M16	295,0 11.614	276,0 10.866	250,0 9.843	35,0 1.378	30,0 1.181	59,5 2.343	31,7 1.248	396,7 15.618	3,7	1	1	G6.3	5,8 12.790

Spare Parts, included in delivery

For	Sealing Screws
	
DIN40	950A0406
DIN50	950A0606

Guide

HSK-A

HSK-E

DIN

BT IIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

Steadyline®, vibration damping
– Metric/ Inch


BT JIS B 6339-ADB



Design 1



Design 2



—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB3	LB1	BD	BD2	BD1	OAL	BHTA°	Design	Max. RPM	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
E3416K82116185	02904504	BT50 ADB	M16	185,0 7.283	147,0 5.787	142,0 5.591	—	22,0 0.866	30,0 1.181	—	30,5 1.201	286,8 11.291	—	2	8000	1	PB	4,4 9.700
BT50ADB-M20-185-K	03308018	BT50 ADB	M20	185,0 7.283	147,0 5.787	142,0 5.591	—	31,0 1.220	36,5 1.437	—	37,0 1.457	286,8 11.291	—	2	9000	1	PB	5,1 11.240

Spare Parts, included in delivery

For	Sealing Screws
BT50	950A0606



Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting accessories


Shrinkfit

BT JIS to Combimaster
– Metric/ Inch


BT JIS B 6339-ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E341458200660	02643832	BT40 ADB	M6	60,0 2.362	33,0 1.299	25,0 0.984	10,0 0.394	11,0 0.433	14,5 0.571	11,7 0.461	125,4 4.937	5,3	1	1	G6.3	1,0 2.200
E341458210860	02444289	BT40 ADB	M8	60,0 2.362	33,0 1.299	25,0 0.984	10,0 0.394	13,5 0.531	–	14,5 0.571	125,4 4.937	–	2	1	G6.3	1,0 2.200
E341458201060	02444177	BT40 ADB	M10	60,0 2.362	33,0 1.299	25,0 0.984	10,0 0.394	18,5 0.728	23,0 0.906	19,7 0.776	125,4 4.937	6,3	1	1	G6.3	1,1 2.430
E341458211060	02444314	BT40 ADB	M10	60,0 2.362	33,0 1.299	25,0 0.984	10,0 0.394	18,5 0.728	–	19,7 0.776	125,4 4.937	–	2	1	G6.3	1,1 2.430
E341458201085	02444181	BT40 ADB	M10	85,0 3.346	58,0 2.283	50,0 1.969	15,0 0.591	18,5 0.728	24,5 0.965	19,7 0.776	150,4 5.921	3,9	1	1	G6.3	1,1 2.430
E3414582010135	02444160	BT40 ADB	M10	135,0 5.315	108,0 4.252	100,0 3.937	20,0 0.787	18,5 0.728	27,5 1.083	19,7 0.776	200,4 7.890	2,8	1	1	G6.3	1,3 2.870
E341458201240	02444230	BT40 ADB	M12	40,0 1.575	13,0 0.512	5,0 0.197	5,0 0.197	23,0 0.906	24,7 0.972	24,7 0.972	105,4 4.150	9,6	1	1	G6.3	1,0 2.200
E341458201260	02444239	BT40 ADB	M12	60,0 2.362	33,0 1.299	25,0 0.984	10,0 0.394	23,0 0.906	28,5 1.122	24,7 0.972	125,4 4.937	7,2	1	1	G6.3	1,1 2.430
E341458211260	02444315	BT40 ADB	M12	60,0 2.362	33,0 1.299	25,0 0.984	10,0 0.394	23,0 0.906	–	23,5 0.925	125,4 4.937	–	2	1	G6.3	1,1 2.430
E341458201285	02444242	BT40 ADB	M12	85,0 3.346	58,0 2.283	50,0 1.969	20,0 0.787	23,0 0.906	30,0 1.181	24,7 0.972	150,4 5.921	5,0	1	1	G6.3	1,2 2.650
E341458211285	02444321	BT40 ADB	M12	85,0 3.346	58,0 2.283	50,0 1.969	20,0 0.787	23,0 0.906	–	23,5 0.925	150,4 5.921	–	2	1	G6.3	1,1 2.430
E3414582012110	02444182	BT40 ADB	M12	110,0 4.331	83,0 3.268	75,0 2.953	25,0 0.984	23,0 0.906	31,5 1.240	24,7 0.972	175,4 6.906	3,9	1	1	G6.3	1,3 2.870
E3414582012135	02444183	BT40 ADB	M12	135,0 5.315	108,0 4.252	100,0 3.937	30,0 1.181	23,0 0.906	33,0 1.299	24,7 0.972	200,4 7.890	3,4	1	1	G6.3	1,4 3.090
E341458201640	02444275	BT40 ADB	M16	40,0 1.575	13,0 0.512	5,0 0.197	5,0 0.197	30,0 1.181	31,7 1.248	31,7 1.248	105,4 4.150	9,6	1	1	G6.3	1,0 2.200
E341458201660	02444280	BT40 ADB	M16	60,0 2.362	33,0 1.299	25,0 0.984	10,0 0.394	30,0 1.181	35,5 1.398	31,7 1.248	125,4 4.937	7,2	1	1	G6.3	1,2 2.650
E341458201685	02444283	BT40 ADB	M16	85,0 3.346	58,0 2.283	50,0 1.969	20,0 0.787	30,0 1.181	37,0 1.457	31,7 1.248	150,4 5.921	5,0	1	1	G6.3	1,3 2.870
E3414582016110	02444243	BT40 ADB	M16	110,0 4.331	83,0 3.268	75,0 2.953	25,0 0.984	30,0 1.181	38,5 1.516	31,7 1.248	175,4 6.906	3,9	1	1	G6.3	1,5 3.310
E3414582016135	02444252	BT40 ADB	M16	135,0 5.315	108,0 4.252	100,0 3.937	30,0 1.181	30,0 1.181	40,5 1.594	31,7 1.248	200,4 7.890	3,6	1	1	G6.3	1,7 3.750
E3414582016185	02444269	BT40 ADB	M16	185,0 7.283	158,0 6.220	150,0 5.906	35,0 1.378	30,0 1.181	50,0 1.969	31,7 1.248	250,4 9.858	4,5	1	1	G6.3	2,4 5.290
E341458212045	02971297	BT40 ADB	M20	45,0 1.772	18,0 0.709	10,0 0.394	5,0 0.197	36,5 1.437	–	37,0 1.457	110,4 4.346	–	2	1	G6.3	1,1 2.430
E341458212085	02971298	BT40 ADB	M20	85,0 3.346	58,0 2.283	50,0 1.969	20,0 0.787	36,5 1.437	–	37,0 1.457	150,4 5.921	–	2	1	G6.3	1,3 2.870
E3414582020110	02928181	BT40 ADB	M20	110,0 4.331	83,0 3.268	75,0 2.953	25,0 0.984	36,5 1.437	44,5 1.752	37,5 1.476	175,4 6.906	4,0	1	1	G6.3	1,6 3.530
BT40ADB-M20-135	03308015	BT40 ADB	M20	135,0 5.315	108,0 4.252	100,0 3.937	30,0 1.181	36,5 1.437	–	37,0 1.457	200,4 7.890	–	2	1	G6.3	1,7 3.750

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Guide	Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balan- cing	Weight
					mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
	BT40ADB-M20-185	03308017	BT40 ADB	M20	185,0 7.283	158,0 6.220	150,0 5.906	35,0 1.378	36,5 1.437	–	37,0 1.457	250,4 9.858	–	2	1	G6.3	2,1 4.630
HSK-A	E341658201295	02444349	BT50 ADB	M12	95,0 3.740	57,0 2.244	50,0 1.969	20,0 0.787	23,0 0.906	35,0 1.378	24,7 0.972	196,8 7.748	9,7	1	1	G6.3	3,8 8.380
	E3416582012145	02444323	BT50 ADB	M12	145,0 5.709	107,0 4.213	100,0 3.937	30,0 1.181	23,0 0.906	41,0 1.614	24,7 0.972	246,8 9.717	6,6	1	1	G6.3	4,1 9.040
	E3416582012195	02444326	BT50 ADB	M12	195,0 7.677	157,0 6.181	150,0 5.906	30,0 1.181	23,0 0.906	42,5 1.673	24,7 0.972	296,8 11.685	4,2	1	1	G6.3	4,4 9.700
HSK-E	E341658201695	02444382	BT50 ADB	M16	95,0 3.740	57,0 2.244	50,0 1.969	20,0 0.787	30,0 1.181	42,5 1.673	31,7 1.248	196,8 7.748	10,2	1	1	G6.3	3,9 8.600
	E3416582016145	02444378	BT50 ADB	M16	145,0 5.709	107,0 4.213	100,0 3.937	30,0 1.181	30,0 1.181	49,0 1.929	31,7 1.248	246,8 9.717	7,0	1	1	G6.3	4,4 9.700
	E3416582016195	02444380	BT50 ADB	M16	195,0 7.677	157,0 6.181	150,0 5.906	35,0 1.378	30,0 1.181	50,0 1.969	31,7 1.248	296,9 11.689	4,5	1	1	G6.3	4,8 10.580
DIN	E3416582016245	02444381	BT50 ADB	M16	245,0 9.646	207,0 8.150	200,0 7.874	35,0 1.378	30,0 1.181	55,0 2.165	31,7 1.248	346,8 13.654	4,0	1	1	G6.3	5,4 11.900
	E3416582016295	02453355	BT50 ADB	M16	295,0 11.614	257,0 10.118	250,0 9.843	35,0 1.378	30,0 1.181	59,5 2.343	31,7 1.248	396,8 15.622	3,7	1	1	G6.3	6,3 13.890
	E341658202095	02928182	BT50 ADB	M20	95,0 3.740	57,0 2.244	50,0 1.969	20,0 0.787	36,5 1.437	48,5 1.909	37,5 1.476	196,8 7.748	10,4	1	1	G6.3	4,0 8.820
BT JIS	BT50ADB-M20-145	03308019	BT50 ADB	M20	145,0 5.709	107,0 4.213	100,0 3.937	30,0 1.181	36,5 1.437	–	37,0 1.457	246,8 9.717	–	2	1	G6.3	4,3 9.480
	BT50ADB-M20-295-V	03308020	BT50 ADB	M20	295,0 11.614	257,0 10.118	249,0 9.803	35,0 1.378	36,5 1.437	68,0 2.677	37,0 1.457	396,8 15.622	4,8	1	1	G6.3	7,8 17.200

Spare Parts, included in delivery

CAT	For	Sealing Screws
		
Combimaster	BT40	950A0406
	BT50	950A0606

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories


Shrinkfit

BT Taper Face to Combimaster – Metric/ Inch


BT Taper-Face-AD/ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD2	BD1	BD	OAL	BHTA°	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E400258201060	02998769	BT30 TF AD	M10	60,0 2.362	38,0 1.496	35,0 1.378	15,0 0.591	23,5 0.925	19,7 0.776	18,5 0.728	108,4 4.268	5,4	1	0	G2.5	0,5 1.100
E400258201260	02998770	BT30 TF AD	M12	60,0 2.362	38,0 1.496	25,0 0.984	10,0 0.394	28,5 1.122	24,7 0.972	23,0 0.906	108,4 4.268	7,2	1	0	G2.5	0,6 1.320
E400258201660	02998771	BT30 TF AD	M16	60,0 2.362	38,0 1.496	25,0 0.984	10,0 0.394	35,5 1.398	31,7 1.248	30,0 1.181	108,4 4.268	7,2	1	0	G2.5	0,6 1.320
E321458201660	02926030	BT40 TF ADB	M16	60,0 2.362	33,0 1.299	25,0 0.984	10,0 0.394	35,5 1.398	31,7 1.248	30,0 1.181	125,4 4.937	7,2	2	1	G6.3	1,2 2.650
E3214582016135	02926031	BT40 TF ADB	M16	135,0 5.315	108,0 4.252	100,0 3.937	30,0 1.181	40,5 1.594	31,7 1.248	30,0 1.181	200,4 7.890	3,6	2	1	G6.3	1,7 3.750
E321658201695	02926040	BT50 TF ADB	M16	95,0 3.740	57,0 2.244	50,0 1.969	20,0 0.787	42,5 1.673	31,7 1.248	30,0 1.181	196,8 7.748	10,2	2	1	G6.3	4,0 8.820
E3216582016195	02926041	BT50 TF ADB	M16	195,0 7.677	157,0 6.181	150,0 5.906	35,0 1.378	50,0 1.969	31,7 1.248	30,0 1.181	296,8 11.685	4,5	2	1	G6.3	4,8 10.580

Spare Parts, included in delivery

For	Sealing Screws
	
BT30	–
BT40	950A0406
BT50	950A0606

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

CAT to Combimaster
– Metric/ Inch


CAT / ASME B5.50-1994-ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
E250258200860	02870633	CAT40 ADB	M8	60,0 2.362	40,95 1.612	25,0 0.984	10,0 0.394	13,5 0.531	18,5 0.728	15,7 0.618	128,4 5.055	5,3	1	1	G6.3	1,0 2.200
E250258201040	02870634	CAT40 ADB	M10	40,0 1.575	20,95 0.825	5,0 0.197	5,0 0.197	18,5 0.728	19,7 0.776	19,7 0.776	108,4 4.268	6,8	1	1	G6.3	1,0 2.200
E250258201085	02870507	CAT40 ADB	M10	85,0 3.346	65,95 2.596	50,0 1.969	15,0 0.591	18,5 0.728	24,5 0.965	19,7 0.776	153,4 6.039	3,9	1	1	G6.3	1,1 2.430
E250258201240	02870635	CAT40 ADB	M12	40,0 1.575	20,95 0.825	5,0 0.197	5,0 0.197	23,0 0.906	25,7 1.012	25,7 1.012	108,4 4.268	9,6	1	1	G6.3	1,0 2.200
E250258211285	02870509	CAT40 ADB	M12	85,0 3.346	65,95 2.596	50,0 1.969	20,0 0.787	23,0 0.906	–	23,5 0.925	153,4 6.039	–	2	1	G6.3	1,1 2.430
E250258201640	02870636	CAT40 ADB	M16	40,0 1.575	20,95 0.825	5,0 0.197	5,0 0.197	30,0 1.181	32,7 1.287	32,7 1.287	108,4 4.268	9,6	1	1	G6.3	1,0 2.200
E250258211685	02870511	CAT40 ADB	M16	85,0 3.346	65,95 2.596	50,0 1.969	20,0 0.787	30,0 1.181	–	30,5 1.201	153,4 6.039	–	2	1	G6.3	1,2 2.650
E2502582116135	02870512	CAT40 ADB	M16	135,0 5.315	115,95 4.565	100,0 3.937	30,0 1.181	30,0 1.181	–	–	203,4 8.008	–	2	1	G6.3	1,5 3.310
E250458201295	02870639	CAT50 ADB	M12	95,0 3.740	75,95 2.990	60,0 2.362	25,0 0.984	23,0 0.906	30,5 1.201	24,7 0.972	196,75 7.746	4,7	1	1	G6.3	3,2 7.050
E2504582012145	02870640	CAT50 ADB	M12	145,0 5.709	125,95 4.959	110,0 4.331	30,0 1.181	23,0 0.906	38,5 1.516	24,7 0.972	246,75 9.715	4,9	1	1	G6.3	3,5 7.720
E250458201695	02870641	CAT50 ADB	M16	95,0 3.740	75,95 2.990	50,0 1.969	20,0 0.787	30,0 1.181	42,5 1.673	31,7 1.248	196,75 7.746	10,2	1	1	G6.3	3,4 7.500
E2504582016145	02870642	CAT50 ADB	M16	145,0 5.709	125,95 4.959	100,0 3.937	30,0 1.181	30,0 1.181	49,0 1.929	31,7 1.248	246,75 9.715	7,0	1	1	G6.3	3,9 8.600
E2504582016195	02870643	CAT50 ADB	M16	195,0 7.677	175,95 6.927	150,0 5.906	35,0 1.378	30,0 1.181	50,0 1.969	31,7 1.248	296,75 11.683	4,55	1	1	G6.3	4,4 9.700
CAT50ADB-M20-3.740	03308033	CAT50 ADB	M20	95,0 3.740	75,89 2.988	50,0 1.969	20,0 0.787	36,5 1.437	–	37,0 1.457	196,75 7.746	–	2	1	G6.3	3,4 7.500
CAT50ADB-M20-5.709	03308034	CAT50 ADB	M20	145,0 5.709	125,9 4.957	100,0 3.937	30,0 1.181	36,5 1.437	–	37,0 1.457	246,5 9.705	–	2	1	G6.3	3,8 8.380

Spare Parts, included in delivery

For	Sealing Screws
CAT40	950A0406
CAT50	950A0606




CAT to Combimaster
– Inch


CAT / ASME B5.50-2009-ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balancing	Weight
				inch	inch	inch	inch	inch	inch	inch	inch					lbs
E260258202040	03029742	CAT40 ADB	M20	1.575	0.823	0.783	0.197	1.437	1.476	1.476	4.268	5,7	1	1	G6.3	1.980
E260258212085	03029743	CAT40 ADB	M20	3.346	2.594	2.437	0.787	1.437	–	1.457	6.039	–	2	1	G6.3	2.870
E2602582120135	03029746	CAT40 ADB	M20	5.315	4.563	4.445	0.787	1.437	–	1.457	8.008	–	2	1	G6.3	3.530
E260458202095	03029757	CAT50 ADB	M20	3.740	2.988	1.969	0.787	1.437	1.909	1.476	7.748	6,9	1	1	G6.3	7.280
E2604582020145	03029758	CAT50 ADB	M20	5.709	4.957	3.937	1.181	1.437	2.146	1.476	9.717	4,1	1	1	G6.3	8.600
E2604582020195	03029759	CAT50 ADB	M20	7.677	6.925	5.906	0.787	1.437	2.205	1.476	11.685	10,4	1	1	G6.3	10.140

Spare Parts, included in delivery

For	Sealing Screws
	
CAT40	950A0406
CAT50	950A0606

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories


Shrinkfit

Steadyline®, vibration damping
– Inch


CAT TF / ASME B5.50-2009-ADB



Design 1



Design 2



—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	LB3	BD	BD2	BD1	OAL	BHTA°	Design	Max. RPM	RFID hole	Balancing	Weight
				inch	inch	inch	inch	inch	inch	inch	inch	inch						lbs
E2644K82116185	02998768	CAT50 TF ADB	M16	7.283	6.531	6.335	0.866	—	1.181	—	1.201	11.289	—	2	8000	1	PB	7.940

Spare Parts, included in delivery

For	Sealing Screws
	
E2644K82116185	950A0606

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

CAT Taper Face to Combimaster
– Metric/ Inch

CAT TF / ASME B5.50-2009-ADB



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD1	OAL	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
CAT40TFADB-M16-5.315	03308028	CAT40 TF ADB	M16	135,0 5.315	115,9 4.563	100,0 3.937	30,0 1.181	30,0 1.181	30,5 1.201	203,4 8.008	1	G6.3	1,4 3.090
CAT40TFADB-M20-1.772	03308029	CAT40 TF ADB	M20	45,0 1.772	25,9 1.020	10,0 0.394	5,0 0.197	36,5 1.437	37,0 1.457	113,4 4.465	1	G6.3	1,0 2.200
CAT40TFADB-M20-3.346	03308030	CAT40 TF ADB	M20	85,0 3.346	65,9 2.594	50,0 1.969	20,0 0.787	36,5 1.437	37,0 1.457	153,4 6.039	1	G6.3	1,3 2.870
CAT40TFADB-M20-5.315	03308031	CAT40 TF ADB	M20	135,0 5.315	115,9 4.563	100,0 3.937	30,0 1.181	36,5 1.437	37,0 1.457	203,4 8.008	1	G6.3	1,7 3.750
CAT50TFADB-M16-5.709	03308035	CAT50 TF ADB	M16	145,0 5.709	125,9 4.957	100,0 3.937	30,0 1.181	30,0 1.181	30,5 1.201	246,75 9.715	1	G6.3	3,4 7.500
CAT50TFADB-M20-3.740	03308036	CAT50 TF ADB	M20	95,0 3.740	75,9 2.988	60,0 2.362	25,0 0.984	36,5 1.437	37,0 1.457	196,75 7.746	1	G6.3	3,1 6.830
CAT50TFADB-M20-5.709	03308037	CAT50 TF ADB	M20	145,0 5.709	125,9 4.957	100,0 3.937	30,0 1.181	36,5 1.437	37,0 1.457	246,75 9.715	1	G6.3	3,5 7.720

Spare Parts, included in delivery

For	Sealing Screws
	
CAT40	950A0406
CAT50	950A0606

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

CAT Taper Face to Combimaster – Inch


CAT TF / ASME B5.50-2009-ADB



Design 1



Design 2



—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balan- cing	Weight
				inch	inch	inch	inch	inch	inch	inch	inch					lbs
E264258201685	02998760	CAT40 TF ADB	M16	3.346	2.596	1.969	0.787	1.181	1.457	1.248	6.039	5,0	1	1	G6.3	2.870
E264258211685	02998761	CAT40 TF ADB	M16	3.346	2.596	2.400	0.984	1.181	—	1.201	6.039	—	2	1	G6.3	2.650
E264458201695	02926852	CAT50 TF ADB	M16	3.740	2.990	2.362	0.984	1.181	1.732	1.248	7.748	10,0	1	1	G6.3	7.050

Spare Parts, included in delivery

For	Sealing Screws
CAT40	950A0406
CAT50	950A0606




Steadyline®, vibration damping
– Metric/ Inch


Seco Capto™



Design 1



Design 2



– With through coolant
– For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB3	LB1	BD	BD1	BD2	OAL	BHTA°	Design	Max. RPM	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
C6-391.K820-12185	02904481	C6	M12	185,0 7.283	160,0 6.299	157,14 6.187	24,0 0.945	20,0 0.787	23,0 0.906	30,0 1.181	43,07 1.696	223,0 8.780	2,75	1	9000	1	PB	2,1 4.630
C6-391.K820-16185	02904483	C6	M16	185,0 7.283	160,0 6.299	157,14 6.187	24,0 0.945	20,0 0.787	30,0 1.181	37,0 1.457	50,07 1.971	223,0 8.780	2,75	1	9000	1	PB	2,8 6.170
C6-391.K820-16235	02904484	C6	M16	235,0 9.252	210,0 8.268	207,14 8.155	24,0 0.945	20,0 0.787	30,0 1.181	37,0 1.457	54,87 2.160	273,0 10.748	2,75	1	8000	1	PB	3,6 7.940
C6-391.K821-16160	02904482	C6	M16	160,0 6.299	135,0 5.315	132,0 5.197	–	22,0 0.866	30,0 1.181	30,5 1.201	–	198,0 7.795	–	2	9000	1	PB	0,7 1.540
C6-391.K820-20185	03029792	C6	M20	185,0 7.283	160,0 6.299	158,1 6.224	29,0 1.142	24,5 0.965	36,5 1.437	45,0 1.772	57,58 2.267	223,0 8.780	2,75	1	8000	1	PB	3,6 7.940
C6-391.K820-20235	03029793	C6	M20	235,0 9.252	210,0 8.268	209,63 8.253	29,0 1.142	24,5 0.965	36,5 1.437	45,0 1.772	62,39 2.456	273,0 10.748	2,75	1	6000	1	PB	4,6 10.140

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

Seco Capto™ to Combimaster – Metric/ Inch


Seco Capto™



Design 1



Design 2



—For ISO attribute explanation, see page 15

	Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD1	BD2	OAL	BHTA°	Design	RFID hole	Balancing	Weight	
																	kg	lbs
BT JIS	C4-391.5820-08030	02532914	C4	M8	30,0 1.181	7,0 0.276	5,0 0.197	5,0 0.197	13,5 0.531	15,7 0.618	—	54,0 2.126	—	2	0	G6.3	0,3 0.660	0,3 0.660
	C4-391.5820-10035	02532915	C4	M10	35,0 1.378	12,0 0.472	10,0 0.394	5,0 0.197	18,5 0.728	19,7 0.776	22,0 0.866	59,0 2.323	13,0	1	0	G6.3	0,3 0.660	0,3 0.660
CAT	C4-391.5820-12040	02532916	C4	M12	40,0 1.575	17,0 0.669	15,0 0.591	10,0 0.394	23,0 0.906	24,7 0.972	28,0 1.102	64,0 2.520	18,3	1	0	G6.3	0,4 0.880	0,4 0.880
	C4-391.5820-16045	02532917	C4	M16	45,0 1.772	22,0 0.866	21,0 0.827	10,0 0.394	30,0 1.181	31,7 1.248	35,5 1.398	69,0 2.717	10,8	1	0	G6.3	0,4 0.880	0,4 0.880
Combimaster	C5-391.5820-08050	02532918	C5	M8	50,0 1.969	27,0 1.063	25,0 0.984	10,0 0.394	13,5 0.531	15,7 0.618	18,5 0.728	80,0 3.150	5,3	1	1	G6.3	0,47 1.040	0,52 1.150
	C5-391.5820-10050	02532920	C5	M10	50,0 1.969	27,0 1.063	25,0 0.984	10,0 0.394	18,5 0.728	19,7 0.776	23,0 0.906	80,0 3.150	6,3	1	1	G6.3	0,6 1.320	0,6 1.320
Graflex	C5-391.5820-12050	02532922	C5	M12	50,0 1.969	27,0 1.063	25,0 0.984	10,0 0.394	23,0 0.906	24,7 0.972	28,5 1.122	80,0 3.150	7,2	1	1	G6.3	0,6 1.320	0,6 1.320
	C5-391.5820-16075	02532925	C5	M16	75,0 2.953	52,0 2.047	50,0 1.969	20,0 0.787	30,0 1.181	31,7 1.248	37,0 1.457	105,0 4.134	5,0	1	1	G6.3	0,8 1.760	0,8 1.760
Seco Capto™	C5-M16-135	03308021	C5	M16	135,0 5.315	112,0 4.409	110,0 4.331	35,0 1.378	30,0 1.181	30,5 1.201	—	165,0 6.496	—	2	1	G6.3	1,1 2.430	1,1 2.430
	C5-391.5820-20075	02928187	C5	M20	75,0 2.953	52,0 2.047	50,0 1.969	20,0 0.787	36,5 1.437	37,5 1.476	43,0 1.693	105,0 4.134	5,3	1	1	G6.3	0,9 1.980	0,9 1.980
Others	C5-M20-135	03308022	C5	M20	135,0 5.315	112,0 4.409	110,0 4.331	35,0 1.378	36,5 1.437	37,0 1.457	—	165,0 6.496	—	2	1	G6.3	1,3 2.870	1,3 2.870
	C6-391.5820-08075	02532928	C6	M8	75,0 2.953	50,0 1.969	45,0 1.772	15,0 0.591	13,5 0.531	15,7 0.618	20,0 0.787	113,0 4.449	4,1	1	1	G6.3	0,9 1.980	0,9 1.980
Operating & setting accessories	C6-391.5820-10075	02532930	C6	M10	75,0 2.953	50,0 1.969	45,0 1.772	15,0 0.591	18,5 0.728	19,7 0.776	24,0 0.945	113,0 4.449	4,1	1	1	G6.3	1,0 2.200	1,0 2.200
	C6-391.5820-12050	02532931	C6	M12	50,0 1.969	25,0 0.984	20,0 0.787	10,0 0.394	23,0 0.906	24,7 0.972	28,0 1.102	88,0 3.465	9,4	1	1	G6.3	0,9 1.980	0,9 1.980
Shrinkfit	C6-391.5820-12075	02532932	C6	M12	75,0 2.953	50,0 1.969	45,0 1.772	20,0 0.787	23,0 0.906	24,7 0.972	29,5 1.161	113,0 4.449	5,5	1	1	G6.3	1,0 2.200	1,0 2.200
	C6-391.5820-16050	02532933	C6	M16	50,0 1.969	25,0 0.984	20,0 0.787	10,0 0.394	30,0 1.181	31,7 1.248	35,5 1.398	88,0 3.465	10,8	1	1	G6.3	1,0 2.200	1,0 2.200
Shrinkfit	C6-391.5820-16075	02532934	C6	M16	75,0 2.953	50,0 1.969	45,0 1.772	20,0 0.787	30,0 1.181	31,7 1.248	37,0 1.457	113,0 4.449	6,1	1	1	G6.3	1,1 2.430	1,1 2.430
	C6-M16-110	03308023	C6	M16	110,0 4.331	85,0 3.346	80,0 3.150	25,0 0.984	30,0 1.181	30,5 1.201	—	148,0 5.827	—	2	1	G6.3	1,3 2.870	1,3 2.870
Shrinkfit	C6-M16-145	03308024	C6	M16	145,0 5.709	120,0 4.724	115,0 4.528	35,0 1.378	30,0 1.181	30,5 1.201	—	183,0 7.205	—	2	1	G6.3	1,5 3.310	1,5 3.310
	C6-391.5820-20075	02928188	C6	M20	75,0 2.953	50,0 1.969	45,0 1.772	20,0 0.787	36,5 1.437	37,5 1.476	42,5 1.673	113,0 4.449	5,8	1	1	G6.3	1,2 2.650	1,2 2.650
Shrinkfit	C6-M20-110	03308025	C6	M20	110,0 4.331	85,0 3.346	80,0 3.150	25,0 0.984	36,5 1.437	37,0 1.457	—	110,0 4.331	—	2	1	G6.3	1,4 3.090	1,4 3.090
	C6-M20-145	03308026	C6	M20	145,0 5.709	120,0 4.724	115,0 4.528	35,0 1.378	36,5 1.437	37,0 1.457	—	183,0 7.205	—	2	1	G6.3	1,7 3.750	1,7 3.750
Shrinkfit	C8-391.5820-12085	02532937	C8	M12	85,0 3.346	52,0 2.047	50,0 1.969	20,0 0.787	23,0 0.906	24,7 0.972	35,0 1.378	133,0 5.236	9,7	1	1	G6.3	2,1 4.630	2,1 4.630

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD1	BD2	OAL	BHTA°	Design	RFID hole	Balan- cing	Weight
				mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>					kg <i>lbs</i>
C8-391.5820-16085	02532938	C8	M16	85,0 3.346	52,0 2.047	50,0 1.969	20,0 0.787	30,0 1.181	31,7 1.248	42,5 1.673	133,0 5.236	10,2	1	1	G6.3	2,3 5.070
C8-M20-145	03308027	C8	M20	145,0 5.709	112,0 4.409	110,0 4.331	35,0 1.378	36,5 1.437	37,0 1.457	–	193,0 7.598	–	2	1	G6.3	2,6 5.730

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

Combimaster to Combimaster – Metric/ Inch




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	BD	OAL	SW	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch			kg lbs
BS00658200625	02643834	M6	M6	25,0 0.984	11,0 0.433	38,5 1.516	9,0 0.354	0	PB	0,1 0.220
BS00858200830	02439880	M8	M8	30,0 1.181	13,5 0.531	47,75 1.880	11,0 0.433	0	PB	0,1 0.220
BS01058201035	02444086	M10	M10	35,0 1.378	18,5 0.728	53,75 2.116	15,0 0.591	0	PB	0,1 0.220
BS01258201240	02444093	M12	M12	40,0 1.575	23,0 0.906	61,75 2.431	19,0 0.748	0	PB	0,2 0.440
BS01658201640	02444106	M16	M16	40,0 1.575	30,0 1.181	62,75 2.470	26,0 1.024	0	PB	0,2 0.440
BS02058202045	02928185	M20	M20	45,0 1.772	36,5 1.437	72,0 2.835	32,0 1.260	0	PB	0,4 0.880


Combimaster to Combimaster – Metric/ Inch



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB1	LB	BD	BD1	BD2	OAL	SW	BHTA°	Design	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BS01058200635	02643838	M10	M6	35,0 1.378	22,0 0.866	6,0 0.236	11,0 0.433	11,7 0.461	18,5 0.728	53,75 2.116	15,0 0.591	12,0	1	0	PB	0,1 0.220
BS01058200830	02439881	M10	M8	30,0 1.181	17,0 0.669	8,0 0.315	13,7 0.539	15,7 0.618	18,5 0.728	48,75 1.919	15,0 0.591	8,8	1	0	PB	0,1 0.220
BS01258201035	02444092	M12	M10	35,0 1.378	24,0 0.945	8,0 0.315	18,5 0.728	19,7 0.776	23,0 0.906	56,75 2.234	19,0 0.748	5,9	1	0	PB	0,1 0.220
BS01658201060	02444098	M16	M10	60,0 2.362	49,0 1.929	8,0 0.315	18,5 0.728	19,7 0.776	30,0 1.181	82,75 3.258	26,0 1.024	7,15	1	0	PB	0,3 0.660
BS01658201240	02444102	M16	M12	40,0 1.575	29,0 1.142	8,0 0.315	23,0 0.906	24,7 0.972	30,0 1.181	62,75 2.470	26,0 1.024	7,2	1	0	PB	0,2 0.440
BS02058201645	02971312	M20	M16	45,0 1.772	27,0 1.063	10,0 0.394	30,0 1.181	31,7 1.248	36,5 1.437	72,0 2.835	32,0 1.260	–	2	0	PB	0,4 0.880

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Combimaster to Shrinkfit – Metric/ Inch

Combimaster



—Delivered with one stop screw
—For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN	LPR	OAL	LB	LSC	CBDP	BD1	BD2	LFN	LF	SW	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BS01656030665	02753121	M16	6,0 0.236	65,0 2.559	87,75 3.455	49,0 1.929	22,0 0.866	37,5 1.476	21,0 0.827	27,0 1.063	29,0 1.142	39,0 1.535	26,0 1.024	M5x0.8	4,5	0	PB	0,3 0.660
BS01656030865	02753123	M16	8,0 0.315	65,0 2.559	87,75 3.455	49,0 1.929	26,0 1.024	37,5 1.476	21,0 0.827	27,0 1.063	29,0 1.142	39,0 1.535	26,0 1.024	M6x1	4,5	0	PB	0,3 0.660
BS01656031070	02753125	M16	10,0 0.394	70,0 2.756	92,75 3.652	54,0 2.126	31,0 1.220	42,5 1.673	24,0 0.945	32,0 1.260	29,0 1.142	39,0 1.535	26,0 1.024	M8x1	4,5	0	PB	0,4 0.880
BS01656031270	02753126	M16	12,0 0.472	70,0 2.756	92,75 3.652	54,0 2.126	34,0 1.339	47,5 1.870	24,0 0.945	32,0 1.260	24,0 0.945	34,0 1.339	26,0 1.024	M10x1	4,5	0	PB	0,4 0.880

Accessories

For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Stop screw
	
BS01656030665	19BDR05165
BS01656030865	19BDR06165
BS01656031070	19BDR08165
BS01656031270	19BDR10165



Graflex

Graflex assemblies include arbors, intermediates, tool holders and boring heads that can be rapidly built together when they are needed. Suitable for milling, drilling, tapping, reaming and boring, Graflex modules offer tooling of variable lengths and diameters and can be fitted on all types of machines simply by substituting the Graflex basic arbor.

- Excellent connection rigidity
- Wide range of modules offer high flexibility
- Through coolant possibilities

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Machine side

Workpiece side



Machine side catalogue designation	Hole for RFID carrier*	DF	DMM	LS	LF
		mm inch	mm inch	mm inch	mm inch
G0	No	16 0.630	8 0.315	12 0.472	8 0.315
G1	No	20 0.787	11 0.433	13 0.512	9,5 0.374
G2	No	25 0.984	14 0.551	16 0.630	11 0.433
G3	No	32 1.260	18 0.709	20 0.787	14 0.551
G4	No	40 1.575	22 0.866	24 0.945	17 0.669
G5	No	50 1.969	28 1.102	30 1.181	20 0.787
G6	No	63 2.480	36 1.417	40 1.575	26 1.024
G7	No	90 3.543	46 1.811	50 1.969	26 1.024


Workpiece side catalogue designation	Hole for RFID carrier*	CBDP	DCB	BD
		mm inch	mm inch	mm inch
G0	No	16 0.630	8 0.315	12 0.472
G1	No	20 0.787	11 0.433	13 0.512
G2	No	25 0.984	14 0.551	16 0.630
G3	No	32 1.260	18 0.709	20 0.787
G4	No	40 1.575	22 0.866	24 0.945
G5	No	50 1.969	28 1.102	30 1.181
G6	No	63 2.480	36 1.417	40 1.575
G7	No	90 3.543	46 1.811	50 1.969

Note: These machine side and workpiece side dimensions are applied to all the holders shown in the Product pages.

* No hole for RFID carriers

HSK-A to Graflex
– Metric/ Inch

HSK-A/ ISO12164-1-HSK-A



–For HSK sealing plugs, coolant tubes and tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
EM93034012870	00086917	HSK-A50	G5	28,0 1.102	70,0 2.756	44,0 1.732	50,0 1.969	95,0 3.740	1	PB	0,9 1.980
EM93044011445	02469722	HSK-A63	G2	14,0 0.551	45,0 1.772	19,0 0.748	25,0 0.984	77,0 3.031	1	G6.3	0,7 1.540
EM93044011850	00086918	HSK-A63	G3	18,0 0.709	50,0 1.969	24,0 0.945	32,0 1.260	82,0 3.228	1	G6.3	0,8 1.760
EM93044012255	00088217	HSK-A63	G4	22,0 0.866	55,0 2.165	29,0 1.142	40,0 1.575	87,0 3.425	1	G6.3	0,9 1.980
EM93044012860	00086920	HSK-A63	G5	28,0 1.102	60,0 2.362	34,0 1.339	50,0 1.969	92,0 3.622	1	PB	1,0 2.200
EM930440128100	00086921	HSK-A63	G5	28,0 1.102	100,0 3.937	74,0 2.913	50,0 1.969	132,0 5.197	1	PB	1,6 3.530
EM930440128140	00086922	HSK-A63	G5	28,0 1.102	140,0 5.512	114,0 4.488	50,0 1.969	172,0 6.772	1	PB	2,18 4.810
EM93044013670	00086923	HSK-A63	G6	36,0 1.417	70,0 2.756	44,0 1.732	63,0 2.480	102,0 4.016	1	PB	1,3 2.870
EM930440136120	00086924	HSK-A63	G6	36,0 1.417	120,0 4.724	94,0 3.701	63,0 2.480	152,0 5.984	1	PB	2,38 5.250
EM93064011855	00086925	HSK-A100	G3	18,0 0.709	55,0 2.165	26,0 1.024	32,0 1.260	105,0 4.134	1	G6.3	2,2 4.850
EM93064012260	00086926	HSK-A100	G4	22,0 0.866	60,0 2.362	31,0 1.220	40,0 1.575	110,0 4.331	1	G6.3	2,3 5.070
EM93064012865	00086927	HSK-A100	G5	28,0 1.102	65,0 2.559	36,0 1.417	50,0 1.969	115,0 4.528	1	PB	2,4 5.290
EM930640128110	00086928	HSK-A100	G5	28,0 1.102	110,0 4.331	81,0 3.189	50,0 1.969	160,0 6.299	1	PB	3,1 6.830
EM930640128150	00086929	HSK-A100	G5	28,0 1.102	150,0 5.906	121,0 4.764	50,0 1.969	200,0 7.874	1	PB	3,7 8.160
EM93064013675	00083432	HSK-A100	G6	36,0 1.417	75,0 2.953	46,0 1.811	63,0 2.480	125,0 4.921	1	PB	2,8 6.170
EM930640136120	00086931	HSK-A100	G6	36,0 1.417	120,0 4.724	91,0 3.583	63,0 2.480	170,0 6.693	1	PB	3,9 8.600
EM930640136160	00086932	HSK-A100	G6	36,0 1.417	160,0 6.299	131,0 5.157	63,0 2.480	210,0 8.268	1	PB	4,8 10.580
EM93064014685	00074385	HSK-A100	G7	46,0 1.811	85,0 3.346	56,0 2.205	90,0 3.543	135,0 5.315	1	PB	4,0 8.820
EM930640146160	00086933	HSK-A100	G7	46,0 1.811	160,0 6.299	131,0 5.157	90,0 3.543	210,0 8.268	1	PB	7,67 16.910
HSKA125-G6-120	03229653	HSK-A125	G6	36,0 1.417	120,0 4.724	91,0 3.583	63,0 2.480	183,0 7.205	1	PB	5,1 11.240
HSKA125-G7-120	03229654	HSK-A125	G7	46,0 1.811	120,0 4.724	91,0 3.583	90,0 3.543	183,0 7.205	1	PB	7,1 15.650

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster


Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit


Accessories		
Guide	For	Locking key
		
HSK-A	G2	03H025
	G3	03H03
	G4	03H04
	G5	03H05
HSK-E	G6	03H06
	G7	03H10
Spare Parts, included in delivery		
DIN	For	Assembly screw
		
BT JIS	G2	90F2
	G3	90F3
	G4	90F4
	G5	90F5
CAT	G6	90F6
	G7	90F7
Combimaster		
Graflex		
Seco Capto™		
Others		
Operating & setting accessories		
Shrinkfit		

DIN 69871 to Graflex
– Metric/ Inch


DIN 69871-ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD1	BD	OAL	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
EM34694011190	02503292	DIN40 ADB	G1	11,0 0.433	90,0 3.543	70,9 2.791	–	20,0 0.787	158,4 6.236	2	1	G6.3	1,0 2.200
EM34694011435	02469729	DIN40 ADB	G2	14,0 0.551	35,0 1.378	15,9 0.626	–	25,0 0.984	103,4 4.071	2	1	G6.3	0,83 1.830
EM34694011490	02503293	DIN40 ADB	G2	14,0 0.551	90,0 3.543	70,9 2.791	–	25,0 0.984	158,4 6.236	2	1	G6.3	1,1 2.430
EM34694011835	02420097	DIN40 ADB	G3	18,0 0.709	35,0 1.378	15,9 0.626	50,0 1.969	32,0 1.260	103,4 4.071	1	1	G6.3	1,0 2.200
EM346940118100	02503298	DIN40 ADB	G3	18,0 0.709	100,0 3.937	80,9 3.185	–	32,0 1.260	168,4 6.630	2	1	G6.3	1,3 2.870
EM34694012235	02503299	DIN40 ADB	G4	22,0 0.866	35,0 1.378	15,9 0.626	50,0 1.969	40,0 1.575	103,4 4.071	1	1	G6.3	0,92 2.030
EM346940122100	02503300	DIN40 ADB	G4	22,0 0.866	100,0 3.937	80,9 3.185	–	40,0 1.575	168,4 6.630	2	1	G6.3	1,5 3.310
EM34694012840	02458421	DIN40 ADB	G5	28,0 1.102	40,0 1.575	20,9 0.823	–	50,0 1.969	108,4 4.268	2	1	PB	1,0 2.200
EM34694012880	02503301	DIN40 ADB	G5	28,0 1.102	80,0 3.150	60,9 2.398	–	50,0 1.969	148,4 5.843	2	1	PB	1,5 3.310
EM346940128120	02503302	DIN40 ADB	G5	28,0 1.102	120,0 4.724	100,9 3.972	–	50,0 1.969	188,4 7.417	2	1	PB	2,1 4.630
EM34694013660	02503303	DIN40 ADB	G6	36,0 1.417	60,0 2.362	40,9 1.610	–	63,0 2.480	128,4 5.055	2	1	PB	1,3 2.870
EM346940136120	02503304	DIN40 ADB	G6	36,0 1.417	120,0 4.724	100,9 3.972	–	63,0 2.480	188,4 7.417	2	1	PB	2,7 5.950
EM347140114100	02503306	DIN50 ADB	G2	14,0 0.551	100,0 3.937	80,9 3.185	–	25,0 0.984	201,7 7.941	2	1	G6.3	2,9 6.390
EM34714011835	02503307	DIN50 ADB	G3	18,0 0.709	35,0 1.378	15,9 0.626	–	32,0 1.260	136,7 5.382	2	1	G6.3	2,67 5.890
EM347140118110	02503308	DIN50 ADB	G3	18,0 0.709	110,0 4.331	90,9 3.579	–	32,0 1.260	211,7 8.335	2	1	G6.3	3,1 6.830
EM34714012235	02503309	DIN50 ADB	G4	22,0 0.866	35,0 1.378	15,9 0.626	80,0 3.150	40,0 1.575	136,7 5.382	1	1	G6.3	2,88 6.350
EM347140122120	02503311	DIN50 ADB	G4	22,0 0.866	120,0 4.724	100,9 3.972	–	40,0 1.575	221,7 8.728	2	1	G6.3	3,4 7.500
EM34714012840	02503312	DIN50 ADB	G5	28,0 1.102	40,0 1.575	20,9 0.823	–	50,0 1.969	141,7 5.579	2	1	PB	2,75 6.060
EM347140128100	02503315	DIN50 ADB	G5	28,0 1.102	100,0 3.937	80,9 3.185	–	50,0 1.969	201,7 7.941	2	1	PB	3,56 7.850
EM347140128140	02503316	DIN50 ADB	G5	28,0 1.102	140,0 5.512	120,9 4.760	–	50,0 1.969	241,7 9.516	2	1	PB	4,08 8.990
EM34714013645	02503317	DIN50 ADB	G6	36,0 1.417	45,0 1.772	25,9 1.020	–	63,0 2.480	146,7 5.776	2	1	PB	2,9 6.390
EM347140136100	02503318	DIN50 ADB	G6	36,0 1.417	100,0 3.937	80,9 3.185	–	63,0 2.480	201,7 7.941	2	1	PB	4,1 9.040
EM347140136140	02503319	DIN50 ADB	G6	36,0 1.417	140,0 5.512	120,9 4.760	–	63,0 2.480	241,7 9.516	2	1	PB	5,1 11.240

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Guide	Designation	Item number	CTMS	CTWS	DCB mm inch	LF mm inch	LB mm inch	BD1 mm inch	BD mm inch	OAL mm inch	Design	RFID hole	Balan- cing	Weight kg lbs
HSK-A	EM34714014650	02503320	DIN50 ADB	G7	46,0 1.811	50,0 1.969	30,9 1.217	–	90,0 3.543	151,7 5.972	2	1	PB	3,3 7.280
	EM347140146120	02503321	DIN50 ADB	G7	46,0 1.811	120,0 4.724	100,9 3.972	–	90,0 3.543	221,7 8.728	2	1	PB	6,5 14.330
	EM347140146200	02503324	DIN50 ADB	G7	46,0 1.811	200,0 7.874	180,9 7.122	–	90,0 3.543	301,7 11.878	2	1	PB	10,4 22.930

Accessories

HSK-E	For	Locking key
DIN	DIN40/ G1	03H02
	DIN40/ G2	03H025
	DIN40/ G3	03H03
	DIN40/ G4	03H04
	DIN40/ G5	03H05
BT JIS	DIN40/ G6	03H06
	DIN50/ G2	03H025
	DIN50/ G3	03H03
CAT	DIN50/ G4	03H04
	DIN50/ G5	03H05
	DIN50/ G6	03H06
	DIN50/ G7	03H10
	EM34714014650	03H10

Spare Parts, included in delivery

Combimaster	For	Assembly screw	Sealing Screws
Graflex	DIN40/ G1	90F1	950A0406
	DIN40/ G2	90F2	950A0406
	DIN40/ G3	90F3	950A0406
	DIN40/ G4	90F4	950A0406
	DIN40/ G5	90F5	950A0406
Seco Capto™	DIN40/ G6	90F6	950A0406
	DIN50/ G2	90F2	950A0606
	DIN50/ G3	90F3	950A0606
Others	DIN50/ G4	90F4	950A0606
	DIN50/ G5	90F5	950A0606
	DIN50/ G6	90F6	950A0606
	DIN50/ G7	90F7	950A0606
Operating & setting accessories	EM34714014650	90F71	950A0606


Shrinkfit	
-----------	--

DIN 2080 to Graflex
– Metric/ Inch


DIN 2080



Design 1



Design 2




–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD1	BD	OAL	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
EM00404013650	00076707	DIN(2080)40	G6	36,0 1.417	50,0 1.969	0,0 –	–	63,0 2.480	143,4 5.646	2	0	PB	1,3 2.870
EM00504012835	00076710	DIN(2080)50	G5	28,0 1.102	35,0 1.378	19,8 0.780	78,0 3.071	50,0 1.969	161,8 6.370	1	0	PB	2,94 6.480
EM00504013640	00076714	DIN(2080)50	G6	36,0 1.417	40,0 1.575	24,8 0.976	–	63,0 2.480	166,8 6.567	2	0	PB	2,9 6.390
EM00504014645	00076718	DIN(2080)50	G7	46,0 1.811	45,0 1.772	29,8 1.173	–	90,0 3.543	171,8 6.764	2	0	PB	3,34 7.360

Accessories

For	Locking key
	
G5	03H05
G6	03H06
G7	03H10

Spare Parts, included in delivery

For	Assembly screw
	
G5	90F5
G6	90F6
G7	90F7

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

BT JIS to Graflex
– Metric/ Inch




–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD	OAL	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
EM40404011835	00056699	BT30 AD	G3	18,0 0.709	35,0 1.378	13,0 0.512	32,0 1.260	83,4 3.283	0	G6.3	0,5 1.100
EM40404012850	00056705	BT30 AD	G5	28,0 1.102	50,0 1.969	25,0 0.984	50,0 1.969	98,4 3.874	0	PB	0,7 1.540

Accessories

For	Locking key
	
EM40404011835	03H03
EM40404012850	03H05

Spare Parts, included in delivery


For	Assembly screw
	
EM40404011835	90F3
EM40404012850	90F5

BT JIS to Graflex
– Metric/ Inch


BT JIS B 6339-ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD1	BD	OAL	Design	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
EM34144011190	02503364	BT40 ADB	G1	11,0 0.433	90,0 3.543	63,0 2.480	–	20,0 0.787	155,4 6.118	2	1	G6.3	1,1 2.430
EM34144011440	02469725	BT40 ADB	G2	14,0 0.551	40,0 1.575	13,0 0.512	–	25,0 0.984	105,4 4.150	2	1	G6.3	0,98 2.160
EM34144011490	02503365	BT40 ADB	G2	14,0 0.551	90,0 3.543	63,0 2.480	–	25,0 0.984	155,4 6.118	2	1	G6.3	1,2 2.650
EM34144011840	02503366	BT40 ADB	G3	18,0 0.709	40,0 1.575	13,0 0.512	62,0 2.441	32,0 1.260	105,4 4.150	1	1	G6.3	1,07 2.360
EM341440118100	02503367	BT40 ADB	G3	18,0 0.709	100,0 3.937	73,0 2.874	–	32,0 1.260	165,4 6.512	2	1	G6.3	1,31 2.890
EM34144012245	02503368	BT40 ADB	G4	22,0 0.866	45,0 1.772	18,0 0.709	62,0 2.441	40,0 1.575	110,4 4.346	1	1	G6.3	1,2 2.650
EM341440122100	02503370	BT40 ADB	G4	22,0 0.866	100,0 3.937	73,0 2.874	–	40,0 1.575	165,4 6.512	2	1	G6.3	1,6 3.530
EM34144012845	02457989	BT40 ADB	G5	28,0 1.102	45,0 1.772	18,0 0.709	62,0 2.441	50,0 1.969	110,4 4.346	1	1	PB	1,2 2.650
EM34144012880	02503371	BT40 ADB	G5	28,0 1.102	80,0 3.150	53,0 2.087	–	50,0 1.969	145,4 5.724	2	1	PB	1,6 3.530
EM341440128120	02503372	BT40 ADB	G5	28,0 1.102	120,0 4.724	93,0 3.661	–	50,0 1.969	185,4 7.299	2	1	PB	2,2 4.850
EM34144013650	02503373	BT40 ADB	G6	36,0 1.417	50,0 1.969	0,0 –	–	63,0 2.480	115,4 4.543	2	0	PB	1,2 2.650
EM341440136120	02503374	BT40 ADB	G6	36,0 1.417	120,0 4.724	0,0 –	–	63,0 2.480	185,4 7.299	2	1	PB	2,8 6.170
EM341640114110	02503375	BT50 ADB	G2	14,0 0.551	110,0 4.331	72,0 2.835	–	25,0 0.984	211,8 8.339	2	1	G6.3	3,8 8.380
EM34164011845	02503376	BT50 ADB	G3	18,0 0.709	45,0 1.772	7,0 0.276	70,0 2.756	32,0 1.260	146,8 5.780	1	1	G6.3	3,6 7.940
EM341640118120	02503377	BT50 ADB	G3	18,0 0.709	120,0 4.724	82,0 3.228	–	32,0 1.260	221,8 8.732	2	1	G6.3	4,0 8.820
EM34164012250	02503378	BT50 ADB	G4	22,0 0.866	50,0 1.969	12,0 0.472	70,0 2.756	40,0 1.575	151,8 5.976	1	1	G6.3	3,7 8.160
EM341640122140	02503379	BT50 ADB	G4	22,0 0.866	140,0 5.512	102,0 4.016	–	40,0 1.575	241,8 9.520	2	1	G6.3	4,4 9.700
EM34164012855	02503380	BT50 ADB	G5	28,0 1.102	55,0 2.165	17,0 0.669	98,0 3.858	50,0 1.969	156,8 6.173	1	1	PB	4,0 8.820
EM341640128100	02503381	BT50 ADB	G5	28,0 1.102	100,0 3.937	62,0 2.441	–	50,0 1.969	201,8 7.945	2	1	PB	4,3 9.480
EM341640128140	02503382	BT50 ADB	G5	28,0 1.102	140,0 5.512	102,0 4.016	–	50,0 1.969	241,8 9.520	2	1	PB	4,9 10.800
EM34164013663	02503383	BT50 ADB	G6	36,0 1.417	63,0 2.480	25,0 0.984	98,0 3.858	63,0 2.480	164,8 6.488	1	1	PB	4,3 9.480
EM341640136100	02503384	BT50 ADB	G6	36,0 1.417	100,0 3.937	62,0 2.441	–	63,0 2.480	201,8 7.945	2	1	PB	4,7 10.360
EM341640136140	02503385	BT50 ADB	G6	36,0 1.417	140,0 5.512	102,0 4.016	–	63,0 2.480	241,8 9.520	2	1	PB	5,6 12.350

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories




Shrinkfit

Guide	Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD1	BD	OAL	Design	RFID hole	Balan- cing	Weight
					mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
HSK-A	EM34164014665	02503386	BT50 ADB	G7	46,0 1.811	65,0 2.559	27,0 1.063	98,0 3.858	90,0 3.543	166,8 6.567	1	1	PB	4,4 9.700
	EM341640146120	02503387	BT50 ADB	G7	46,0 1.811	120,0 4.724	82,0 3.228	–	90,0 3.543	221,8 8.732	2	1	PB	6,9 15.210
	EM341640146200	02503388	BT50 ADB	G7	46,0 1.811	200,0 7.874	162,0 6.378	–	90,0 3.543	301,8 11.882	2	1	PB	10,7 23.590

Accessories

HSK-E	For													
	Locking key													
DIN														
BT JIS														
CAT														

Spare Parts, included in delivery

Combimaster	For													
	Assembly screw							Sealing Screws						
Graflex														
Seco Capto™														
Others														


Operating & setting acces- series														
Shrinkfit														

BT Taper Face to Graflex – Metric/ Inch


BT Taper-Face-AD/ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD	OAL	Design	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
EM40024011850	02998757	BT30 TF AD	G3	18,0 0.709	50,0 1.969	28,0 1.102	32,0 1.260	98,4 3.874	1	0	G6.3	0,6 1.320
EM40024012250	02998758	BT30 TF AD	G4	22,0 0.866	50,0 1.969	28,0 1.102	40,0 1.575	98,4 3.874	1	0	G6.3	0,6 1.320
EM321440122100	02998754	BT40 TF ADB	G4	22,0 0.866	100,0 3.937	73,0 2.874	40,0 1.575	165,4 6.512	2	1	G6.3	1,6 3.530
EM321440128120	02926006	BT40 TF ADB	G5	28,0 1.102	120,0 4.724	93,0 3.661	50,0 1.969	185,4 7.299	2	1	PB	2,2 4.850
EM321440136120	02998755	BT40 TF ADB	G6	36,0 1.417	120,0 4.724	93,0 3.661	63,0 2.480	185,4 7.299	2	1	PB	2,8 6.170
EM321640128140	02998756	BT50 TF ADB	G5	28,0 1.102	140,0 5.512	102,0 4.016	50,0 1.969	241,8 9.520	2	1	PB	4,9 10.800
EM321640136140	02926009	BT50 TF ADB	G6	36,0 1.417	140,0 5.512	102,0 4.016	63,0 2.480	241,8 9.520	2	1	PB	5,6 12.350
EM321640146200	02926010	BT50 TF ADB	G7	46,0 1.811	200,0 7.874	162,0 6.378	90,0 3.543	301,8 11.882	2	1	PB	10,8 23.810

Accessories

For	Locking key
	
EM321440122100	03H04
EM321440128120	03H05
EM321440136120	03H06
EM321640128140	03H05
EM321640136140	03H06
EM321640146200	03H10
EM40024011850	03H03
EM40024012250	03H04

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Spare Parts, included in delivery


Guide	Spare Parts, included in delivery		
	For	Assembly screw	Sealing Screws
			
HSK-A	EM321440122100	90F4	950A0406
	EM321440128120	90F5	950A0406
	EM321440136120	90F6	950A0406
	EM321640128140	90F5	950A0606
HSK-E	EM321640136140	90F6	950A0606
	EM321640146200	90F7	950A0606
	EM40024011850	90F3	-
	EM40024012250	90F4	-
DIN			
BT JIS			
CAT			
Combimaster			
Graflex			
Seco Capto™			
Others			
Operating & setting accessories			
Shrinkfit			

CAT to Graflex
– Inch


CAT / ASME B5.50-1994-ADB



Design 1



Design 2



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD1	BD	OAL	Design	RFID hole	Balan- cing	Weight
				inch	inch	inch	inch	inch	inch				lbs
EM25024011435	02469734	CAT40 ADB	G2	0.551	1.380	0.630	1.750	0.984	4.070	1	1	G6.3	2.120
EM25024011835	00056660	CAT40 ADB	G3	0.709	1.380	0.630	1.750	1.260	4.070	1	1	G6.3	2.200
EM25024012235	00056661	CAT40 ADB	G4	0.866	1.380	0.630	1.750	1.575	4.070	1	1	G6.3	1.980
EM25024012840	00056663	CAT40 ADB	G5	1.102	1.570	0.820	1.750	1.969	4.270	2	1	PB	1.980
EM250240128100	00056662	CAT40 ADB	G5	1.102	3.940	3.190	1.750	1.969	7.420	2	1	PB	3.970
EM25024013660	00056665	CAT40 ADB	G6	1.417	2.360	1.610	1.750	2.480	5.060	2	1	PB	2.870
EM25044011835	00056666	CAT50 ADB	G3	0.709	1.380	0.630	2.750	1.260	5.380	1	1	G6.3	6.830
EM25044012235	00056667	CAT50 ADB	G4	0.866	1.380	0.630	2.750	1.575	5.380	1	1	G6.3	6.610
EM25044012840	00056669	CAT50 ADB	G5	1.102	1.570	0.820	2.750	1.969	5.580	2	1	PB	6.610
EM250440128100	00056668	CAT50 ADB	G5	1.102	3.940	3.190	2.750	1.969	7.940	2	1	PB	8.380
EM25044013645	00056671	CAT50 ADB	G6	1.417	1.770	1.020	2.750	2.480	5.780	1	1	PB	6.610
EM250440136120	00056670	CAT50 ADB	G6	1.417	4.720	3.970	2.750	2.480	9.520	1	1	PB	10.360
EM25044014665	00056675	CAT50 ADB	G7	1.811	2.560	1.810	2.750	3.543	5.970	2	1	PB	8.380
EM250440146120	00056673	CAT50 ADB	G7	1.811	4.720	3.970	2.750	3.543	8.730	2	1	PB	13.890
EM250440146200	00056674	CAT50 ADB	G7	1.811	7.870	7.120	2.750	3.543	11.880	2	1	PB	22.270

Accessories

For	Locking key
	
CAT40/ G2	03H025
CAT40/ G3	03H03
CAT40/ G4	03H04
CAT40/ G5	03H05
CAT40/ G6	03H06
CAT50/ G3	03H03
CAT50/ G4	03H04
CAT50/ G5	03H05
CAT50/ G6	03H06
CAT50/ G7	03H10

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery		
	For	Assembly screw	Sealing Screws
			
HSK-A	CAT40/ G2	90F2	950A0406
	CAT40/ G3	90F3	950A0406
	CAT40/ G4	90F4	950A0406
	CAT40/ G5	90F5	950A0406
HSK-E	CAT40/ G6	90F6	950A0406
	CAT50/ G3	90F3	950A0606
	CAT50/ G4	90F4	950A0606
	CAT50/ G5	90F5	950A0606
	CAT50/ G6	90F6	950A0606
DIN	CAT50/ G7	90F7	950A0606
BT JIS			
CAT			
Combimaster			
Graflex			
Seco Capto™			
Others			
Operating & setting accessories			
Shrinkfit			

CAT Taper Face to Graflex
– Inch

CAT TF / ASME B5.50-2009-ADB




–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD	OAL	Design	RFID hole	Balancing	Weight
				inch	inch	inch	inch	inch				lbs
EM26424011880	02998750	CAT40 TF ADB	G3	0.709	3.150	2.398	1.260	5.843	2	1	G6.3	2.650
EM26424012280	02998751	CAT40 TF ADB	G4	0.866	3.150	2.398	1.575	5.843	2	1	G6.3	3.090
EM264240128100	02998752	CAT40 TF ADB	G5	1.102	3.937	3.185	1.969	6.630	2	1	PB	4.190
EM264240136100	02998753	CAT40 TF ADB	G6	1.417	3.937	3.185	2.480	6.630	2	1	PB	5.290
EM264440122100	02964322	CAT50 TF ADB	G4	0.866	3.937	3.185	1.575	7.943	2	1	G6.3	7.280
EM264440128100	02964323	CAT50 TF ADB	G5	1.102	3.937	3.185	1.969	7.943	2	1	PB	7.940
EM264440136120	02926850	CAT50 TF ADB	G6	1.417	4.724	3.972	2.480	8.732	1	1	PB	10.140
EM264440146200	02926851	CAT50 TF ADB	G7	1.811	7.874	7.122	3.543	11.880	2	1	PB	22.710

Accessories


For	Locking key
	
EM26424011880	03H03
EM26424012280	03H04
EM264240128100	03H05
EM264240136100	03H06
EM264440122100	03H04
EM264440128100	03H05
EM264440136120	03H06
EM264440146200	03H10

Spare Parts, included in delivery

For	Assembly screw	Sealing Screws
		
EM26424011880	90F3	950A0406
EM26424012280	90F4	950A0406
EM264240128100	90F5	950A0406
EM264240136100	90F6	950A0406
EM264440122100	90F4	950A0606
EM264440128100	90F5	950A0606
EM264440136120	90F6	950A0606
EM264440146200	90F7	950A0606

Seco Capto™ to Graflex – Metric/ Inch

Seco Capto™




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCB	LF	LB	BD	OAL	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
C3-391.0401-08025	02532939	C3	G0	8,0 0.315	25,0 0.984	7,0 0.276	16,0 0.630	44,0 1.732	0	G6.3	0,2 0.440
C3-391.0401-11025	02532940	C3	G1	11,0 0.433	25,0 0.984	7,0 0.276	20,0 0.787	44,0 1.732	0	G6.3	0,14 0.310
C3-391.0401-14025	02532941	C3	G2	14,0 0.551	25,0 0.984	7,0 0.276	25,0 0.984	44,0 1.732	0	G6.3	0,2 0.440
C3-391.0401-18030	02532942	C3	G3	18,0 0.709	30,0 1.181	0,0 —	32,0 1.260	49,0 1.929	0	G6.3	0,16 0.350
C4-391.0401-18035	02532943	C4	G3	18,0 0.709	35,0 1.378	12,0 0.472	32,0 1.260	59,0 2.323	0	G6.3	0,4 0.880
C4-391.0401-22035	02532944	C4	G4	22,0 0.866	35,0 1.378	0,0 —	40,0 1.575	59,0 2.323	0	G6.3	0,31 0.680
C5-391.0401-14030	02532945	C5	G2	14,0 0.551	30,0 1.181	7,0 0.276	25,0 0.984	60,0 2.362	1	G6.3	0,47 1.040
C5-391.0401-18035	02532947	C5	G3	18,0 0.709	35,0 1.378	12,0 0.472	32,0 1.260	65,0 2.559	1	G6.3	0,5 1.100
C5-391.0401-22035	02532948	C5	G4	22,0 0.866	35,0 1.378	12,0 0.472	40,0 1.575	65,0 2.559	1	G6.3	0,5 1.100
C5-391.0401-28045	02532949	C5	G5	28,0 1.102	45,0 1.772	22,0 0.866	50,0 1.969	75,0 2.953	1	PB	0,7 1.540
C6-391.0401-18035	02532950	C6	G3	18,0 0.709	35,0 1.378	10,0 0.394	32,0 1.260	73,0 2.874	1	G6.3	0,9 1.980
C6-391.0401-22040	02532951	C6	G4	22,0 0.866	40,0 1.575	15,0 0.591	40,0 1.575	78,0 3.071	1	G6.3	0,9 1.980
C6-391.0401-28050	02532952	C6	G5	28,0 1.102	50,0 1.969	25,0 0.984	50,0 1.969	88,0 3.465	1	PB	1,1 2.430
C6-391.0401-36055	02532953	C6	G6	36,0 1.417	55,0 2.165	0,0 —	63,0 2.480	93,0 3.661	1	PB	1,2 2.650
C8-391.0401-28050	02532954	C8	G5	28,0 1.102	50,0 1.969	17,0 0.669	50,0 1.969	98,0 3.858	1	PB	2,0 4.410
C8-391.0401-36055	02532955	C8	G6	36,0 1.417	55,0 2.165	22,0 0.866	63,0 2.480	103,0 4.055	1	PB	2,1 4.630
C8-391.0401-46065	02532956	C8	G7	46,0 1.811	65,0 2.559	35,0 1.378	90,0 3.543	113,0 4.449	1	PB	2,8 6.170

Accessories

For	Locking key	
		
G0	03H02	Guide
G1	03H02	
G2	03H025	
G3	03H03	HSK-A
G4	03H04	
G5	03H05	HSK-E
G6	03H06	
G7	03H10	

Spare Parts, included in delivery

For	Assembly screw	
		
G0	90F0	DIN
G1	90F1	
G2	90F2	
G3	90F3	BT JIS
G4	90F4	
G5	90F5	CAT
G6	90F6	
G7	90F7	

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Graflex to Graflex
– Metric/ Inch




–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	DCB	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch			kg lbs
M402000	00056752	G0	G0	30,0 1.181	8,0 0.315	16,0 0.630	42,0 1.654	0	PB	0,1 0.220
M402001	00056753	G0	G0	50,0 1.969	8,0 0.315	16,0 0.630	62,0 2.441	0	PB	0,1 0.220
M402110	00056754	G1	G1	30,0 1.181	11,0 0.433	20,0 0.787	43,0 1.693	0	PB	0,1 0.220
M402111	00056755	G1	G1	50,0 1.969	11,0 0.433	20,0 0.787	63,0 2.480	0	PB	0,2 0.440
M402220	00056756	G2	G2	30,0 1.181	14,0 0.551	25,0 0.984	46,0 1.811	0	PB	0,2 0.440
M402221	00056757	G2	G2	50,0 1.969	14,0 0.551	25,0 0.984	66,0 2.598	0	PB	0,2 0.440
M402330	00056758	G3	G3	40,0 1.575	18,0 0.709	32,0 1.260	60,0 2.362	0	PB	0,3 0.660
M402331	75056759	G3	G3	60,0 2.362	18,0 0.709	32,0 1.260	80,0 3.150	0	PB	0,4 0.880
M402440	00056760	G4	G4	40,0 1.575	22,0 0.866	40,0 1.575	64,0 2.520	0	PB	0,4 0.880
M402441	00056761	G4	G4	60,0 2.362	22,0 0.866	40,0 1.575	84,0 3.307	0	PB	0,6 1.320
M402444	02786252	G4	G4	200,0 7.874	22,0 0.866	40,0 1.575	224,0 8.819	0	PB	1,95 4.300
M402550	00056762	G5	G5	50,0 1.969	28,0 1.102	50,0 1.969	80,0 3.150	0	PB	0,8 1.760
M402551	00056763	G5	G5	75,0 2.953	28,0 1.102	50,0 1.969	105,0 4.134	0	PB	1,2 2.650
M402552	00056764	G5	G5	100,0 3.937	28,0 1.102	50,0 1.969	130,0 5.118	0	PB	1,5 3.310
M402554	02786254	G5	G5	250,0 9.843	28,0 1.102	50,0 1.969	280,0 11.024	0	PB	3,8 8.380
M402660	00056765	G6	G6	60,0 2.362	36,0 1.417	63,0 2.480	100,0 3.937	0	PB	1,4 3.090
M402661	00056766	G6	G6	90,0 3.543	36,0 1.417	63,0 2.480	130,0 5.118	0	PB	2,2 4.850
M402662	00056767	G6	G6	120,0 4.724	36,0 1.417	63,0 2.480	160,0 6.299	0	PB	2,9 6.390
M402664	02786255	G6	G6	300,0 11.811	36,0 1.417	63,0 2.480	340,0 13.386	0	PB	7,2 15.870
M402770	00056768	G7	G7	60,0 2.362	46,0 1.811	90,0 3.543	110,0 4.331	0	-	2,9 6.390
M402771	00056769	G7	G7	90,0 3.543	46,0 1.811	90,0 3.543	140,0 5.512	0	-	4,4 9.700
M402772	00056770	G7	G7	120,0 4.724	46,0 1.811	90,0 3.543	170,0 6.693	0	-	5,8 12.790
M402774	02786257	G7	G7	300,0 11.811	46,0 1.811	90,0 3.543	350,0 13.780	0	-	14,6 32.190

Accessories

For	Locking key
	
G0	03H02
G1	03H02
G2	03H025
G3	03H03
G4	03H04
G5	03H05
G6	03H06
G7	03H10

Spare Parts, included in delivery

For	Assembly screw	Tenon
		
G0	90F0	90M0
G1	90F1	90M1
G2	90F2	90M2
G3	90F3	90M3
G4	90F4	90M4
G5	90F5	90M5
G6	90F6	90M6
G7	90F7	90M7

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Graflex to Graflex – Metric/ Inch




–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	DCB	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
M40310	00056771	G1	G0	30,0 1.181	22,0 0.866	8,0 0.315	16,0 0.630	43,0 1.693	0	PB	0,1 0.220
M40320	00056772	G2	G0	30,0 1.181	19,0 0.748	8,0 0.315	16,0 0.630	46,0 1.811	0	PB	0,1 0.220
M40321	00056773	G2	G1	30,0 1.181	19,0 0.748	11,0 0.433	20,0 0.787	46,0 1.811	0	PB	0,1 0.220
M40330	00056774	G3	G0	30,0 1.181	16,0 0.630	8,0 0.315	16,0 0.630	50,0 1.969	0	PB	0,2 0.440
M40331	00056775	G3	G1	30,0 1.181	16,0 0.630	11,0 0.433	20,0 0.787	50,0 1.969	0	PB	0,15 0.330
M40332	00056776	G3	G2	30,0 1.181	16,0 0.630	14,0 0.551	25,0 0.984	50,0 1.969	0	PB	0,2 0.440
M40341	00056778	G4	G1	30,0 1.181	13,0 0.512	11,0 0.433	20,0 0.787	54,0 2.126	0	PB	0,25 0.550
M40342	00056779	G4	G2	30,0 1.181	13,0 0.512	14,0 0.551	25,0 0.984	54,0 2.126	0	PB	0,3 0.660
M40343	00056780	G4	G3	30,0 1.181	13,0 0.512	18,0 0.709	32,0 1.260	54,0 2.126	0	PB	0,3 0.660
M40350	00056781	G5	G0	40,0 1.575	20,0 0.787	8,0 0.315	16,0 0.630	70,0 2.756	0	PB	0,47 1.040
M40351	00056783	G5	G1	40,0 1.575	20,0 0.787	11,0 0.433	20,0 0.787	70,0 2.756	0	PB	0,5 1.100
M40352	00056785	G5	G2	40,0 1.575	20,0 0.787	14,0 0.551	25,0 0.984	70,0 2.756	0	PB	0,5 1.100
M40353	00056787	G5	G3	40,0 1.575	20,0 0.787	18,0 0.709	32,0 1.260	70,0 2.756	0	PB	0,6 1.320
M40354	00056789	G5	G4	40,0 1.575	20,0 0.787	22,0 0.866	40,0 1.575	70,0 2.756	0	PB	0,6 1.320
M40363	00056797	G6	G3	40,0 1.575	14,0 0.551	18,0 0.709	32,0 1.260	80,0 3.150	0	PB	1,0 2.200
M40364	00056799	G6	G4	40,0 1.575	14,0 0.551	22,0 0.866	40,0 1.575	80,0 3.150	0	PB	1,0 2.200
M40365	00056807	G6	G5	45,0 1.772	19,0 0.748	28,0 1.102	50,0 1.969	85,0 3.346	0	PB	1,1 2.430
M40375	00056811	G7	G5	50,0 1.969	24,0 0.945	28,0 1.102	50,0 1.969	100,0 3.937	0	–	2,1 4.630
M40376	00056812	G7	G6	55,0 2.165	29,0 1.142	36,0 1.417	63,0 2.480	105,0 4.134	0	–	2,3 5.070

Accessories

For	Locking key
	
M40310	03H02
M40320	03H02
M40321	03H02
M40330	03H02
M40331	03H02
M40332	03H025
M40341	03H02
M40342	03H025
M40343	03H03
M40350	03H02
M40351	03H02
M40352	03H025
M40353	03H03
M40354	03H04
M40363	03H03
M40364	03H04
M40365	03H05
M40375	03H05
M40376	03H06

Spare Parts, included in delivery

For	Assembly screw	Tenon
		
M40310	90F0	90M1
M40320	90F0	90M2
M40321	90F1	90M2
M40330	90F0	90M3
M40331	90F1	90M3
M40332	90F2	90M3
M40341	90F1	90M4
M40342	90F2	90M4
M40343	90F3	90M4
M40350	90F0	90M5
M40351	90F1	90M5
M40352	90F2	90M5
M40353	90F3	90M5
M40354	90F4	90M5
M40363	90F3	90M6
M40364	90F4	90M6
M40365	90F5	90M6
M40375	90F5	90M7
M40376	90F6	90M7

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

Graflex to Graflex – Metric/ Inch



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	DCB	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
M40350070	00056782	G5	G0	70,0 2.756	50,0 1.969	8,0 0.315	16,0 0.630	100,0 3.937	0	PB	0,6 1.320
M40351080	00056784	G5	G1	80,0 3.150	60,0 2.362	11,0 0.433	20,0 0.787	110,0 4.331	0	PB	0,6 1.320
M40352100	00056786	G5	G2	100,0 3.937	80,0 3.150	14,0 0.551	25,0 0.984	130,0 5.118	0	PB	0,8 1.760
M40353120	00056788	G5	G3	120,0 4.724	100,0 3.937	18,0 0.709	32,0 1.260	150,0 5.906	0	PB	1,1 2.430
M40354150	00056790	G5	G4	150,0 5.906	130,0 5.118	22,0 0.866	40,0 1.575	180,0 7.087	0	PB	1,7 3.750
M40361090	00056794	G6	G1	90,0 3.543	64,0 2.520	11,0 0.433	20,0 0.787	130,0 5.118	0	PB	1,08 2.380
M40362110	00056796	G6	G2	110,0 4.331	84,0 3.307	14,0 0.551	25,0 0.984	150,0 5.906	0	PB	1,3 2.870
M40363120	00056798	G6	G3	120,0 4.724	94,0 3.701	18,0 0.709	32,0 1.260	160,0 6.299	0	PB	1,5 3.310
M40364150	00056800	G6	G4	150,0 5.906	124,0 4.882	22,0 0.866	40,0 1.575	190,0 7.480	0	PB	2,1 4.630
M40365190	00056808	G6	G5	190,0 7.480	164,0 6.457	28,0 1.102	50,0 1.969	230,0 9.055	0	PB	3,3 7.280


Accessories

For	Locking key
	
M40350070	03H02
M40351080	03H02
M40352100	03H025
M40353120	03H03
M40354150	03H04
M40361090	03H02
M40362110	03H025
M40363120	03H03
M40364150	03H04
M40365190	03H05

Spare Parts, included in delivery

For	Assembly screw	Tenon	
			Guide
M40350070	90F0	90M5	HSK-A
M40351080	90F1	90M5	
M40352100	90F2	90M5	
M40353120	90F3	90M5	
M40354150	90F4	90M5	HSK-E
M40361090	90F1	90M6	
M40362110	90F2	90M6	
M40363120	90F3	90M6	
M40364150	90F4	90M6	DIN
M40365190	90F5	90M6	
			BT JIS
			CAT
			Combimaster
			Graflex
			Seco Capto™
			Others
			Operating & setting accessories
			Shrinkfit

Graflex to Graflex – Metric/ Inch



—For ISO attribute explanation, see page 15


Designation	Item number	CTMS	CTWS	LPR	DCB	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch			kg lbs
M40356	00056791	G5	G6	55,0 2.165	36,0 1.417	63,0 2.480	85,0 3.346	0	PB	1,1 2.430
M40367	00056810	G6	G7	80,0 3.150	46,0 1.811	90,0 3.543	120,0 4.724	0	PB	3,5 7.720

Accessories

For	Locking key
M40356	03H06
M40367	03H10

Spare Parts, included in delivery

For	Assembly screw	Tenon
M40356	90F6	90M5
M40367	90F7	90M6



With through coolant channels
– Metric/ Inch

Graflex®

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series


Shrinkfit



Design 1



Design 2




– * Diameter BD on type 5524 is smaller than on type 5525
– For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant


Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	*	Design	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch						kg lbs
M55251816	02422059	G3	16,0 0.630	20,0 0.787	32,0 1.260	57,0 2.244	6,0 0.236	17,0 0.669		1	–	0	PB	0,2 0.440
M55252216R	02422060	G4R	16,0 0.630	25,0 0.984	38,0 1.496	66,0 2.598	8,0 0.315	17,0 0.669		1	–	0	PB	0,4 0.880
M55252222	02422061	G4	22,0 0.866	25,0 0.984	48,0 1.890	68,0 2.677	8,0 0.315	19,0 0.748		2	45,0	0	PB	0,5 1.100
M55252816	02422063	G5	16,0 0.630	32,0 1.260	38,0 1.496	79,0 3.110	12,0 0.472	17,0 0.669		1	45,0	0	PB	0,6 1.320
M55252822R	02422064	G5R	22,0 0.866	32,0 1.260	48,0 1.890	81,0 3.189	12,0 0.472	19,0 0.748		1	–	0	PB	0,7 1.540
M55252827	02422065	G5	27,0 1.063	32,0 1.260	60,0 2.362	83,0 3.268	12,0 0.472	21,0 0.827	*	2	45,0	0	PB	0,86 1.900
M55242827R	02449581	G5R	27,0 1.063	32,0 1.260	48,0 1.890	83,0 3.268	12,0 0.472	21,0 0.827	*	1	–	0	PB	0,7 1.540
M55253622	02422067	G6	22,0 0.866	40,0 1.575	48,0 1.890	99,0 3.898	14,0 0.551	19,0 0.748		1	45,0	0	PB	1,3 2.870
M55253622120	02422066	G6	22,0 0.866	120,0 4.724	48,0 1.890	179,0 7.047	94,0 3.701	19,0 0.748		1	30,0	0	PB	2,4 5.290
M55253627R	02422069	G6R	27,0 1.063	40,0 1.575	60,0 2.362	101,0 3.976	14,0 0.551	21,0 0.827		1	–	0	PB	1,3 2.870
M55253627120R	02422068	G6R	27,0 1.063	120,0 4.724	60,0 2.362	181,0 7.126	94,0 3.701	21,0 0.827		1	–	0	PB	3,1 6.830
M55253632	02422070	G6	32,0 1.260	40,0 1.575	78,0 3.071	104,0 4.094	14,0 0.551	24,0 0.945		2	30,0	0	PB	1,7 3.750
M55254627R	02422071	G7R	27,0 1.063	40,0 1.575	60,0 2.362	111,0 4.370	14,0 0.551	21,0 0.827		1	45,0	0	PB	2,0 4.410
M55254632	02422072	G7	32,0 1.260	40,0 1.575	78,0 3.071	114,0 4.488	14,0 0.551	24,0 0.945		1	45,0	0	PB	2,7 5.950

Accessories

Guide	Accessories		
	For	Bolt, through coolant	Spanner
			
HSK-A	M55242827R	5802712L	5812712
	M55251816	5801608L	5811608
	M55252216R	5801608L	5811608
	M55252222	5802210L	5812210
HSK-E	M55252816	5801608L	5811608
	M55252822R	5802210L	5812210
	M55252827	5802712L	5812712
	M55253622	5802210L	5812210
DIN	M55253622120	5802210L	5812210
	M55253627120R	5802712L	5812712
	M55253627R	5802712L	5812712
	M55253632	5803216L	5813216
BT JIS	M55254627R	5802712L	5812712
	M55254632	5803216L	5813216

Spare Parts, included in delivery

BT JIS	Spare Parts, included in delivery				
	For	Bolt	Screw	Tenon (machine side)	Tenon (workpiece side)
					
CAT	M55242827R	5802712	950D0512	90M5R	16C127
	M55251816	5801608	950D0308	90M3	16C116
	M55252216R	5801608	950D0310	90M4R	16C10810164
	M55252222	5802210	950D0414	90M4	16C11012206
Combimaster	M55252816	5801608	950D0310	90M5	16C10810164
	M55252822R	5802210	950D0414	90M5R	16C11012206
	M55252827	5802712	950D0516	90M5	16C11214243
	M55253622	5802210	950D0414	90M6	16C11012206
Graflex	M55253622120	5802210	950D0414	90M6	16C11012206
	M55253627120R	5802712	950D0516	90M6R	16C11214243
	M55253627R	5802712	950D0516	90M6R	16C11214243
	M55253632	5803216	950D0516	90M6	16C2141421
Seco Capto™	M55254627R	5802712	950D0516	90M7R	16C11214243
	M55254632	5803216	950D0516	90M7	16C2141421


Others

Operating & setting accessories

Shrinkfit

With through coolant channels
– Inch

Graflex®




–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	BHTA°	RFID hole	Balan- cing	Weight
			inch	inch	inch	inch	inch	inch				lbs
M552528075	14000757	G5	0.750	1.260	1.750	3.130	0.472	0.689	45,0	0	PB	1.370
M552536100	14000760	G6	1.000	1.575	2.250	3.839	0.551	0.689	45,0	0	PB	2.840
M552546150	14000763	G7	1.500	2.000	3.500	4.909	0.976	0.941	45,0	0	PB	7.500

Spare Parts, included in delivery

For	Bolt	Screw	Tenon (machine side)	Tenon (workpiece side)
				
M552528075	58211905	950D0312	90M5	16C11905
M552536100	58212540	950D0416	90M6	16C12540
M552546150	58213810	950D0616	90M7	16C23810

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

Flange mounting – DIN 6357/ DIN 2079
– Metric/ Inch



–DMM 40, with additional central thread and bolt according to ISO 3937
–For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	LSC	BD	OAL	DBC	TDZ	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
M5694640	00076744	G7	40,0 1.575	46,0 1.811	27,0 1.063	89,0 3.504	123,0 4.843	66,7 2.626	M12x1.75	0	PB	3,1 6.830
M5694660	00076745	G7	60,0 2.362	54,0 2.126	40,0 1.575	129,0 5.079	144,0 5.669	101,6 4.000	M16x2	0	PB	5,6 12.350

Accessories

For	Spanner
M5694640	5814020
M5694660	-

Spare Parts, included in delivery

For	Bolt	Screw	Tenon (machine side)	Tenon (workpiece side)
				
M5694640	5804020	950D0616	90M7	16C34040
M5694660	-	950D1225	90M7	16C35060

– Metric/ Inch

Graflex®

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster


Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit




– Best suited for Seco disc mill cutters Type A
– For ISO attribute explanation, see page 15


Spare parts:
1 = Slide rod
2 = Screw

Designation	Item number	CTMS	DMM	LF	BD	LB	OAL	FLGT	LSCN	LSCX	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
M56562222	00076737	G4	22,0 0.866	60,0 2.362	35,0 1.378	43,0 1.693	84,0 3.307	4,0 0.157	0,0 0.0	12,0 0.472	0	PB	0,6 1.320
M56562827	00076738	G5	27,0 1.063	65,0 2.559	42,0 1.654	45,0 1.772	95,0 3.740	5,0 0.197	0,0 0.0	15,0 0.591	0	PB	0,95 2.090
M5656283212	02422074	G5	32,0 1.260	80,0 3.150	48,0 1.890	60,0 2.362	110,0 4.331	6,0 0.236	0,0 0.0	24,0 0.945	0	PB	1,32 2.910
M56563640	00076741	G6	40,0 1.575	110,0 4.331	58,0 2.283	84,0 3.307	150,0 5.906	7,0 0.276	0,0 0.0	30,0 1.181	0	PB	2,8 6.170
M56564650	00076743	G7	50,0 1.969	130,0 5.118	72,0 2.835	104,0 4.094	180,0 7.087	8,0 0.315	0,0 0.0	32,0 1.260	0	PB	5,4 11.900


Spare Parts, included in delivery

For	Screw	Slide rod	Tenon
			
M56562222	950D0860	565622	90M4
M56562827	950D1070	565627	90M5
M5656283212	950D1290	56563202	90M5
M56563640	950D16110	565640	90M6
M56564650	950D16120	565650	90M7


DIN 1835 Form B/ DIN 6535 Form HB
– Metric/ Inch



Design 1



Design 2



–Weldon ØDCBN-DCBX 20, 25, 32 and 40 mm / 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
–For ISO attribute explanation, see page 15


Spare parts:
1 = Locking screw 1
2 = Locking screw 2

Designation	Item number	CTMS	DCBN-DCBX	LPR	LSC	LB	BD	OAL	LFS	Design	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
M5842806	00076748	G5	6,0 0.236	45,0 1.772	27,0 1.063	25,0 0.984	25,0 0.984	75,0 2.953	27,5 1.083	1	0	PB	0,6 1.320
M5842808	00076749	G5	8,0 0.315	45,0 1.772	30,0 1.181	25,0 0.984	28,0 1.102	75,0 2.953	27,5 1.083	1	0	PB	0,52 1.150
M5842810	00076750	G5	10,0 0.394	55,0 2.165	36,0 1.417	35,0 1.378	35,0 1.378	85,0 3.346	35,5 1.398	1	0	PB	0,7 1.540
M5842812	00076751	G5	12,0 0.472	60,0 2.362	43,0 1.693	40,0 1.575	42,0 1.654	90,0 3.543	38,0 1.496	1	0	PB	0,8 1.760
M5842814	00076752	G5	14,0 0.551	60,0 2.362	43,0 1.693	40,0 1.575	44,0 1.732	90,0 3.543	38,0 1.496	1	0	PB	0,81 1.790
M5842816	00076753	G5	16,0 0.630	65,0 2.559	46,0 1.811	45,0 1.772	48,0 1.890	95,0 3.740	41,5 1.634	1	0	PB	1,0 2.200
M5842818	00076754	G5	18,0 0.709	65,0 2.559	46,0 1.811	45,0 1.772	50,0 1.969	95,0 3.740	41,5 1.634	1	0	PB	0,96 2.120
M5842820	00071723	G5	20,0 0.787	65,0 2.559	48,0 1.890	45,0 1.772	52,0 2.047	95,0 3.740	40,5 1.594	1	0	PB	1,0 2.200
M5843616	00076761	G6	16,0 0.630	65,0 2.559	46,0 1.811	39,0 1.535	48,0 1.890	105,0 4.134	41,5 1.634	1	0	PB	1,4 3.090
M5843620	00076763	G6	20,0 0.787	65,0 2.559	48,0 1.890	39,0 1.535	52,0 2.047	105,0 4.134	40,5 1.594	1	0	PB	1,4 3.090
M5843625	00072478	G6	25,0 0.984	80,0 3.150	54,0 2.126	54,0 2.126	63,0 2.480	120,0 4.724	56,5 2.224	2	0	PB	1,9 4.190
M5843632	00071725	G6	32,0 1.260	80,0 3.150	58,0 2.283	54,0 2.126	72,0 2.835	120,0 4.724	56,5 2.224	2	0	PB	2,1 4.630
M5844640	00076767	G7	40,0 1.575	100,0 3.937	68,0 2.677	74,0 2.913	80,0 3.150	150,0 5.906	70,5 2.776	2	0	PB	4,0 8.820

Spare Parts, included in delivery

For	Locking screw	Locking screw, reduced	Tenon	
				Guide
M5842806	951C0610	–	90M5	HSK-A
M5842808	951C0810	–	90M5	
M5842810	951C1012	–	90M5	
M5842812	951C1216	–	90M5	
M5842814	951C1216	–	90M5	HSK-E
M5842816	951C1416	–	90M5	
M5842818	951C1416	–	90M5	
M5842820	951C1616	–	90M5	
M5843616	951C1416	–	90M6	DIN
M5843620	951C1616	–	90M6	
M5843625	951C1820	–	90M6	
M5843632	951C2020	951C2017	90M6	
M5844640	951C2020	–	90M7	BT JIS
				CAT
				Combimaster
				Graflex
				Seco Capto™
				Others
				Operating & setting accessories
				Shrinkfit

– Metric/ Inch



–Run-out 8 µm maximum at 3 x ØDCBN-DCBX
 –For ER HP collets type 5672, see page(s) 389, 390, 391-397
 –For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	RFID hole	Balan- cing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
G5-ERHP25-060	10359270	G5	1,0 0.039	16,0 0.630	HP 25	60,0 2.362	40,0 1.575	40,0 1.575	90,0 3.543	40,0 1.575	0	PB	0,7 1.540
G6-ERHP32-070	10359271	G6	2,0 0.079	20,0 0.787	HP 32	70,0 2.756	50,0 1.969	50,0 1.969	110,0 4.331	44,0 1.732	0	PB	1,4 3.090

Accessories


For	Key	Socket	Torque key
			
ERHP25	03LME1418260	03ER040	03DYE010100B
ERHP32	03LME1418370	03ER050	03DYE040200

Spare Parts, included in delivery

For	Nut
	
ERHP25	08B567225C
ERHP32	08B567232C

Conventional type
– Metric/ Inch

Graflex®



–For reduction sleeves, see page(s) 381, 382
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
G5-HC20-090	10137322	G5	20,0 0.787	90,0 3.543	70,0 2.756	47,0 1.850	52,0 2.047	50,0 1.969	42,0 1.654	120,0 4.724	38,0 1.496	48,0 1.890	M10x1.5	30,0	0	PB	1,2 2.650
G6-HC25-100	10137323	G6	25,0 0.984	100,0 3.937	74,0 2.913	50,0 1.969	58,0 2.283	63,0 2.480	58,0 2.283	140,0 5.512	42,0 1.654	52,0 2.047	M10x1.5	45,0	0	PB	2,3 5.070
G6-HC32-100	10137324	G6	32,0 1.260	100,0 3.937	74,0 2.913	–	63,0 2.480	–	64,0 2.520	140,0 5.512	37,0 1.457	62,0 2.441	–	–	0	PB	2,3 5.070

Accessories

For	Key
G5	03MS04C
G6	03MS04C



Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit


ISO 15488
– Metric/ Inch



–For ER extensions and ER collets, see page(s) 362, 363, 399, 400, 401, 402
–For ER sealing rings, see page(s) 410, 411
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	LFN	LF	TDZ	RFID hole	Balancing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
G3-ER25-070-N1	10229745	G3	1,0 0.039	16,0 0.630	ER 25	70,0 2.756	32,0 1.260	35,0 1.378	90,0 3.543	56,0 2.205	12,0 0.472	32,0 1.260	M10X1.5	0	PB	0,4 0.880
G5-ER25-060	10229746	G5	1,0 0.039	16,0 0.630	ER 25	60,0 2.362	42,0 1.654	42,0 1.654	90,0 3.543	40,0 1.575	6,0 0.236	22,0 0.866	M12X1.75	0	PB	0,7 1.540
G5-ER32-075	10229747	G5	2,0 0.079	20,0 0.787	ER 32	75,0 2.953	50,0 1.969	50,0 1.969	105,0 4.134	55,0 2.165	15,0 0.591	35,0 1.378	M12X1.75	0	PB	1,0 2.200
G6-ER25-060	10229748	G6	1,0 0.039	16,0 0.630	ER 25	60,0 2.362	42,0 1.654	42,0 1.654	100,0 3.937	34,0 1.339	6,0 0.236	22,0 0.866	M12X1.75	0	PB	1,1 2.430
G6-ER32-075	10229749	G6	2,0 0.079	20,0 0.787	ER 32	75,0 2.953	50,0 1.969	50,0 1.969	115,0 4.528	49,0 1.929	17,0 0.669	35,0 1.378	M12X1.75	0	PB	1,4 3.090
G6-ER40-085	10229750	G6	3,0 0.118	26,0 1.024	ER 40	85,0 3.346	63,0 2.480	63,0 2.480	125,0 4.921	59,0 2.323	20,0 0.787	40,0 1.575	M12X1.75	0	PB	1,7 3.750


Accessories

For	Seal nut	Spanner
		
G3-ER25-070-N1	–	03B545025
G5-ER25-060	08B587525IC	03B587525
G5-ER32-075	08B587532IC	03B587532
G6-ER25-060	08B587525IC	03B587525
G6-ER32-075	08B587532IC	03B587532
G6-ER40-085	08B587540IC	03B587540

Spare Parts, included in delivery

For	Nut	Stop screw	Tenon
			
G3-ER25-070-N1	08B587525M	19LRC1020	90M3
G5-ER25-060	08B587525X	19LRC1225	90M5C
G5-ER32-075	08B587532X	19LRC1225	90M5
G6-ER25-060	08B587525X	19LRC1225	90M62
G6-ER32-075	08B587532X	19LRC1225	90M6
G6-ER40-085	08B587540X	19LRC1225	90M6

– Metric/ Inch



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	OAL	LPR	LB	BD1	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
M50852813L	00055942	G5	1,0 0.039	13,0 0.512	130,0 5.118	100,0 3.937	80,0 3.150	43,0 1.693	0	PB	0,92 2.030
M50853616L	00055943	G6	2,5 0.098	16,0 0.630	160,0 6.299	120,0 4.724	94,0 3.701	56,0 2.205	0	PB	2,1 4.630

Spare Parts, included in delivery

For	Tenon
	
M50852813L	90M5
M50853616L	90M6

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit




Seco Capto™

Seco Capto™ is a leading quick-change modular tooling system for quick setup and replacement of cutting edge holders. The Seco Capto™ modular tooling range uses Polygonal Shank Coupling (PSC) in accordance with ISO 26623 and features a self-locking taper joint.

- Tool holders range, such as Shrinkfit, collet chuck and shell mill
- Seco Capto™ basic arbors with HSK, DIN, BT connections
- Seco Capto™ cassette for greater reliability and insert clamping

ISO 26623-1-PSC/ ISO 26623-2-PSC



Machine side catalogue designation	Hole for RFID carrier**	d ₁	d ₂	d ₄	d ₁₁	Dm	b ₁	b ₂	l ₁	l ₂	l _{3 min}	l ₅	l ₆	l ₁₆	h ₁	h ₃	r ₁
		mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
C3	No**	32 1.260	15 0.591	M12	5 0.197	22 0.866	39 1.535	28,3 1.114	2,5 0.098	19 0.748	15 0.591	3,2 0.126	6 0.236	9 0.354	9 0.354	5,4 0.213	3 0.118
C4	No**	40 1.575	18 0.709	M14	5 0.197	28 1.102	46 1.811	35,3 1.390	2,5 0.098	24 0.945	20 0.787	4 0.157	8 0.315	12 0.472	11 0.433	5,2 0.205	3 0.118
C5	**	50 1.969	21 0.827	M16	7 0.276	35 1.378	59,3 2.335	44,4 1.748	3 0.118	30 1.181	20 0.787	5,3 0.209	10 0.394	12 0.472	14 0.551	5,1 0.201	4 0.157
C6	**	63 2.480	28 1.102	M20	7 0.276	44 1.732	70,7 2.783	55,8 2.197	3 0.118	38 1.496	22 0.866	6,2 0.244	12 0.472	12 0.472	18 0.709	5 0.197	5 0.197
C8	**	80 3.150	32 1.260	M20	7 0.276	55 2.165	86 3.386	71,1 2.799	3 0.118	48 1.890	30 1.181	8 0.315	12 0.472	12 0.472	22,2 0.874	4,9 0.193	6 0.236

Workpiece side catalogue designation	Hole for RFID carrier**	d _{1 min}	d ₃	Dm	l ₁	l ₂	l ₃	l ₄
		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
C3	No	32 1.260	2 0.079	22 0.866	2,3 0.091	18,4 0.724	16,5 0.650	9,4 0.370
C4	No	40 1.575	2,5 0.098	28 1.102	2,3 0.091	23,4 0.921	21 0.827	11,5 0.453
C5	No	50 1.969	3 0.118	35 1.378	2,8 0.110	29,4 1.157	26 1.024	14,5 0.571
C6	**	63 2.480	4 0.157	44 1.732	2,8 0.110	37,4 1.472	33,5 1.319	18,5 0.728
C8	**	80 3.150	5 0.197	55 2.165	2,8 0.110	47,4 1.866	43 1.693	22,8 0.898

Note: These machine side and workpiece side dimensions are applied to all the holders shown in the Product pages.

* The Seco Capto™ machine side of short extensions can only be hold by spindles with segment clamping (not with center bolt clamping). The Seco Capto™ machine side of short reducers can only be hold by spindles with segment clamping (not with center bolt clamping).

** In order to know if a hole for RFID carrier exists, see 'RFID hole' column in Product pages: 1= hole for RFID carrier available, if required a carrier can be fitted on request, please enquire.

0= hole for RFID carrier not available, if required hole can be machined and a carrier can be fitted on request, please enquire.

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Seco Capto™ – ISO 26623-2 – Metric/ Inch



DIN 2080




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	BD	OAL	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch			kg lbs
C3-390.00-40030	75039844	DIN(2080)40	C3	30,0 1.181	18,4 0.724	32,0 1.260	123,4 4.858	0	—	0,9 1.980
C4-390.00-40030	75039848	DIN(2080)40	C4	30,0 1.181	18,4 0.724	40,0 1.575	123,4 4.858	0	—	1,0 2.200
C4-390.00-40060	75039849	DIN(2080)40	C4	60,0 2.362	48,4 1.906	40,0 1.575	153,4 6.039	0	—	1,08 2.380
C5-390.00-40030	75039852	DIN(2080)40	C5	30,0 1.181	18,4 0.724	50,0 1.969	123,4 4.858	0	—	0,81 1.790
C6-390.00-40075	00048158	DIN(2080)40	C6	75,0 2.953	0,0 —	63,0 2.480	168,4 6.630	0	—	1,82 4.010
C3-390.00-50030	75039846	DIN(2080)50	C3	30,0 1.181	14,8 0.583	32,0 1.260	156,8 6.173	0	—	2,5 5.510
C3-390.00-50060	75039847	DIN(2080)50	C3	60,0 2.362	44,8 1.764	32,0 1.260	186,8 7.354	0	—	2,5 5.510
C4-390.00-50030	75039850	DIN(2080)50	C4	30,0 1.181	14,8 0.583	40,0 1.575	156,8 6.173	0	—	2,5 5.510
C4-390.00-50060	75039851	DIN(2080)50	C4	60,0 2.362	44,8 1.764	40,0 1.575	186,8 7.354	0	—	2,5 5.510
C5-390.00-50030	75039854	DIN(2080)50	C5	30,0 1.181	14,8 0.583	50,0 1.969	156,8 6.173	0	—	2,62 5.780
C5-390.00-50070	75039855	DIN(2080)50	C5	70,0 2.756	54,8 2.157	50,0 1.969	196,8 7.748	0	—	3,29 7.250
C6-390.00-50030	75039856	DIN(2080)50	C6	30,0 1.181	14,8 0.583	63,0 2.480	156,8 6.173	0	—	2,56 5.640
C6-390.00-50080	75039857	DIN(2080)50	C6	80,0 3.150	64,8 2.551	63,0 2.480	206,8 8.142	0	—	3,27 7.210
C8-390.00-50070	75039858	DIN(2080)50	C8	70,0 2.756	54,8 2.157	80,0 3.150	196,8 7.748	0	—	3,8 8.380
C8-390.00-50120	75039859	DIN(2080)50	C8	120,0 4.724	104,8 4.126	80,0 3.150	246,8 9.717	0	—	5,6 12.350


Accessories

For	Extension key	Spanner
		
C3	5680015-05	5680065-13
C4	5680015-05	5680065-10
C5	5680015-01	5680065-11
C6-400	5680015-01	5680065-12
C6-500	5680015-02	5680065-12
C8	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Retaining nut
		
C3	5512063-10	5512091-04
C4	5512063-07	5512091-03
C5	5512063-08	5512091-01
C6-400	5512063-13	5512091-02
C6-500	5512063-09	5512091-02
C8	5512063-09	5512091-02

Accessories / Spare Parts



Accessories:
3 = Extension key
4 = Spanner

Spare parts:
1 = Center screw
2 = Retaining nut

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

Seco Capto™ – ISO 26623-2 – Inch



CAT / ASME B5.50-2009-ADB




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	BD	BD1	OAL	Design	RFID hole	Balancing	Weight
				inch	inch	inch	inch	inch				lbs
C3-A390B.45-40060	02925929	CAT40 ADB	C3	2.362	1.610	1.260	1.260	5.055	2	0	PB	2.200
C4-A390B.45-40030	02925932	CAT40 ADB	C4	1.181	0.429	1.575	1.575	3.874	2	0	PB	1.980
C4-A390B.45-40060	02925933	CAT40 ADB	C4	2.362	1.610	1.575	1.575	5.055	2	0	PB	2.430
C5-A390B.45-40040	02925935	CAT40 ADB	C5	1.575	0.823	1.969	1.969	4.268	2	0	PB	2.200
C5-A390B.45-40080	02925936	CAT40 ADB	C5	3.150	2.398	1.969	1.969	5.843	2	0	PB	3.310
C6-A390B.45-40085	02925939	CAT40 ADB	C6	3.346	1.378	2.480	2.480	6.039	2	0	PB	4.190
C3-A390B.45-50030	02925930	CAT50 ADB	C3	1.181	0.429	1.260	1.260	5.185	2	0	PB	6.390
C3-A390B.45-50060	02925931	CAT50 ADB	C3	2.362	1.610	1.260	1.260	6.366	2	0	PB	5.970
C4-A390B.45-50030	02925948	CAT50 ADB	C4	1.181	0.429	1.575	1.575	5.185	2	0	PB	5.780
C4-A390B.45-50060	02925934	CAT50 ADB	C4	2.362	1.610	1.969	1.575	6.366	2	0	PB	6.610
C5-A390B.45-50030	02925937	CAT50 ADB	C5	1.181	0.429	1.969	1.969	5.185	2	0	PB	5.510
C5-A390B.45-50070	02925938	CAT50 ADB	C5	2.756	2.004	1.969	1.969	6.760	2	0	PB	6.610
C6-A390B.45-50030	02925940	CAT50 ADB	C6	1.181	0.429	2.480	2.480	5.185	2	0	PB	5.510
C6-A390B.45-50080	02925941	CAT50 ADB	C6	3.150	2.398	2.480	2.480	7.154	2	0	PB	7.940
C8-A390B.45-50070	02925942	CAT50 ADB	C8	2.756	2.004	3.150	3.150	6.760	2	0	PB	7.940
C8-A390B.45-50120	02925943	CAT50 ADB	C8	4.724	3.972	3.150	3.150	8.728	2	0	PB	12.350


Accessories

For	Extension key	Spanner
		
CAT40/ C3	5680015-05	5680065-13
CAT40/ C4	5680015-05	5680065-10
CAT40/ C5	5680015-01	5680065-11
CAT40/ C6	5680015-01	5680065-12
CAT50/ C3	5680015-05	5680065-13
CAT50/ C4-50030	5680015-05	5680065-10
CAT50/ C4-50060	5680015-05	5680065-10
CAT50/ C5	5680015-01	5680065-11
CAT50/ C6	5680015-02	5680065-12
CAT50/ C8	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Plug	Retaining nut
			
CAT40/ C3	5512063-10	564301701	5512091-04
CAT40/ C4	5512063-07	564301701	5512091-03
CAT40/ C5	5512063-08	564301701	5512091-01
CAT40/ C6	5512063-13	564301701	5512091-02
CAT50/ C3	5512063-10	564301702	5512091-04
CAT50/ C4-50030	5512063-07	564301701	5512091-03
CAT50/ C4-50060	5512063-07	564301702	5512091-03
CAT50/ C5	5512063-08	564301702	5512091-01
CAT50/ C6	5512063-09	564301702	5512091-02
CAT50/ C8	5512063-09	564301702	5512091-02

Accessories / Spare Parts



Accessories:
4 = Extension key
5 = Spanner

Spare parts:
1 = Center screw
2 = Retaining nut
3 = Plugs (dowels)

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

Seco Capto™ – ISO 26623-2 – Metric/ Inch


HSK-A/ ISO12164-1-HSK-A



Design 1






Design 2




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	LB1	BD	BD1	OAL	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
HA06-C3-032-075	10197962	HSK-A63	C3	75,0 2.953	49,0 1.929	—	32,0 1.260	—	107,0 4.213	1	1	PB	0,9 1.980
HA06-C4-040-080	10197964	HSK-A63	C4	80,0 3.150	54,0 2.126	—	40,0 1.575	—	112,0 4.409	1	1	PB	1,1 2.430
HA06-C5-050-090	10197966	HSK-A63	C5	90,0 3.543	64,0 2.520	—	50,0 1.969	—	122,0 4.803	1	1	PB	1,3 2.870
HA10-C3-032-080	10197961	HSK-A100	C3	80,0 3.150	51,0 2.008	—	32,0 1.260	—	130,0 5.118	1	1	PB	2,5 5.510
HA10-C4-040-090	10197963	HSK-A100	C4	90,0 3.543	61,0 2.402	—	40,0 1.575	—	140,0 5.512	1	1	PB	2,5 5.510
HA10-C5-050-100	10197965	HSK-A100	C5	100,0 3.937	71,0 2.795	—	50,0 1.969	—	150,0 5.906	1	1	PB	2,9 6.390
HA10-C6-063-110	10197967	HSK-A100	C6	110,0 4.331	81,0 3.189	—	63,0 2.480	—	160,0 6.299	1	1	PB	3,6 7.940
HA10-C8-080-120	10197968	HSK-A100	C8	120,0 4.724	91,0 3.583	—	80,0 3.150	—	170,0 6.693	1	1	PB	4,8 10.580
HSKA125-C6-120	03229625	HSK-A125	C6	120,0 4.724	91,0 3.583	—	63,0 2.480	—	183,0 7.205	1	1	PB	5,2 11.460
HSKA125-C6-120-V	03229626	HSK-A125	C6	120,0 4.724	91,0 3.583	30,0 1.181	63,0 2.480	108,0 4.252	183,0 7.205	2	1	PB	6,4 14.110
HSKA125-C8-130	03229627	HSK-A125	C8	130,0 5.118	101,0 3.976	—	80,0 3.150	—	193,0 7.598	1	1	PB	6,5 14.330
HSKA125-C8-130-V	03229628	HSK-A125	C8	130,0 5.118	101,0 3.976	30,0 1.181	80,0 3.150	105,0 4.134	193,0 7.598	2	1	PB	7,8 17.200


Accessories

For	Extension key	Key	Spanner
			
HA06-C3-032-075	5680015-05	5680094-04	5680065-13
HA06-C4-040-080	5680015-05	5680094-04	5680065-10
HA06-C5-050-090	5680015-01	5680094-04	5680065-11
HA10-C3-032-080	5680015-05	5680094-06	5680065-13
HA10-C4-040-090	5680015-05	5680094-06	5680065-10
HA10-C5-050-100	5680015-01	5680094-06	5680065-11
HA10-C6-063-110	5680015-02	5680094-06	5680065-12
HA10-C8-080-120	5680015-02	5680094-06	5680065-12
HSKA125-C6-120	5680015-02	5680094-07	5680065-12
HSKA125-C6-120-V	5680015-02	5680094-07	5680065-12
HSKA125-C8-130	5680015-02	5680094-07	5680065-12
HSKA125-C8-130-V	5680015-02	5680094-07	5680065-12

Spare Parts, included in delivery

For	Centre screw	Coolant tube	Retaining nut
			
HA06-C3-032-075	5512067-01	5692020-04	5512091-04
HA06-C4-040-080	5512067-02	5692020-04	5512091-03
HA06-C5-050-090	5512067-03	5692020-04	5512091-01
HA10-C3-032-080	5512067-01	5692020-06	5512091-04
HA10-C4-040-090	5512067-02	5692020-06	5512091-03
HA10-C5-050-100	5512067-03	5692020-06	5512091-01
HA10-C6-063-110	5512067-04	5692020-06	5512091-02
HA10-C8-080-120	5512067-04	5692020-06	5512091-02
HSKA125-C6-120	5512063-09	5692020-07	5512091-02
HSKA125-C6-120-V	5512063-09	5692020-07	5512091-02
HSKA125-C8-130	5512063-09	5692020-07	5512091-02
HSKA125-C8-130-V	5512063-09	5692020-07	5512091-02

Accessories / Spare Parts




Accessories:
2 = Extension key
4 = Spanner
6 = Key for coolant tube

Spare parts:
1 = Center screw
3 = Retaining nut
5 = Coolant tube*

*A specific coolant tube is delivered together with each HSK-A to Seco Capto™ holder

Seco Capto™ – ISO 26623-2
– Metric/ Inch



HSK-T/ ISO12164-3-HSK-T




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch			kg lbs
C4-390.411-63080	02786511	HSK-T63	C4	80,0 3.150	54,0 2.126	40,0 1.575	112,0 4.409	1	—	1,1 2.430
C5-390.411-63090	02786520	HSK-T63	C5	90,0 3.543	64,0 2.520	50,0 1.969	122,0 4.803	1	—	1,5 3.310
C4-390.411-100090	02786519	HSK-T100	C4	90,0 3.543	61,0 2.402	40,0 1.575	140,0 5.512	1	—	2,6 5.730
C5-390.411-100100	02786521	HSK-T100	C5	100,0 3.937	71,0 2.795	50,0 1.969	150,0 5.906	1	—	3,0 6.610
C6-390.411-100110	02786522	HSK-T100	C6	110,0 4.331	81,0 3.189	63,0 2.480	160,0 6.299	1	—	3,6 7.940
C8-390.411-100120	02786523	HSK-T100	C8	120,0 4.724	91,0 3.583	80,0 3.150	170,0 6.693	1	—	4,8 10.580


Accessories

For	Extension key	Key	Spanner
			
C4-390.411-100090	5680015-05	5680094-06	5680065-10
C4-390.411-63080	5680015-05	5680094-04	5680065-10
C5-390.411-100100	5680015-01	5680094-06	5680065-11
C5-390.411-63090	5680015-01	5680094-04	5680065-11
C6-390.411-100110	5680015-02	5680094-06	5680065-12
C8-390.411-100120	5680015-02	5680094-06	5680065-12

Spare Parts, included in delivery

For	Centre screw	Coolant tube	Retaining nut
			
C4-390.411-100090	5512063-07	20E9306	5512091-03
C4-390.411-63080	5512063-07	5692020-04	5512091-03
C5-390.411-100100	5512063-08	20E9306	5512091-01
C5-390.411-63090	5512063-08	5692020-04	5512091-01
C6-390.411-100110	5512063-09	5692020-06	5512091-02
C8-390.411-100120	5512063-09	5692020-06	5512091-02

Accessories / Spare Parts



Accessories:
2 = Extension key
4 = Spanner
6 = Key for coolant tube


Spare parts:
1 = Center screw
3 = Retaining nut
5 = Coolant tube*

*A specific coolant tube is delivered together with each HSK-A to Seco Capto™ holder

Guide
HSK-A
HSK-E
DIN
BT JIS
CAT
Combimaster
Graflex
Seco Capto™
Others
Operating & setting accessories
Shrinkfit

Seco Capto™ – ISO 26623-2 – Metric/ Inch



DIN 69871-ADB




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch			kg lbs
C3-390B.140-40030	02924104	DIN40 ADB	C3	30,0 1.181	10,9 0.429	32,0 1.260	98,4 3.874	0	PB	0,8 1.760
C3-390B.140-40060	02924105	DIN40 ADB	C3	60,0 2.362	40,9 1.610	32,0 1.260	128,4 5.055	0	PB	0,9 1.980
C4-390B.140-40030	02924108	DIN40 ADB	C4	30,0 1.181	10,9 0.429	40,0 1.575	98,4 3.874	0	PB	0,8 1.760
C4-390B.140-40060	02924109	DIN40 ADB	C4	60,0 2.362	40,9 1.610	40,0 1.575	128,4 5.055	0	PB	1,1 2.430
C5-390B.140-40040	02924112	DIN40 ADB	C5	40,0 1.575	20,9 0.823	50,0 1.969	108,4 4.268	0	PB	0,9 1.980
C5-390B.140-40080	02924113	DIN40 ADB	C5	80,0 3.150	60,9 2.398	50,0 1.969	148,4 5.843	0	PB	1,5 3.310
C6-390B.140-40085	02924116	DIN40 ADB	C6	85,0 3.346	65,9 2.594	63,0 2.480	153,4 6.039	0	PB	1,8 3.970
C3-390B.140-50030	02924106	DIN50 ADB	C3	30,0 1.181	10,9 0.429	32,0 1.260	131,7 5.185	0	PB	2,6 5.730
C3-390B.140-50060	02924107	DIN50 ADB	C3	60,0 2.362	40,9 1.610	32,0 1.260	161,7 6.366	0	PB	2,7 5.950
C4-390B.140-50030	02924110	DIN50 ADB	C4	30,0 1.181	10,9 0.429	40,0 1.575	131,7 5.185	0	PB	2,6 5.730
C4-390B.140-50060	02924111	DIN50 ADB	C4	60,0 2.362	40,9 1.610	40,0 1.575	161,7 6.366	0	PB	2,8 6.170
C5-390B.140-50030	02924114	DIN50 ADB	C5	30,0 1.181	10,9 0.429	50,0 1.969	131,7 5.185	0	PB	2,6 5.730
C5-390B.140-50070	02924115	DIN50 ADB	C5	70,0 2.756	50,9 2.004	50,0 1.969	171,7 6.760	0	PB	3,1 6.830
C6-390B.140-50030	02924117	DIN50 ADB	C6	30,0 1.181	10,9 0.429	63,0 2.480	131,7 5.185	0	PB	2,4 5.290
C6-390B.140-50080	02924118	DIN50 ADB	C6	80,0 3.150	60,9 2.398	63,0 2.480	181,7 7.154	0	PB	3,6 7.940
C8-390B.140-50070	02924119	DIN50 ADB	C8	70,0 2.756	50,9 2.004	80,0 3.150	171,7 6.760	0	PB	3,7 8.160
C8-390B.140-50120	02924120	DIN50 ADB	C8	120,0 4.724	100,9 3.972	80,0 3.150	221,7 8.728	0	PB	5,5 12.130


Accessories

For	Extension key	Spanner
		
C3-400	5680015-05	5680065-13
C3-500	5680015-05	5680065-13
C4-400	5680015-05	5680065-10
C4-500	5680015-05	5680065-10
C5-400	5680015-01	5680065-11
C5-500	5680015-01	5680065-11
C6-400	5680015-01	5680065-12
C6-500	5680015-02	5680065-12
C8	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Plug	Retaining nut
			
C3-400	5512063-10	564301701	5512091-04
C3-500	5512063-10	564301702	5512091-04
C4-400	5512063-07	564301701	5512091-03
C4-500	5512063-07	564301702	5512091-03
C5-400	5512063-08	564301701	5512091-01
C5-500	5512063-08	564301702	5512091-01
C6-400	5512063-13	564301701	5512091-02
C6-500	5512063-09	564301702	5512091-02
C8	5512063-09	564301702	5512091-02

Accessories / Spare Parts



Accessories:
4 = Extension key
5 = Spanner

Spare parts:
1 = Center screw
2 = Retaining nut
3 = Plugs (dowels)

Guide

HSK-A

HSK-E

DIN

BT IIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

Seco Capto™ – ISO 26623-2 – Metric/ Inch



DIN Taper-Face-ADB




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	BD	OAL	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch			kg lbs
E316951915050	03030258	DIN40 TF ADB	C5	50,0 1.969	30,9 1.217	50,0 1.969	118,4 4.661	1	PB	1,1 2.430
E317151915070	03030264	DIN50 TF ADB	C5	70,0 2.756	50,9 2.004	50,0 1.969	171,7 6.760	1	PB	3,1 6.830
E317151916350	03030262	DIN50 TF ADB	C6	50,0 1.969	30,9 1.217	63,0 2.480	151,7 5.972	0	—	2,9 6.390
E3171519163100	03030265	DIN50 TF ADB	C6	100,0 3.937	80,9 3.185	63,0 2.480	201,7 7.941	1	PB	4,1 9.040
E317151918070	03030263	DIN50 TF ADB	C8	70,0 2.756	50,9 2.004	80,0 3.150	171,7 6.760	0	—	3,9 8.600
E3171519180120	03030266	DIN50 TF ADB	C8	120,0 4.724	100,9 3.972	80,0 3.150	221,7 8.728	0	—	5,6 12.350


Accessories

For	Extension key	Spanner
		
DIN40 TF/ C5	5680015-01	5680065-11
DIN50 TF/ C5	5680015-01	5680065-11
DIN50 TF/ C6-C8	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Plug	Retaining nut
			
DIN40 TF/ C5	5512063-08	564301701	5512091-01
DIN50 TF/ C5	5512063-08	564301702	5512091-01
DIN50 TF/ C6-C8	5512063-09	564301702	5512091-02

Accessories / Spare Parts



Accessories:
4 = Extension key
5 = Spanner

Spare parts:
1 = Center screw
2 = Retaining nut
3 = Plugs (dowels)


Guide
HSK-A
HSK-E
DIN
BT JIS
CAT
Combimaster
Graflex
Seco Capto™
Others
Operating & setting accessories
Shrinkfit

Seco Capto™ – ISO 26623-2 – Metric/ Inch


BT JIS B 6339



Design 1





Design 2




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	BD	OAL	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch				kg lbs
C3-390.55-30030	75039807	BT30 AD	C3	30,0 1.181	8,0 0.315	32,0 1.260	78,4 3.087	1	0	PB	0,53 1.170
C3-390.55-30060	75039808	BT30 AD	C3	60,0 2.362	38,0 1.496	32,0 1.260	108,4 4.268	1	0	PB	0,73 1.610
C3-390B.55-40030	02925959	BT40 ADB	C3	30,0 1.181	3,0 0.118	32,0 1.260	95,4 3.756	2	0	PB	1,0 2.200
C3-390B.55-40060	02925960	BT40 ADB	C3	60,0 2.362	33,0 1.299	32,0 1.260	125,4 4.937	2	0	PB	1,1 2.430
C4-390B.55-40030	02925963	BT40 ADB	C4	30,0 1.181	3,0 0.118	40,0 1.575	95,4 3.756	2	0	PB	0,9 1.980
C4-390B.55-40060	02925964	BT40 ADB	C4	60,0 2.362	33,0 1.299	40,0 1.575	125,4 4.937	2	0	PB	1,2 2.650
C5-390B.55-40050	02925967	BT40 ADB	C5	50,0 1.969	23,0 0.906	50,0 1.969	115,4 4.543	2	0	PB	1,1 2.430
C5-390B.55-40090	02925968	BT40 ADB	C5	90,0 3.543	63,0 2.480	50,0 1.969	155,4 6.118	2	0	PB	1,7 3.750
C6-390B.55-40075	02925971	BT40 ADB	C6	75,0 2.953	54,6 2.150	63,0 2.480	140,4 5.528	2	0	PB	1,7 3.750
C3-390B.58-50040	02925961	BT50 ADB	C3	40,0 1.575	2,0 0.079	32,0 1.260	141,8 5.583	2	0	PB	3,5 7.720
C3-390B.58-50070	02925962	BT50 ADB	C3	70,0 2.756	32,0 1.260	32,0 1.260	171,8 6.764	2	0	PB	3,7 8.160
C4-390B.58-50040	02925965	BT50 ADB	C4	40,0 1.575	2,0 0.079	40,0 1.575	141,8 5.583	2	0	PB	3,5 7.720
C4-390B.58-50070	02925966	BT50 ADB	C4	70,0 2.756	32,0 1.260	40,0 1.575	171,8 6.764	2	0	PB	3,8 8.380
C5-390B.58-50040	02925969	BT50 ADB	C5	40,0 1.575	2,0 0.079	50,0 1.969	141,8 5.583	2	0	PB	3,4 7.500
C5-390B.58-50080	02925970	BT50 ADB	C5	80,0 3.150	42,0 1.654	50,0 1.969	181,8 7.157	2	0	PB	3,9 8.600
C6-390B.58-50050	02925972	BT50 ADB	C6	50,0 1.969	12,0 0.472	63,0 2.480	151,8 5.976	2	0	PB	3,5 7.720
C6-390B.58-50100	02925973	BT50 ADB	C6	100,0 3.937	62,0 2.441	63,0 2.480	201,8 7.945	2	0	PB	4,6 10.140
C8-390B.58-50070	02925974	BT50 ADB	C8	70,0 2.756	32,0 1.260	80,0 3.150	171,8 6.764	2	0	PB	4,0 8.820
C8-390B.58-50120	02925975	BT50 ADB	C8	120,0 4.724	82,0 3.228	80,0 3.150	221,8 8.732	2	0	PB	5,9 13.010


Accessories

For	Extension key	Spanner
		
C3-390.55	5680015-05	5680065-13
C3-390B.55	5680015-05	5680065-13
C3-390B.58	5680015-05	5680065-13
C4-390B.55	5680015-05	5680065-10
C4-390B.58	5680015-05	5680065-10
C5-390B.55	5680015-01	5680065-11
C5-390B.58	5680015-01	5680065-11
C6-390B.55	5680015-01	5680065-12
C6-390B.58	5680015-02	5680065-12
C8	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Plug	Retaining nut
			
C3-390.55	5512063-10	—	5512091-04
C3-390B.55	5512063-10	564301701	5512091-04
C3-390B.58	5512063-10	564301702	5512091-04
C4-390B.55	5512063-07	564301701	5512091-03
C4-390B.58	5512063-07	564301702	5512091-03
C5-390B.55	5512063-08	564301701	5512091-01
C5-390B.58	5512063-08	564301702	5512091-01
C6-390B.55	5512063-13	564301701	5512091-02
C6-390B.58	5512063-09	564301702	5512091-02
C8	5512063-09	564301702	5512091-02

Accessories / Spare Parts



Accessories:
4 = Extension key
5 = Spanner

Spare parts:
1 = Center screw
2 = Retaining nut
3 = Plugs (dowels)

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit



Seco Capto™ – ISO 26623-2 – Metric/ Inch





– Mazak design means 90° rotated Seco Capto™ polygon compared to classic BT basic holders
– For Mazak e-machines
– For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	BD	OAL	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch			kg lbs
C5-390.605-40030	02606358	BT40 AD Mazak	C5	30,0 1.181	3,0 0.118	50,0 1.969	95,4 3.756	0	–	1,1 2.430
C6-390.605-50040	02606354	BT50 AD Mazak	C6	40,0 1.575	2,0 0.079	63,0 2.480	141,8 5.583	0	–	3,3 7.280
C8-390.605-50070	02646032	BT50 AD Mazak	C8	70,0 2.756	70,0 2.756	80,0 3.150	171,8 6.764	0	–	4,0 8.820


Accessories

For	Extension key	Spanner
		
C5	5680015-01	5680065-11
C6	5680015-02	5680065-12
C8	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Retaining nut
		
C5	5512063-08	5512091-01
C6	5512063-09	5512091-02
C8	5512063-09	5512091-02

Accessories / Spare Parts



Accessories:
3 = Extension key
4 = Spanner

Spare parts:
1 = Center screw
2 = Retaining nut


Guide
HSK-A
HSK-E
DIN
BT JIS
CAT
Combimaster
Graflex
Seco Capto™
Others
Operating & setting accessories
Shrinkfit

Seco Capto™ – ISO 26623-2 – Metric/ Inch


BT Taper-Face-AD/ADB



Design 1





Design 2




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	BD	OAL	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch				kg lbs
E400251913240	03030234	BT30 TF AD	C3	40,0 1.575	22,0 0.866	32,0 1.260	88,4 3.480	1	1	PB	0,454 1.000
E400251914060	03030235	BT30 TF AD	C4	60,0 2.362	22,0 0.866	40,0 1.575	108,4 4.268	1	1	PB	0,7 1.540
E311451914040	03030236	BT40 TF ADB	C4	40,0 1.575	13,0 0.512	40,0 1.575	105,4 4.150	2	0	PB	1,1 2.430
E311451915050	03030237	BT40 TF ADB	C5	50,0 1.969	23,0 0.906	50,0 1.969	115,4 4.543	2	0	PB	1,2 2.650
E311451916375	03030238	BT40 TF ADB	C6	75,0 2.953	48,0 1.890	63,0 2.480	140,4 5.528	2	0	PB	1,7 3.750
E311651914040	03030239	BT50 TF ADB	C4	40,0 1.575	2,0 0.079	50,0 1.969	141,8 5.583	2	1	PB	3,5 7.720
E311651915040	03030240	BT50 TF ADB	C5	40,0 1.575	2,0 0.079	50,0 1.969	141,8 5.583	2	0	PB	3,4 7.500
E311651916350	03030241	BT50 TF ADB	C6	50,0 1.969	12,0 0.472	63,0 2.480	151,8 5.976	2	0	PB	3,5 7.720
E3116519163100	03030242	BT50 TF ADB	C6	100,0 3.937	62,0 2.441	63,0 2.480	201,8 7.945	2	0	PB	4,8 10.580
E311651918070	03030243	BT50 TF ADB	C8	70,0 2.756	32,0 1.260	80,0 3.150	171,8 6.764	2	0	PB	4,0 8.820
E3116519180120	03030244	BT50 TF ADB	C8	120,0 4.724	82,0 3.228	80,0 3.150	121,8 4.795	2	1	PB	5,9 13.010


Accessories

For	Extension key	Spanner
		
BT30 TF/ C3	5680015-05	5680065-13
BT30 TF/ C4	5680015-05	5680065-10
BT40 TF/ C4	5680015-05	5680065-10
BT40 TF/ C5	5680015-01	5680065-11
BT40 TF/ C6	5680015-01	5680065-12
BT50 TF/ C4	5680015-05	5680065-10
BT50 TF/ C5	5680015-01	5680065-11
BT50 TF/ C6-C8	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Plug	Retaining nut
			
BT30 TF/ C3	5512063-10	–	5512091-04
BT30 TF/ C4	5512063-07	–	5512091-03
BT40 TF/ C4	5512063-07	564301701	5512091-03
BT40 TF/ C5	5512063-08	564301701	5512091-01
BT40 TF/ C6	5512063-13	564301701	5512091-02
BT50 TF/ C4	5512063-07	564301702	5512091-03
BT50 TF/ C5	5512063-08	564301702	5512091-01
BT50 TF/ C6-C8	5512063-09	564301702	5512091-02

Accessories / Spare Parts



Accessories:
4 = Extension key
5 = Spanner

Spare parts:
1 = Center screw
2 = Retaining nut
3 = Plugs (dowels)

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

Seco Capto™ – ISO 26623-2 – Inch


CAT TF / ASME B5.50-1994-ADB



Design 1





Design 2




—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	LB1	BD	BD1	OAL	Design	RFID hole	Balancing	Weight
				inch	inch	inch	inch	inch	inch				lbs
E234251915050	03030247	CAT40 TF ADB	C5	1.969	1.220	1.220	1.969	1.750	4.660	2	1	PB	2.250
E234451914040	03030249	CAT50 TF ADB	C4	1.575	0.090	0.090	1.575	2.750	5.580	1	1	PB	6.830
E234451915040	03030250	CAT50 TF ADB	C5	1.575	0.090	0.090	1.969	2.750	5.580	1	0	—	6.610
E234451916340	03030251	CAT50 TF ADB	C6	1.575	0.120	0.120	2.480	2.750	5.580	1	0	—	6.170
E234451916390	03030252	CAT50 TF ADB	C6	3.543	2.085	2.085	2.480	2.750	7.543	1	0	—	8.600
E2344519180100	03030253	CAT50 TF ADB	C8	3.937	3.185	3.185	3.150	2.750	7.937	2	1	PB	10.140


Accessories

For	Extension key	Spanner
		
CAT40/ C5	5680015-01	5680065-11
CAT50/ C4	5680015-05	5680065-10
CAT50/ C5	5680015-01	5680065-11
CAT50/ C6	5680015-02	5680065-12
CAT50/ C8	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Plug	Retaining nut
			
CAT40/ C5	5512063-08	564301701	5512091-01
CAT50/ C4	5512063-07	564301702	5512091-03
CAT50/ C5	5512063-08	564301702	5512091-01
CAT50/ C6	5512063-09	564301702	5512091-02
CAT50/ C8	5512063-09	564301702	5512091-02

Accessories / Spare Parts



Accessories:
4 = Extension key
5 = Spanner

Spare parts:
1 = Center screw
2 = Retaining nut
3 = Plugs (dowels)

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Seco Capto™ – ISO 26623-2 – Inch

CAT TF Mazak™ e-machine and Mori Seiki NT™ -Series



–90° rotated polygon for precision tool tip control
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LF	LB	LB1	BD	BD1	OAL	Design	RFID hole	Balan- cing	Weight
				inch	inch	inch	inch	inch	inch				lbs
E947451916350	03030255	CAT50 TF AD Mazak	C6	1.969	0.510	0.510	2.480	2.750	5.960	1	0	PB	6.830


Accessories

For	Extension key	Spanner
E947451916350	5680015-02	5680065-12

Spare Parts, included in delivery

For	Centre screw	Retaining nut
E947451916350	5512063-09	5512091-02

Accessories / Spare Parts




Accessories:
3 = Extension key
4 = Retaining nut spanner

Spare parts:
1 = Center screw
2 = Retaining nut

Seco Capto™ – ISO 26623-2
– Metric/ Inch



Seco Capto™ – ISO 26623-1



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch			kg lbs
C3-391.01-32060A	75039884	C3	C3	60,0 2.362	32,0 1.260	79,0 3.110	0	–	0,4 0.880
C3-391.01-32080A	00090847	C3	C3	80,0 3.150	32,0 1.260	99,0 3.898	0	–	0,5 1.100
C4-391.01-40060A	75039885	C4	C4	60,0 2.362	40,0 1.575	84,0 3.307	0	–	0,6 1.320
C4-391.01-40080A	02207391	C4	C4	80,0 3.150	40,0 1.575	104,0 4.094	0	–	0,8 1.760
C5-391.01-50080A	75039886	C5	C5	80,0 3.150	50,0 1.969	110,0 4.331	0	–	1,1 2.430
C5-391.01-50100A	00004773	C5	C5	100,0 3.937	50,0 1.969	130,0 5.118	0	–	1,4 3.090
C6-391.01-63100A	75039887	C6	C6	100,0 3.937	63,0 2.480	138,0 5.433	0	–	2,2 4.850
C6-391.01-63140A	00004840	C6	C6	140,0 5.512	63,0 2.480	178,0 7.008	0	–	3,1 6.830
C8-391.01-80100A	75039888	C8	C8	100,0 3.937	80,0 3.150	148,0 5.827	0	–	3,7 8.160
C8-391.01-80125A	00004841	C8	C8	125,0 4.921	80,0 3.150	173,0 6.811	0	–	4,6 10.140

Accessories

For	Extension key	Spanner
		
C3	5680015-05	5680065-13
C4	5680015-05	5680065-10
C5	5680015-01	5680065-11
C6	5680015-02	5680065-12
C8	5680015-02	5680065-12

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others


Operating &
setting acces-
series

Shrinkfit

Spare Parts, included in delivery

Guide	For	Centre screw	Retaining nut
			
HSK-A	C3	5512067-01	5512091-04
	C4	5512067-02	5512091-03
	C5	5512067-03	5512091-01
	C6	5512067-04	5512091-02
	C8	5512067-04	5512091-02

Accessories / Spare Parts




Accessories:
 3 = Extension key
 4 = Retaining nut spanner

Spare parts:
 1 = Center screw
 2 = Retaining nut

Seco Capto™ – ISO 26623-2
– Metric/ Inch


Short version for segment clamping only – ISO 26623-1




–The Seco Capto™ machine side of short extensions can only be hold by spindles with segment clamping (not with centre bolt clamping)
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	BD	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch			kg lbs
C3-391.01-32035	02535685	C3	C3	35,0 1.378	32,0 1.260	54,0 2.126	0	–	0,3 0.660
C4-391.01-40040	02535686	C4	C4	40,0 1.575	40,0 1.575	64,0 2.520	0	–	0,4 0.880
C5-391.01-50050	02484934	C5	C5	50,0 1.969	50,0 1.969	80,0 3.150	0	–	0,7 1.540
C6-391.01-63060	02300834	C6	C6	60,0 2.362	63,0 2.480	98,0 3.858	0	–	1,3 2.870
C8-391.01-80065	02417041	C8	C8	65,0 2.559	80,0 3.150	113,0 4.449	0	–	2,4 5.290

Accessories

For	Extension key
	
C3-391.01-32035	5680015-05
C4-391.01-40040	5680015-05
C5-391.01-50050	5680015-05
C6-391.01-63060	5680015-02
C8-391.01-80065	5680015-02

Spare Parts, included in delivery

For	Centre screw	Circlip
		
C3-391.01-32035	5512068-01	5545040-02
C4-391.01-40040	5512068-02	5545040-03
C5-391.01-50050	5512068-03	5545040-07
C6-391.01-63060	5512068-04	5545040-08
C8-391.01-80065	5512068-05	5545040-08

Accessories / Spare Parts

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster


Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit



Accessories:
3 = Extension key


Spare parts:
1 = Center screw
2 = Circlip

Seco Capto™ – ISO 26623-2 – Metric/ Inch


Seco Capto™ – ISO 26623-1



Design 1





Design 2




–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	BD	OAL	Design	BHTA°	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch					kg lbs
C4-391.02-32055A	75039889	C4	C3	55,0 2.165	31,0 1.220	32,0 1.260	79,0 3.110	1	–	0	–	0,42 0.930
C4-391.02-32070A	02535687	C4	C3	70,0 2.756	–	32,0 1.260	94,0 3.701	2	6,0	0	–	0,56 1.230
C5-391.02-32060A	75039890	C5	C3	60,0 2.362	34,8 1.370	32,0 1.260	90,0 3.543	1	–	0	–	0,7 1.540
C5-391.02-40065A	75039891	C5	C4	65,0 2.559	40,0 1.575	40,0 1.575	95,0 3.740	1	–	0	–	0,8 1.760
C6-391.02-32070A	75039892	C6	C3	70,0 2.756	39,0 1.535	32,0 1.260	108,0 4.252	1	–	0	–	1,1 2.430
C6-391.02-40080A	75039893	C6	C4	80,0 3.150	51,4 2.024	40,0 1.575	118,0 4.646	1	–	0	–	1,2 2.650
C6-391.02-50080A	75039894	C6	C5	80,0 3.150	51,5 2.028	50,0 1.969	118,0 4.646	1	–	0	–	1,4 3.090
C6-391.02-50110A	02207400	C6	C5	110,0 4.331	12,0 0.472	50,0 1.969	148,0 5.827	2	4,5	0	–	2,2 4.850
C8-391.02-32060B	03080008	C8	C3	60,0 2.362	20,7 0.815	32,0 1.260	108,0 4.252	1	–	0	–	2,0 4.410
C8-391.02-40070B	03080009	C8	C4	70,0 2.756	31,4 1.236	40,0 1.575	118,0 4.646	1	–	0	–	2,1 4.630
C8-391.02-50080B	03080011	C8	C5	80,0 3.150	42,8 1.685	50,0 1.969	128,0 5.039	1	–	0	–	2,4 5.290
C8-391.02-63080B	02527212	C8	C6	80,0 3.150	44,5 1.752	63,0 2.480	128,0 5.039	1	–	0	–	2,6 5.730
C8-391.02-63120A	02207176	C8	C6	120,0 4.724	12,0 0.472	63,0 2.480	168,0 6.614	2	6,0	0	–	4,1 9.040


Accessories

For	Extension key	Spanner
		
C...-32	5680015-05	5680065-13
C...-40	5680015-05	5680065-10
C...-50	5680015-01	5680065-11
C...-63	5680015-02	5680065-12

Spare Parts, included in delivery

Guide	For	Centre screw	Retaining nut
			
HSK-A	C...-32	5512067-01	5512091-04
	C...-40	5512067-02	5512091-03
	C...-50	5512067-03	5512091-01
	C...-63	5512067-04	5512091-02

Accessories / Spare Parts




Accessories:
 3 = Extension key
 4 = Retaining nut spanner

Spare parts:
 1 = Center screw
 2 = Retaining nut

Seco Capto™ – ISO 26623-2 – Metric/ Inch


Short version for segment clamping only – ISO 26623-1



- The Seco Capto™ machine side of short reducers can only be hold by spindles with segment clamping (not with centre bolt clamping)
- * With 180° offset Machine side vs Workpiece side
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	BD	OAL	*	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch				kg lbs
C5-391.02-32033A	03080025	C5	C3	33,0 1.299	5,0 0.197	32,0 1.260	63,0 2.480		0	PB	0,6 1.320
C5-391.02-40040A	03079983	C5	C4	40,0 1.575	15,0 0.591	40,0 1.575	70,0 2.756		0	–	0,6 1.320
C6-391.02-32032	02535690	C6	C3	32,0 1.260	6,0 0.236	32,0 1.260	70,0 2.756		0	–	0,85 1.870
C6-391.02-40040	02459467	C6	C4	40,0 1.575	11,0 0.433	40,0 1.575	78,0 3.071		0	–	0,9 1.980
C6-391.02-50050A	03080019	C6	C5	50,0 1.969	20,0 0.787	50,0 1.969	88,0 3.465		0	–	1,1 2.430
C8-391.02-50045A	03080010	C8	C5	45,0 1.772	5,0 0.197	50,0 1.969	93,0 3.661		0	–	1,9 4.190
C8-391.02-63055A	03080012	C8	C6	55,0 2.165	15,0 0.591	63,0 2.480	103,0 4.055		0	–	2,1 4.630
C8-391.02R-63055A	03080030	C8	C6	55,0 2.165	15,0 0.591	63,0 2.480	103,0 4.055	*	0	–	1,9 4.190

Accessories

For	Extension key
	
C5-391.02-32033A	5680015-05
C5-391.02-40040A	5680015-05
C6-391.02-32032	5680015-05
C6-391.02-40040	5680015-05
C6-391.02-50050A	5680015-01
C8-391.02-50045A	5680015-01
C8-391.02-63055A	5680015-02
C8-391.02R-63055A	5680015-02

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others


Operating &
setting acces-
sories

Shrinkfit

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery		
	For	Centre screw	Circlip
HSK-A			
	C5-391.02-32033A	5512068-01	5545040-02
	C5-391.02-40040A	5512068-06	5545040-07
	C6-391.02-32032	5512068-01	5545040-02
HSK-E	C6-391.02-40040	5512068-02	5545040-03
	C6-391.02-50050A	5512068-07	5545040-08
	C8-391.02-50045A	5512068-08	5545040-08
	C8-391.02-63055A	5512068-05	5545040-08
	C8-391.02R-63055A	5512068-05	5545040-08

Accessories / Spare Parts


DIN	 Accessories: 3 = Extension key Spare parts: 1 = Center screw 2 = Circlip	
BT / IS		
CAT		
Combimaster		
Graflex		
Seco Capto™		
Others		
Operating & setting accessories		
Shrinkfit		

Steadyline®, vibration damping
– Metric/ Inch


Seco Capto™



Design 1



Design 2




–DMM 40 mm / 1.575", includes 4 threaded holes on the bearing face according to DIN 6357
–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	BD1	OAL	LB	LSC	Design	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
C6-391.5555-16160	02706268	C6	16,0 0.630	160,0 6.299	38,0 1.496	38,0 1.496	215,0 8.465	135,0 5.315	17,0 0.669	1	–	1	PB	2,12 4.670
C6-391.5555-22210	02675777	C6	22,0 0.866	210,0 8.268	48,0 1.890	48,0 1.890	267,0 10.512	185,0 7.283	19,0 0.748	1	–	1	PB	3,64 8.020
C6-391.5556-22260	02675778	C6	22,0 0.866	260,0 10.236	48,0 1.890	60,0 2.362	317,0 12.480	235,0 9.252	19,0 0.748	2	1,3	1	PB	4,0 8.820
C6-391.5555-27260	02675779	C6	27,0 1.063	260,0 10.236	60,0 2.362	60,0 2.362	319,0 12.559	235,0 9.252	21,0 0.827	1	–	1	PB	6,78 14.950
C8-391.5555-22210	02675780	C8	22,0 0.866	210,0 8.268	48,0 1.890	48,0 1.890	277,0 10.906	177,0 6.969	19,0 0.748	1	–	1	PB	4,54 10.010
C8-391.5556-22260	02675781	C8	22,0 0.866	260,0 10.236	48,0 1.890	64,0 2.520	327,0 12.874	227,0 8.937	19,0 0.748	2	1,8	1	PB	6,42 14.150
C8-391.5555-27260	02675782	C8	27,0 1.063	260,0 10.236	60,0 2.362	60,0 2.362	329,0 12.953	227,0 8.937	21,0 0.827	1	–	1	PB	7,62 16.800
C8-391.5556-27320	02675783	C8	27,0 1.063	320,0 12.598	60,0 2.362	78,0 3.071	389,0 15.315	287,0 11.299	21,0 0.827	2	1,6	1	PB	10,6 23.370
C8-391.5555-32330	02706271	C8	32,0 1.260	330,0 12.992	78,0 3.071	78,0 3.071	402,0 15.827	297,0 11.693	24,0 0.945	1	–	1	PB	14,5 31.970
C8-391.5555-40350	02753473	C8	40,0 1.575	350,0 13.780	89,0 3.504	89,0 3.504	425,0 16.732	317,0 12.480	27,0 1.063	1	–	1	PB	19,0 41.890

Accessories

For	Bolt, through coolant	Spanner
		
16/ 0.630	5801608L	5811608
22/ 0.866	5802210L	5812210
27/ 1.063	5802712L	5812712
32/ 1.260	5803216L	5813216
40/ 1.575	5804020L	5814020

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

Spare Parts, included in delivery


Guide	Spare Parts, included in delivery			
	For	Bolt	Screw	Tenon
				
HSK-A	16/ 0.630	5801608	950D0312	16C2080810A
	22/ 0.866	5802210	950D0416	16C2101111
	27/ 1.063	5802712	950D0516	16C2121214A
	32/ 1.260	5803216	950D0516	16C2141421A
HSK-E	40/ 1.575	5804020	950D0616	16C2161621A
DIN				
BT JIS				
CAT				
Combimaster				
Graflex				
Seco Capto™				
Others				
Operating & setting accessories				
Shrinkfit				

Steadyline®, vibration damping
– Inch


Seco Capto™



Design 1



Design 2




–DMM 40 mm / 1.575", includes 4 threaded holes on the bearing face according to DIN 6357
–For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	BD1	OAL	LB	LSC	Design	BHTA°	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch					lbs
C6-391.5555-075750	02753487	C6	0.750	7.500	1.750	1.750	9.685	6.516	0.689	1	–	1	PB	6.770
C6-391.5556-075900	02753488	C6	0.750	9.000	1.750	2.347	11.185	8.016	0.689	2	2,0	1	PB	10.140
C6-391.5555-100900	02753490	C6	1.000	9.000	2.250	2.250	11.185	8.016	0.689	1	–	1	PB	12.790
C8-391.5556-100C00	02753494	C8	1.000	12.000	2.250	3.051	14.579	10.701	0.689	2	2,0	1	PB	22.930
C8-391.5555-150D75	02753485	C8	1.500	13.752	3.500	3.500	16.583	12.453	0.941	1	–	1	PB	41.230

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
			
0.750	58211905	950D0308	16C11905
1.000 (C6)	58212540	950D0416	16C2091014A
1.000 (C8)	58212540	950D0416	16C12540
1.500	58213810	950D0616	16C2151421A

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

With through coolant channels – ISO 3937
– Metric/ Inch

Seco Capto™




–Type 5524: small face shell mill holders
–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant


Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			
C3-391.5525-16030	02532782	C3	16,0 0.630	30,0 1.181	38,0 1.496	66,0 2.598	12,0 0.472	17,0 0.669	0	G6.3	0,27 0.600
C4-391.5525-16035	02532783	C4	16,0 0.630	35,0 1.378	38,0 1.496	76,0 2.992	12,0 0.472	17,0 0.669	0	G6.3	0,5 1.100
C4-391.5525-22040	02532784	C4	22,0 0.866	40,0 1.575	48,0 1.890	83,0 3.268	17,0 0.669	19,0 0.748	0	G6.3	0,6 1.320
C5-391.5525-16035	02532786	C5	16,0 0.630	35,0 1.378	38,0 1.496	82,0 3.228	12,0 0.472	17,0 0.669	1	G6.3	0,6 1.320
C5-391.5525-22040	02532787	C5	22,0 0.866	40,0 1.575	48,0 1.890	89,0 3.504	17,0 0.669	19,0 0.748	1	G6.3	0,8 1.760
C5-391.5525-27040	02532788	C5	27,0 1.063	40,0 1.575	60,0 2.362	91,0 3.583	17,0 0.669	21,0 0.827	1	G6.3	0,95 2.090
C5-391.5524-27040	02532785	C5	27,0 1.063	40,0 1.575	48,0 1.890	91,0 3.583	17,0 0.669	21,0 0.827	1	G6.3	0,9 1.980
C6-391.5525-16035	02532790	C6	16,0 0.630	35,0 1.378	38,0 1.496	90,0 3.543	10,0 0.394	17,0 0.669	1	G6.3	1,0 2.200
C6-391.5525-22040	02532791	C6	22,0 0.866	40,0 1.575	48,0 1.890	97,0 3.819	15,0 0.591	19,0 0.748	1	G6.3	1,1 2.430
C6-391.5525-27040	02532792	C6	27,0 1.063	40,0 1.575	60,0 2.362	99,0 3.898	15,0 0.591	21,0 0.827	1	G6.3	1,3 2.870
C6-391.5525-32040	02532793	C6	32,0 1.260	40,0 1.575	78,0 3.071	102,0 4.016	15,0 0.591	24,0 0.945	1	G6.3	1,6 3.530
C6-391.5524-27040	02532789	C6	27,0 1.063	40,0 1.575	48,0 1.890	99,0 3.898	15,0 0.591	21,0 0.827	1	G6.3	1,12 2.470
C8-391.5525-27050	02532795	C8	27,0 1.063	50,0 1.969	60,0 2.362	119,0 4.685	17,0 0.669	21,0 0.827	1	G6.3	2,3 5.070
C8-391.5525-32050	02532796	C8	32,0 1.260	50,0 1.969	78,0 3.071	122,0 4.803	17,0 0.669	24,0 0.945	1	G6.3	2,7 5.950
C8-391.5525-40055	02532797	C8	40,0 1.575	55,0 2.165	89,0 3.504	130,0 5.118	22,0 0.866	27,0 1.063	1	G6.3	3,2 7.050

Accessories

For	Bolt, through coolant	Spanner
		
16/ 0.630	5801608L	5811608
22/ 0.866	5802210L	5812210
27/ 1.063 -5524	5802712L	5812712
27/ 1.063 -5525	5802712L	5812712
32/ 1.260	5803216L	5813216
40/ 1.575	5804020L	5814020

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
			
16/ 0.630	5801608	950D0310	16C10810164
22/ 0.866	5802210	950D0414	16C11012206
27/ 1.063 -5524	5802712	950D0512	16C127
27/ 1.063 -5525	5802712	950D0516	16C11214243
32/ 1.260	5803216	950D0516	16C2141421
40/ 1.575	5804020	950D0616	16C2161621

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

With through coolant channels
– Inch




—For ISO attribute explanation, see page 15

Spare parts:
1 = Bolt
2 = Tenon/Screw


Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch			lbs
C4-391.5525-075150	02610375	C4	0.750	1.500	1.750	3.134	0.594	0.689	0	G6.3	1.100
C5-391.5525-075150	02610376	C5	0.750	1.500	1.750	3.370	0.594	0.689	1	G6.3	1.500
C5-391.5525-100150	02610377	C5	1.000	1.500	2.067	3.370	0.594	0.689	1	G6.3	1.760
C6-391.5525-075150	02610378	C6	0.750	1.500	1.750	3.685	0.516	0.689	1	G6.3	2.430
C6-391.5525-100150	02610379	C6	1.000	1.500	2.250	3.685	0.516	0.689	1	G6.3	2.650
C6-391.5525-125150	02610380	C6	1.250	1.500	2.750	3.685	0.516	0.689	1	G6.3	3.020
C6-391.5525-150175	02610388	C6	1.500	1.750	3.500	4.187	0.766	0.941	1	G6.3	4.850
C8-391.5525-125200	02610391	C8	1.250	2.000	2.750	4.579	0.701	0.689	1	G6.3	5.580
C8-391.5525-150200	02610394	C8	1.500	2.000	3.500	4.831	0.701	0.941	1	G6.3	6.610

Spare Parts, included in delivery

For	Bolt	Screw	Tenon
			
0.750	58211905	950D0312	16C11905A
1.250	58213175	950D0516	16C23175
1.500	58213810	950D0616	16C23810
C5-391.5525-100150	58212540	950D0414	16C12540A
C6-391.5525-100150	58212540	950D0416	16C12540A

Small face without through coolant channels – ISO 3937 – Metric/ Inch

Seco Capto™




–For ISO attribute explanation, see page 15

Accessories:
4 = Bolt, through coolant


Spare parts:
1 = Bolt
2 = Tenon/Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSC	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
C3-391.0552-16030	02752390	C3	16,0 0.630	30,0 1.181	32,0 1.260	66,0 2.598	15,0 0.591	17,0 0.669	0	G6.3	0,24 0.530
C4-391.0552-16032	02752391	C4	16,0 0.630	32,0 1.260	32,0 1.260	73,0 2.874	9,0 0.354	17,0 0.669	0	G6.3	0,36 0.790
C4-391.0552-22055	02752392	C4	22,0 0.866	55,0 2.165	40,0 1.575	98,0 3.858	32,0 1.260	19,0 0.748	0	G6.3	0,66 1.460
C5-391.0552-22070	02752397	C5	22,0 0.866	70,0 2.756	40,0 1.575	119,0 4.685	47,0 1.850	19,0 0.748	1	G6.3	1,0 2.200
C5-391.0552-27035	02752398	C5	27,0 1.063	35,0 1.378	48,0 1.890	86,0 3.386	12,0 0.472	21,0 0.827	1	G6.3	0,8 1.760
C6-391.0552-22035	02752399	C6	22,0 0.866	35,0 1.378	40,0 1.575	92,0 3.622	10,0 0.394	19,0 0.748	1	G6.3	1,0 2.200
C6-391.0552-27035	02752400	C6	27,0 1.063	35,0 1.378	48,0 1.890	94,0 3.701	10,0 0.394	21,0 0.827	1	G6.3	1,1 2.430
C6-391.0552-32035	02752401	C6	32,0 1.260	35,0 1.378	58,0 2.283	97,0 3.819	10,0 0.394	24,0 0.945	1	G6.3	1,22 2.690
C8-391.0552-27035	02752403	C8	27,0 1.063	35,0 1.378	48,0 1.890	104,0 4.094	2,0 0.079	21,0 0.827	1	G6.3	2,0 4.410
C8-391.0552-32035	02752404	C8	32,0 1.260	35,0 1.378	58,0 2.283	107,0 4.213	2,0 0.079	24,0 0.945	1	G6.3	2,03 4.480
C8-391.0552-40035	02752405	C8	40,0 1.575	35,0 1.378	70,0 2.756	110,0 4.331	2,0 0.079	27,0 1.063	1	G6.3	2,3 5.070


Accessories

For	Bolt, through coolant	Spanner
		
16/ 0.630	5801608L	5811608
22/ 0.866	5802210L	5812210
27/ 1.063	5802712L	5812712
32/ 1.260	5803216L	5813216
40/ 1.575	5804020L	5814020

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery			
	For	Bolt	Screw	Tenon
				
HSK-A	16/ 0.630	5801608	950D0308	16C116
	22/ 0.866	5802210	950D0414	16C122
	27/ 1.063	5802712	950D0512	16C127
	32/ 1.260	5803216	950D0514	16C132
	40/ 1.575	5804020	950D0616	16C140
HSK-E				
DIN				
BT JIS				
CAT				
Combimaster				
Graflex				
Seco Capto™				
Others				
Operating & setting accessories				
Shrinkfit				

Flange mounting – DIN 6357/ DIN 2079
– Inch



–For ISO attribute explanation, see page 15

Spare parts:
2 = Tenon/Screw (not removable)

Designation	Item number	CTMS	LSC	DMM	LF	BD	OAL	LSC	DBC	TDZ	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch				lbs
C8-A391.05-63060	10116829	C8	1.142	2.500	2.362	5.118	5.394	1.142	4.000	5/8" - 11 UNC	–	PB	13.450

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

– Metric/ Inch




–For ISO attribute explanation, see page 15

Spare parts:
1 = Slide rod
2 = Screw

Designation	Item number	CTMS	DMM	LF	BD	OAL	LB	LSCN	LSCX	FLGT	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
C5-391.5657-27090	02532800	C5	27,0 1.063	90,0 3.543	42,0 1.654	120,0 4.724	67,0 2.638	0,0 0.0	15,0 0.591	5,0 0.197	1	PB	1,21 2.670
C6-391.5657-22080	02532802	C6	22,0 0.866	80,0 3.150	35,0 1.378	118,0 4.646	55,0 2.165	0,0 0.0	12,0 0.472	4,0 0.157	1	PB	1,24 2.730
C6-391.5657-27090	02532803	C6	27,0 1.063	90,0 3.543	42,0 1.654	128,0 5.039	65,0 2.559	0,0 0.0	15,0 0.591	5,0 0.197	1	PB	1,54 3.400
C6-391.5657-40150	02532805	C6	40,0 1.575	150,0 5.906	58,0 2.283	188,0 7.402	125,0 4.921	0,0 0.0	30,0 1.181	7,0 0.276	1	PB	3,5 7.720
C8-391.5657-50200	02532809	C8	50,0 1.969	200,0 7.874	72,0 2.835	248,0 9.764	167,0 6.575	0,0 0.0	32,0 1.260	8,0 0.315	1	PB	7,12 15.700

Spare Parts, included in delivery


For	Screw	Slide rod
		
22/ 0.866	19C565722	565722
27/ 1.063	19C565727	565727
40/ 1.575	19C565740	565740
50/ 1.969	19C565750	565750

DIN 1835 Form B/ DIN 6535 Form HB
– Metric/ Inch


Seco Capto™



Design 1



Design 2



- Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
- With 2 coolant channels for front lubrication which can be sealed with included screws
- For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LFS	BD	OAL	LB	LSC	Design	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
C4-EM06-050-L1	10327217	C4	6,0 0.236	50,0 1.969	32,0 1.260	25,0 0.984	74,0 2.913	27,0 1.063	27,0 1.063	1	–	0	PB	0,4 0.880
C4-EM08-050-L1	10327218	C4	8,0 0.315	50,0 1.969	32,0 1.260	28,0 1.102	74,0 2.913	27,0 1.063	30,0 1.181	1	–	0	PB	0,4 0.880
C4-EM10-050-L1	10327219	C4	10,0 0.394	50,0 1.969	30,0 1.181	35,0 1.378	74,0 2.913	27,0 1.063	36,0 1.417	1	–	0	PB	0,5 1.100
C4-EM12-055-L1	10327220	C4	12,0 0.472	55,0 2.165	32,5 1.280	42,0 1.654	79,0 3.110	35,0 1.378	43,0 1.693	1	30,0	0	PB	0,6 1.320
C4-EM16-055-L1	10327221	C4	16,0 0.630	55,0 2.165	31,0 1.220	48,0 1.890	79,0 3.110	35,0 1.378	46,0 1.811	1	15,0	0	PB	0,6 1.320
C5-EM06-050-L1	10327222	C5	6,0 0.236	50,0 1.969	32,0 1.260	25,0 0.984	80,0 3.150	27,0 1.063	27,0 1.063	1	–	1	PB	0,1 0.220
C5-EM08-050-L1	10327223	C5	8,0 0.315	50,0 1.969	32,0 1.260	28,0 1.102	80,0 3.150	27,0 1.063	30,0 1.181	1	–	1	PB	0,6 1.320
C5-EM10-055-L1	10327224	C5	10,0 0.394	55,0 2.165	35,0 1.378	35,0 1.378	85,0 3.346	32,0 1.260	36,0 1.417	1	–	1	PB	0,7 1.540
C5-EM12-060-L1	10327225	C5	12,0 0.472	60,0 2.362	37,5 1.476	42,0 1.654	90,0 3.543	37,0 1.457	43,0 1.693	1	–	1	PB	0,8 1.760
C5-EM16-060-L1	10327226	C5	16,0 0.630	60,0 2.362	36,0 1.417	48,0 1.890	90,0 3.543	37,0 1.457	46,0 1.811	1	–	1	PB	0,9 1.980
C5-EM20-060-L1	10327227	C5	20,0 0.787	60,0 2.362	35,0 1.378	52,0 2.047	90,0 3.543	40,0 1.575	49,0 1.929	1	30,0	1	PB	0,9 1.980
C5-EM25-080-L1	10327228	C5	25,0 0.984	80,0 3.150	56,0 2.205	63,0 2.480	110,0 4.331	60,0 2.362	56,0 2.205	2	15,0	1	PB	1,5 3.310
C6-EM06-060-L1	10327229	C6	6,0 0.236	60,0 2.362	42,0 1.654	25,0 0.984	98,0 3.858	35,0 1.378	27,0 1.063	1	–	1	PB	1,0 2.200
C6-EM08-055-L1	10327230	C6	8,0 0.315	55,0 2.165	37,0 1.457	28,0 1.102	93,0 3.661	30,0 1.181	30,0 1.181	1	–	1	PB	1,0 2.200
C6-EM10-060-L1	10327231	C6	10,0 0.394	60,0 2.362	40,0 1.575	35,0 1.378	98,0 3.858	35,0 1.378	36,0 1.417	1	–	1	PB	1,1 2.430
C6-EM12-060-L1	10327232	C6	12,0 0.472	60,0 2.362	37,5 1.476	42,0 1.654	98,0 3.858	35,0 1.378	43,0 1.693	1	–	1	PB	1,2 2.650
C6-EM14-060-L1	10327233	C6	14,0 0.551	60,0 2.362	37,5 1.476	44,0 1.732	98,0 3.858	35,0 1.378	43,0 1.693	1	–	1	PB	1,2 2.650
C6-EM16-065-L1	10327234	C6	16,0 0.630	65,0 2.559	41,0 1.614	48,0 1.890	103,0 4.055	40,0 1.575	46,0 1.811	1	–	1	PB	1,3 2.870
C6-EM20-065-L1	10327235	C6	20,0 0.787	65,0 2.559	40,0 1.575	52,0 2.047	103,0 4.055	40,0 1.575	49,0 1.929	1	–	1	PB	1,4 3.090
C6-EM25-080-L1	10327236	C6	25,0 0.984	80,0 3.150	56,0 2.205	63,0 2.480	118,0 4.646	58,0 2.283	54,0 2.126	2	–	1	PB	1,9 4.190
C6-EM32-090-L1	10327237	C6	32,0 1.260	90,0 3.543	66,0 2.598	72,0 2.835	128,0 5.039	68,0 2.677	59,0 2.323	2	15,0	1	PB	2,4 5.290
C6-EM40-100-L1	10327238	C6	40,0 1.575	100,0 3.937	70,0 2.756	80,0 3.150	138,0 5.433	78,0 3.071	68,0 2.677	2	15,0	1	PB	2,9 6.390

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Guide	Designation	Item number	CTMS	DCBN-DCBX	LPR	LFS	BD	OAL	LB	LSC	Design	BHTA°	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
HSK-A	C8-EM10-070-L1	10327239	C8	10,0 0.394	70,0 2.756	50,0 1.969	35,0 1.378	118,0 4.646	37,0 1.457	36,0 1.417	1	–	1	PB	2,1 4.630
	C8-EM12-070-L1	10327240	C8	12,0 0.472	70,0 2.756	47,5 1.870	42,0 1.654	118,0 4.646	37,0 1.457	43,0 1.693	1	–	1	PB	2,2 4.850
	C8-EM16-070-L1	10327241	C8	16,0 0.630	70,0 2.756	46,0 1.811	48,0 1.890	118,0 4.646	37,0 1.457	46,0 1.811	1	–	1	PB	2,3 5.070
HSK-E	C8-EM20-070-L1	10327242	C8	20,0 0.787	70,0 2.756	45,0 1.772	52,0 2.047	118,0 4.646	37,0 1.457	48,0 1.890	1	–	1	PB	2,3 5.070
	C8-EM25-080-L1	10327243	C8	25,0 0.984	80,0 3.150	56,0 2.205	65,0 2.559	128,0 5.039	47,0 1.850	54,0 2.126	2	–	1	PB	2,7 5.950
	C8-EM32-080-L1	10327244	C8	32,0 1.260	80,0 3.150	56,0 2.205	72,0 2.835	128,0 5.039	47,0 1.850	59,0 2.323	2	–	1	PB	2,8 6.170
DIN	C8-EM40-110-L1	10327245	C8	40,0 1.575	110,0 4.331	80,0 3.150	80,0 3.150	158,0 6.220	77,0 3.031	68,0 2.677	2	–	1	PB	3,9 8.600
	C8-EM50-120-L1	10327246	C8	50,0 1.969	120,0 4.724	85,0 3.346	100,0 3.937	168,0 6.614	90,0 3.543	78,0 3.071	2	15,0	1	PB	5,5 12.130

Spare Parts, included in delivery


BT JIS	For DCBN-DCBX	Coolant screw	Locking screw
			
CAT	6 / 0.236	950A0304	951C0610
	8 / 0.315	950A0304	951C0810
	10 / 0.394	950A0304	951C1012
Combimaster	12 / 0.472	950A0304	951C1216
	14 / 0.551	950A0304	951C1216
	16 / 0.630	950A0304	951C1416
Graflex	20 / 0.787	950A0404	951C1616
	25 / 0.984	950A0404	951C1820
	32 / 1.260	950A0404	951C2020
Seco Capto™	40 / 1.575	950A0404	951C2020
	50 / 1.969	950A0404	951C2425

DIN 1835 Form B/ DIN 6535 Form HB
– Inch


Seco Capto™



Design 1



Design 2



- Weldon ØDCBN-DCBX 16, 20, 25, 32 and 40 mm / 0.630, 0.787, 0.984, 1.260 and 1.575" with ground face (Seco-Weldon compatible)
- With 2 coolant channels for front lubrication which can be sealed with included screws
- For ISO attribute explanation, see page 15

1 = Screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LFS	BD	OAL	LB	LSC	Design	BHTA°	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch					lbs
C4-EM0.375-2.500-L1	10327247	C4	0.375	2.500	1.750	1.370	3.445	1.594	1.496	1	–	0	PB	1.320
C4-EM0.500-2.500-L1	10327248	C4	0.500	2.500	1.630	1.614	3.445	1.713	1.614	1	30,0	0	PB	1.320
C4-EM0.625-2.500-L1	10327249	C4	0.625	2.500	1.590	1.870	3.445	1.713	1.870	1	30,0	0	PB	1.540
C4-EM0.750-2.360-L1	10327250	C4	0.750	2.362	1.362	2.000	3.307	1.575	2.008	1	30,0	0	PB	1.540
C5-EM0.375-2.500-L1	10327251	C5	0.375	2.500	1.750	1.370	3.681	1.594	1.496	1	–	1	PB	1.540
C5-EM0.500-2.360-L1	10327252	C5	0.500	2.362	1.492	1.614	3.543	1.457	1.614	1	–	1	PB	1.760
C5-EM0.625-2.500-L1	10327268	C5	0.625	2.500	1.590	1.870	3.681	1.594	1.870	1	–	1	PB	1.980
C5-EM0.750-2.360-L1	10327253	C5	0.750	2.362	1.362	2.000	3.543	1.575	2.008	1	–	1	PB	1.980
C5-EM1.000-3.500-L1	10327255	C5	1.000	3.500	2.380	2.500	4.681	2.713	2.244	2	15,0	1	PB	3.750
C6-EM0.375-2.500-L1	10327256	C6	0.375	2.500	1.750	1.370	3.996	1.516	1.496	1	–	1	PB	2.430
C6-EM0.500-2.500-L1	10327257	C6	0.500	2.500	1.630	1.614	3.996	1.516	1.614	1	–	1	PB	2.650
C6-EM0.625-2.500-L1	10327258	C6	0.625	2.500	1.590	1.870	3.996	1.516	1.870	1	–	1	PB	2.870
C6-EM0.750-2.500-L1	10327259	C6	0.750	2.500	1.500	2.000	3.996	1.516	2.008	1	–	1	PB	2.870
C6-EM1.000-3.500-L1	10327261	C6	1.000	3.500	2.380	2.500	4.996	2.496	2.244	2	–	1	PB	4.410
C6-EM1.250-3.500-L1	10327262	C6	1.250	3.500	2.380	2.748	4.996	2.634	2.303	2	15,0	1	PB	4.850
C6-EM1.500-4.331-L1	10327263	C6	1.500	4.331	2.831	3.500	5.827	3.465	2.618	2	15,0	1	PB	9.260
C8-EM1.250-3.500-L1	10327264	C8	1.250	3.500	2.380	2.748	5.390	2.201	2.303	2	–	1	PB	6.610
C8-EM1.500-5.000-L1	10327265	C8	1.500	5.000	3.500	3.500	6.890	3.819	2.618	2	15,0	1	PB	12.130
C8-EM2.000-5.000-L1	10327266	C8	2.000	5.000	3.590	4.000	6.890	3.819	3.110	2	15,0	1	PB	13.450


Spare Parts, included in delivery

For DCBN-DCBX	Coolant screw	Locking screw
		
0.375	950A0304	951CNC037031
0.500	950A0304	951CNC043037
0.625	950A0304	951CNC056050
0.750	950A0304	951CNC062050
1.000-1.500	950A0404	951CNC075068
2.000	950A0404	951CNS100087


ISO 9766
– Metric/ Inch



Design 1



Design 2



– Only for ISO 9766 drill shank
– For ISO attribute explanation, see page 15

Spare parts:
1 = Locking screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LFS	BD	OAL	LB	LSC	Design	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
C3-391.27-16056	75040036	C3	16,0 0.630	56,0 2.205	41,2 1.622	36,0 1.417	75,0 2.953	41,0 1.614	49,5 1.949	1	60,0	0	PB	0,4 0.880
C3-391.27-20060	75040039	C3	20,0 0.787	60,0 2.362	45,2 1.780	40,0 1.575	79,0 3.110	45,0 1.772	51,5 2.028	1	–	0	PB	0,5 1.100
C4-391.27-16056	75040040	C4	16,0 0.630	56,0 2.205	41,2 1.622	36,0 1.417	80,0 3.150	32,5 1.280	49,5 1.949	2	60,0	0	PB	0,5 1.100
C4-391.27-20060	75040041	C4	20,0 0.787	60,0 2.362	45,2 1.780	40,0 1.575	84,0 3.307	51,5 2.028	51,5 2.028	2	–	0	PB	0,6 1.320
C4-391.27-25077	75040042	C4	25,0 0.984	77,0 3.031	60,2 2.370	45,0 1.772	101,0 3.976	57,0 2.244	57,5 2.264	1	–	0	PB	0,8 1.760
C5-391.27-16065	75040043	C5	16,0 0.630	65,0 2.559	50,2 1.976	36,0 1.417	95,0 3.740	41,7 1.642	49,5 1.949	2	25,0	0	PB	0,8 1.760
C5-391.27-20060	75040044	C5	20,0 0.787	60,0 2.362	45,2 1.780	40,0 1.575	90,0 3.543	37,7 1.484	51,5 2.028	2	25,0	0	PB	0,7 1.540
C5-391.27-25071	02432677	C5	25,0 0.984	71,0 2.795	54,2 2.134	45,0 1.772	101,0 3.976	46,7 1.839	62,5 2.461	2	60,0	0	PB	0,9 1.980
C5-391.27-32075	75040046	C5	32,0 1.260	75,0 2.953	75,0 2.953	52,0 2.047	105,0 4.134	55,0 2.165	61,5 2.421	1	–	0	PB	1,0 2.200
C6-391.27-16070	75040047	C6	16,0 0.630	70,0 2.756	55,2 2.173	36,0 1.417	108,0 4.252	43,0 1.693	49,5 1.949	2	20,0	0	PB	1,1 2.430
C6-391.27-20070	75040048	C6	20,0 0.787	70,0 2.756	55,2 2.173	40,0 1.575	108,0 4.252	43,8 1.724	51,5 2.028	2	20,0	0	PB	1,1 2.430
C6-391.27-25070A	02450595	C6	25,0 0.984	72,0 2.835	55,2 2.173	45,0 1.772	110,0 4.331	45,8 1.803	59,5 2.343	2	25,0	0	PB	1,2 2.650
C6-391.27-32075	75040050	C6	32,0 1.260	75,0 2.953	58,2 2.291	52,0 2.047	113,0 4.449	49,8 1.961	61,5 2.421	2	30,0	0	PB	1,3 2.870
C6-391.27-40085	00024796	C6	40,0 1.575	85,0 3.346	85,0 3.346	65,0 2.559	123,0 4.843	63,0 2.480	71,5 2.815	1	–	0	PB	1,7 3.750
C8-391.27-16080	02300843	C8	16,0 0.630	80,0 3.150	80,0 3.150	36,0 1.417	128,0 5.039	42,0 1.654	49,5 1.949	2	20,0	0	PB	2,14 4.720
C8-391.27-20080	02300847	C8	20,0 0.787	80,0 3.150	80,0 3.150	40,0 1.575	128,0 5.039	43,8 1.724	51,5 2.028	2	17,0	0	PB	2,16 4.760
C8-391.27-25085	02300848	C8	25,0 0.984	85,0 3.346	85,0 3.346	45,0 1.772	133,0 5.236	49,8 1.961	57,5 2.264	2	17,0	0	PB	2,3 5.070
C8-391.27-32090	02300849	C8	32,0 1.260	90,0 3.543	90,0 3.543	52,0 2.047	138,0 5.433	53,8 2.118	61,5 2.421	2	14,0	0	PB	2,4 5.290
C8-391.27-40095	02207177	C8	40,0 1.575	95,0 3.740	95,0 3.740	65,0 2.559	143,0 5.630	62,8 2.472	71,5 2.815	2	17,0	0	PB	2,7 5.950

Spare Parts, included in delivery

For	Locking screw
	
16/ 0.630	5514042-04
20/ 0.787	5514042-04
25/ 0.984	416.1-838
32/ 1.260	416.1-838
40/ 1.575	5514042-06

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

DIN type
– Metric/ Inch



–Run-out ≤3 µm
–Delivered with one stop screw
–Without threads for balancing screws
–For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
C3-391.5603-06065	02753139	C3	6,0 0.236	65,0 2.559	47,0 1.850	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	84,0 3.307	29,0 1.142	39,0 1.535	M5x0.8	4,5	0	G6.3	0,3 0.660
C3-391.5603-08065	02753140	C3	8,0 0.315	65,0 2.559	47,0 1.850	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	84,0 3.307	29,0 1.142	39,0 1.535	M6x1	4,5	0	G6.3	0,3 0.660
C3-391.5603-10070	02753141	C3	10,0 0.394	70,0 2.756	55,0 2.165	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	89,0 3.504	29,0 1.142	39,0 1.535	M8x1	4,5	0	G6.3	0,4 0.880
C3-391.5603-12070	02753142	C3	12,0 0.472	70,0 2.756	55,0 2.165	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	89,0 3.504	24,0 0.945	34,0 1.339	M10x1	4,5	0	G6.3	0,4 0.880
C4-391.5603-06075	02753144	C4	6,0 0.236	75,0 2.953	52,0 2.047	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	99,0 3.898	39,0 1.535	49,0 1.929	M5x0.8	4,5	0	G6.3	0,5 1.100
C4-391.5603-08075	02753145	C4	8,0 0.315	75,0 2.953	52,0 2.047	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	99,0 3.898	39,0 1.535	49,0 1.929	M6x1	4,5	0	G6.3	0,5 1.100
C4-391.5603-10075	02753146	C4	10,0 0.394	75,0 2.953	52,0 2.047	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	99,0 3.898	34,0 1.339	44,0 1.732	M8x1	4,5	0	G6.3	0,5 1.100
C4-391.5603-12075	02753147	C4	12,0 0.472	75,0 2.953	52,0 2.047	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	99,0 3.898	29,0 1.142	39,0 1.535	M10x1	4,5	0	G6.3	0,5 1.100
C4-391.5603-14080	02753149	C4	14,0 0.551	80,0 3.150	57,0 2.244	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	104,0 4.094	34,0 1.339	44,0 1.732	M10x1	4,5	0	G6.3	0,6 1.320
C4-391.5603-16080	02753150	C4	16,0 0.630	80,0 3.150	57,0 2.244	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	104,0 4.094	31,0 1.220	41,0 1.614	M12x1	4,5	0	G6.3	0,6 1.320
C5-391.5603-06075	02753151	C5	6,0 0.236	75,0 2.953	52,0 2.047	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	105,0 4.134	39,0 1.535	49,0 1.929	M5x0.8	4,5	1	G6.3	0,7 1.540
C5-391.5603-08075	02753153	C5	8,0 0.315	75,0 2.953	52,0 2.047	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	105,0 4.134	39,0 1.535	49,0 1.929	M6x1	4,5	1	G6.3	0,7 1.540
C5-391.5603-10075	02753154	C5	10,0 0.394	75,0 2.953	52,0 2.047	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	105,0 4.134	34,0 1.339	44,0 1.732	M8x1	4,5	1	G6.3	0,68 1.500
C5-391.5603-12075	02753156	C5	12,0 0.472	75,0 2.953	52,0 2.047	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	105,0 4.134	29,0 1.142	39,0 1.535	M10x1	4,5	1	G6.3	0,67 1.480
C5-391.5603-14080	02753157	C5	14,0 0.551	80,0 3.150	57,0 2.244	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	110,0 4.331	34,0 1.339	44,0 1.732	M10x1	4,5	1	G6.3	0,74 1.630
C5-391.5603-16080	02753158	C5	16,0 0.630	80,0 3.150	57,0 2.244	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	110,0 4.331	31,0 1.220	41,0 1.614	M12x1	4,5	1	G6.3	0,8 1.760
C5-391.5603-18080	02753159	C5	18,0 0.709	80,0 3.150	57,0 2.244	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	110,0 4.331	31,0 1.220	41,0 1.614	M12x1	4,5	1	G6.3	0,9 1.980
C5-391.5603-20085	02753160	C5	20,0 0.787	85,0 3.346	62,0 2.441	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	115,0 4.528	34,0 1.339	44,0 1.732	M16x1	4,5	1	G6.3	0,9 1.980
C5-391.5603-25090	02753161	C5	25,0 0.984	90,0 3.543	70,0 2.756	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	120,0 4.724	33,0 1.299	43,0 1.693	M16x1	4,5	1	G6.3	1,3 2.870
C6-391.5603-06080	02753167	C6	6,0 0.236	80,0 3.150	55,0 2.165	37,5 1.476	22,0 0.866	21,0 0.827	27,0 1.063	118,0 4.646	44,0 1.732	54,0 2.126	M5x0.8	4,5	1	G6.3	1,1 2.430
C6-391.5603-08080	02753168	C6	8,0 0.315	80,0 3.150	55,0 2.165	37,5 1.476	26,0 1.024	21,0 0.827	27,0 1.063	118,0 4.646	44,0 1.732	54,0 2.126	M6x1	4,5	1	G6.3	1,0 2.200
C6-391.5603-10080	02753169	C6	10,0 0.394	80,0 3.150	55,0 2.165	42,5 1.673	31,0 1.220	24,0 0.945	32,0 1.260	118,0 4.646	39,0 1.535	49,0 1.929	M8x1	4,5	1	G6.3	1,1 2.430

Designation	Item number	CTMS	DCBN- DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
C6-391.5603-12080	02753170	C6	12,0 0.472	80,0 3.150	55,0 2.165	47,5 1.870	34,0 1.339	24,0 0.945	32,0 1.260	118,0 4.646	34,0 1.339	44,0 1.732	M10x1	4,5	1	G6.3	1,1 2.430
C6-391.5603-14085	02753172	C6	14,0 0.551	85,0 3.346	60,0 2.362	47,5 1.870	34,0 1.339	27,0 1.063	34,0 1.339	123,0 4.843	39,0 1.535	49,0 1.929	M10x1	4,5	1	G6.3	1,2 2.650
C6-391.5603-16085	02753174	C6	16,0 0.630	85,0 3.346	60,0 2.362	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	123,0 4.843	36,0 1.417	46,0 1.811	M12x1	4,5	1	G6.3	1,1 2.430
C6-391.5603-18085	02753175	C6	18,0 0.709	85,0 3.346	60,0 2.362	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	123,0 4.843	36,0 1.417	46,0 1.811	M12x1	4,5	1	G6.3	1,3 2.870
C6-391.5603-20085	02753176	C6	20,0 0.787	85,0 3.346	60,0 2.362	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	123,0 4.843	34,0 1.339	44,0 1.732	M16x1	4,5	1	G6.3	1,2 2.650
C6-391.5603-25090	02753178	C6	25,0 0.984	90,0 3.543	65,0 2.559	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	128,0 5.039	33,0 1.299	43,0 1.693	M16x1	4,5	1	G6.3	1,6 3.530
C6-391.5603-32095	02753185	C6	32,0 1.260	95,0 3.740	70,0 2.756	62,5 2.461	51,0 2.008	44,0 1.732	53,0 2.087	133,0 5.236	34,0 1.339	44,0 1.732	M16x1	4,5	1	G6.3	1,5 3.310
C8-391.5603-16090	02753186	C8	16,0 0.630	90,0 3.543	57,0 2.244	50,5 1.988	39,0 1.535	27,0 1.063	34,0 1.339	138,0 5.433	41,0 1.614	51,0 2.008	M12x1	4,5	1	G6.3	2,1 4.630
C8-391.5603-18090	02753187	C8	18,0 0.709	90,0 3.543	57,0 2.244	50,5 1.988	39,0 1.535	33,0 1.299	42,0 1.654	138,0 5.433	41,0 1.614	51,0 2.008	M12x1	4,5	1	G6.3	2,4 5.290
C8-391.5603-20090	02753189	C8	20,0 0.787	90,0 3.543	57,0 2.244	52,5 2.067	41,0 1.614	33,0 1.299	42,0 1.654	138,0 5.433	39,0 1.535	49,0 1.929	M16x1	4,5	1	G6.3	2,2 4.850
C8-391.5603-25090	02753190	C8	25,0 0.984	90,0 3.543	57,0 2.244	58,5 2.303	47,0 1.850	44,0 1.732	53,0 2.087	138,0 5.433	33,0 1.299	43,0 1.693	M16x1	4,5	1	G6.3	2,4 5.290
C8-391.5603-32090	02753191	C8	32,0 1.260	90,0 3.543	57,0 2.244	62,5 2.461	51,0 2.008	44,0 1.732	53,0 2.087	138,0 5.433	29,0 1.142	39,0 1.535	M16x1	4,5	1	G6.3	2,2 4.850

Spare Parts, included in delivery

For	Stop screw
	
6/ 0.236	19BDR05165
8/ 0.315	19BDR06165
10/ 0.394	19BDR08165
12-14/ 0.472-0.551	19BDR10165
16-18/ 0.630-0.709	19BDR12165
20-32/ 0.787-1.260	19BDR16165

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

DIN type
– Inch

Seco Capto™



–Run-out $\leq 3 \mu\text{m}$
 –Delivered with one stop screw
 –Without threads for balancing screws
 –For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CDBP	LSC	BD1	BD2	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
C3-391.5603-025065	02753407	C3	0.250	2.559	1.850	1.476	0.866	0.827	1.063	3.307	1.142	1.535	M5x0.8	4,5	0	G6.3	0.660
C3-391.5603-031065	02753409	C3	0.3135	2.559	1.850	1.476	1.024	0.827	1.063	3.307	1.142	1.535	M6x1	4,5	0	G6.3	0.660
C3-391.5603-037070	02753410	C3	0.375	2.756	2.165	1.673	1.220	0.945	1.260	3.504	1.142	1.535	M8x1	4,5	0	G6.3	0.880
C3-391.5603-050070	02753411	C3	0.500	2.756	2.165	1.791	1.339	0.945	1.260	3.504	1.024	1.417	M10x1	4,5	0	G6.3	0.880
C4-391.5603-025075	02753415	C4	0.250	2.953	2.047	1.476	0.866	0.827	1.063	3.898	1.535	1.929	M5x0.8	4,5	0	G6.3	1.100
C4-391.5603-031075	02753418	C4	0.3135	2.953	2.047	1.476	1.024	0.827	1.063	3.898	1.535	1.929	M6x1	4,5	0	G6.3	1.100
C4-391.5603-037075	02753419	C4	0.375	2.953	2.047	1.673	1.220	0.945	1.260	3.898	1.339	1.732	M8x1	4,5	0	G6.3	1.320
C4-391.5603-050075	02753421	C4	0.500	2.953	2.047	1.791	1.339	0.945	1.260	3.898	1.220	1.614	M10x1	4,5	0	G6.3	1.100
C4-391.5603-062080	02753422	C4	0.625	3.150	2.244	1.988	1.535	1.063	1.339	4.094	1.220	1.614	M12x1	4,5	0	G6.3	1.320
C5-391.5603-025075	02753423	C5	0.250	2.953	2.047	1.476	0.866	0.827	1.063	4.134	1.535	1.929	M5x0.8	4,5	1	G6.3	1.540
C5-391.5603-031075	02753424	C5	0.3135	2.953	2.047	1.476	1.024	0.827	1.063	4.134	1.535	1.929	M6x1	4,5	1	G6.3	1.540
C5-391.5603-037075	02753425	C5	0.375	2.953	2.047	1.673	1.220	0.945	1.260	4.134	1.339	1.732	M8x1	4,5	1	G6.3	1.540
C5-391.5603-050075	02753426	C5	0.500	2.953	2.047	1.791	1.339	0.945	1.260	4.134	1.220	1.614	M10x1	4,5	1	G6.3	1.540
C5-391.5603-062080	02753428	C5	0.625	3.150	2.244	1.988	1.535	1.063	1.339	4.331	1.220	1.614	M12x1	4,5	1	G6.3	1.760
C5-391.5603-075085	02753429	C5	0.750	3.346	2.441	2.067	1.614	1.299	1.654	4.528	1.339	1.732	M16x1	4,5	1	G6.3	1.980
C5-391.5603-100090	02753430	C5	1.000	3.543	2.756	2.303	1.850	1.732	2.087	4.724	1.299	1.693	M16x1	4,5	1	G6.3	2.870
C5-391.5603-125090	02753431	C5	1.250	3.543	2.756	2.461	2.008	1.732	2.087	4.724	1.142	1.535	M16x1	4,5	1	G6.3	2.430
C6-391.5603-025075	02753432	C6	0.250	2.953	1.969	1.476	0.866	0.827	1.063	4.449	1.535	1.929	M5x0.8	4,5	1	G6.3	2.200
C6-391.5603-031075	02753433	C6	0.3135	2.953	1.969	1.476	1.024	0.827	1.063	4.449	1.535	1.929	M6x1	4,5	1	G6.3	2.200
C6-391.5603-037080	02753434	C6	0.375	3.150	2.165	1.673	1.220	0.945	1.260	4.646	1.535	1.929	M8x1	4,5	1	G6.3	2.430
C6-391.5603-050080	02753435	C6	0.500	3.150	2.165	1.791	1.339	0.945	1.260	4.646	1.417	1.811	M10x1	4,5	1	G6.3	2.430
C6-391.5603-062085	02753436	C6	0.625	3.346	2.362	1.988	1.535	1.063	1.339	4.843	1.417	1.811	M12x1	4,5	1	G6.3	2.430
C6-391.5603-075085	02753437	C6	0.750	3.346	2.362	2.067	1.614	1.299	1.654	4.843	1.339	1.732	M16x1	4,5	1	G6.3	2.650
C6-391.5603-100090	02753439	C6	1.000	3.543	2.559	2.303	1.850	1.732	2.087	5.039	1.299	1.693	M16x1	4,5	1	G6.3	3.530
C6-391.5603-125095	02753440	C6	1.250	3.740	2.756	2.461	2.008	1.732	2.087	5.236	1.339	1.732	M16x1	4,5	1	G6.3	3.310
C8-391.5603-062090	02753441	C8	0.625	3.543	2.244	1.988	1.535	1.063	1.339	5.433	1.614	2.008	M12x1	4,5	1	G6.3	4.630
C8-391.5603-075095	02753442	C8	0.750	3.740	2.441	2.067	1.614	1.299	1.654	5.630	1.732	2.126	M16x1	4,5	1	G6.3	4.850
C8-391.5603-100095	02753443	C8	1.000	3.740	2.441	2.303	1.850	1.732	2.087	5.630	1.496	1.890	M16x1	4,5	1	G6.3	5.510
C8-391.5603-125095	02753445	C8	1.250	3.740	2.441	2.461	2.008	1.732	2.087	5.630	1.339	1.732	M16x1	4,5	1	G6.3	5.290

Accessories

For	Stop screw
	
0.250	19BDR05165
0.313	19BDR06165
0.375	19BDR08165
0.500	19BDR10165
0.625	19BDR12165
0.750	19BDR16165
1.000	19BDR16165
1.250	19BDR16165

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Reinforced type – Metric/ Inch

Seco Capto™



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR*	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
C6-391.5600-12080	02904834	C6	12,0 0.472	80,0 3.150	55,0 2.165	47,5 1.870	34,0 1.339	27,0 1.063	35,2 1.385	118,0 4.646	34,0 1.339	44,0 1.732	13,5 0.531	M10x1	4,5	1	G6.3	1,2 2.650
C6-391.5600-16085	02904835	C6	16,0 0.630	85,0 3.346	60,0 2.362	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	123,0 4.843	36,0 1.417	46,0 1.811	17,0 0.669	M12x1	4,5	1	G6.3	1,3 2.870
C6-391.5600-20085	02904836	C6	20,0 0.787	85,0 3.346	60,0 2.362	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	123,0 4.843	34,0 1.339	44,0 1.732	21,5 0.846	M16x1	4,5	1	G6.3	1,6 3.530
C6-391.5600-25090	02904837	C6	25,0 0.984	90,0 3.543	65,0 2.559	58,5 2.303	47,0 1.850	48,0 1.890	57,1 2.249	128,0 5.039	33,0 1.299	43,0 1.693	25,0 0.984	M16x1	4,5	1	G6.3	1,7 3.750
C8-391.5600-16095	02904838	C8	16,0 0.630	95,0 3.740	62,0 2.441	50,5 1.988	39,0 1.535	33,0 1.299	42,1 1.659	143,0 5.630	46,0 1.811	56,0 2.205	17,0 0.669	M12x1	4,5	1	G6.3	2,3 5.070
C8-391.5600-20095	02904839	C8	20,0 0.787	95,0 3.740	62,0 2.441	52,5 2.067	41,0 1.614	44,0 1.732	53,1 2.092	143,0 5.630	44,0 1.732	54,0 2.126	21,5 0.846	M16x1	4,5	1	G6.3	2,6 5.730
C8-391.5600-25100	02904840	C8	25,0 0.984	100,0 3.937	67,0 2.638	58,5 2.303	47,0 1.850	48,0 1.890	57,1 2.249	148,0 5.827	43,0 1.693	53,0 2.087	25,0 0.984	M16x1	4,5	1	G6.3	2,8 6.170

Accessories


For	Balancing screws
	
All	90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Stop screw
		
12/ 0.472	90AI03	19BDR10165
16/ 0.630	90AI03	19BDR12165
20-25/ 0.787-0.984	90AI04	19BDR16165

Reinforced type – Inch

Seco Capto™ / ISO 26623-1



- Run-out $\leq 3 \mu\text{m}$
- With coolant supply channels towards the tool (plugged)
- Delivered with one stop screw
- For ISO attribute explanation, see page 15

Spare parts:
1 = Stop screw
2 = Sealing plugs

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	CBDP	LSC	BD1	BD2	OAL	LFN	LF	RL	TDZ	BHTA°	RFID hole	Balancing	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch	inch					lbs
C6-391.5600-050312	02904863	C6	0.500	3.125	2.141	1.870	1.339	1.063	1.385	4.621	1.314	1.708	0.531	M10x1	4,5	1	G6.3	2.430
C6-391.5600-062337	02904864	C6	0.625	3.375	2.391	1.988	1.535	1.299	1.659	4.871	1.446	1.840	0.669	M12x1	4,5	1	G6.3	2.870
C6-391.5600-075337	02904865	C6	0.750	3.375	2.391	2.067	1.614	1.732	2.092	4.871	1.367	1.761	0.846	M16x1	4,5	1	G6.3	3.530
C8-391.5600-075375	02904866	C8	0.750	3.750	2.451	2.067	1.614	1.732	2.092	5.640	1.742	2.136	0.846	M16x1	4,5	1	G6.3	5.730
C8-391.5600-100400	02904867	C8	1.000	4.000	2.701	2.303	1.850	1.890	2.249	5.890	1.756	2.150	0.984	M16x1	4,5	1	G6.3	6.170
C8-391.5600-125400	02904868	C8	1.250	4.000	2.701	2.461	2.008	1.890	2.249	5.890	1.598	1.992	0.984	M16x1	4,5	1	G6.3	5.730

Accessories

For	Balancing screws
	
0.500	90ZQ01
0.625	90ZQ01
0.750-1.250	90ZQ01

Spare Parts, included in delivery

For	Sealing plugs	Stop screw
		
0.500	90AI03	19BDR10165
0.625	90AI03	19BDR12165
0.750-1.250	90AI04	19BDR16165

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

– Metric/ Inch





–Run-out 3 µm maximum at 3 x ØDCBN-DCBX
 –For ER HP collets type 5672, see page(s) 389, 390, 391-397
 –For stop screws, see instructions at www.secotools.com
 –For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD1	BD2	OAL	LB	RFID hole	Balancing	Weight
			mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
C3-ERHP11R-045	10358848	C3	1,0 0.039	7,0 0.276	HP 11R	45,0 1.772	16,0 0.630	16,0 0.630	64,0 2.520	27,0 1.063	0	G6.3	0,2 0.440
C3-ERHP16R-045	10358849	C3	1,0 0.039	10,0 0.394	HP 16R	45,0 1.772	22,0 0.866	22,0 0.866	64,0 2.520	27,0 1.063	0	G6.3	0,2 0.440
C4-ERHP11R-045	10358850	C4	1,0 0.039	7,0 0.276	HP 11R	45,0 1.772	16,0 0.630	16,0 0.630	69,0 2.717	22,0 0.866	0	G6.3	0,3 0.660
C4-ERHP16R-055	10358851	C4	1,0 0.039	10,0 0.394	HP 16R	55,0 2.165	22,0 0.866	22,0 0.866	79,0 3.110	32,0 1.260	0	G6.3	0,4 0.880
C4-ERHP20-055	10358852	C4	1,0 0.039	13,0 0.512	HP 20	55,0 2.165	32,0 1.260	32,0 1.260	79,0 3.110	32,0 1.260	0	G6.3	0,4 0.880
C5-ERHP16-065	10358853	C5	1,0 0.039	10,0 0.394	HP 16	65,0 2.559	30,0 1.181	30,0 1.181	95,0 3.740	42,0 1.654	1	G6.3	0,7 1.540
C5-ERHP16-100	10358854	C5	1,0 0.039	10,0 0.394	HP 16	100,0 3.937	30,0 1.181	30,0 1.181	130,0 5.118	77,0 3.031	1	G6.3	2,6 5.730
C5-ERHP20-085	10358855	C5	1,0 0.039	13,0 0.512	HP 20	85,0 3.346	32,0 1.260	32,0 1.260	115,0 4.528	62,0 2.441	1	G6.3	0,8 1.760
C5-ERHP20-130	10358856	C5	1,0 0.039	13,0 0.512	HP 20	130,0 5.118	32,0 1.260	32,0 1.260	160,0 6.299	107,0 4.213	1	G6.3	1,0 2.200
C5-ERHP25-085	10358857	C5	1,0 0.039	16,0 0.630	HP 25	85,0 3.346	40,0 1.575	40,0 1.575	115,0 4.528	62,0 2.441	1	G6.3	0,9 1.980
C5-ERHP25-130	10358858	C5	1,0 0.039	16,0 0.630	HP 25	130,0 5.118	40,0 1.575	40,0 1.575	160,0 6.299	107,0 4.213	1	G6.3	1,3 2.870
C5-ERHP32-085	10358859	C5	2,0 0.079	20,0 0.787	HP 32	85,0 3.346	50,0 1.969	50,0 1.969	115,0 4.528	62,0 2.441	1	G6.3	1,1 2.430
C5-ERHP32-130	10358860	C5	2,0 0.079	20,0 0.787	HP 32	130,0 5.118	50,0 1.969	50,0 1.969	160,0 6.299	107,0 4.213	1	G6.3	1,7 3.750
C6-ERHP11R-050	10358861	C6	1,0 0.039	7,0 0.276	HP 11R	50,0 1.969	16,0 0.630	16,0 0.630	88,0 3.465	25,0 0.984	1	G6.3	0,9 1.980
C6-ERHP16-076	10358862	C6	1,0 0.039	10,0 0.394	HP 16	76,0 2.992	30,0 1.181	30,0 1.181	114,0 4.488	51,0 2.008	1	G6.3	1,1 2.430
C6-ERHP16-100	10358863	C6	1,0 0.039	10,0 0.394	HP 16	100,0 3.937	30,0 1.181	30,0 1.181	138,0 5.433	75,0 2.953	1	G6.3	1,2 2.650
C6-ERHP16-130	10358864	C6	1,0 0.039	10,0 0.394	HP 16	130,0 5.118	30,0 1.181	30,0 1.181	168,0 6.614	105,0 4.134	1	G6.3	1,3 2.870
C6-ERHP20-076	10358865	C6	1,0 0.039	13,0 0.512	HP 20	76,0 2.992	32,0 1.260	32,0 1.260	114,0 4.488	51,0 2.008	1	G6.3	1,1 2.430
C6-ERHP20-130	10358866	C6	1,0 0.039	13,0 0.512	HP 20	130,0 5.118	32,0 1.260	32,0 1.260	168,0 6.614	105,0 4.134	1	G6.3	1,4 3.090
C6-ERHP25-090	10358867	C6	1,0 0.039	16,0 0.630	HP 25	90,0 3.543	40,0 1.575	40,0 1.575	128,0 5.039	65,0 2.559	1	G6.3	1,3 2.870
C6-ERHP25-130	10358868	C6	1,0 0.039	16,0 0.630	HP 25	130,0 5.118	40,0 1.575	40,0 1.575	168,0 6.614	105,0 4.134	1	G6.3	1,6 3.530
C6-ERHP25-160	10358869	C6	1,0 0.039	16,0 0.630	HP 25	160,0 6.299	40,0 1.575	40,0 1.575	198,0 7.795	135,0 5.315	1	G6.3	1,8 3.970

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	CTWS	LPR mm inch	BD1 mm inch	BD2 mm inch	OAL mm inch	LB mm inch	RFID hole	Balan- cing	Weight kg lbs
C6-ERHP32-100	10358870	C6	2,0 0.079	20,0 0.787	HP 32	100,0 3.937	50,0 1.969	50,0 1.969	138,0 5.433	75,0 2.953	1	G6.3	1,7 3.750
C6-ERHP32-130	10358871	C6	2,0 0.079	20,0 0.787	HP 32	130,0 5.118	50,0 1.969	50,0 1.969	168,0 6.614	105,0 4.134	1	G6.3	2,3 5.070
C6-ERHP32-160	10358872	C6	2,0 0.079	20,0 0.787	HP 32	160,0 6.299	50,0 1.969	50,0 1.969	198,0 7.795	135,0 5.315	1	G6.3	2,4 5.290
C8-ERHP25-100	10358873	C8	1,0 0.039	16,0 0.630	HP 25	100,0 3.937	40,0 1.575	40,0 1.575	148,0 5.827	67,0 2.638	1	G6.3	2,3 5.070
C8-ERHP32-100	10358874	C8	2,0 0.079	20,0 0.787	HP 32	100,0 3.937	50,0 1.969	50,0 1.969	148,0 5.827	67,0 2.638	1	G6.3	2,5 5.510

Accessories

For	Key	Socket	Torque key
			
ERHP11R	03LME0912140	03ER016	03DYE003025
ERHP16R	03LME0912140	03ER022	03DYE010050
ERHP16	03LME1418260	03ER030B	03DYE010100B
ERHP20	03LME1418260	03ER032B	03DYE010100B
ERHP25	03LME1418260	03ER040	03DYE010100B
ERHP32	03LME1418370	03ER050	03DYE040200

Spare Parts, included in delivery

For	Nut
	
ERHP11R	08B567211RC
ERHP16R	08B567216RC
ERHP16	08B567216C
ERHP20	08B567220C
ERHP25	08B567225C
ERHP32	08B567232C

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Conventional type – Metric/ Inch

Seco Capto™




–Run-out $\leq 3 \mu\text{m}$
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CBDP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
C5-HC06-065	10137305	C5	6,0 0.236	65,0 2.559	45,0 1.772	23,0 0.906	38,0 1.496	50,0 1.969	26,0 1.024	95,0 3.740	27,0 1.063	37,0 1.457	M5x0.8	30,0	1	–	0,8 1.760
C5-HC08-065	10137306	C5	8,0 0.315	65,0 2.559	45,0 1.772	24,0 0.945	38,0 1.496	50,0 1.969	28,0 1.102	95,0 3.740	27,0 1.063	37,0 1.457	M5x0.8	30,0	1	–	0,8 1.760
C5-HC10-075	10137307	C5	10,0 0.394	75,0 2.953	55,0 2.165	34,0 1.339	42,0 1.654	50,0 1.969	30,0 1.181	105,0 4.134	33,0 1.299	43,0 1.693	M8x1.25	30,0	1	–	0,9 1.980
C5-HC12-080	10137308	C5	12,0 0.472	80,0 3.150	60,0 2.362	40,0 1.575	47,0 1.850	50,0 1.969	32,0 1.260	110,0 4.331	33,0 1.299	43,0 1.693	M10x1.5	30,0	1	–	0,9 1.980
C5-HC16-085	10137309	C5	16,0 0.630	85,0 3.346	65,0 2.559	46,0 1.811	50,0 1.969	50,0 1.969	38,0 1.496	115,0 4.528	35,0 1.378	45,0 1.772	M10x1.5	30,0	1	–	1,0 2.200
C5-HC20-085	10137310	C5	20,0 0.787	85,0 3.346	65,0 2.559	47,0 1.850	52,0 2.047	50,0 1.969	42,0 1.654	115,0 4.528	33,0 1.299	43,0 1.693	M10x1.5	30,0	1	–	1,1 2.430
C5-HC25-095	10137311	C5	25,0 0.984	95,0 3.740	75,0 2.953	–	58,0 2.283	–	58,0 2.283	125,0 4.921	37,0 1.457	47,0 1.850	M10x1.5	–	1	–	1,7 3.750
C6-HC06-065	10137312	C6	6,0 0.236	65,0 2.559	40,0 1.575	23,0 0.906	38,0 1.496	50,0 1.969	26,0 1.024	103,0 4.055	27,0 1.063	37,0 1.457	M5x0.8	30,0	1	–	1,2 2.650
C6-HC08-065	10137313	C6	8,0 0.315	65,0 2.559	40,0 1.575	24,0 0.945	38,0 1.496	50,0 1.969	28,0 1.102	103,0 4.055	27,0 1.063	37,0 1.457	M5x0.8	30,0	1	–	1,2 2.650
C6-HC10-075	10137314	C6	10,0 0.394	75,0 2.953	50,0 1.969	34,0 1.339	42,0 1.654	50,0 1.969	30,0 1.181	113,0 4.449	33,0 1.299	43,0 1.693	M8x1.25	30,0	1	–	1,2 2.650
C6-HC12-080	10137315	C6	12,0 0.472	80,0 3.150	55,0 2.165	40,0 1.575	47,0 1.850	50,0 1.969	32,0 1.260	118,0 4.646	33,0 1.299	43,0 1.693	M10x1.5	30,0	1	–	1,2 2.650
C6-HC16-085	10137316	C6	16,0 0.630	85,0 3.346	60,0 2.362	46,0 1.811	50,0 1.969	50,0 1.969	38,0 1.496	123,0 4.843	35,0 1.378	45,0 1.772	M10x1.5	30,0	1	–	1,4 3.090
C6-HC20-085	10137317	C6	20,0 0.787	85,0 3.346	60,0 2.362	47,0 1.850	52,0 2.047	50,0 1.969	42,0 1.654	123,0 4.843	33,0 1.299	43,0 1.693	M10x1.5	30,0	1	–	1,4 3.090
C6-HC25-095	10137318	C6	25,0 0.984	95,0 3.740	70,0 2.756	–	58,0 2.283	–	58,0 2.283	133,0 5.236	37,0 1.457	47,0 1.850	–	–	1	–	2,0 4.410
C6-HC32-100	10137319	C6	32,0 1.260	100,0 3.937	78,0 3.071	–	63,0 2.480	–	64,0 2.520	138,0 5.433	37,0 1.457	47,0 1.850	M10x1.5	–	1	–	2,3 5.070
C8-HC20-095	10137320	C8	20,0 0.787	95,0 3.740	62,0 2.441	47,0 1.850	52,0 2.047	50,0 1.969	42,0 1.654	143,0 5.630	43,0 1.693	53,0 2.087	M10x1.5	30,0	1	–	2,4 5.290
C8-HC32-105	10137321	C8	32,0 1.260	105,0 4.134	72,0 2.835	60,0 2.362	63,0 2.480	70,0 2.756	64,0 2.520	153,0 6.024	42,0 1.654	52,0 2.047	M10x1.5	30,0	1	G6.3	3,3 7.280

Accessories

For	Key
	
All	03MS04C

Reinforced type
– Metric/ Inch



– Run-out $\leq 3 \mu\text{m}$
– For reduction sleeves, see page(s) 381, 382
– For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	LB	LB1	CDBP	BD2	BD1	OAL	LFN	LF	TDZ	BHTA°	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
C6-HCR12-075	10137146	C6	12,0 0.472	75,0 2.953	53,0 2.087	33,0 1.299	47,5 1.870	62,5 2.461	42,0 1.654	113,0 4.449	29,0 1.142	39,0 1.535	M8x1	20,0	0	G2.5	1,5 3.310
C6-HCR20-080	10137147	C6	20,0 0.787	80,0 3.150	57,4 2.260	41,0 1.614	52,5 2.067	62,5 2.461	52,5 2.067	118,0 4.646	29,0 1.142	39,0 1.535	M8x1	20,0	0	G2.5	1,7 3.750

Accessories

For	Key
	
All	H05-4

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

– Metric/ Inch




–For reduction sleeves, see page(s) 385–386
 –For ‘Stop screws for through coolant’, see page(s) 387–388
 –For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	OAL	LPR	LB	CBDP	BD1	RFID hole	Balancing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
C6-PMC20-080	03211193	C6	20,0 0.787	118,0 4.646	80,0 3.150	58,0 2.283	60,0 2.362	49,0 1.929	1	PB	1,4 3.090
C6-PMC32-100	03211194	C6	32,0 1.260	138,0 5.433	100,0 3.937	78,0 3.071	80,0 3.150	67,0 2.638	1	PB	2,2 4.850
C8-PMC20-080	03211195	C8	20,0 0.787	128,0 5.039	80,0 3.150	50,0 1.969	60,0 2.362	49,0 1.929	1	PB	2,3 5.070
C8-PMC32-100	03211196	C8	32,0 1.260	148,0 5.827	100,0 3.937	70,0 2.756	80,0 3.150	67,0 2.638	1	PB	3,0 6.610

Accessories

For	Spanner
-----	---------



20/ 0.787	03BPMC20
32/ 1.260	03BPMC32

Spare Parts, included in delivery


For	Extractor for reduction sleeves
-----	---------------------------------



20/ 0.787	03EXTPMC
32/ 1.260	03EXTPMC

ISO 15488
– Metric/ Inch

Seco Capto™




–Run-out 15 µm/ .0006" maximum at 3 x ØDCBN-DCBX
–For ER extensions and ER collets, see page(s) 362, 363, 399, 400, 401, 402
–For ER sealing rings, see page(s) 410, 411
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN mm inch	DCBX mm inch	CTWS	LPR mm inch	BD2 mm inch	BD1 mm inch	OAL mm inch	LB mm inch	LFN mm inch	LF mm inch	RFID hole	Balan- cing	Weight kg lbs
C3-ER16-045	10229708	C3	0,5 0.020	10,0 0.394	ER 16	45,0 1.772	32,0 1.260	28,0 1.102	64,0 2.520	27,0 1.063	6,0 0.236	13,0 0.512	0	G6.3	0,3 0.660
C4-ER16-070	10229709	C4	0,5 0.020	10,0 0.394	ER 16	70,0 2.756	28,0 1.102	28,0 1.102	94,0 3.701	47,0 1.850	26,0 1.024	38,0 1.496	0	G6.3	0,5 1.100
C4-ER20-052	10229710	C4	1,0 0.039	13,0 0.512	ER 20	52,0 2.047	40,0 1.575	34,0 1.339	76,0 2.992	29,0 1.142	6,0 0.236	18,0 0.709	0	G6.3	0,4 0.880
C4-ER25-052	10229711	C4	1,0 0.039	16,0 0.630	ER 25	52,0 2.047	40,0 1.575	42,0 1.654	76,0 2.992	29,0 1.142	6,0 0.236	14,0 0.551	0	G6.3	0,4 0.880
C4-ER32-054	10229712	C4	2,0 0.079	20,0 0.787	ER 32	54,0 2.126	40,0 1.575	50,0 1.969	78,0 3.071	34,0 1.339	7,0 0.276	14,0 0.551	0	G6.3	0,5 1.100
C5-ER16-100	10229713	C5	0,5 0.020	10,0 0.394	ER 16	100,0 3.937	28,0 1.102	28,0 1.102	130,0 5.118	77,0 3.031	53,0 2.087	68,0 2.677	1	G6.3	0,8 1.760
C5-ER20-055	10229714	C5	1,0 0.039	13,0 0.512	ER 20	55,0 2.165	34,0 1.339	34,0 1.339	85,0 3.346	32,0 1.260	7,0 0.276	21,0 0.827	1	G6.3	0,6 1.320
C5-ER25-055	10229715	C5	1,0 0.039	16,0 0.630	ER 25	55,0 2.165	42,0 1.654	42,0 1.654	85,0 3.346	32,0 1.260	7,0 0.276	17,0 0.669	1	G6.3	0,7 1.540
C5-ER25-100	10229716	C5	1,0 0.039	16,0 0.630	ER 25	100,0 3.937	42,0 1.654	42,0 1.654	130,0 5.118	77,0 3.031	42,0 1.654	62,0 2.441	1	G6.3	1,1 2.430
C5-ER32-057	10229717	C5	2,0 0.079	20,0 0.787	ER 32	57,0 2.244	50,0 1.969	50,0 1.969	87,0 3.425	34,0 1.339	7,0 0.276	17,0 0.669	1	G6.3	0,7 1.540
C5-ER32-100	10229718	C5	2,0 0.079	20,0 0.787	ER 32	100,0 3.937	50,0 1.969	50,0 1.969	130,0 5.118	80,0 3.150	40,0 1.575	60,0 2.362	1	G6.3	1,3 2.870
C6-ER16-060	10229719	C6	0,5 0.020	10,0 0.394	ER 16	60,0 2.362	28,0 1.102	28,0 1.102	98,0 3.858	35,0 1.378	9,0 0.354	28,0 1.102	1	G6.3	1,0 2.200
C6-ER16-100	10229720	C6	0,5 0.020	10,0 0.394	ER 16	100,0 3.937	28,0 1.102	28,0 1.102	138,0 5.433	75,0 2.953	53,0 2.087	68,0 2.677	1	G6.3	1,1 2.430
C6-ER16-130	10229721	C6	0,5 0.020	10,0 0.394	ER 16	130,0 5.118	28,0 1.102	28,0 1.102	168,0 6.614	105,0 4.134	83,0 3.268	98,0 3.858	1	G6.3	1,3 2.870
C6-ER16-160	10229722	C6	0,5 0.020	10,0 0.394	ER 16	160,0 6.299	28,0 1.102	28,0 1.102	198,0 7.795	135,0 5.315	113,0 4.449	128,0 5.039	1	G6.3	1,4 3.090
C6-ER20-060	10229723	C6	1,0 0.039	13,0 0.512	ER 20	60,0 2.362	34,0 1.339	34,0 1.339	98,0 3.858	35,0 1.378	9,0 0.354	26,0 1.024	1	G6.3	1,0 2.200
C6-ER20-100	10229724	C6	1,0 0.039	13,0 0.512	ER 20	100,0 3.937	34,0 1.339	34,0 1.339	138,0 5.433	75,0 2.953	51,0 2.008	66,0 2.598	1	G6.3	1,3 2.870
C6-ER20-160	10229725	C6	1,0 0.039	13,0 0.512	ER 20	160,0 6.299	34,0 1.339	34,0 1.339	198,0 7.795	135,0 5.315	111,0 4.370	126,0 4.961	1	G6.3	1,7 3.750
C6-ER25-060	10229726	C6	1,0 0.039	16,0 0.630	ER 25	60,0 2.362	42,0 1.654	42,0 1.654	98,0 3.858	35,0 1.378	9,0 0.354	22,0 0.866	1	G6.3	1,0 2.200
C6-ER25-100	10229727	C6	1,0 0.039	16,0 0.630	ER 25	100,0 3.937	42,0 1.654	42,0 1.654	138,0 5.433	75,0 2.953	42,0 1.654	62,0 2.441	1	G6.3	1,4 3.090
C6-ER25-130	10229728	C6	1,0 0.039	16,0 0.630	ER 25	130,0 5.118	42,0 1.654	42,0 1.654	168,0 6.614	105,0 4.134	72,0 2.835	92,0 3.622	1	G6.3	1,7 3.750
C6-ER25-160	10229729	C6	1,0 0.039	16,0 0.630	ER 25	160,0 6.299	42,0 1.654	42,0 1.654	198,0 7.795	135,0 5.315	102,0 4.016	122,0 4.803	1	G6.3	2,0 4.410

Guide
HSK-A
HSK-E
DIN
BT JIS
CAT
Combimaster
Graflex
Seco Capto™
Others
Operating & setting accessories
Shrinkfit

Guide	Designation	Item number	CTMS	DCBN	DCBX	CTWS	LPR	BD2	BD1	OAL	LB	LFN	LF	RFID hole	Balan- cing	Weight
				mm inch	mm inch		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
HSK-A	C6-ER32-060	10229730	C6	2,0 0.079	20,0 0.787	ER 32	60,0 2.362	63,0 2.480	50,0 1.969	98,0 3.858	35,0 1.378	9,0 0.354	20,0 0.787	1	G6.3	1,1 2.430
	C6-ER32-100	10229731	C6	2,0 0.079	20,0 0.787	ER 32	100,0 3.937	50,0 1.969	50,0 1.969	138,0 5.433	75,0 2.953	34,0 1.339	60,0 2.362	1	G6.3	1,6 3.530
	C6-ER32-130	10229732	C6	2,0 0.079	20,0 0.787	ER 32	130,0 5.118	50,0 1.969	50,0 1.969	168,0 6.614	105,0 4.134	70,0 2.756	90,0 3.543	1	G6.3	2,1 4.630
HSK-E	C6-ER32-160	10229733	C6	2,0 0.079	20,0 0.787	ER 32	160,0 6.299	50,0 1.969	50,0 1.969	198,0 7.795	135,0 5.315	100,0 3.937	120,0 4.724	1	G6.3	2,5 5.510
	C6-ER40-065	10229734	C6	3,0 0.118	26,0 1.024	ER 40	65,0 2.559	63,0 2.480	63,0 2.480	103,0 4.055	43,0 1.693	9,0 0.354	20,0 0.787	1	G6.3	1,3 2.870
	C8-ER32-070	10229735	C8	2,0 0.079	20,0 0.787	ER 32	70,0 2.756	80,0 3.150	50,0 1.969	118,0 4.646	37,0 1.457	10,0 0.394	30,0 1.181	1	G6.3	2,1 4.630
DIN	C8-ER32-160	10229736	C8	2,0 0.079	20,0 0.787	ER 32	160,0 6.299	50,0 1.969	50,0 1.969	208,0 8.189	127,0 5.000	100,0 3.937	120,0 4.724	1	G6.3	3,4 7.500
	C8-ER40-070	10229737	C8	3,0 0.118	26,0 1.024	ER 40	70,0 2.756	80,0 3.150	63,0 2.480	118,0 4.646	37,0 1.457	9,0 0.354	25,0 0.984	1	G6.3	2,2 4.850

Accessories

BT / IIS	For	Seal nut	Spanner
			
CAT	...16-045 / 060	08B587516IC	03B587516UM
	...16-070 / 100 / 130 / 160	08B587516IC	03B587516UM
	...20-052 / 055 / 060	-	03B587520UM
Combimaster	...20-100 / 160	-	03B587520UM
	...25-052 / 055 / 060	08B587525IC	03B587525
	...25-100 / 130 / 160	08B587525IC	03B587525
Graflex	...32-054 / 057 / 060 / 070	08B587532IC	03B587532
	...32-100 / 130 / 160	08B587532IC	03B587532
	...40	08B587540IC	03B587540

Spare Parts, included in delivery


Seco Capto™	For	Nut	Stop screw
			
Others	...16-045 / 060	08B587516UM	-
	...16-070 / 100 / 130 / 160	08B587516UM	19LRC1020
	...20-052 / 055 / 060	08B587520UM	-
Operating & setting accessories	...20-100 / 160	08B587520UM	19LRC1020
	...25-052 / 055 / 060	08B587525X	-
	...25-100 / 130 / 160	08B587525X	19LRC1225
Shrinkfit	...32-054 / 057 / 060 / 070	08B587532X	-
	...32-100 / 130 / 160	08B587532X	19LRC1225
	...40	08B587540X	-

For synchronized tapping, with micro-compensation
– Metric/ Inch


Seco Capto™



Design 1





Design 2



- Maximum coolant pressure 80 bar/ 1160 psi
- For ER tapping collets with square drive, see page(s) 407, 408–409
- For TCER 5867 sealing rings, see page(s) 410, 411
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCBN	DCBX	LPR	LB	LB1	BD	BD1	OAL	SW	Design	RFID hole	Balancing	Weight
						mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
C4-391.5867-11080	02926957	C4	ER 11	M2	M5	80,0 3.150	60,0 2.362	24,1 0.949	23,5 0.925	18,7 0.736	104,0 4.094	12,7 0.500	1	0	–	0,4 0.880
C4-391.5867-20102	02926958	C4	ER 20	M4	M12	97,2 3.827	77,0 3.031	35,3 1.390	35,0 1.378	33,7 1.327	121,2 4.772	22,0 0.866	1	0	–	0,7 1.540
C4-391.5867-25122	02926959	C4	ER 25	M8	M20	116,6 4.591	96,6 3.803	37,1 1.461	44,0 1.732	42,0 1.654	140,6 5.535	28,0 1.102	2	0	–	0,9 1.980
C5-391.5867-20103	02926960	C5	ER 20	M4	M12	97,7 3.846	77,7 3.059	35,3 1.390	35,0 1.378	33,7 1.327	127,7 5.028	22,0 0.866	1	0	–	0,9 1.980
C5-391.5867-25122	02926961	C5	ER 25	M8	M20	117,1 4.610	97,1 3.823	37,1 1.461	44,0 1.732	42,0 1.654	147,1 5.791	28,0 1.102	2	0	–	1,2 2.650
C5-391.5867-40154	02926962	C5	ER 40	M16	M33	148,6 5.850	46,6 1.835	25,5 1.004	62,0 2.441	62,7 2.469	178,6 7.031	39.6875 1.563	2	0	–	2,8 6.170
C6-391.5867-20105	02926963	C6	ER 20	M4	M12	99,7 3.925	77,7 3.059	35,3 1.390	35,0 1.378	33,7 1.327	137,7 5.421	22,0 0.866	1	0	–	1,2 2.650
C6-391.5867-25124	02926964	C6	ER 25	M8	M20	119,1 4.689	97,1 3.823	37,1 1.461	44,0 1.732	42,0 1.654	157,1 6.185	28,0 1.102	2	0	–	1,5 3.310
C6-391.5867-40154	02926965	C6	ER 40	M16	M33	148,1 5.831	126,1 4.965	46,6 1.835	62,0 2.441	62,7 2.469	186,1 7.327	39.6875 1.563	2	0	–	2,9 6.390
C6-391.5867-50210	03131173	C6	ER 50	M20	M48	208,0 8.189	134,5 5.295	76,5 3.012	86,0 3.386	78,0 3.071	246,0 9.685	56,2 2.213	2	0	–	5,9 13.010
C8-391.5867-20112	02926966	C8	ER 20	M4	M12	106,7 4.201	76,7 3.020	35,3 1.390	35,0 1.378	33,7 1.327	154,7 6.091	22,0 0.866	1	0	–	2,2 4.850
C8-391.5867-25131	02926967	C8	ER 25	M8	M20	126,1 4.965	96,1 3.783	37,1 1.461	44,0 1.732	42,0 1.654	174,1 6.854	28,0 1.102	2	0	–	2,5 5.510
C8-391.5867-40161	02926968	C8	ER 40	M16	M33	155,1 6.106	125,1 4.925	46,6 1.835	62,0 2.441	62,7 2.469	203,1 7.996	39,6 1.559	2	0	–	3,9 8.600

Accessories

For	Locking key	Seal nut	Spanner
			
ER 11	5680092-03	–	03B587511UM
ER 20	5680092-04	5533051-02	03B587520UM
ER 25	5680092-05	5533051-03	03B587525
ER 40	5680092-06	5533051-05	03B587540
ER 50	5680092-07	5533051-14	03B587550

Spare Parts, included in delivery

Guide	Spare Parts, included in delivery	
	For	Nut
HSK-A	ER 11	5533050-07
	ER 20	5533050-08
	ER 25	5533050-02
	ER 40	5533050-04
	ER 50	5533050-05
HSK-E		
DIN		
BT JIS		
CAT		
Combimaster		
Graflex		
Seco Capto™		
Others		
Operating & setting accessories		
Shrinkfit		





Cylindrical/ Weldon


Seco allows you to get the most out of both your machine and tools by offering a comprehensive range of tool holders to connect them. Besides all common connections Seco also offer Cylindrical and Weldon back ends.

- Cylindrical Tool holders for Combimaster and Graflex solutions
- Cylindrical shrinkfit extensions
- Cylindrical ER extensions
- Weldon Tool holders for Combimaster and Tapping chucks


Steel, Heavy metal or Carbide
– Metric/ Inch




Design 1



Design 2



Design 3



–D = heavy metal, E = carbide
–CTMS tolerance h5
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BD01258220660	02643840	12	M6	60,0 2.362	60,0 2.362	–	–	11,0 0.433	–	–	105,0 4.134	–	3	0	PB	0,1 0.220
BD01258220695E	02643841	12	M6	95,0 3.740	95,0 3.740	–	–	11,0 0.433	–	–	140,0 5.512	30,0	3	0	PB	0,3 0.660
BD01458220860	02447683	14	M8	60,0 2.362	60,0 2.362	–	–	13,5 0.531	–	–	105,0 4.134	30,0	3	0	PB	0,2 0.440
BD01458220895E	02447684	14	M8	95,0 3.740	95,0 3.740	–	–	13,5 0.531	–	–	140,0 5.512	30,0	3	0	PB	0,3 0.660
BD01658220865	02453089	16	M8	65,0 2.559	65,0 2.559	–	–	15,6 0.614	–	–	113,0 4.449	30,0	3	0	PB	0,2 0.440
BD016582208105E	02453090	16	M8	105,0 4.134	105,0 4.134	–	–	13,5 0.531	–	–	153,0 6.024	30,0	3	0	PB	0,5 1.100
BD016582108105E	02549210	16	M8	105,0 4.134	105,0 4.134	50,0 1.969	–	13,5 0.531	–	14,5 0.571	153,0 6.024	–	2	0	PB	0,4 0.880
BD01858221070	02447686	18	M10	70,0 2.756	70,0 2.756	–	–	18,0 0.709	–	–	118,0 4.646	30,0	3	0	PB	0,2 0.440
BD018582210125E	02447685	18	M10	125,0 4.921	125,0 4.921	–	–	18,0 0.709	–	–	173,0 6.811	30,0	3	0	PB	0,6 1.320
BD02058221075	02447687	20.0	M10	75,0 2.953	75,0 2.953	15,0 0.591	–	18,5 0.728	–	19,6 0.772	125,0 4.921	30,0	2	0	PB	0,3 0.660
BD02058211040D	02447653	20	M10	40,0 1.575	25,0 0.984	25,0 0.984	–	18,5 0.728	–	18,5 0.728	90,0 3.543	–	2	0	PB	0,5 1.100
BD020582110110	02447652	20	M10	110,0 4.331	65,0 2.559	65,0 2.559	–	18,5 0.728	–	18,5 0.728	160,0 6.299	–	2	0	PB	0,4 0.880
BD020582110110D	02441829	20	M10	110,0 4.331	65,0 2.559	65,0 2.559	–	18,5 0.728	–	18,5 0.728	160,0 6.299	–	2	0	PB	0,8 1.760
BD02558221280	02447689	25	M12	80,0 3.150	80,0 3.150	–	–	23,0 0.906	–	–	136,0 5.354	30,0	3	0	PB	0,5 1.100
BD025582112185E	02549211	25	M12	185,0 7.283	85,0 3.346	–	–	23,0 0.906	–	23,5 0.925	241,0 9.488	–	2	0	PB	1,6 3.530
BD025582112185	02441831	25	M12	185,0 7.283	85,0 3.346	–	–	23,0 0.906	–	23,5 0.925	241,0 9.488	–	2	0	PB	0,8 1.760

Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balan- cing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BD025582112185D	02447656	25	M12	185,0 7.283	85,0 3.346	–	–	23,0 0.906	–	23,0 0.906	241,0 9.488	–	2	0	PB	1,9 4.190
BD032582012100	02447657	32	M12	100,0 3.937	65,0 2.559	–	25,0 0.984	23,0 0.906	31,0 1.220	24,7 0.972	160,0 6.299	4,5	1	0	PB	0,9 1.980
BD032582012240	02447659	32	M12	240,0 9.449	145,0 5.709	–	30,0 1.181	23,0 0.906	31,0 1.220	24,7 0.972	300,0 11.811	1,6	1	0	PB	1,4 3.090
BD03258221695	02447690	32	M16	95,0 3.740	95,0 3.740	–	–	30,0 1.181	–	–	155,0 6.102	30,0	3	0	PB	1,0 2.200
BD032582116100	02447663	32	M16	100,0 3.937	65,0 2.559	–	–	30,0 1.181	–	30,0 1.181	160,0 6.299	–	2	0	PB	0,9 1.980
BD032582116100D	02442105	32	M16	100,0 3.937	65,0 2.559	–	–	30,0 1.181	–	30,0 1.181	160,0 6.299	–	2	0	PB	2,0 4.410
BD032582116145D	02447665	32	M16	145,0 5.709	110,0 4.331	–	–	30,0 1.181	–	30,0 1.181	205,0 8.071	–	2	0	PB	2,5 5.510
BD032582116240	02447667	32	M16	240,0 9.449	145,0 5.709	–	–	30,0 1.181	–	30,0 1.181	300,0 11.811	–	2	0	PB	1,7 3.750
BD032582116240D	02442107	32	M16	240,0 9.449	145,0 5.709	–	–	30,0 1.181	–	30,0 1.181	300,0 11.811	–	2	0	PB	3,8 8.380
BD04058201690	02447672	40	M16	90,0 3.543	65,0 2.559	–	25,0 0.984	30,0 1.181	39,0 1.535	31,7 1.248	160,0 6.299	5,2	1	0	PB	1,4 3.090
BD040582016135	02447668	40	M16	135,0 5.315	110,0 4.331	–	35,0 1.378	30,0 1.181	39,0 1.535	31,7 1.248	205,0 8.071	2,8	1	0	PB	1,7 3.750
BD040582016230	02447669	40	M16	230,0 9.055	145,0 5.709	–	35,0 1.378	30,0 1.181	39,0 1.535	31,7 1.248	300,0 11.811	1,9	1	0	PB	2,5 5.510

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating &
setting acces-
series

Shrinkfit


Steel, Heavy metal or Carbide
– Inch




Design 1



Design 2



Design 3



– D = heavy metal, E = carbide
– CTMS tolerance h5
– For ISO attribute explanation, see page 15


Designation	Item number	CTMS	CTWS	LPR	LB	LB2	LB1	BD	BD2	BD1	OAL	BHTA°	Design	RFID hole	Balancing	Weight
		inch		inch	inch	inch	inch	inch	inch	inch	inch					lbs
BD115582208275	02487317	0.625	M8	2.750	2.750	–	–	0.512	–	–	4.500	30,0	3	0	PB	0.440
BD115582208425E	02487322	0.625	M8	4.250	4.250	–	–	0.512	–	–	6.000	30,0	3	0	PB	1.100
BD119582210150	02454190	0.750	M10	1.500	1.500	–	–	0.709	–	–	3.500	30,0	3	0	PB	0.440
BD119582210300	02487324	0.750	M10	3.000	3.000	–	–	0.709	–	–	5.000	30,0	3	0	PB	0.660
BD119582210500E	02487327	0.750	M10	5.000	5.000	–	–	0.709	–	–	7.000	30,0	3	0	PB	1.540
BD125582212325	02487329	1.000	M12	3.250	3.250	–	–	0.906	–	–	5.500	30,0	3	0	PB	1.320
BD125582212675E	02487330	1.000	M12	6.750	6.750	–	–	0.906	–	–	9.000	30,0	3	0	PB	3.310
BD131582012425	02454199	1.250	M12	4.250	4.250	–	0.790	0.906	1.210	0.970	6.500	3,5	1	0	PB	1.980
BD131582116425	02454203	1.250	M16	4.250	2.750	–	–	1.181	–	–	6.500	–	2	0	PB	2.200
BD131582116600	02454204	1.250	M16	6.000	4.480	–	–	1.181	–	–	8.250	–	2	0	PB	2.650
BD131582116600D	02454205	1.250	M16	6.000	4.480	–	–	1.181	–	–	8.250	–	2	0	PB	5.730
BD131582216375	02487331	1.250	M16	3.748	3.748	–	–	1.181	–	–	5.949	30,0	3	0	PB	1.980
BD131582220375	03029778	1.250	M20	3.748	1.972	–	–	1.437	–	1.437	6.000	30,0	2	0	PB	2.200
BD131582220425	03029776	1.250	M20	4.248	2.472	–	–	1.437	–	1.437	6.500	30,0	2	0	PB	2.290
BD131582220600	03029777	1.250	M20	6.000	4.220	–	–	1.437	–	1.437	8.252	30,0	2	0	PB	3.090

Mold and Die type
– Metric/ Inch


Cylindrical



Design 1



Design 2



– Run-out $\leq 3 \mu\text{m}$
– CTMS tolerance h5
– For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LB	LB1	BD1	BD2	OAL	CDBP	LSC	Design	BHTA°	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch					kg lbs
BD01658010352	00030175	16	3,0 0.118	52,0 2.047	51,2 2.016	9,0 0.354	14,4 0.567	100,0 3.937	–	13,0 0.512	1	3,0	0	PB	0,2 0.440
BD016580103102	00030174	16	3,0 0.118	102,0 4.016	66,8 2.630	9,0 0.354	16,0 0.630	150,0 5.906	–	13,0 0.512	2	3,0	0	PB	0,2 0.440
BD01658010452	00030178	16	4,0 0.157	52,0 2.047	51,7 2.035	10,0 0.394	15,4 0.606	100,0 3.937	–	15,0 0.591	1	3,0	0	PB	0,2 0.440
BD016580104102	00030750	16	4,0 0.157	102,0 4.016	57,2 2.252	10,0 0.394	16,0 0.630	150,0 5.906	–	15,0 0.591	2	3,0	0	PB	0,2 0.440
BD01658010552	00030180	16	5,0 0.197	52,0 2.047	47,7 1.878	11,0 0.433	16,0 0.630	100,0 3.937	–	18,0 0.709	2	3,0	0	PB	0,2 0.440
BD01658010652	00030182	16	6,0 0.236	52,0 2.047	38,2 1.504	12,0 0.472	16,0 0.630	100,0 3.937	40,0 1.575	26,0 1.024	2	3,0	0	PB	0,2 0.440
BD016580106102	00030181	16	6,0 0.236	102,0 4.016	38,2 1.504	12,0 0.472	16,0 0.630	150,0 5.906	40,0 1.575	26,0 1.024	2	3,0	0	PB	0,2 0.440
BD02058010850	00030185	20	8,0 0.315	50,0 1.969	38,2 1.504	16,0 0.630	20,0 0.787	100,0 3.937	44,0 1.732	30,0 1.181	2	3,0	0	PB	0,2 0.440
BD020580108100	00030184	20	8,0 0.315	100,0 3.937	38,2 1.504	16,0 0.630	20,0 0.787	150,0 5.906	44,0 1.732	30,0 1.181	2	3,0	0	PB	0,32 0.710
BD02058011050	00030190	20	10,0 0.394	50,0 1.969	19,1 0.752	18,0 0.709	20,0 0.787	100,0 3.937	45,0 1.772	32,0 1.260	2	3,0	0	PB	0,21 0.460
BD020580110100	00030186	20	10,0 0.394	100,0 3.937	19,1 0.752	18,0 0.709	20,0 0.787	150,0 5.906	45,0 1.772	32,0 1.260	2	3,0	0	PB	0,4 0.880
BD02058011250	00030195	20	12,0 0.472	50,0 1.969	40,0 1.575	20,0 0.787	20,0 0.787	100,0 3.937	46,0 1.811	34,0 1.339	2	3,0	0	PB	0,19 0.420
BD020580112100	00030194	20	12,0 0.472	100,0 3.937	50,0 1.969	20,0 0.787	20,0 0.787	150,0 5.906	46,0 1.811	34,0 1.339	2	3,0	0	PB	0,4 0.880

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating &
setting acces-
series

Shrinkfit


Mold and Die type
– Inch



Design 1



Design 2




–Run-out $\leq 3 \mu\text{m}$
–CTMS tolerance h5
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LB	LB1	BD1	BD2	OAL	CBDP	LSC	Design	BHTA°	RFID hole	Balancing	lbs
BD1155801012400	02522850	0.625	0.125	4.000	2.582	0.354	0.625	5.875	–	0.512	1	3,0	0	PB	0.440
BD1155801018400	02522851	0.625	0.188	4.000	1.831	0.433	0.625	5.875	–	0.709	1	3,0	0	PB	0.400
BD1155801025400	02522854	0.625	0.250	4.000	1.456	0.472	0.625	5.875	1.476	0.866	2	3,0	0	PB	0.420
BD1195801031400	02522857	0.750	0.313	4.000	1.897	0.551	0.750	6.000	1.575	1.181	2	3,0	0	PB	0.660

Conventional type
– Metric/ Inch

Cylindrical



–Run-out $\leq 6 \mu\text{m}$
–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	DCBN-DCBX	LPR	CBDP	BD1	OAL	LFN	LF	TDZ	RFID hole	Balan- cing	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
ST20-HC12-100	10137352	20	12,0 0.472	100,0 3.937	47,5 1.870	25,0 0.984	150,0 5.906	54,0 2.126	64,0 2.520	M6	0	G2.5	0,5 1.100
ST20-HC20-100	10137353	20	20,0 0.787	100,0 3.937	51,5 2.028	31,5 1.240	150,0 5.906	49,0 1.929	59,0 2.323	M10x1	0	G2.5	0,6 1.320
ST32-HC20-090	10137354	32	20,0 0.787	90,0 3.543	51,5 2.028	31,5 1.240	150,0 5.906	39,0 1.535	49,0 1.929	M10x1	0	G2.5	0,8 1.760

Accessories

For	Key
	
All	H05-4

Guide

HSK-A

HSK-E

DIN

BT / IS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit



– Metric/ Inch



–Run-out 5 µm maximum at 3 x ØDCBN-DCBX
 –For ER collets, see page(s) 399, 400, 401, 402
 –For stop screws, see instructions at www.secotools.com
 –For ISO attribute explanation, see page 15

Designation	Item number	LPR	DCBN	DCBX	Size	BD1	OAL	RFID hole	Balancing	Weight
		mm inch	mm inch	mm inch		mm inch	mm inch			kg lbs
ST10-ERHP08R-080	10359272	40,0 1.575	1,0 0.039	5,0 0.197	HP 08R	10,0 0.394	80,0 3.150	0	PB	0,1 0.220
ST10-ERHP08R-150	10359273	110,0 4.331	1,0 0.039	5,0 0.197	HP 08R	10,0 0.394	150,3 5.917	0	PB	0,1 0.220
ST10-ERHP08R-200	10359274	160,0 6.299	1,0 0.039	5,0 0.197	HP 08R	10,0 0.394	200,3 7.886	0	PB	0,1 0.220
ST12-ERHP08R-120	10359275	75,0 2.953	1,0 0.039	5,0 0.197	HP 08R	10,0 0.394	120,0 4.724	0	PB	0,1 0.220
ST12-ERHP08R-160	10359276	115,0 4.528	1,0 0.039	5,0 0.197	HP 08R	10,0 0.394	160,0 6.299	0	PB	0,2 0.440
ST12-ERHP08R-200	10359277	155,0 6.102	1,0 0.039	5,0 0.197	HP 08R	10,0 0.394	200,0 7.874	0	PB	0,2 0.440
ST16-ERHP11R-150	10359278	102,9 4.051	1,0 0.039	7,0 0.276	HP 11R	16,0 0.630	150,9 5.941	0	PB	0,2 0.440
ST16-ERHP11R-200	10359279	152,9 6.020	1,0 0.039	7,0 0.276	HP 11R	16,0 0.630	200,9 7.909	0	PB	0,3 0.660
ST16-ERHP16R-150	10359280	102,6 4.039	1,0 0.039	10,0 0.394	HP 16R	24,0 0.945	150,6 5.929	0	PB	0,2 0.440
ST16-ERHP16R-200	10359281	152,0 5.984	1,0 0.039	10,0 0.394	HP 16R	22,0 0.866	200,0 7.874	0	PB	0,3 0.660
ST20-ERHP16R-150	10359282	100,6 3.961	1,0 0.039	10,0 0.394	HP 16R	22,0 0.866	150,6 5.929	0	PB	0,3 0.660
ST20-ERHP16R-200	10359283	150,6 5.929	1,0 0.039	10,0 0.394	HP 16R	22,0 0.866	200,6 7.898	0	PB	0,4 0.880

Accessories

For	Key	Socket	Torque key
			
ERHP08R	–	03ERB010	03DYE003025
ERHP11R	03LME0912140	03ER016	03DYE003025
ERHP16R	03LME0912140	03ER022	03DYE010050

Spare Parts, included in delivery

For		Nut	
			
ERHP08R		08B567208RC	
ERHP11R		08B567211RC	
ERHP16R		08B567216RC	

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit


ISO 15488
– Metric/ Inch



–Run-out 15 µm/ .0006" maximum at 3 x ØDCBN-DCBX
–DMM tolerance h5
–For ER collets, see page(s) 399, 400, 401, 402
–For ER sealing rings, see page(s) 410, 411
–For ISO attribute explanation, see page 15

Designation	Item number	DMM	LPR	DCBN	DCBX	Size	BD1	OAL	LFN	LF	TDZ	RFID hole	Balancing	Weight
		mm inch	mm inch	mm inch	mm inch		mm inch	mm inch	mm inch	mm inch				kg lbs
ST12-ER08R-150	10229738	12,0 0.472	105,0 4.134	0,5 0.020	5,0 0.197	ER 08	12,0 0.472	150,0 5.906	112,0 4.409	112,0 4.409	–	0	PB	0,2 0.440
ST16-ER11R-150	10229739	16,0 0.630	102,0 4.016	0,5 0.020	7,0 0.276	ER 11	16,0 0.630	150,0 5.906	120,5 4.744	129,12 5.083	M6X1.0	0	PB	0,2 0.440
ST16-ER16R-160	10229740	16,0 0.630	112,0 4.409	0,5 0.020	10,0 0.394	ER 16	22,0 0.866	160,0 6.299	126,5 4.980	128,0 5.039	M8X1.25	0	PB	0,2 0.440
ST20-ER20R-160	10229741	20,0 0.787	110,0 4.331	0,5 0.020	13,0 0.512	ER 20	28,0 1.102	160,0 6.299	78,5 3.091	113,5 4.469	M12X1.75	0	PB	0,4 0.880
ST25-ER25R-160	10229742	25,0 0.984	104,0 4.094	1,0 0.039	16,0 0.630	ER 25	35,0 1.378	160,0 6.299	78,0 3.071	113,0 4.449	M12X1.75	0	PB	0,5 1.100
ST32-ER25R-160	10229743	32,0 1.260	100,0 3.937	1,0 0.039	16,0 0.630	ER 25	35,0 1.378	160,0 6.299	108,0 4.252	128,0 5.039	M12X1.75	0	PB	0,8 1.760
ST32-ER32-160	10229744	32,0 1.260	100,0 3.937	2,0 0.079	20,0 0.787	ER 32	50,0 1.969	160,0 6.299	82,0 3.228	113,9 4.484	12X1.75	0	PB	1,0 2.200

Accessories

For	Seal nut	Spanner
		
ST12-ER08R-150	–	03B545008
ST16-ER11R-150	–	03B545011
ST16-ER16R-160	08B587516MC	03B545016
ST20-ER20R-160	–	03B545020
ST25-ER25R-160	08B587525MC	03B545025
ST32-ER25R-160	08B587525MC	03B587532
ST32-ER32-160	08B587532IC	03B587532

Spare Parts, included in delivery

For	Nut	Stop screw
		
ST12-ER08R-150	08B587508M	19LRC1020
ST16-ER11R-150	08B587511M	19LRC1225
ST16-ER16R-160	08B587516M	19LRC0820
ST20-ER20R-160	08B587520M	19LRC1225
ST25-ER25R-160	08B587525M	19LRC1240
ST32-ER25R-160	08B587532X	19LRC1225
ST32-ER32-160	08B587532X	19LRC1225

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

For synchronized tapping, with micro-compensation
– Metric/ Inch

Cylindrical



- Maximum coolant pressure 80 bar/ 1160 psi
- For ER collets, see page(s) 399, 400, 401, 402
- For ER sealing rings, see page(s) 410, 411
- Cylindrical machine side shank CTMS with tolerance g6, not compatible with Shrinkfit holders
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCBN	DCBX	LPR	LB	LB1	BD1	BD	OAL	SW	RFID hole	Balan- cing	Weight
						mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BD01658671152	02926969	16	ER 11	M2	M5	51,9 2.043	25,2 0.992	11,5 0.453	18,7 0.736	23,5 0.925	96,4 3.795	12,7 0.500	0	–	0,2 0.440
BD02058672069	02926970	20	ER 20	M4	M12	63,7 2.508	35,3 1.390	19,1 0.752	34,0 1.339	34,6 1.362	114,5 4.508	22,0 0.866	0	–	0,5 1.100

Accessories

For	Locking key	Seal nut	Spanner
			
BD01658671152	5680092-03	–	03B587511UM
BD02058672069	5680092-04	5533051-02	03B587520UM

Spare Parts, included in delivery


For	Nut
	
BD01658671152	5533050-07
BD02058672069	5533050-08

For synchronized tapping, with micro-compensation
– Metric/ Inch


Weldon and WN shanks



Design 1






Design 2



- Maximum coolant pressure 80 bar/ 1160 psi
- For ER collets, see page(s) 399, 400, 401, 402
- For ER sealing rings, see page(s) 410, 411
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCBN	DCBX	LPR	LB	LB1	BD1	BD	OAL	SW	Design	RFID hole	Balancing	Weight
		mm inch				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
BW22058671151	02926947	20 0.787	ER 11	M2	M5	51,9 2.043	49,1 1.933	25,2 0.992	18,7 0.736	23,5 0.925	102,7 4.043	12,7 0.500	1	0	–	0,2 0.440
BW22558672069	02926948	25 0.984	ER 20	M4	M12	63,7 2.508	63,7 2.508	36,1 1.421	34,0 1.339	34,6 1.362	114,5 4.508	22,3 0.878	1	0	–	0,5 1.100
BW22558672588	02926949	25 0.984	ER 25	M8	M20	83,1 3.272	83,1 3.272	37,2 1.465	41,7 1.642	44,0 1.732	133,9 5.272	28,0 1.102	2	0	–	0,8 1.760
BW225586740117	02926950	25 0.984	ER 40	M16	M33	112,1 4.413	112,1 4.413	45,7 1.799	63,0 2.480	62,0 2.441	162,9 6.413	39,7 1.563	2	0	–	2,0 4.410
BW240586750164	03131179	40 1.575	ER 50	M20	M48	155,8 6.134	126,3 4.972	70,0 2.756	78,0 3.071	86,0 3.386	225,8 8.890	56,2 2.213	2	0	–	5,4 11.900

Accessories


For	Locking key	Seal nut	Spanner
			
BW22058671151	5680092-03	–	03B587511UM
BW22558672069	5680092-04	5533051-02	03B587520UM
BW22558672588	5680092-05	5533051-03	03B587525
BW225586740117	5680092-06	5533051-05	03B587540
BW240586750164	5680092-07	5533051-14	03B587550

Spare Parts, included in delivery

For	Nut
	
BW22058671151	5533050-07
BW22558672069	5533050-08
BW22558672588	5533050-02
BW225586740117	5533050-04
BW240586750164	5533050-05

For synchronized tapping, with micro-compensation
– Inch



Weldon and WN shanks



- Maximum coolant pressure 80 bar/ 1160 psi
- For ER collets, see page(s) 399, 400, 401, 402
- For ER sealing rings, see page(s) 410, 411
- For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	DCBN	DCBX	LPR	LB	LB1	BD1	BD	OAL	SW	RFID hole	Balan- cing	Weight
		inch				inch	inch	inch	inch	inch	inch	inch			lbs
BW925586711052	03131176	1.000	ER 11	M2	M5	2.043	0.992	0.453	0.925	0.748	4.043	0.500	0	–	0.660
BW925586720069	03131177	1.000	ER 20	M4	M12	2.508	1.382	0.752	1.362	1.339	4.508	0.866	0	–	1.100
BW925586725088	03131178	1.000	ER 25	M8	M20	3.272	1.465	0.787	1.732	1.654	5.272	1.102	0	–	1.980

Accessories


For	Locking key	Seal nut	Spanner
			
BW925586711052	5680092-03	–	03B587511UM
BW925586720069	5680092-04	5533051-02	03B587520UM
BW925586725088	5680092-05	5533051-03	03B587525

Spare Parts, included in delivery

For	Nut
	
BW925586711052	5533050-07
BW925586720069	5533050-08
BW925586725088	5533050-02

Arbors
– Metric/ Inch

Weldon/ DIN 1835-1 Form B



–For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB1	BD	BD1	OAL	RFID hole	Balancing	Weight
				mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
BW02058211030	02501657	20	M10	30,0 1.181	25,0 0.984	10,0 0.394	18,5 0.728	18,5 0.728	80,0 3.150	0	PB	0,2 0.440
BW020582110102	02501661	20	M10	102,0 4.016	97,0 3.819	20,0 0.787	18,5 0.728	18,5 0.728	152,0 5.984	0	PB	0,4 0.880
BW02558211245	02501663	25	M12	45,0 1.772	40,0 1.575	20,0 0.787	23,0 0.906	23,5 0.925	101,0 3.976	0	PB	0,4 0.880
BW025582112115	02501664	25	M12	115,0 4.528	110,0 4.331	30,0 1.181	23,0 0.906	23,5 0.925	171,0 6.732	0	PB	0,6 1.320
BW03258211645	02501665	32	M16	45,0 1.772	40,0 1.575	20,0 0.787	30,0 1.181	30,5 1.201	105,0 4.134	0	PB	0,6 1.320
BW040582120102	02971313	40	M20	102,0 4.016	97,0 3.819	30,0 1.181	36,5 1.437	37,0 1.457	172,0 6.772	0	PB	1,5 3.310

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

Arbors
– Inch

Weldon/ DIN 1835–1 Form B



—For ISO attribute explanation, see page 15

Designation	Item number	CTMS	CTWS	LPR	LB	LB1	BD	BD1	OAL	RFID hole	Balan- cing	Weight
		inch		inch	inch	inch	inch	inch	inch			lbs
BW519582210125	02454250	0.750	M10	1.250	0.591	–	0.732	0.732	3.250	0	PB	0.440
BW525582212075	02454252	1.000	M12	0.750	0.591	–	0.984	0.984	3.000	0	PB	0.660
BW625582112250	02454256	1.000	M12	2.500	2.250	–	0.925	0.925	5.750	0	PB	1.100
BW531582116150	02454254	1.250	M16	1.500	1.250	–	1.201	1.201	3.750	0	PB	1.320
BW631582116300	02454261	1.250	M16	3.000	2.559	–	1.181	1.181	6.250	0	PB	1.980
BW631582116400	02454262	1.250	M16	4.000	3.750	–	1.201	1.201	7.250	0	PB	2.430




Operating and setting accessories

Seco offers a wide variety of operating accessories to ensure you get the most out of your tooling systems. Seco's range of setting accessories allow you to quickly and correctly set tools to ensure your application benefits from the full accuracy capabilities of your tooling and holder.

- Coolant tubes, Operating accessories, Sealing plugs and Pull studs
- Reduction sleeves, Collets for Collet chucks and Sealing rings
- Tool boy for assembly support and Control gauges


– Metric/ Inch



– HSK-A to Seco Capto holders are delivered with a specific coolant tube available as spare parts and need a specific coolant tube spanner, see product page(s) 298, 299–300, 301
– For ISO attribute explanation, see page 15

Description	Designation	Item number	For holders HSK A and E	LB1	LB2	KEY	CNT	TDZ	BHTA°
				mm inch	mm inch	mm inch	mm		
Coolant tubes (1)	20E9301	00088814	HSK-A32 & HSK-E32	5,5 0.217	20,5 0.807	–	6	M10x1	1,0
	20E9302	00088815	HSK-A40 & HSK-E40	7,5 0.295	22,0 0.866	–	8	M12x1	1,0
	20E9303	00086740	HSK-A50 & HSK-E50	9,5 0.374	23,5 0.925	–	6	M16x1	1,0
	20E9304	00086741	HSK-A63 & HSK-E63	11,5 0.453	25,0 0.984	–	8	M18x1	1,0
	20E9306	00086742	HSK-A100 & HSK-E100	15,5 0.610	28,5 1.122	–	6	M24x1,5	1,0
	20E9307	00088816	HSK-A125	17,5 0.689	30,5 1.201	–	18	M30x1.5	1,0
Coolant tube spanners (2)	03E9301	00088811	HSK-A32 & HSK-E32	–	–	–	–	–	–
	03E9302	00088812	HSK-A40 & HSK-E40	–	–	–	–	–	–
	03E9303	00069969	HSK-A50 & HSK-E50	–	–	–	–	–	–
	03E9304	00069970	HSK-A63 & HSK-E63	–	–	–	–	–	–
	03E9305	00032296	HSK-A80 & HSK-E80	–	–	–	–	–	–
	03E9306	00084012	HSK-A100 & HSK-E100	–	–	–	–	–	–
	5680094-07	03248614	HSK-A125	–	–	–	–	–	–
Sealing plugs (3)	02E9301	00031588	HSK-A32 & HSK-E32	5,0 0.197	–	3,0 0.118	–	M10x1	–
	02E9302	00031593	HSK-A40 & HSK-E40	7,0 0.276	–	4,0 0.157	–	M12x1	–
	02E9303	00001002	HSK-A50 & HSK-E50	9,0 0.354	–	5,0 0.197	–	M16x1	–
	02E9304	00010101	HSK-A63 & HSK-E63	11,0 0.433	–	6,0 0.236	–	M18x1	–
	02E9306	00014002	HSK-A100 & HSK-E100	15,0 0.591	–	10,0 0.394	–	M24x1,5	–
	02E9307	00033649	HSK-A125	17,0 0.669	–	12,0 0.472	–	M30x1.5	–

– Metric/ Inch




–For HSK coolant tube spanners, see page(s) 370
–For ISO attribute explanation, see page 15

Designation	Item number	For holders	CND	LB1	LB2	CNDP	BD1	OAL	TDZ	BHTA°	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			kg lbs
20E9304	00086741	HSK-A63 & HSK-E63	8,0 0.315	11,5 0.453	25,0 0.984	8,0 0.315	12,0 0.472	36,5 1.437	M18x1	1,0	0,1 0.220
20E9306M1	03103663	HSK-A100	8,0 0.315	16,0 0.630	28,0 1.102	12,0 0.472	16,0 0.630	44,0 1.732	M24x1.5	1,0	0,1 0.220


– Metric/ Inch



Design 1



Design 2



–With tapered contact surface for MQL tool according to DIN 69090-3
–For ISO attribute explanation, see page 15


Description	Designation	Item number	OAL	CND	LB4	LB3	LB2	LB1	BD2	BD1	WF	CNT	BHTA°	Design	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
Short	19MQL106S	02967758	17,0 0.669	3,0 0.118	15,5 0.610	12,0 0.472	–	1,5 0.059	5,8 0.228	–	2,5 0.098	M5	90,0	1	0,1 0.220
	19MQL108S	02967759	18,0 0.709	3,5 0.138	15,5 0.610	12,0 0.472	–	2,5 0.098	7,8 0.307	–	3,0 0.118	M6	90,0	1	0,1 0.220
	19MQL110S	02967760	18,0 0.709	4,7 0.185	15,0 0.591	12,0 0.472	–	3,0 0.118	9,8 0.386	–	4,0 0.157	M8x1	90,0	1	0,1 0.220
CAT	19MQL112S	02967761	18,0 0.709	5,8 0.228	15,0 0.591	11,0 0.433	–	3,0 0.118	11,8 0.465	–	5,0 0.197	M10x1	90,0	1	0,1 0.220
	19MQL114S	02967762	19,5 0.768	5,8 0.228	15,5 0.610	12,5 0.492	–	4,0 0.157	13,8 0.543	–	5,0 0.197	M10x1	90,0	1	0,1 0.220
	19MQL116S	02967763	22,0 0.866	5,8 0.228	17,0 0.669	12,0 0.472	–	5,0 0.197	15,8 0.622	–	5,0 0.197	M10x1	90,0	1	0,1 0.220
Combimaster	19MQL118S	02967764	22,0 0.866	5,8 0.228	16,0 0.630	12,0 0.472	–	6,0 0.236	17,8 0.701	–	5,0 0.197	M10x1	90,0	1	0,1 0.220
	19MQL120S	02967765	23,5 0.925	5,8 0.228	16,5 0.650	12,0 0.472	–	7,0 0.276	19,8 0.780	–	5,0 0.197	M10x1	90,0	1	0,1 0.220
	19MQL125S	02967766	27,5 1.083	5,8 0.228	18,0 0.709	13,0 0.512	–	9,5 0.374	24,8 0.976	–	5,0 0.197	M10x1	90,0	1	0,1 0.220
Graflex	19MQL132S	02967767	30,5 1.201	5,8 0.228	17,5 0.689	13,0 0.512	–	13,0 0.512	31,8 1.252	–	5,0 0.197	M10x1	90,0	1	0,1 0.220
	Long 19MQL106L	02967768	34,0 1.339	3,0 0.118	32,5 1.280	30,0 1.181	15,0 0.591	1,5 0.059	5,8 0.228	4,1 0.161	2,5 0.098	M5x0.8	90,0	2	0,1 0.220
	19MQL108L	02967769	34,0 1.339	3,5 0.138	31,5 1.240	29,0 1.142	15,0 0.591	2,5 0.098	7,8 0.307	4,9 0.193	3,0 0.118	M6x1	90,0	2	0,1 0.220
Seco Capto™	19MQL110L	02967770	35,0 1.378	4,7 0.185	32,0 1.260	28,0 1.102	15,0 0.591	3,0 0.118	9,8 0.386	6,9 0.272	4,0 0.157	M8x1	90,0	2	0,1 0.220
	19MQL112L	02967771	35,0 1.378	5,8 0.228	32,0 1.260	27,0 1.063	15,0 0.591	3,0 0.118	11,8 0.465	8,9 0.350	5,0 0.197	M10x1	90,0	2	0,1 0.220
	19MQL114L	02967772	35,5 1.398	5,8 0.228	31,5 1.240	26,0 1.024	15,5 0.610	4,0 0.157	13,8 0.543	8,9 0.350	5,0 0.197	M10x1	90,0	2	0,1 0.220
Others	19MQL116L	02967773	37,0 1.457	5,8 0.228	32,0 1.260	27,0 1.063	15,0 0.591	5,0 0.197	15,8 0.622	8,9 0.350	5,0 0.197	M10x1	90,0	2	0,1 0.220
	19MQL118L	02967774	37,5 1.476	5,8 0.228	31,5 1.240	26,0 1.024	15,5 0.610	6,0 0.236	17,8 0.701	8,9 0.350	5,0 0.197	M10x1	90,0	2	0,1 0.220
	19MQL120L	02967775	40,0 1.575	5,8 0.228	33,0 1.299	28,0 1.102	15,0 0.591	7,0 0.276	19,8 0.780	8,9 0.350	5,0 0.197	M10x1	90,0	2	0,1 0.220
Operating & setting accessories	19MQL125L	02967776	44,0 1.732	5,8 0.228	34,5 1.358	29,0 1.142	15,0 0.591	9,5 0.374	24,8 0.976	8,9 0.350	5,0 0.197	M10x1	90,0	2	0,1 0.220
	19MQL132L	02967777	45,0 1.772	5,8 0.228	32,0 1.260	27,0 1.063	14,0 0.551	13,0 0.512	31,8 1.252	8,9 0.350	5,0 0.197	M10x1	90,0	2	0,1 0.220

ISO / DIN
– Metric/ Inch


ISO 7388-3/ DIN 69871



Design 1 = Without through coolant



Design 2 = With through coolant



With chamfer



With radius



- * With external sealing ring
- ** With internal and external sealing rings
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side For taper	OAL	LPR	LB1	DF	BD3	BD2	BD1	CND	KEY	CRKS	* / **			BHTA°		Design	Weight
			mm	mm	mm	mm	mm	mm	mm	mm	mm	mm			With	With			
			inch	inch	inch	inch	inch	inch	inch	inch	inch	inch			chamfer	radius		kg	
PS-I40-75-001	03119900	DIN 40	54,0 2.126	26,0 1.024	20,0 0.787	23,0 0.906	17,0 0.669	14,0 0.551	19,0 0.748	—	19,0 0.748	M16	*	■		15,0	1	0,1 0.220	
PS-I40C-75-001	03119899	DIN 40	54,0 2.126	26,0 1.024	20,0 0.787	23,0 0.906	17,0 0.669	14,0 0.551	19,0 0.748	7,0 0.276	19,0 0.748	M16		■		15,0	2	0,1 0.220	
PS-I40C-75-002	03119901	DIN 40	54,0 2.126	26,0 1.024	20,0 0.787	23,0 0.906	17,0 0.669	14,0 0.551	19,0 0.748	7,0 0.276	19,0 0.748	M16			■	15,0	2	0,1 0.220	
PS-I40C-75-003	03119946	DIN 40	54,0 2.126	29,0 1.142	23,0 0.906	23,0 0.906	17,0 0.669	14,0 0.551	19,0 0.748	7,0 0.276	19,0 0.748	M16	**	■		15,0	2	0,1 0.220	
PS-I50-75-001	03119903	DIN 50	74,0 2.913	34,0 1.339	25,0 0.984	36,0 1.417	25,0 0.984	21,0 0.827	28,0 1.102	—	30,0 1.181	M24	*	■		15,0	1	0,3 0.660	
PS-I50-75-003	03119945	DIN 50	74,0 2.913	34,0 1.339	25,0 0.984	36,0 1.417	25,0 0.984	21,0 0.827	28,0 1.102	—	30,0 1.181	M24	*		■	15,0	1	0,3 0.660	
PS-I50C-75-001	03119902	DIN 50	74,0 2.913	34,0 1.339	25,0 0.984	36,0 1.417	25,0 0.984	21,0 0.827	28,0 1.102	11,5 0.453	30,0 1.181	M24		■		15,0	2	0,3 0.660	
PS-I50C-75-002	03119904	DIN 50	74,0 2.913	34,0 1.339	25,0 0.984	36,0 1.417	25,0 0.984	21,0 0.827	28,0 1.102	11,5 0.453	30,0 1.181	M24			■	15,0	2	0,3 0.660	

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories


Shrinkfit

ISO / DIN
– Metric/ Inch


ISO 7388-3/ DIN 69871



Design 1 = Without through coolant



Design 2 = With through coolant



With chamfer



With radius



—* With external sealing ring
—** With internal sealing ring
—For ISO attribute explanation, see page 15


Designation	Item number	Machine side For taper	OAL	LPR	LB1	DF	BD3	BD2	BD1	CND	KEY	CRKS	* / **	BHTA°		Design	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch		With chamfer	With radius		
PS-I40C-45-001	03119898	ISO 40	44,4 1.748	16,4 0.646	11,15 0.439	22,5 0.886	17,0 0.669	12,95 0.510	18,95 0.746	7,35 0.289	18,0 0.709	M16		■	45,0	2	0,1 0.220
PS-I40C-45-002	03119947	DIN 40	41,25 1.624	16,25 0.640	11,18 0.440	21,8 0.858	17,0 0.669	12,45 0.490	18,8 0.740	7,0 0.276	19,0 0.748	M16		■	45,0	2	0,1 0.220
PS-I40C-45-003	03119950	DIN 40	44,106 1.736	19,106 0.752	14,026 0.552	22,0 0.866	17,0 0.669	12,446 0.490	18,796 0.740	7,0 0.276	19,0 0.748	M16		■	45,0	2	0,1 0.220
PS-I50-45-001	03119897	ISO 50	65,55 2.581	25,55 1.006	17,95 0.707	37,0 1.457	25,0 0.984	19,6 0.772	29,1 1.146	— —	30,0 1.181	M24	*	■	45,0	1	0,3 0.660
PS-I50C-45-001	03119896	ISO 50	65,55 2.581	25,55 1.006	17,95 0.707	37,0 1.457	25,0 0.984	19,6 0.772	29,1 1.146	11,5 0.453	30,0 1.181	M24		■	45,0	2	0,2 0.440
PS-I50C-45-003	03119949	DIN 50	65,4 2.575	25,4 1.000	17,78 0.700	36,56 1.439	25,0 0.984	20,828 0.820	28,956 1.140	10,0 0.394	30,15 1.187	M24		■	45,0	2	0,2 0.440
PS-I50C-45-004	03119948	DIN 50	65,4 2.575	25,4 1.000	17,78 0.700	36,56 1.439	25,0 0.984	20,828 0.820	28,956 1.140	10,0 0.394	30,15 1.187	M24	**	■	45,0	2	0,2 0.440

ISO / BT JIS
– Metric/ Inch

ISO 7388-3/ JIS B 6339




Design 1 = Without through coolant



With chamfer



Design 2 = With through coolant



With radius



- * With external sealing ring
- ** With internal and external sealing rings
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side For taper	OAL	LPR	LB1	DF	BD3	BD2	BD1	CND	KEY	CRKS	* / **	BHTA° Design Weight		
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch		With chamfer	With radius	kg lbs
PS-B30-45-001	03119886	BT 30	43,0 1.693	23,0 0.906	18,0 0.709	16,5 0.650	12,5 0.492	7,0 0.276	11,0 0.433	–	13,0 0.512	M12		■	45,0	1 0.220
PS-B30-60-001	03119889	BT 30	43,0 1.693	23,0 0.906	18,0 0.709	16,5 0.650	12,5 0.492	7,0 0.276	11,0 0.433	–	13,0 0.512	M12		■	30,0	1 0.220
PS-B30C-45-001	03119887	BT 30	43,0 1.693	23,0 0.906	18,0 0.709	16,5 0.650	12,5 0.492	7,0 0.276	11,0 0.433	3,0 0.118	13,0 0.512	M12		■	45,0	2 0.220
PS-B30C-45-003	03119939	BT 30	43,0 1.693	23,0 0.906	18,0 0.709	16,5 0.650	12,5 0.492	8,0 0.315	11,0 0.433	4,0 0.157	13,0 0.512	M12	*	■	45,0	2 0.220
PS-B30C-60-001	03119890	BT 30	43,0 1.693	23,0 0.906	18,0 0.709	16,5 0.650	12,5 0.492	7,0 0.276	11,0 0.433	3,0 0.118	13,0 0.512	M12		■	30,0	2 0.220
PS-B30C-60-002	03119891	BT 30	43,0 1.693	23,0 0.906	18,0 0.709	16,5 0.650	12,5 0.492	7,5 0.295	11,0 0.433	3,0 0.118	13,0 0.512	M12		■	30,0	2 0.220
PS-B40-45-001	03119894	BT 40	60,0 2.362	35,0 1.378	28,0 1.102	23,0 0.906	17,0 0.669	10,0 0.394	15,0 0.591	–	19,0 0.748	M16		■	45,0	1 0.220
PS-B40-60-001	03119906	BT 40	60,0 2.362	35,0 1.378	28,0 1.102	23,0 0.906	17,0 0.669	10,0 0.394	15,0 0.591	–	19,0 0.748	M16		■	30,0	1 0.220
PS-B40-90-001	03119884	BT 40	60,0 2.362	35,0 1.378	28,0 1.102	23,0 0.906	17,0 0.669	10,0 0.394	15,0 0.591	–	19,0 0.748	M16		■	0,0	1 0.220
PS-B40C-45-001	03119895	BT 40	60,0 2.362	35,0 1.378	28,0 1.102	23,0 0.906	17,0 0.669	10,0 0.394	15,0 0.591	3,0 0.118	19,0 0.748	M16		■	45,0	2 0.220
PS-B40C-60-001	03119930	BT 40	60,0 2.362	35,0 1.378	28,0 1.102	23,0 0.906	17,0 0.669	10,0 0.394	15,0 0.591	3,0 0.118	19,0 0.748	M16		■	30,0	2 0.220
PS-B40C-90-001	03119885	BT 40	60,0 2.362	35,0 1.378	28,0 1.102	23,0 0.906	17,0 0.669	10,0 0.394	15,0 0.591	3,0 0.118	19,0 0.748	M16		■	0,0	2 0.220
PS-B50-45-001	03119931	BT 50	85,0 3.346	45,0 1.772	35,0 1.378	38,0 1.496	25,0 0.984	17,0 0.669	23,0 0.906	–	30,0 1.181	M24		■	45,0	1 0.660
PS-B50-45-002	03119983	BT 50	84,8 3.339	45,0 1.772	35,0 1.378	34,8 1.370	25,0 0.984	16,9 0.665	23,0 0.906	–	30,1 1.185	M24		■	45,0	1 0.660
PS-B50-90-001	03119934	BT 50	85,0 3.346	45,0 1.772	35,0 1.378	38,0 1.496	25,0 0.984	17,0 0.669	23,0 0.906	–	30,0 1.181	M24		■	0,0	1 0.660
PS-B50C-45-001	03119932	BT 50	85,0 3.346	45,0 1.772	35,0 1.378	38,0 1.496	25,0 0.984	17,0 0.669	23,0 0.906	8,5 0.335	30,0 1.181	M24		■	45,0	2 0.660
PS-B50C-60-001	03119938	BT 50	85,0 3.346	45,0 1.772	35,0 1.378	38,0 1.496	25,0 0.984	17,0 0.669	23,0 0.906	9,5 0.374	30,0 1.181	M24		■	30,0	2 0.660
PS-B50C-90-001	03119933	BT 50	71,0 2.795	31,0 1.220	23,0 0.906	36,0 1.417	25,0 0.984	18,0 0.709	24,0 0.945	6,0 0.236	30,0 1.181	M24		■	0,0	2 0.660
PS-B50C-90-002	03119935	BT 50	85,0 3.346	45,0 1.772	35,0 1.378	38,0 1.496	25,0 0.984	17,0 0.669	23,0 0.906	8,0 0.315	30,0 1.181	M24		■	0,0	2 0.660

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Grafix

Seco Capto™

Others

Operating &
setting acces-
series


Shrinkfit

DIN
– Metric/ Inch

DIN 69871/ DIN 2080



With through coolant



—For ISO attribute explanation, see page 15


Designation	Item number	Machine side For taper	OAL	LPR	LB1	DF	BD3	BD2	BD1	CND	KEY	CRKS	TDZ	BHTA°	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch				kg lbs
PS-B40C-75-001	03119936	CAT DIN 40, DIN 2080 compatible	53,1 2.091	25,1 0.988	13,7 0.539	25,3 0.996	17,0 0.669	21,1 0.831	25,3 0.996	7,35 0.289	18,0 0.709	M16	M16	15,0	0,1 0.220

BT JIS
– Metric/ Inch

JIS B 6339



With through coolant



With chamfer



With radius




- * With external sealing ring
- ** With internal and external sealing rings
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side For taper	OAL	LPR	LB1	DF	BD3	BD2	BD1	CND	KEY	CRKS	* / **	BHTA°		Design	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch		With chamfer	With radius		
PS-B40C-75-002	03119940	BT 40	54,0 2.126	29,0 1.142	23,0 0.906	23,0 0.906	17,0 0.669	14,0 0.551	19,0 0.748	7,0 0.276	19,0 0.748	M16		■	15,0	—	0,1 0.220
PS-B40C-75-003	03119987	BT40	54,0 2.126	26,0 1.024	20,0 0.787	23,0 0.906	17,0 0.669	13,9 0.547	19,0 0.748	7,0 0.276	18,8 0.740	M16		■	15,0	1	0,1 0.220
PS-B50C-75-001	03119973	BT 50	74,0 2.913	34,0 1.339	25,0 0.984	38,0 1.496	25,0 0.984	21,0 0.827	28,0 1.102	11,5 0.453	30,0 1.181	M24		■	15,0	—	0,3 0.660

DIN / CAT-V
– Metric/ Inch



With through coolant



With chamfer



With radius




–* With external sealing ring
–** With internal and external sealing rings
–For ISO attribute explanation, see page 15

Designation	Item number	Machine side For taper	OAL	LPR	LB1	DF	BD2	BD1	CND	KEY	CRKS	* / **	ADIF1	BHTA°	Weight
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch	mm inch			With chamfer	With radius	kg lbs
PS-V40C-45-001	03119892	DIN CAT 40, ANSI B5-50 metric thread	38,0 1.496	16,25 0.640	11,0 0.433	22,0 0.866	12,8 0.504	18,8 0.740	7,5 0.295	17,8 0.701	M16	–	Flange connec- tion: radius	45,0	0,1 0.220
PS-V50C-45-001	03119893	DIN CAT 50, ANSI B5-50 metric thread	58,4 2.299	25,4 1.000	17,8 0.701	36,5 1.437	19,45 0.766	29,0 1.142	11,5 0.453	30,0 1.181	M24	–	Flange connec- tion: radius	45,0	0,2 0.440

CAT-V
– Inch




Design 1 = Without through coolant



With chamfer




Design 2 = With through coolant



With radius



Design 3 = With through coolant



- * With external sealing ring
- ** With internal and external sealing rings
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side For taper	OAL	LPR	LB1	DF	BD3	BD2	BD1	CND	KEY	CRKS	* / **		BHTA°	Design Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch		With chamfer	With radius		lbs
PS-V40-45-003	03119989	CAT 40	1.681	0.642	0.441	0.929	0.642	0.488	0.740	–	0.744	5/8-11 UNC		■	45,0	1 0.880
PS-V40C-45-002	03119960	CAT 40	1.500	0.642	0.441	0.929	–	0.488	0.740	0.280	0.744	5/8-11 UNC		■	45,0	2 0.220
PS-V40C-45-004	03119963	CAT 40	1.626	0.642	0.441	0.929	–	0.488	0.740	0.236	0.744	5/8-11 UNC		■	45,0	2 0.220
PS-V40C-45-005	03119965	CAT 40	1.650	0.642	0.441	0.929	0.669	0.492	0.740	0.280	0.752	M16		■	45,0	2 0.220
PS-V40C-45-007	03119977	CAT 40	1.500	0.642	0.441	0.929	–	0.492	0.740	0.280	0.744	M16		■	45,0	2 0.220
PS-V40C-45-009	03119981	CAT 40	1.681	0.642	0.441	0.929	0.642	0.488	0.740	0.280	0.744	5/8-11 UNC		■	45,0	2 0.220
PS-V40C-75-001	03119964	CAT 40	2.063	1.024	0.787	0.906	0.642	0.547	0.744	0.276	0.740	5/8-11 UNC		■	15,0	3 0.220
PS-V40C-75-002	03119979	CAT 40	2.008	1.028	0.791	0.906	0.642	0.547	0.744	0.236	0.740	5/8-11 UNC	*	■	15,0	3 0.220
PS-V50C-45-002	03119967	CAT 50	2.299	1.000	0.701	1.429	–	0.819	1.142	0.469	1.252	1-8 UNC		■	45,0	2 0.440
PS-V50C-45-005	03119970	CAT 50	2.299	1.000	0.701	1.429	1.031	0.819	1.142	0.469	1.252	1-8 UNC		■	45,0	2 0.440
PS-V50C-45-006	03119972	CAT 50	2.579	1.000	0.701	1.429	0.984	0.819	1.142	0.469	1.252	M24		■	45,0	2 0.660
PS-V50C-45-007	03119974	CAT 50	2.539	1.000	0.701	1.429	1.031	0.819	1.142	0.280	1.252	1-8 UNC		■	45,0	2 0.440
PS-V50C-45-008	03119976	CAT 50	3.142	1.780	1.386	1.496	0.984	0.665	0.906	0.252	1.181	1-8 UNC	*	■	45,0	3 0.660
PS-V50C-60-001	03119971	CAT 50	3.248	1.772	1.378	1.496	1.024	0.669	0.906	0.236	1.181	1-8 UNC	*	■	30,0	3 0.660

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating &
setting accessories

Shrinkfit


CAT-V
– Inch



Design 1 = Without through coolant



Design 2 = With through coolant



With chamfer



With radius




—* With external sealing ring
—** With internal and external sealing rings
—For ISO attribute explanation, see page 15

Designation	Item number	Machine side For taper	OAL	LPR	LB1	DF	BD3	BD2	BD1	CND	KEY	CRKS	* / **	BHTA°	Design	Weight
			inch	inch	inch	inch	inch	inch	inch	inch	inch		With chamfer	With radius		lbs
PS-V40-45-001	03119956	CAT 40	2.252	1.272	0.988	0.941	0.614	0.394	0.591	—	0.744	5/8-11 UNC		■	45,0	1 0.220
PS-V40-45-002	03119957	CAT 40	2.303	1.264	0.988	0.941	0.642	0.394	0.591	—	0.744	5/8-11 UNC		■	45,0	1 0.220
PS-V40-45-004	03119990	CAT 40	2.264	1.264	1.000	0.909	—	0.394	0.591	—	0.744	5/8-11 UNC		■	45,0	1 0.440
PS-V40-90-001	03119958	CAT 40	2.315	1.276	0.988	0.858	0.642	0.390	0.587	—	0.689	5/8-11 UNC		■	0,0	1 0.220
PS-V40C-45-003	03119961	CAT 40	2.307	1.272	0.988	0.858	0.642	0.390	0.587	0.157	0.689	5/8-11 UNC		■	45,0	2 0.220
PS-V40C-45-008	03119980	CAT 40	2.303	1.264	0.988	0.941	0.642	0.394	0.591	0.197	0.744	5/8-11 UNC		■	45,0	2 0.220
PS-V40C-45-010	03119986	CAT 40	2.252	1.264	0.988	0.933	0.669	0.394	0.587	0.173	0.744	M16		■	45,0	2 0.220
PS-V40C-75-004	03119988	CAT 40	2.122	1.024	0.787	0.906	0.642	0.547	0.744	0.236	0.740	5/8-11 UNC		■	15,0	2 0.220
PS-V50C-45-003	03119968	CAT 50	3.331	1.787	1.374	1.370	1.031	0.661	0.898	0.252	1.185	1-8 UNC		■	45,0	2 0.660

Hydraulic chucks

– Metric/ Inch



– Nominal clamping diameter only (no clamping range): tool shank tolerance h6 maximum

– ...L1 = with peripheral coolant

– For ISO attribute explanation, see page 15

Designation	Item number	Machine side	Workpiece side	LS	FLGT	DF	LSC
		DCON	DCB				
		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
05FHC1203	10137358	12,0 0.472	3,0 0.118	45,0 0.608	2,0 0.079	16,5 0.650	15,45 0.608
05FHC1204	10137359	12,0 0.472	4,0 0.157	45,0 0.620	2,0 0.079	16,5 0.650	15,75 0.620
05FHC1205	10137360	12,0 0.472	5,0 0.197	45,0 0.634	2,0 0.079	16,5 0.650	16,1 0.634
05FHC1206	10137361	12,0 0.472	6,0 0.236	45,0 0.953	2,0 0.079	16,5 0.650	24,21 0.953
05FHC1208	10137362	12,0 0.472	8,0 0.315	45,0 0.977	2,0 0.079	16,5 0.650	24,81 0.977
05FHC1210	10137363	12,0 0.472	10,0 0.394	45,0 1.000	2,0 0.079	16,5 0.650	25,41 1.000
05FHC2003	10137364	20,0 0.787	3,0 0.118	50,5 0.616	2,0 0.079	24,0 0.945	15,65 0.616
05FHC2004	10137365	20,0 0.787	4,0 0.157	50,5 0.628	2,0 0.079	24,0 0.945	15,95 0.628
05FHC2005	10137366	20,0 0.787	5,0 0.197	50,5 0.640	2,0 0.079	24,0 0.945	16,25 0.640
05FHC2006	10137367	20,0 0.787	6,0 0.236	50,5 1.006	2,0 0.079	24,0 0.945	25,55 1.006
05FHC2008	10137368	20,0 0.787	8,0 0.315	50,5 1.030	2,0 0.079	24,0 0.945	26,15 1.030
05FHC2010	10137369	20,0 0.787	10,0 0.394	50,5 1.211	2,0 0.079	24,0 0.945	30,75 1.211
05FHC2012	10137370	20,0 0.787	12,0 0.472	50,5 1.367	2,0 0.079	24,0 0.945	34,71 1.367
05FHC2014	10137371	20,0 0.787	14,0 0.551	50,5 1.390	2,0 0.079	24,0 0.945	35,31 1.390
05FHC2016	10137372	20,0 0.787	16,0 0.630	50,5 1.414	2,0 0.079	24,0 0.945	35,91 1.414
05FHC3206	10137373	32,0 1.260	6,0 0.236	60,5 0.922	2,0 0.079	35,5 1.398	23,42 0.922
05FHC3208	10137374	32,0 1.260	8,0 0.315	60,5 0.946	2,0 0.079	35,5 1.398	24,03 0.946
05FHC3210	10137375	32,0 1.260	10,0 0.394	60,5 1.107	2,0 0.079	35,5 1.398	28,13 1.107
05FHC3212	10137376	32,0 1.260	12,0 0.472	60,5 1.131	2,0 0.079	35,5 1.398	28,73 1.131
05FHC3214	10137377	32,0 1.260	14,0 0.551	60,5 1.155	2,0 0.079	35,5 1.398	29,33 1.155
05FHC3216	10137378	32,0 1.260	16,0 0.630	60,5 1.583	2,0 0.079	35,5 1.398	40,2 1.583
05FHC3218	10137379	32,0 1.260	18,0 0.709	60,5 1.594	2,0 0.079	35,5 1.398	40,5 1.594
05FHC3220	10137380	32,0 1.260	20,0 0.787	60,5 1.618	2,0 0.079	35,5 1.398	41,1 1.618

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

Guide	Designation	Item number	Machine side	Workpiece side	LS	FLGT	DF	LSC
			DCON	DCB				
			mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
HSK-A	05FHC3225	10137381	32,0 1.260	25,0 0.984	60,5 1.846	2,0 0.079	35,5 1.398	46,9 1.846
	05FHC1203L1	10137409	12,0 0.472	3,0 0.118	45,0 0.608	2,0 0.079	16,5 0.650	15,45 0.608
	05FHC1204L1	10137410	12,0 0.472	4,0 0.157	45,0 0.620	2,0 0.079	16,5 0.650	15,75 0.620
HSK-E	05FHC1205L1	10137411	12,0 0.472	5,0 0.197	45,0 0.632	2,0 0.079	16,5 0.650	16,05 0.632
	05FHC1206L1	10137412	12,0 0.472	6,0 0.236	45,0 0.953	2,0 0.079	16,5 0.650	24,21 0.953
	05FHC1208L1	10137413	12,0 0.472	8,0 0.315	45,0 0.977	2,0 0.079	16,5 0.650	24,81 0.977
DIN	05FHC2003L1	10137414	20,0 0.787	3,0 0.118	50,5 0.616	2,0 0.079	24,0 0.945	15,65 0.616
	05FHC2004L1	10137415	20,0 0.787	4,0 0.157	50,5 0.628	2,0 0.079	24,0 0.945	15,95 0.628
	05FHC2005L1	10137416	20,0 0.787	5,0 0.197	50,5 0.640	2,0 0.079	24,0 0.945	16,25 0.640
BT JIS	05FHC2006L1	10137417	20,0 0.787	6,0 0.236	50,5 1.007	2,0 0.079	24,0 0.945	25,57 1.007
	05FHC2008L1	10137418	20,0 0.787	8,0 0.315	50,5 1.030	2,0 0.079	24,0 0.945	26,15 1.030
	05FHC2010L1	10137419	20,0 0.787	10,0 0.394	50,5 1.211	2,0 0.079	24,0 0.945	30,75 1.211
CAT	05FHC2012L1	10137420	20,0 0.787	12,0 0.472	50,5 1.367	2,0 0.079	24,0 0.945	34,71 1.367
	05FHC2014L1	10137421	20,0 0.787	14,0 0.551	50,5 1.390	2,0 0.079	24,0 0.945	35,31 1.390
	05FHC2016L1	10137422	20,0 0.787	16,0 0.630	50,5 1.414	2,0 0.079	24,0 0.945	35,91 1.414
Combimaster	05FHC3206L1	10137423	32,0 1.260	6,0 0.236	60,5 0.922	2,0 0.079	35,5 1.398	23,42 0.922
	05FHC3208L1	10137424	32,0 1.260	8,0 0.315	60,5 0.946	2,0 0.079	35,5 1.398	24,02 0.946
	05FHC3210L1	10137425	32,0 1.260	10,0 0.394	60,5 1.107	2,0 0.079	35,5 1.398	28,13 1.107
Graflex	05FHC3212L1	10137426	32,0 1.260	12,0 0.472	60,5 1.131	2,0 0.079	35,5 1.398	28,73 1.131
	05FHC3214L1	10137427	32,0 1.260	14,0 0.551	60,5 1.155	2,0 0.079	35,5 1.398	29,33 1.155
	05FHC3216L1	10137428	32,0 1.260	16,0 0.630	60,5 1.583	2,0 0.079	35,5 1.398	40,2 1.583
Seco Capto™	05FHC3218L1	10137429	32,0 1.260	18,0 0.709	60,5 1.594	2,0 0.079	35,5 1.398	40,5 1.594
	05FHC3220L1	10137430	32,0 1.260	20,0 0.787	60,5 1.618	2,0 0.079	35,5 1.398	41,1 1.618
	05FHC3225L1	10137431	32,0 1.260	25,0 0.984	60,5 1.847	2,0 0.079	35,5 1.398	46,91 1.847
Others								
Operating & setting accessories								
Shrinkfit								

Hydraulic chucks – Inch




- Nominal clamping diameter only (no clamping range): tool shank tolerance h6 maximum
- ...L1 = with peripheral coolant
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side DCON	Workpiece side DCB	LS	FLGT	DF	LSC
		inch	inch	inch	inch	inch	inch
05FHC120125	10137382	0.472	0.125	1.772	0.079	0.650	0.610
05FHC120187	10137383	0.472	0.188	1.772	0.079	0.650	0.629
05FHC120250	10137384	0.472	0.250	1.772	0.079	0.650	0.957
05FHC120312	10137385	0.472	0.313	1.772	0.079	0.650	0.976
05FHC120375	10137386	0.472	0.375	1.772	0.079	0.650	0.995
05FHC200125	10137387	0.787	0.125	1.988	0.079	0.945	0.618
05FHC200187	10137388	0.787	0.188	1.988	0.079	0.945	0.637
05FHC200250	10137389	0.787	0.250	1.988	0.079	0.945	1.010
05FHC200312	10137390	0.787	0.313	1.988	0.079	0.945	1.029
05FHC200375	10137391	0.787	0.375	1.988	0.079	0.945	1.048
05FHC200437	10137392	0.787	0.438	1.988	0.079	0.945	1.224
05FHC200500	10137393	0.787	0.500	1.988	0.079	0.945	1.375
05FHC200562	10137394	0.787	0.563	1.988	0.079	0.945	1.394
05FHC200625	10137395	0.787	0.625	1.988	0.079	0.945	1.412
05FHC320250	10137396	1.260	0.250	2.382	0.079	1.398	0.926
05FHC320312	10137397	1.260	0.313	2.382	0.079	1.398	0.945
05FHC320375	10137398	1.260	0.375	2.382	0.079	1.398	1.102
05FHC320437	10137399	1.260	0.438	2.382	0.079	1.398	1.120
05FHC320500	10137400	1.260	0.500	2.382	0.079	1.398	1.139
05FHC320562	10137401	1.260	0.563	2.382	0.079	1.398	1.158
05FHC320625	10137402	1.260	0.625	2.382	0.079	1.398	1.581
05FHC320687	10137403	1.260	0.687	2.382	0.079	1.398	1.588
05FHC320750	10137404	1.260	0.750	2.382	0.079	1.398	1.607
05FHC320812	10137405	1.260	0.812	2.382	0.079	1.398	1.600
05FHC320875	10137406	1.260	0.875	2.382	0.079	1.398	1.619
05FHC320937	10137407	1.260	0.937	2.382	0.079	1.398	1.833
05FHC321000	10137408	1.260	1.000	2.382	0.079	1.398	1.850
05FHC120125L1	10137432	0.472	0.125	1.772	0.079	0.650	0.610
05FHC120187L1	10137433	0.472	0.188	1.772	0.079	0.650	0.629
05FHC120250L1	10137434	0.472	0.250	1.772	0.079	0.650	0.957
05FHC120312L1	10137435	0.472	0.313	1.772	0.079	0.650	0.976
05FHC120375L1	10137436	0.472	0.375	1.772	0.079	0.650	0.995
05FHC200187L1	10137438	0.787	0.188	1.988	0.079	0.945	0.637
05FHC200250L1	10137439	0.787	0.250	1.988	0.079	0.945	1.010
05FHC200312L1	10137440	0.787	0.313	1.988	0.079	0.945	1.029

Guide	Designation	Item number	Machine side DCON	Workpiece side DCB	LS	FLGT	DF	LSC
			<i>inch</i>	<i>inch</i>	<i>inch</i>	<i>inch</i>	<i>inch</i>	<i>inch</i>
HSK-A	05FHC200375L1	10137441	0.787	0.375	1.988	0.079	0.945	1.048
	05FHC200437L1	10137442	0.787	0.438	1.988	0.079	0.945	1.224
	05FHC200500L1	10137443	0.787	0.500	1.988	0.079	0.945	1.375
	05FHC200562L1	10137444	0.787	0.563	1.988	0.079	0.945	1.394
	05FHC200625L1	10137445	0.787	0.625	1.988	0.079	0.945	1.412
HSK-E	05FHC200125L1	10137437	0.787	0.125	1.988	0.079	0.945	0.618
	05FHC320500L1	10137446	1.260	0.500	2.382	0.079	1.398	1.139
	05FHC320625L1	10137447	1.260	0.625	2.382	0.079	1.398	1.581
	05FHC320750L1	10137448	1.260	0.750	2.382	0.079	1.398	1.607
	05FHC320875L1	10137449	1.260	0.875	2.382	0.079	1.398	1.619
DIN	05FHC321000L1	10137450	1.260	1.000	2.382	0.079	1.398	1.850
BT JIS								
CAT								
Combimaster								
Graflex								
Seco Capto™								
Others								
Operating & setting accessories								
Shrinkfit								

Power milling chucks – Metric/ Inch



– Nominal clamping diameter only (no clamping range): tool shank tolerance h6 maximum
– For ISO attribute explanation, see page 15

Designation	Item number	Machine side	Workpiece side	LS	FLGT	DF	LSC
		DCON	DCB				
		mm inch	mm inch	mm inch	mm inch	mm inch	mm inch
05FPMC2006	03211223	20,0 0.787	6,0 0.236	47,5 1.181	2,5 0.098	24,0 0.945	30,0 1.181
05FPMC2008	03211224	20,0 0.787	8,0 0.315	47,5 1.260	2,5 0.098	24,0 0.945	32,0 1.260
05FPMC2010	03211225	20,0 0.787	10,0 0.394	47,5 1.378	2,5 0.098	24,0 0.945	35,0 1.378
05FPMC2012	03211226	20,0 0.787	12,0 0.472	47,5 1.378	2,5 0.098	24,0 0.945	35,0 1.378
05FPMC2014	03211227	20,0 0.787	14,0 0.551	47,5 1.378	2,5 0.098	24,0 0.945	35,0 1.378
05FPMC2016	03211228	20,0 0.787	16,0 0.630	47,5 1.575	2,5 0.098	24,0 0.945	40,0 1.575
05FPMC3210	03211229	32,0 1.260	10,0 0.394	60,5 1.378	2,5 0.098	36,0 1.417	35,0 1.378
05FPMC3212	03211230	32,0 1.260	12,0 0.472	60,5 1.575	2,5 0.098	36,0 1.417	40,0 1.575
05FPMC3214	03211231	32,0 1.260	14,0 0.551	60,5 1.575	2,5 0.098	36,0 1.417	40,0 1.575
05FPMC3216	03211232	32,0 1.260	16,0 0.630	60,5 1.575	2,5 0.098	36,0 1.417	40,0 1.575
05FPMC3218	03211233	32,0 1.260	18,0 0.709	60,5 1.732	2,5 0.098	36,0 1.417	44,0 1.732
05FPMC3220	03211234	32,0 1.260	20,0 0.787	60,5 1.732	2,5 0.098	36,0 1.417	44,0 1.732
05FPMC3225	03211235	32,0 1.260	25,0 0.984	60,5 1.890	2,5 0.098	36,0 1.417	48,0 1.890

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

Power milling chucks – Inch




—Nominal clamping diameter only (no clamping range): tool shank tolerance h6 maximum
—For ISO attribute explanation, see page 15

Designation	Item number	Machine side DCON	Workpiece side DCB	LS	FLGT	DF	LSC
		<i>inch</i>	<i>inch</i>	<i>inch</i>	<i>inch</i>	<i>inch</i>	<i>inch</i>
05FPMC075006	03211245	0.750	0.236	1.870	0.098	0.945	1.181
05FPMC07500250	03211256	0.750	0.250	1.870	0.098	0.945	1.181
05FPMC075008	03211246	0.750	0.315	1.870	0.098	0.945	1.260
05FPMC07500375	03211257	0.750	0.375	1.870	0.098	0.945	1.378
05FPMC075010	03211247	0.750	0.394	1.870	0.098	0.945	1.378
05FPMC075012	03211248	0.750	0.472	1.870	0.098	0.945	1.378
05FPMC07500500	03211258	0.750	0.500	1.870	0.098	0.945	1.378
05FPMC07500625	03211259	0.750	0.625	1.870	0.098	0.945	1.575
05FPMC075016	03211249	0.750	0.630	1.870	0.098	0.945	1.575
05FPMC200250	03211236	0.787	0.250	1.870	0.098	0.945	1.181
05FPMC200375	03211237	0.787	0.375	1.870	0.098	0.945	1.378
05FPMC200500	03211238	0.787	0.500	1.870	0.098	0.945	1.378
05FPMC200625	03211239	0.787	0.625	1.870	0.098	0.945	1.575
05FPMC12500375	03211260	1.250	0.375	2.382	0.098	1.417	1.378
05FPMC125010	03211250	1.250	0.394	2.382	0.098	1.417	1.378
05FPMC125012	03211251	1.250	0.472	2.382	0.098	1.417	1.575
05FPMC12500500	03211261	1.250	0.500	2.382	0.098	1.417	1.575
05FPMC12500625	03211262	1.250	0.625	2.382	0.098	1.417	1.575
05FPMC125016	03211252	1.250	0.630	2.382	0.098	1.417	1.575
05FPMC125018	03211253	1.250	0.709	2.382	0.098	1.417	1.732
05FPMC12500750	03211263	1.250	0.750	2.382	0.098	1.417	1.732
05FPMC125020	03211254	1.250	0.787	2.382	0.098	1.417	1.732
05FPMC125025	03211255	1.250	0.984	2.382	0.098	1.417	1.890
05FPMC12501000	03211264	1.250	1.000	2.382	0.098	1.417	1.890
05FPMC320375	03211240	1.260	0.375	2.382	0.098	1.417	1.378
05FPMC320500	03211241	1.260	0.500	2.382	0.098	1.417	1.575
05FPMC320625	03211242	1.260	0.625	2.382	0.098	1.417	1.575
05FPMC320750	03211243	1.260	0.750	2.382	0.098	1.417	1.732
05FPMC321000	03211244	1.260	1.000	2.382	0.098	1.417	1.890


– Metric/ Inch



Design 1



Design 2



- For reliable coolant flow for tools with coolant through channel(s)
- Select the suitable screw in the 'Stop screws for through coolant' selection chart
- For ISO attribute explanation, see page 15

Designation	Item number	DCBN	DCBX	OAL	BD1	WF	CNT	Design
		mm inch	mm inch	mm inch	mm inch	mm inch		
19BPMC2001A	03211273	6,0 0.236	12,0 0.472	21,5 0.846	20,0 0.787	4,0 0.157	–	2
19BPMC2001B	03211274	14,0 0.551	20,0 0.787	18,0 0.709	20,0 0.787	4,0 0.157	–	2
19BPMC2002A	03211275	6,0 0.236	12,0 0.472	35,5 1.398	–	4,0 0.157	M16	1
19BPMC2002B	03211276	14,0 0.551	20,0 0.787	27,5 1.083	–	4,0 0.157	M16	1
19BPMC3201A	03211277	6,0 0.236	12,0 0.472	37,5 1.476	32,0 1.260	4,0 0.157	–	2
19BPMC3201B	03211278	14,0 0.551	20,0 0.787	31,0 1.220	32,0 1.260	4,0 0.157	–	2
19BPMC3201C	03211279	25,0 0.984	32,0 1.260	28,5 1.122	32,0 1.260	4,0 0.157	–	2
19BPMC3203A	03211280	6,0 0.236	12,0 0.472	55,5 2.185	–	4,0 0.157	M16	1
19BPMC3203B	03211281	14,0 0.551	20,0 0.787	52,0 2.047	–	4,0 0.157	M16	1
19BPMC3203C	03211282	25,0 0.984	32,0 1.260	37,5 1.476	–	4,0 0.157	M16	1
19BPMC3204A	03211283	6,0 0.236	12,0 0.472	77,5 3.051	–	4,0 0.157	M16	1
19BPMC3204B	03211284	14,0 0.551	20,0 0.787	74,0 2.913	–	4,0 0.157	M16	1
19BPMC3204C	03211285	25,0 0.984	32,0 1.260	58,5 2.303	–	4,0 0.157	M16	1

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories


Shrinkfit

Selection chart for Stop screws for coolant through, for Power milling chucks:
selection is according to PMC Ø size used, taper type and tool shank diameter.

PMC Ø size	Taper type	Tool shank Ø	Designation Screw	Item number
20	HSK63 / HSK 100 / C6 / C8	6 - 8 - 10 - 12	19BPMC2001A	03211273
20	HSK63 / HSK 100 / C6 / C8	14 - 16 - 18 - 20	19BPMC2001B	03211274
20	DIN 40 / DIN 50 / BT40 / BT 50	6 - 8 - 10 - 12	19BPMC2002A	03211275
20	DIN 40 / DIN 50 / BT40 / BT 50	14 - 16 - 18 - 20	19BPMC2002B	03211276
32	HSK63 / HSK 100 / C6 / C8	6 - 8 - 10 - 12	19BPMC3201A	03211277
32	HSK63 / HSK 100 / C6 / C8	14 - 16 - 18 - 20	19BPMC3201B	03211278
32	HSK63 / HSK 100 / C6 / C8	25 - 32	19BPMC3201C	03211279
32	DIN 40 / BT 40	6 - 8 - 10 - 12	19BPMC3203A	03211280
32	DIN 40 / BT 40	14 - 16 - 18 - 20	19BPMC3203B	03211281
32	DIN 40 / BT 40	25 - 32	19BPMC3203C	03211282
32	DIN 50 / BT 50	6 - 8 - 10 - 12	19BPMC3204A	03211283
32	DIN 50 / BT 50	14 - 16 - 18 - 20	19BPMC3204B	03211284
32	DIN 50 / BT 50	25 - 32	19BPMC3204C	03211285
PMC Ø size	Taper type	Tool shank Ø	Designation Screw	Item number
3/4	HSK63 / HSK 100	1/4 - 3/8	19BPMC190505D	03211287
3/4	HSK63 / HSK 100	1/2 - 5/8	19BPMC190505E	03211288
3/4	CAT 40 / CAT 50	1/4 - 3/8	19BPMC190506D	03211289
3/4	CAT 40 / CAT 50	1/2 - 5/8	19BPMC190506E	03211290
1-1/4	HSK63 / HSK 100	3/8 - 1/2	19BPMC317505F	03211291
1-1/4	HSK63 / HSK 100	5/8 - 3/4	19BPMC317505G	03211292
1-1/4	HSK63 / HSK 100	1 - 1-1/4	19BPMC317505H	03211293
1-1/4	CAT 40 / CAT 50	3/8 - 1/2	19BPMC317506F	03211294
1-1/4	CAT 40 / CAT 50	5/8 - 3/4	19BPMC317506G	03211295
1-1/4	CAT 40 / CAT 50	1 - 1-1/4	19BPMC317506H	03211296

Not sealed
– Metric/ Inch

Similar to ISO 15488-B



- Run-out 3 µm maximum at 3 x ØDCBN-DCBX when assembled on a HP collet chuck, ERHP 5672
- Nominal clamping diameter only (no clamping range): tool shank tolerance h10 maximum
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX	OAL		BD1		BHTA°
				mm inch	mm inch	mm inch	mm inch	
56721101	02882782	HP 11	1,0 0.039	18,0 0.709		11,5 0.453		8,0
567211015	02882783	HP 11	1,5 0.059	18,0 0.709		11,5 0.453		8,0
56721102	02882784	HP 11	2,0 0.079	18,0 0.709		11,5 0.453		8,0
567211025	02882785	HP 11	2,5 0.098	18,0 0.709		11,5 0.453		8,0
56721103	02882786	HP 11	3,0 0.118	18,0 0.709		11,5 0.453		8,0
567211035	02882787	HP 11	3,5 0.138	18,0 0.709		11,5 0.453		8,0
56721104	02882788	HP 11	4,0 0.157	18,0 0.709		11,5 0.453		8,0
567211045	02882789	HP 11	4,5 0.177	18,0 0.709		11,5 0.453		8,0
56721105	02882791	HP 11	5,0 0.197	18,0 0.709		11,5 0.453		8,0
567211055	02882792	HP 11	5,5 0.217	18,0 0.709		11,5 0.453		8,0
56721106	02882793	HP 11	6,0 0.236	18,0 0.709		11,5 0.453		8,0
567211065	02882794	HP 11	6,5 0.256	18,0 0.709		11,5 0.453		8,0
56721107	02882795	HP 11	7,0 0.276	18,0 0.709		11,5 0.453		8,0
56721601	02828312	HP 16	1,0 0.039	27,5 1.083		17,0 0.669		8,0
567216015	02828313	HP 16	1,5 0.059	27,5 1.083		17,0 0.669		8,0
56721602	02828314	HP 16	2,0 0.079	27,5 1.083		17,0 0.669		8,0
567216025	02828315	HP 16	2,5 0.098	27,5 1.083		17,0 0.669		8,0
56721603	02828316	HP 16	3,0 0.118	27,5 1.083		17,0 0.669		8,0
567216035	02828317	HP 16	3,5 0.138	27,5 1.083		17,0 0.669		8,0
56721604	02828318	HP 16	4,0 0.157	27,5 1.083		17,0 0.669		8,0
567216045	02828319	HP 16	4,5 0.177	27,5 1.083		17,0 0.669		8,0
56721605	02828320	HP 16	5,0 0.197	27,5 1.083		17,0 0.669		8,0

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories


Shrinkfit

Guide	Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX	OAL	BD1	BHTA°
				mm inch	mm inch	mm inch	
HSK-A	567216055	02828321	HP 16	5,5 0.217	27,5 1.083	17,0 0.669	8,0
	56721606	02828322	HP 16	6,0 0.236	27,5 1.083	17,0 0.669	8,0
	567216065	02828323	HP 16	6,5 0.256	27,5 1.083	17,0 0.669	8,0
HSK-E	56721607	02828324	HP 16	7,0 0.276	27,5 1.083	17,0 0.669	8,0
	567216075	02828325	HP 16	7,5 0.295	27,5 1.083	17,0 0.669	8,0
	56721608	02828326	HP 16	8,0 0.315	27,5 1.083	17,0 0.669	8,0
DIN	567216085	02828327	HP 16	8,5 0.335	27,5 1.083	17,0 0.669	8,0
	56721609	02828328	HP 16	9,0 0.354	27,5 1.083	17,0 0.669	8,0
	567216095	02828329	HP 16	9,5 0.374	27,5 1.083	17,0 0.669	8,0
BT JIS	56721610	02828330	HP 16	10,0 0.394	27,5 1.083	17,0 0.669	8,0
	56722502	02828342	HP 25	2,0 0.079	34,0 1.339	26,0 1.024	8,0
	567225025	02828343	HP 25	2,5 0.098	34,0 1.339	26,0 1.024	8,0
CAT	56722503	02828344	HP 25	3,0 0.118	34,0 1.339	26,0 1.024	8,0
	567225035	02828345	HP 25	3,5 0.138	34,0 1.339	26,0 1.024	8,0
	56722504	02828346	HP 25	4,0 0.157	34,0 1.339	26,0 1.024	8,0
Combimaster	567225045	02828347	HP 25	4,5 0.177	34,0 1.339	26,0 1.024	8,0
	56722505	02828348	HP 25	5,0 0.197	34,0 1.339	26,0 1.024	8,0
	567225055	02828349	HP 25	5,5 0.217	34,0 1.339	26,0 1.024	8,0
Graflex	56722506	02828350	HP 25	6,0 0.236	34,0 1.339	26,0 1.024	8,0
	567225065	02828351	HP 25	6,5 0.256	34,0 1.339	26,0 1.024	8,0
	56722507	02828352	HP 25	7,0 0.276	34,0 1.339	26,0 1.024	8,0
Seco Capto™	567225075	02828353	HP 25	7,5 0.295	34,0 1.339	26,0 1.024	8,0
	56722508	02828354	HP 25	8,0 0.315	34,0 1.339	26,0 1.024	8,0
	567225085	02828355	HP 25	8,5 0.335	34,0 1.339	26,0 1.024	8,0
Others	56722509	02828356	HP 25	9,0 0.354	34,0 1.339	26,0 1.024	8,0
	567225095	02828357	HP 25	9,5 0.374	34,0 1.339	26,0 1.024	8,0
	56722510	02828358	HP 25	10,0 0.394	34,0 1.339	26,0 1.024	8,0
Operating & setting accessories	56722511	02828359	HP 25	11,0 0.433	34,0 1.339	26,0 1.024	8,0
	56722512	02828360	HP 25	12,0 0.472	34,0 1.339	26,0 1.024	8,0
	56722513	02828361	HP 25	13,0 0.512	34,0 1.339	26,0 1.024	8,0
Shrinkfit	56722514	02828362	HP 25	14,0 0.551	34,0 1.339	26,0 1.024	8,0
	56722515	02828363	HP 25	15,0 0.591	34,0 1.339	26,0 1.024	8,0
	56722516	02828364	HP 25	16,0 0.630	34,0 1.339	26,0 1.024	8,0

Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX	OAL	BD1	BHTA°	Guide
			mm inch	mm inch	mm inch		
56723202	02828366	HP 32	2,0 0.079	40,0 1.575	33,0 1.299	8,0	HSK-A
56723203	02828367	HP 32	3,0 0.118	40,0 1.575	33,0 1.299	8,0	
56723204	02828368	HP 32	4,0 0.157	40,0 1.575	33,0 1.299	8,0	
56723205	02828369	HP 32	5,0 0.197	40,0 1.575	33,0 1.299	8,0	HSK-E
56723206	02828370	HP 32	6,0 0.236	40,0 1.575	33,0 1.299	8,0	
56723207	02828371	HP 32	7,0 0.276	40,0 1.575	33,0 1.299	8,0	
56723208	02828372	HP 32	8,0 0.315	40,0 1.575	33,0 1.299	8,0	DIN
56723209	02828373	HP 32	9,0 0.354	40,0 1.575	33,0 1.299	8,0	
56723210	02828374	HP 32	10,0 0.394	40,0 1.575	33,0 1.299	8,0	
56723211	02828375	HP 32	11,0 0.433	40,0 1.575	33,0 1.299	8,0	BT JIS
56723212	02828376	HP 32	12,0 0.472	40,0 1.575	33,0 1.299	8,0	
56723213	02828377	HP 32	13,0 0.512	40,0 1.575	33,0 1.299	8,0	
56723214	02828378	HP 32	14,0 0.551	40,0 1.575	33,0 1.299	8,0	CAT
56723215	02828379	HP 32	15,0 0.591	40,0 1.575	33,0 1.299	8,0	
56723216	02828380	HP 32	16,0 0.630	40,0 1.575	33,0 1.299	8,0	
56723217	02828381	HP 32	17,0 0.669	40,0 1.575	33,0 1.299	8,0	Combimaster
56723218	02828382	HP 32	18,0 0.709	40,0 1.575	33,0 1.299	8,0	
56723219	02828383	HP 32	19,0 0.748	40,0 1.575	33,0 1.299	8,0	
56723220	02828384	HP 32	20,0 0.787	40,0 1.575	33,0 1.299	8,0	Graflex
							Seco Capto™
							Others
							Operating & setting accessories
							Shrinkfit

Not sealed
– Inch

Similar to ISO 15488-B




- Run-out 3 µm maximum at 3 x ØDCBN-DCBX when assembled on a HP collet chuck, ERHP 5672
- Nominal clamping diameter only (no clamping range): tool shank tolerance h10 maximum
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX	OAL	BD1	BHTA°
			<i>inch</i>	<i>inch</i>	<i>inch</i>	
5672110158	02882796	HP 11	0.062	0.709	0.453	8,0
5672110317	02882797	HP 11	0.125	0.709	0.453	8,0
5672110476	02882798	HP 11	0.188	0.709	0.453	8,0
5672110635	02882799	HP 11	0.250	0.709	0.453	8,0
5672160317	02828385	HP 16	0.125	1.083	0.669	8,0
5672160476	02828386	HP 16	0.188	1.083	0.669	8,0
5672160635	02828417	HP 16	0.250	1.083	0.669	8,0
5672160952	02828428	HP 16	0.375	1.083	0.669	8,0
5672250317	02828429	HP 25	0.125	1.339	1.024	8,0
5672250476	02828434	HP 25	0.188	1.339	1.024	8,0
5672250635	02828435	HP 25	0.250	1.339	1.024	8,0
5672250793	02828436	HP 25	0.313	1.339	1.024	8,0
5672250952	02828446	HP 25	0.375	1.339	1.024	8,0
567225127	02828387	HP 25	0.500	1.339	1.024	8,0
5672320317	02828448	HP 32	0.125	1.575	1.299	8,0
5672320635	02828452	HP 32	0.250	1.575	1.299	8,0
5672320952	02828453	HP 32	0.375	1.575	1.299	8,0
567232127	02828388	HP 32	0.500	1.575	1.299	8,0
5672321587	02828455	HP 32	0.625	1.575	1.299	8,0
5672321905	02828456	HP 32	0.750	1.575	1.299	8,0

Sealed
– Metric/ Inch

Similar to ISO 15488-B



- Run-out 3 µm maximum at 3 x ØDCBN-DCBX when assembled on a HP collet chuck, ERHP 5672
- Nominal clamping diameter only (no clamping range): tool shank tolerance h8 maximum
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX	OAL	BD1	BHTA°
			mm inch			
5672S1103	02892583	HP 11	3,0 0.118	18,0 0.709	11,5 0.453	8,0
5672S1104	02892584	HP 11	4,0 0.157	18,0 0.709	11,5 0.453	8,0
5672S1105	02892585	HP 11	5,0 0.197	18,0 0.709	11,5 0.453	8,0
5672S1106	02892586	HP 11	6,0 0.236	18,0 0.709	11,5 0.453	8,0
5672S1603	02845288	HP 16	3,0 0.118	27,5 1.083	17,0 0.669	8,0
5672S1604	02845289	HP 16	4,0 0.157	27,5 1.083	17,0 0.669	8,0
5672S1605	02845290	HP 16	5,0 0.197	27,5 1.083	17,0 0.669	8,0
5672S1606	02845291	HP 16	6,0 0.236	27,5 1.083	17,0 0.669	8,0
5672S1607	02845292	HP 16	7,0 0.276	27,5 1.083	17,0 0.669	8,0
5672S1608	02845293	HP 16	8,0 0.315	27,5 1.083	17,0 0.669	8,0
5672S1609	02845294	HP 16	9,0 0.354	27,5 1.083	17,0 0.669	8,0
5672S1610	02845295	HP 16	10,0 0.394	27,5 1.083	17,0 0.669	8,0
5672S2503	02845297	HP 25	3,0 0.118	34,0 1.339	26,0 1.024	8,0
5672S2504	02845298	HP 25	4,0 0.157	34,0 1.339	26,0 1.024	8,0
5672S2505	02845299	HP 25	5,0 0.197	34,0 1.339	26,0 1.024	8,0
5672S2506	02845300	HP 25	6,0 0.236	34,0 1.339	26,0 1.024	8,0
5672S2507	02845301	HP 25	7,0 0.276	34,0 1.339	26,0 1.024	8,0
5672S2508	02845302	HP 25	8,0 0.315	34,0 1.339	26,0 1.024	8,0
5672S2509	02845303	HP 25	9,0 0.354	34,0 1.339	26,0 1.024	8,0
5672S2510	02845304	HP 25	10,0 0.394	34,0 1.339	26,0 1.024	8,0
5672S2511	02845305	HP 25	11,0 0.433	34,0 1.339	26,0 1.024	8,0
5672S2512	02845306	HP 25	12,0 0.472	34,0 1.339	26,0 1.024	8,0

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others


Operating &
setting acces-
sories

Shrinkfit

Guide						
	Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX	OAL	BD1
HSK-A				mm <i>inch</i>	mm <i>inch</i>	mm <i>inch</i>
	5672S2513	02845307	HP 25	13,0 0.512	34,0 1.339	26,0 1.024
	5672S2514	02845308	HP 25	14,0 0.551	34,0 1.339	26,0 1.024
HSK-E	5672S2515	02845309	HP 25	15,0 0.591	34,0 1.339	26,0 1.024
	5672S2516	02845310	HP 25	16,0 0.630	34,0 1.339	26,0 1.024
	5672S3203	02845314	HP 32	3,0 0.118	40,0 1.575	33,0 1.299
DIN	5672S3204	02845315	HP 32	4,0 0.157	40,0 1.575	33,0 1.299
	5672S3205	02845316	HP 32	5,0 0.197	40,0 1.575	33,0 1.299
	5672S3206	02845317	HP 32	6,0 0.236	40,0 1.575	33,0 1.299
BT JIS	5672S3207	02845318	HP 32	7,0 0.276	40,0 1.575	33,0 1.299
	5672S3208	02845319	HP 32	8,0 0.315	40,0 1.575	33,0 1.299
	5672S3209	02845320	HP 32	9,0 0.354	40,0 1.575	33,0 1.299
CAT	5672S3210	02845321	HP 32	10,0 0.394	40,0 1.575	33,0 1.299
	5672S3211	02845322	HP 32	11,0 0.433	40,0 1.575	33,0 1.299
	5672S3212	02845323	HP 32	12,0 0.472	40,0 1.575	33,0 1.299
Combimaster	5672S3213	02845324	HP 32	13,0 0.512	40,0 1.575	33,0 1.299
	5672S3214	02845325	HP 32	14,0 0.551	40,0 1.575	33,0 1.299
	5672S3215	02845326	HP 32	15,0 0.591	40,0 1.575	33,0 1.299
Graflex	5672S3216	02845327	HP 32	16,0 0.630	40,0 1.575	33,0 1.299
	5672S3217	02845328	HP 32	17,0 0.669	40,0 1.575	33,0 1.299
	5672S3218	02845329	HP 32	18,0 0.709	40,0 1.575	33,0 1.299
Seco Capto™	5672S3219	02845330	HP 32	19,0 0.748	40,0 1.575	33,0 1.299
	5672S3220	02845331	HP 32	20,0 0.787	40,0 1.575	33,0 1.299
Others						
Operating & setting accessories						
Shrinkfit						

Sealed
– Inch

Similar to ISO 15488-B



- Run-out 3 µm maximum at 3 x ØDCBN-DCBX when assembled on a HP collet chuck, ERHP 5672
- Nominal clamping diameter only (no clamping range): tool shank tolerance h8 maximum
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX	OAL	BD1	BHTA°
			<i>inch</i>	<i>inch</i>	<i>inch</i>	
5672S110317	02892587	HP 11	0.125	0.709	0.453	8,0
5672S110476	02892588	HP 11	0.188	0.709	0.453	8,0
5672S110635	02892589	HP 11	0.250	0.709	0.453	8,0
5672S160317	02845332	HP 16	0.125	1.083	0.669	8,0
5672S160476	02845333	HP 16	0.188	1.083	0.669	8,0
5672S160635	02845334	HP 16	0.250	1.083	0.669	8,0
5672S160793	02845335	HP 16	0.313	1.083	0.669	8,0
5672S160952	02845336	HP 16	0.375	1.083	0.669	8,0
5672S250317	02845337	HP 25	0.125	1.339	1.024	8,0
5672S250476	02845338	HP 25	0.188	1.339	1.024	8,0
5672S250635	02845339	HP 25	0.250	1.339	1.024	8,0
5672S250793	02845340	HP 25	0.313	1.339	1.024	8,0
5672S250952	02845341	HP 25	0.375	1.339	1.024	8,0
5672S25127	02845342	HP 25	0.500	1.339	1.024	8,0
5672S251587	02845343	HP 25	0.625	1.339	1.024	8,0
5672S320317	02845344	HP 32	0.125	1.575	1.299	8,0
5672S320476	02845345	HP 32	0.188	1.575	1.299	8,0
5672S320635	02845346	HP 32	0.250	1.575	1.299	8,0
5672S320793	02845347	HP 32	0.313	1.575	1.299	8,0
5672S320952	02845348	HP 32	0.375	1.575	1.299	8,0
5672S32127	02845349	HP 32	0.500	1.575	1.299	8,0
5672S321587	02845350	HP 32	0.625	1.575	1.299	8,0
5672S321905	02845351	HP 32	0.750	1.575	1.299	8,0

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
sories

Shrinkfit

With coolant supply channels towards the tool
– Metric/ Inch

Similar to ISO 15488-B




- Run-out 3 µm maximum at 3 x ØDCBN-DCBX when assembled on a HP collet chuck, ERHP 5672
- Nominal clamping diameter only (no clamping range): tool shank tolerance h8 maximum
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX		OAL	BD1	BHTA°
			mm	inch			
5672S1604L	03070197	HP 16	4,0	0.157	27,5 1.083	17,0 0.669	8,0
5672S1606L	03070198	HP 16	6,0	0.236	27,5 1.083	17,0 0.669	8,0
5672S1608L	03070199	HP 16	8,0	0.315	27,5 1.083	17,0 0.669	8,0
5672S2504L	03070200	HP 25	4,0	0.157	34,0 1.339	26,0 1.024	8,0
5672S2506L	03070201	HP 25	6,0	0.236	34,0 1.339	26,0 1.024	8,0
5672S2508L	03070202	HP 25	8,0	0.315	34,0 1.339	26,0 1.024	8,0
5672S2510L	03070203	HP 25	10,0	0.394	34,0 1.339	26,0 1.024	8,0
5672S2512L	03070204	HP 25	12,0	0.472	34,0 1.339	26,0 1.024	8,0
5672S2514L	03070205	HP 25	14,0	0.551	34,0 1.339	26,0 1.024	8,0
5672S3204L	03070206	HP 32	4,0	0.157	40,0 1.575	33,0 1.299	8,0
5672S3206L	03070207	HP 32	6,0	0.236	40,0 1.575	33,0 1.299	8,0
5672S3208L	03070208	HP 32	8,0	0.315	40,0 1.575	33,0 1.299	8,0
5672S3210L	03070209	HP 32	10,0	0.394	40,0 1.575	33,0 1.299	8,0
5672S3212L	03070210	HP 32	12,0	0.472	40,0 1.575	33,0 1.299	8,0
5672S3214L	03070211	HP 32	14,0	0.551	40,0 1.575	33,0 1.299	8,0
5672S3216L	03070212	HP 32	16,0	0.630	40,0 1.575	33,0 1.299	8,0
5672S3218L	03070213	HP 32	18,0	0.709	40,0 1.575	33,0 1.299	8,0
5672S3220L	03070214	HP 32	20,0	0.787	40,0 1.575	33,0 1.299	8,0

With coolant supply channels towards the tool
– Inch

Similar to ISO 15488-B



- Run-out 3 µm maximum at 3 x ØDCBN-DCBX when assembled on a HP collet chuck, ERHP 5672
- Nominal clamping diameter only (no clamping range): tool shank tolerance h8 maximum
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	Workpiece side Collet bore size DCBN-DCBX	OAL	BD1	BHTA°
			<i>inch</i>	<i>inch</i>	<i>inch</i>	
5672S160317L	03070215	HP 16	0.125	1.083	0.669	8,0
5672S160476L	03070216	HP 16	0.187	1.083	0.669	8,0
5672S160635L	03070217	HP 16	0.250	1.083	0.669	8,0
5672S250317L	03070219	HP 25	0.125	1.339	1.024	8,0
5672S250476L	03070220	HP 25	0.187	1.339	1.024	8,0
5672S250635L	03070221	HP 25	0.250	1.339	1.024	8,0
5672S250793L	03070222	HP 25	0.312	1.339	1.024	8,0
5672S250952L	03070223	HP 25	0.375	1.339	1.024	8,0
5672S251111L	03070225	HP 25	0.437	1.339	1.024	8,0
5672S25127L	03070226	HP 25	0.500	1.339	1.024	8,0
5672S251428L	03070227	HP 25	0.562	1.339	1.024	8,0
5672S320317L	03070228	HP 32	0.125	1.575	1.299	8,0
5672S320476L	03070229	HP 32	0.187	1.575	1.299	8,0
5672S320635L	03070230	HP 32	0.250	1.575	1.299	8,0
5672S320793L	03070231	HP 32	0.312	1.575	1.299	8,0
5672S320952L	03070232	HP 32	0.375	1.575	1.299	8,0
5672S321111L	03070233	HP 32	0.437	1.575	1.299	8,0
5672S32127L	03070234	HP 32	0.500	1.575	1.299	8,0
5672S321428L	03070235	HP 32	0.562	1.575	1.299	8,0
5672S321587L	03070236	HP 32	0.625	1.575	1.299	8,0
5672S321746L	03070237	HP 32	0.687	1.575	1.299	8,0
5672S321905L	03070238	HP 32	0.750	1.575	1.299	8,0

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories


Shrinkfit

ER HP Collets – SETS – Metric/ Inch

Guide	Description	Item number	Item number	Item number	Item number	Item number	Item number	Item number
	SET-ERHP16-06 = 1 piece of:	10358947 = 1 piece of:	SET-ERHP20-07 = 1 piece of:	10358948 = 1 piece of:	SET-ERHP25-07 = 1 piece of:	10358949 = 1 piece of:	SET-ERHP32-08 = 1 piece of:	10358950 = 1 piece of:
HSK-A	56721603	02828316	56722003	02849413	56722504	02828346	56723204	02828368
	56721604	02828318	56722004	02849415	56722506	02828350	56723206	02828370
	56721605	02828320	56722005	02849417	56722508	02828354	56723208	02828372
	56721606	02828322	56722006	02849419	56722510	02828358	56723210	02828374
	56721608	02828326	56722008	02849423	56722512	02828360	56723212	02828376
HSK-E	56721610	02828330	56722010	02849427	56722514	02828362	56723214	02828378
			56722012	02849432	56722516	02828364	56723216	02828380
							56723220	02828384
DIN	Description	Item number	Item number	Item number	Item number	Item number	Item number	Item number
	SET-ERHPS16-06 = 1 piece of:	10358951 = 1 piece of:	SET-ERHPS20-07 = 1 piece of:	10358952 = 1 piece of:	SET-ERHPS25-07 = 1 piece of:	10358953 = 1 piece of:	SET-ERHPS32-08 = 1 piece of:	10358954 = 1 piece of:
BT JIS	5672S1603	02845288	5672S2003	10358922	5672S2504	02842598	5672S3204	02845315
	5672S1604	02845289	5672S2004	10358923	5672S2506	02845300	5672S3206	02845317
	5672S1605	02845290	5672S2005	10358924	5672S2508	02845302	5672S3208	02845319
	5672S1608	02845293	5672S2006	10358925	5672S2510	02845304	5672S3210	02845321
	5672S1609	02845294	5672S2008	10299857	5672S2512	02845306	5672S3212	02845323
CAT	5672S1610	02845295	5672S2010	10299859	5672S2514	02845308	5672S3214	02845325
			5672S2012	10299861	5672S2516	02845310	5672S3216	02845327
							5672S3220	02845331
Combimaster	Description	Item number	Item number	Item number	Item number	Item number	Item number	Item number
	SET-ERHP16-05-I = 1 piece of:	10358955 = 1 piece of:	SET-ERHP20-06-I = 1 piece of:	10358976 = 1 piece of:	SET-ERHP25-08-I = 1 piece of:	10358977 = 1 piece of:	SET-ERHP32-08A-I = 1 piece of:	10358978 = 1 piece of:
Graflex	5672160317	02828385	5672200317	10155969	5672250317	02828429	5672320317	02828448
	5672160476	02828386	5672200476	10359007	5672250476	02828434	5672320635	02828452
	5672160635	02828417	5672200635	10359008	5672250635	02828435	5672320793	10359016
	5672160793	10359005	5672200952	10359010	5672250793	02828436	5672320952	02828453
	5672160952	02828428	5672201111	10359011	5672250952	02828446	567232127	02828388
Seco Capto™			567220127	10358921	567225127	02828387	5672321428	10349492
					5672251428	10359013	5672321587	02828455
					5672251587	10359014	5672321905	02828456
Others	Description	Item number	Item number	Item number	Item number	Item number	Item number	Item number
	SET-ERHPS16-05-I = 1 piece of:	10358956 = 1 piece of:	SET-ERHPS20-06-I = 1 piece of:	10358957 = 1 piece of:	SET-ERHPS25-08-I = 1 piece of:	10358958 = 1 piece of:	SET-ERHPS32-08A-I = 1 piece of:	10358959 = 1 piece of:
Shrinkfit	5672S160317	02845332	5672S200317	10358927	5672S250317	02845337	5672S320476	02845345
	5672S160476	02845333	5672S200476	10358928	5672S250476	02845338	5672S320635	02845346
	5672S160635	02845334	5672S200635	10358929	5672S250635	02845339	5672S320793	05845347
	5672S160793	02845335	5672S200793	10358930	5672S250793	02845340	5672S320952	02845348
	5672S160952	02845336	5672S200952	10358931	5672S250952	02845341	5672S32127	02845349
Operating & setting accessories			5672S20127	10358933	5672S25127	02845342	5672S321428	03078105
					5672S251428	03078095	5672S321587	02845350
					5672S251587	02845343	5672S321905	02845351



– Metric/ Inch



- Run-out 15 µm maximum at 3 x ØDCBN-DCBX when assembled on an ER collet chuck
- Clamping range -0,5 or -1 mm
- Sets of collets in different sizes can be ordered, see page 403
- Wooden box for storage and protection can be ordered, see page 403
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	DCBN	DCBX	OAL	BD1	BHTA°
			mm inch	mm inch	mm inch	mm inch	
58800801	75042144	ER 08	0,5 0.020	1,0 0.039	13,5 0.531	8,5 0.335	8,0
588008015	75042145	ER 08	1,0 0.039	1,5 0.059	13,5 0.531	8,5 0.335	8,0
58800802	75042146	ER 08	1,5 0.059	2,0 0.079	13,5 0.531	8,5 0.335	8,0
588008025	75042147	ER 08	2,0 0.079	2,5 0.098	13,5 0.531	8,5 0.335	8,0
58800803	75042148	ER 08	2,5 0.098	3,0 0.118	13,5 0.531	8,5 0.335	8,0
588008035	75042149	ER 08	3,0 0.118	3,5 0.138	13,5 0.531	8,5 0.335	8,0
58800804	75042151	ER 08	3,5 0.138	4,0 0.157	13,5 0.531	8,5 0.335	8,0
588008045	75042152	ER 08	4,0 0.157	4,5 0.177	13,5 0.531	8,5 0.335	8,0
58800805	75042153	ER 08	4,5 0.177	5,0 0.197	13,5 0.531	8,5 0.335	8,0
58801101	75042154	ER 11	0,5 0.020	1,0 0.039	18,0 0.709	11,3 0.445	8,0
588011015	75042155	ER 11	1,0 0.039	1,5 0.059	18,0 0.709	11,3 0.445	8,0
58801102	75042156	ER 11	1,5 0.059	2,0 0.079	18,0 0.709	11,3 0.445	8,0
588011025	75042157	ER 11	2,0 0.079	2,5 0.098	18,0 0.709	11,3 0.445	8,0
58801103	75042158	ER 11	2,5 0.098	3,0 0.118	18,0 0.709	11,3 0.445	8,0
588011035	75042159	ER 11	3,0 0.118	3,5 0.138	18,0 0.709	11,3 0.445	8,0
58801104	75042161	ER 11	3,5 0.138	4,0 0.157	18,0 0.709	11,3 0.445	8,0
588011045	75042163	ER 11	4,0 0.157	4,5 0.177	18,0 0.709	11,3 0.445	8,0
58801105	75042164	ER 11	4,5 0.177	5,0 0.197	18,0 0.709	11,3 0.445	8,0
588011055	75042165	ER 11	5,0 0.197	5,5 0.217	18,0 0.709	11,3 0.445	8,0
58801106	75042166	ER 11	5,5 0.217	6,0 0.236	18,0 0.709	11,3 0.445	8,0
588011065	75042167	ER 11	6,0 0.236	6,5 0.256	18,0 0.709	11,3 0.445	8,0

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating & setting accessories

Shrinkfit

Guide								
	Designation	Item number	Machine side Chuck size	DCBN	DCBX	OAL	BD1	BHTA°
HSK-A				mm inch	mm inch	mm inch	mm inch	
	58801107	75042168	ER 11	6,5 0.256	7,0 0.276	18,0 0.709	11,3 0.445	8,0
	58801601	75042062	ER 16	0,5 0.020	1,0 0.039	27,0 1.063	17,0 0.669	8,0
HSK-E	58801602	75042064	ER 16	1,5 0.059	2,0 0.079	27,0 1.063	17,0 0.669	8,0
	58801603	75042065	ER 16	2,0 0.079	3,0 0.118	27,0 1.063	17,0 0.669	8,0
	58801604	75042066	ER 16	3,0 0.118	4,0 0.157	27,0 1.063	17,0 0.669	8,0
DIN	58801605	75042067	ER 16	4,0 0.157	5,0 0.197	27,0 1.063	17,0 0.669	8,0
	58801606	75042068	ER 16	5,0 0.197	6,0 0.236	27,0 1.063	17,0 0.669	8,0
	58801607	75042073	ER 16	6,0 0.236	7,0 0.276	27,0 1.063	17,0 0.669	8,0
BT JIS	58801608	75042074	ER 16	7,0 0.276	8,0 0.315	27,0 1.063	17,0 0.669	8,0
	58801609	75042075	ER 16	8,0 0.315	9,0 0.354	27,0 1.063	17,0 0.669	8,0
	58801610	75042076	ER 16	9,0 0.354	10,0 0.394	27,0 1.063	17,0 0.669	8,0
CAT	58802001	02504419	ER 20	0,5 0.020	1,0 0.039	31,5 1.240	21,0 0.827	8,0
	58802002	02436302	ER 20	1,5 0.059	2,0 0.079	31,5 1.240	21,0 0.827	8,0
	58802003	02428799	ER 20	2,0 0.079	3,0 0.118	31,5 1.240	21,0 0.827	8,0
Combimaster	58802004	02428800	ER 20	3,0 0.118	4,0 0.157	31,5 1.240	21,0 0.827	8,0
	58802005	02428801	ER 20	5,0 0.197	5,0 0.197	31,5 1.240	21,0 0.827	8,0
	58802006	02428802	ER 20	5,0 0.197	6,0 0.236	31,5 1.240	21,0 0.827	8,0
Graflex	58802007	14000856	ER 20	6,0 0.236	7,0 0.276	31,5 1.240	21,0 0.827	8,0
	58802008	02434262	ER 20	7,0 0.276	8,0 0.315	31,5 1.240	21,0 0.827	8,0
	58802009	14000857	ER 20	8,0 0.315	9,0 0.354	31,5 1.240	21,0 0.827	8,0
Seco Capto™	58802010	02433824	ER 20	9,0 0.354	10,0 0.394	31,5 1.240	21,0 0.827	8,0
	58802011	14000380	ER 20	10,0 0.394	11,0 0.433	31,5 1.240	21,0 0.827	8,0
	58802012	14000381	ER 20	11,0 0.433	12,0 0.472	31,5 1.240	21,0 0.827	8,0
Others	58802013	14000382	ER 20	12,0 0.472	13,0 0.512	31,5 1.240	21,0 0.827	8,0
	58802502	75042081	ER 25	1,5 0.059	2,0 0.079	34,0 1.339	25,8 1.016	8,0
	58802503	75042083	ER 25	2,0 0.079	3,0 0.118	34,0 1.339	25,8 1.016	8,0
Operating & setting accessories	58802504	75042084	ER 25	3,0 0.118	4,0 0.157	34,0 1.339	25,8 1.016	8,0
	58802505	75042085	ER 25	4,0 0.157	5,0 0.197	34,0 1.339	25,8 1.016	8,0
	58802506	75042086	ER 25	5,0 0.197	6,0 0.236	34,0 1.339	25,8 1.016	8,0
Shrinkfit	58802507	75042087	ER 25	6,0 0.236	7,0 0.276	34,0 1.339	25,8 1.016	8,0
	58802508	75042088	ER 25	7,0 0.276	8,0 0.315	34,0 1.339	25,8 1.016	8,0
	58802509	75042089	ER 25	8,0 0.315	9,0 0.354	34,0 1.339	25,8 1.016	8,0
	58802510	75042090	ER 25	9,0 0.354	10,0 0.394	34,0 1.339	25,8 1.016	8,0

Designation	Item number	Machine side Chuck size	DCBN	DCBX	OAL	BD1	BHTA°	Guide
			mm inch	mm inch	mm inch	mm inch		
58802511	75042091	ER 25	10,0 0.394	11,0 0.433	34,0 1.339	25,8 1.016	8,0	HSK-A
58802512	75042094	ER 25	11,0 0.433	12,0 0.472	34,0 1.339	25,8 1.016	8,0	
58802513	75042095	ER 25	12,0 0.472	13,0 0.512	34,0 1.339	25,8 1.016	8,0	
58802514	75042097	ER 25	13,0 0.512	14,0 0.551	34,0 1.339	25,8 1.016	8,0	HSK-E
58802515	75042098	ER 25	14,0 0.551	15,0 0.591	34,0 1.339	25,8 1.016	8,0	
58802516	75042099	ER 25	15,0 0.591	16,0 0.630	34,0 1.339	25,8 1.016	8,0	
58803204	75041875	ER 32	3,0 0.118	4,0 0.157	40,0 1.575	33,0 1.299	8,0	DIN
58803205	75041876	ER 32	4,0 0.157	5,0 0.197	40,0 1.575	33,0 1.299	8,0	
58803206	75041886	ER 32	5,0 0.197	6,0 0.236	40,0 1.575	33,0 1.299	8,0	
58803207	75041888	ER 32	6,0 0.236	7,0 0.276	40,0 1.575	33,0 1.299	8,0	BT JIS
58803208	75041890	ER 32	7,0 0.276	8,0 0.315	40,0 1.575	33,0 1.299	8,0	
58803209	75041891	ER 32	8,0 0.315	9,0 0.354	40,0 1.575	33,0 1.299	8,0	
58803210	75041892	ER 32	9,0 0.354	10,0 0.394	40,0 1.575	33,0 1.299	8,0	CAT
58803211	75041894	ER 32	10,0 0.394	11,0 0.433	40,0 1.575	33,0 1.299	8,0	
58803212	75041895	ER 32	11,0 0.433	12,0 0.472	40,0 1.575	33,0 1.299	8,0	
58803213	75041896	ER 32	12,0 0.472	13,0 0.512	40,0 1.575	33,0 1.299	8,0	Combimaster
58803214	75041925	ER 32	13,0 0.512	14,0 0.551	40,0 1.575	33,0 1.299	8,0	
58803215	75042101	ER 32	14,0 0.551	15,0 0.591	40,0 1.575	33,0 1.299	8,0	
58803216	75041927	ER 32	15,0 0.591	16,0 0.630	40,0 1.575	33,0 1.299	8,0	Graflex
58803217	75042102	ER 32	16,0 0.630	17,0 0.669	40,0 1.575	33,0 1.299	8,0	
58803218	75042103	ER 32	17,0 0.669	18,0 0.709	40,0 1.575	33,0 1.299	8,0	
58803219	75042104	ER 32	18,0 0.709	19,0 0.748	40,0 1.575	33,0 1.299	8,0	Seco Capto™
58803220	75041940	ER 32	19,0 0.748	20,0 0.787	40,0 1.575	33,0 1.299	8,0	
58804004	75042105	ER 40	3,0 0.118	4,0 0.157	46,0 1.811	41,0 1.614	8,0	Others
58804005	75042106	ER 40	4,0 0.157	5,0 0.197	46,0 1.811	41,0 1.614	8,0	
58804006	75042109	ER 40	5,0 0.197	6,0 0.236	46,0 1.811	41,0 1.614	8,0	
58804007	75042112	ER 40	6,0 0.236	7,0 0.276	46,0 1.811	41,0 1.614	8,0	
58804008	75042113	ER 40	7,0 0.276	8,0 0.315	46,0 1.811	41,0 1.614	8,0	
58804009	75042114	ER 40	8,0 0.315	9,0 0.354	46,0 1.811	41,0 1.614	8,0	Operating & setting accessories
58804010	75042115	ER 40	9,0 0.354	10,0 0.394	46,0 1.811	41,0 1.614	8,0	
58804011	75042118	ER 40	10,0 0.394	11,0 0.433	46,0 1.811	41,0 1.614	8,0	
58804012	75042119	ER 40	11,0 0.433	12,0 0.472	46,0 1.811	41,0 1.614	8,0	Shrinkfit
58804013	75042121	ER 40	12,0 0.472	13,0 0.512	46,0 1.811	41,0 1.614	8,0	

Guide								
	Designation	Item number	Machine side Chuck size	DCBN mm inch	DCBX mm inch	OAL mm inch	BD1 mm inch	BHTA°
HSK-A	58804014	75042122	ER 40	13,0 0.512	14,0 0.551	46,0 1.811	41,0 1.614	8,0
	58804015	75042123	ER 40	14,0 0.551	15,0 0.591	46,0 1.811	41,0 1.614	8,0
	58804016	75042124	ER 40	15,0 0.591	16,0 0.630	46,0 1.811	41,0 1.614	8,0
HSK-E	58804017	75042125	ER 40	16,0 0.630	17,0 0.669	46,0 1.811	41,0 1.614	8,0
	58804018	75042126	ER 40	17,0 0.669	18,0 0.709	46,0 1.811	41,0 1.614	8,0
	58804019	75042127	ER 40	18,0 0.709	19,0 0.748	46,0 1.811	41,0 1.614	8,0
DIN	58804020	75042128	ER 40	19,0 0.748	20,0 0.787	46,0 1.811	41,0 1.614	8,0
	58804021	75042129	ER 40	20,0 0.787	21,0 0.827	46,0 1.811	41,0 1.614	8,0
	58804022	75042130	ER 40	21,0 0.827	22,0 0.866	46,0 1.811	41,0 1.614	8,0
BT JIS	58804023	75042131	ER 40	22,0 0.866	23,0 0.906	46,0 1.811	41,0 1.614	8,0
	58804024	75042132	ER 40	23,0 0.906	24,0 0.945	46,0 1.811	41,0 1.614	8,0
	58804025	75042133	ER 40	24,0 0.945	25,0 0.984	46,0 1.811	41,0 1.614	8,0
CAT	58804026	00042134	ER 40	25,0 0.984	26,0 1.024	46,0 1.811	41,0 1.614	8,0
Combimaster								
Graflex								
Seco Capto™								
Others								
Operating & setting accessories								
Shrinkfit								

ER Collets – SETS – Metric/ Inch

Description	Item number	Description	Item number	Description	Item number	Description	Item number
SET-5880-08-09 = 1 piece of:	10329292 = 1 piece of:	SET-5880-11-13 = 1 piece of:	10329293 = 1 piece of:	SET-5880-16-10 = 1 piece of:	10329294 = 1 piece of:	SET-5880-20-12 = 1 piece of:	10329295 = 1 piece of:
58800801	75042144	58801101	7502154	58801601	75042062	58802002	02436302
588008015	75042145	588011015	7502155	58801602	75042064	58802003	02428799
58800802	75042146	58801102	7502156	58801603	75042065	58802004	02428800
588008025	75042147	588011025	7502157	58801604	75042066	58802005	02488801
58800803	75042148	58801103	7502158	58801605	75042067	58802006	02488802
588008035	75042149	588011035	7502159	58801606	75042068	58802007	14000856
58800804	75042151	58801104	7502161	58801607	75042073	58802008	02434262
588008045	75042152	588011045	7502163	58801608	75042074	58802009	14000857
58800805	75042153	58801105	7502164	58801609	75042075	58802010	02433824
		588011055	7502165	58801610	75042076	58802011	14000380
		58801106	7502166			58802012	14000381
		588011065	7502167			58802013	14000382
		58801107	7502168				

Description	Item number	Description	Item number	Description	Item number
SET-5880-25-15 = 1 piece of:	10329296 = 1 piece of:	SET-5880-32-18 = 1 piece of:	10329297 = 1 piece of:	SET-5880-40-23 = 1 piece of:	10329298 = 1 piece of:
58802502	75042081	58803203	75041874	58804004	75042105
58802503	75042083	58803204	75041875	58804005	75042106
58802504	75042084	58803205	75041876	58804006	75042109
58802505	75042085	58803206	75041886	58804007	75042112
58802506	75042086	58803207	75041888	58804008	75042113
58802507	75042087	58803208	75041890	58804009	75042114
58802508	75042088	58803209	75041891	58804010	75042115
58802509	75042089	58803210	75041892	58804011	75042118
58802510	75042090	58803211	75041894	58804012	75042119
58802511	75042091	58803212	75041895	58804013	75042121
58802512	75042094	58803213	75041896	58804014	75042122
58802513	75042095	58803214	75041925	58804015	75042123
58802514	75042097	58803215	75042101	58804016	75042124
58802515	75042098	58803216	75041927	58804017	75042125
58802516	75042099	58803217	75042102	58804018	75042126
		58803218	75042103	58804019	75042127
		58803219	75042104	58804020	75042128
		58803220	75041940	58804021	75042129
				58804022	75042130
				58804023	75042131
				58804024	75042132
				58804025	75042133
				58804026	00042134

Wooden box for storage and protection – can be ordered as an accessory

	Description	Item number
	41BOX-ER11-13	10329304
	41BOX-ER16-10	10329305
	41BOX-ER20-12	10329306
	41BOX-ER25-15	10329307
	41BOX-ER32-18	10329308
	41BOX-ER40-23	10329309
	41BOX-ER08-09	10329310

Guide

HSK-A

HSK-E

DIN

BT IIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

– Inch



- Run-out 15 µm maximum at 3 x ØDCBN-DCBX when assembled on an ER collet chuck
- Clamping range –0,5 or –1 mm
- Sets of collets in different sizes can be ordered, see page 406
- Wooden box for storage and protection can be ordered, see page 406
- For ISO attribute explanation, see page 15

	Designation	Item number	Machine side Chuck size	DCBN	DCBX	OAL	BD1	BHTA°
				<i>inch</i>	<i>inch</i>	<i>inch</i>	<i>inch</i>	
CAT	5880110317	10329241	ER 11	0.106	0.125	0.709	0.445	8,0
	5880110476	10329242	ER 11	0.168	0.187	0.709	0.445	8,0
	5880110635	10329243	ER 11	0.230	0.250	0.709	0.445	8,0
Combimaster	5880160158	10329244	ER 16	0.043	0.063	1.083	0.669	8,0
	5880160238	10329245	ER 16	0.074	0.094	1.083	0.669	8,0
	5880160317	10329246	ER 16	0.086	0.125	1.083	0.669	8,0
	5880160397	10329247	ER 16	0.117	0.156	1.083	0.669	8,0
	5880160476	10329248	ER 16	0.148	0.187	1.083	0.669	8,0
Graflex	5880160556	10329249	ER 16	0.180	0.219	1.083	0.669	8,0
	5880160635	10329250	ER 16	0.211	0.250	1.083	0.669	8,0
	5880160714	10329251	ER 16	0.242	0.281	1.083	0.669	8,0
	5880160793	10329252	ER 16	0.273	0.313	1.083	0.669	8,0
	5880160873	10329253	ER 16	0.304	0.344	1.083	0.669	8,0
Seco Capto™	5880160952	10329254	ER 16	0.336	0.375	1.083	0.669	8,0
	5880161032	10329255	ER 16	0.367	0.406	1.083	0.669	8,0
	5880200317	10329256	ER 20	0.086	0.125	1.240	0.827	8,0
	5880200476	10329257	ER 20	0.148	0.187	1.240	0.827	8,0
	5880200635	10329258	ER 20	0.211	0.250	1.240	0.827	8,0
Others	5880200793	10329259	ER 20	0.273	0.313	1.240	0.827	8,0
	5880200952	10329260	ER 20	0.336	0.375	1.240	0.827	8,0
	5880201111	10329261	ER 20	0.398	0.437	1.240	0.827	8,0
	5880201270	10329262	ER 20	0.461	0.500	1.240	0.827	8,0
	5880250317	10329263	ER 25	0.086	0.125	1.339	1.024	8,0
Operating & setting accessories	5880250476	10329264	ER 25	0.148	0.187	1.339	1.024	8,0
	5880250635	10329265	ER 25	0.211	0.250	1.339	1.024	8,0
	5880250793	10329266	ER 25	0.273	0.313	1.339	1.024	8,0
	5880250952	10329267	ER 25	0.336	0.375	1.339	1.024	8,0
	5880251111	10329268	ER 25	0.398	0.437	1.339	1.024	8,0
Shrinkfit	5880251270	10329269	ER 25	0.461	0.500	1.339	1.024	8,0
	5880251429	10329270	ER 25	0.523	0.563	1.339	1.024	8,0
	5880251587	10329271	ER 25	0.586	0.625	1.339	1.024	8,0
	5880320317	10329272	ER 32	0.086	0.125	1.575	1.299	8,0

Designation	Item number	Machine side Chuck size	DCBN	DCBX	OAL	BD1	BHTA°
			<i>inch</i>	<i>inch</i>	<i>inch</i>	<i>inch</i>	
5880320476	10329273	ER 32	0.148	0.187	1.575	1.299	8,0
5880320635	10329274	ER 32	0.211	0.250	1.575	1.299	8,0
5880320793	10329275	ER 32	0.273	0.313	1.575	1.299	8,0
5880320952	10329276	ER 32	0.336	0.375	1.575	1.299	8,0
5880321111	10329277	ER 32	0.398	0.437	1.575	1.299	8,0
5880321270	10329278	ER 32	0.461	0.500	1.575	1.299	8,0
5880321428	10329279	ER 32	0.523	0.563	1.575	1.299	8,0
5880321587	10329280	ER 32	0.586	0.625	1.575	1.299	8,0
5880321746	10329281	ER 32	0.648	0.687	1.575	1.299	8,0
5880321905	10329282	ER 32	0.711	0.750	1.575	1.299	8,0
5880322063	10329283	ER 32	0.773	0.813	1.575	1.299	8,0
5880400317	10329284	ER 40	0.086	0.125	1.811	1.614	8,0
5880400635	10329285	ER 40	0.211	0.250	1.811	1.614	8,0
5880400952	10329286	ER 40	0.336	0.375	1.811	1.614	8,0
5880401270	10329287	ER 40	0.461	0.500	1.811	1.614	8,0
5880401587	10329288	ER 40	0.586	0.625	1.811	1.614	8,0
5880401905	10329289	ER 40	0.711	0.750	1.811	1.614	8,0
5880402222	10329290	ER 40	0.836	0.875	1.811	1.614	8,0
5880402540	10329291	ER 40	0.961	1.000	1.811	1.614	8,0

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
sories

Shrinkfit

ER Collets – SETS – Inch


Description	Item number	Description	Item number	Description	Item number
SET-5880-16-12-I = 1 piece of:	10329299 = 1 piece of:	SET-5880-20-7-I = 1 piece of:	10329300 = 1 piece of:	SET-5880-25-9-I = 1 piece of:	103292301 = 1 piece of:
5880160158	10329244	5880200317	10329256	5880250317	10329263
5880160238	10329245	5880200476	10329257	5880250476	10329264
5880160317	10329246	5880200635	10329258	5880250635	10329265
5880160397	10329247	5880200793	10329259	5880250793	10329266
5880160476	10329248	5880200952	10329260	5880250952	10329267
5880160556	10329249	5880201111	10329261	5880251111	10329268
5880160635	10329250	5880201270	10329262	5880251270	10329269
5880160714	10329251			5880251429	10329270
5880160793	10329252			5880251587	10329271
5880160873	10329253				
5880160952	10329254				
5880161032	10329255				

Description	Item number	Description	Item number
SET-5880-32-12-I = 1 piece of:	10329302 = 1 piece of:	SET-5880-40-08-I = 1 piece of:	10329303 = 1 piece of:
5880320317	10329272	5880400317	10329284
5880320476	10329273	5880400635	10329285
5880320635	10329274	5880400952	10329286
5880320793	10329275	5880401270	10329287
5880320952	10329276	5880401587	10329288
5880321111	10329277	5880401905	10329289
5880321270	10329278	5880402222	10329290
5880321428	10329279	5880402540	10329291
5880321587	10329280		
5880321746	10329281		
5880321905	10329282		
5880322063	10329283		

Wooden box for storage and protection – can be ordered as an accessory

Graflex		Description	Item number
		41BOX-ER11-13	10329304
		41BOX-ER16-10	10329305
		41BOX-ER20-12	10329306
		41BOX-ER25-15	10329307
		41BOX-ER32-18	10329308
		41BOX-ER40-23	10329309
		41BOX-ER08-09	10329310

– Metric/ Inch



- For TCER 5867 tapping chucks
- * Without square in the collet (use square inside the TCER tapping holder)
- For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	DCBN-DCBX	OAL	LB	BD1	KWW	*	BHTA°
			mm inch	mm inch	mm inch	mm inch	mm inch		
393.14-11D025X021	03131636	ER 11	2,5 0.098	18,0 0.709	12,0 0.472	11,3 0.445	2,1 0.083		8,0
393.14-11D028X021	02926995	ER 11	2,8 0.110	18,0 0.709	12,0 0.472	11,3 0.445	2,1 0.083		8,0
393.14-11D035X027	02926996	ER 11	3,5 0.138	18,0 0.709	14,0 0.551	11,3 0.445	2,7 0.106		8,0
393.14-11D040X030	02926997	ER 11	4,0 0.157	18,0 0.709	14,0 0.551	11,3 0.445	3,0 0.118		8,0
393.14-11D040X0315	03131670	ER 11	4,0 0.157	18,0 0.709	14,0 0.551	11,3 0.445	3,1 0.122		8,0
393.14-11D045X034	02926998	ER 11	4,5 0.177	18,0 0.709	14,0 0.551	11,3 0.445	3,4 0.134		8,0
393.14-11D050X040	03131671	ER 11	5,0 0.197	18,0 0.709	14,0 0.551	11,3 0.445	4,0 0.157		8,0
393.14-11D060X049	02926999	ER 11	6,0 0.236	18,0 0.709	14,0 0.551	11,3 0.445	4,9 0.193		8,0
393.14-20D035X027	03131672	ER 20	3,5 0.138	31,5 1.240	14,0 0.551	20,8 0.819	2,7 0.106		8,0
393.14-20D040X0315	03131673	ER 20	4,0 0.157	31,5 1.240	15,0 0.591	20,8 0.819	3,15 0.124		8,0
393.14-20D045X034	02927000	ER 20	4,5 0.177	31,5 1.240	18,0 0.709	20,8 0.819	3,4 0.134		8,0
393.14-20D050X040	03131674	ER 20	5,0 0.197	31,5 1.240	18,0 0.709	20,8 0.819	4,0 0.157		8,0
393.14-20D055X043	03131675	ER 20	5,5 0.217	31,5 1.240	18,0 0.709	20,8 0.819	4,3 0.169		8,0
393.14-20D060X049	02927001	ER 20	6,0 0.236	31,5 1.240	18,0 0.709	20,8 0.819	4,9 0.193		8,0
393.14-20D063X050	03131676	ER 20	6,3 0.248	31,5 1.240	18,0 0.709	20,8 0.819	5,0 0.197		8,0
393.14-20D070X055	02927002	ER 20	7,0 0.276	31,5 1.240	18,0 0.709	20,8 0.819	5,5 0.217		8,0
393.14-20D071X056	03131677	ER 20	7,1 0.280	31,5 1.240	18,0 0.709	20,8 0.819	5,6 0.220		8,0
393.14-20D080X063	02927003	ER 20	8,0 0.315	31,5 1.240	22,0 0.866	20,8 0.819	6,3 0.248		8,0
393.14-20D090X071	02927004	ER 20	9,0 0.354	31,5 1.240	22,0 0.866	20,8 0.819	7,1 0.280		8,0
393.14-20D100X080	02927005	ER 20	10,0 0.394	31,5 1.240	25,0 0.984	20,8 0.819	8,0 0.315		8,0
393.14-25D060X049	03131691	ER 25	6,0 0.236	34,0 1.339	18,0 0.709	25,8 1.016	4,9 0.193		8,0
393.14-25D070X055	03131692	ER 25	7,0 0.276	34,0 1.339	18,0 0.709	25,8 1.016	5,5 0.217		8,0

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating & setting accessories

Shrinkfit

Guide	Designation	Item number	Machine side Chuck size	DCBN-DCBX	OAL	LB	BD1	KWW	*	BHTA°
				mm inch	mm inch	mm inch	mm inch	mm inch		
HSK-A	393.14-25D080X063	02927006	ER 25	8,0 0.315	34,0 1.339	22,0 0.866	25,8 1.016	6,3 0.248		8,0
	393.14-25D090X071	02728005	ER 25	9,0 0.354	34,0 1.339	22,0 0.866	25,8 1.016	7,1 0.280		8,0
	393.14-25D100X080	02927007	ER 25	10,0 0.394	34,0 1.339	25,0 0.984	25,8 1.016	8,0 0.315		8,0
HSK-E	393.14-25D110X090	02927008	ER 25	11,0 0.433	34,0 1.339	25,0 0.984	25,8 1.016	9,0 0.354		8,0
	393.14-25D112X090	03131693	ER 25	11,2 0.441	34,0 1.339	24,8 0.976	25,8 1.016	9,0 0.354		8,0
	393.14-25D120X090	02927009	ER 25	12,0 0.472	34,0 1.339	25,0 0.984	25,8 1.016	9,0 0.354		8,0
DIN	393.14-25D125X100	03131694	ER 25	12,5 0.492	34,0 1.339	24,8 0.976	25,8 1.016	10,0 0.394		8,0
	393.14-25D140X112	02927010	ER 25	14,0 0.551	34,0 1.339	25,0 0.984	25,8 1.016	11,2 0.441		8,0
	393.14-25D160X120	02927011	ER 25	16,0 0.630	34,0 1.339	25,0 0.984	25,8 1.016	12,0 0.472		8,0
BT JIS	393.14-40D120X090	02927012	ER 40	12,0 0.472	46,0 1.811	25,0 0.984	41,0 1.614	9,0 0.354		8,0
	393.14-40D125X100	03131695	ER 40	12,5 0.492	46,0 1.811	24,8 0.976	41,0 1.614	10,0 0.394		8,0
	393.14-40D140X112	02927013	ER 40	14,0 0.551	46,0 1.811	25,0 0.984	41,0 1.614	11,2 0.441		8,0
CAT	393.14-40D160X125	02927015	ER 40	16,0 0.630	46,0 1.811	25,0 0.984	41,0 1.614	12,5 0.492		8,0
	393.14-40D180X145	02927016	ER 40	18,0 0.709	46,0 1.811	25,0 0.984	41,0 1.614	14,5 0.571		8,0
	393.14-40D200X160	02927017	ER 40	20,0 0.787	46,0 1.811	28,0 1.102	41,0 1.614	16,0 0.630		8,0
Combimaster	393.14-40D220X180	02927018	ER 40	22,0 0.866	46,0 1.811	28,0 1.102	41,0 1.614	18,0 0.709		8,0
	393.14-50D220X180	03131696	ER 50	22,0 0.866	60,0 2.362	41,0 1.614	50,0 1.969	18,0 0.709		8,0
	393.14-50D250X200	03131697	ER 50	25,0 0.984	60,0 2.362	41,0 1.614	50,0 1.969	20,0 0.787		8,0
Graflex	393.14-50D280X220	03131698	ER 50	28,0 1.102	60,0 2.362	41,0 1.614	50,0 1.969	22,0 0.866		8,0
	393.14-50D320X240	03131699	ER 50	32,0 1.260	60,0 2.362	41,0 1.614	50,0 1.969	24,0 0.945		8,0
	393.14-50360	03131700	ER 50	36,0 1.417	60,0 2.362	41,0 1.614	50,0 1.969	–	*	8,0
Seco Capto™										
Others										
Operating & setting accessories										
Shrinkfit										

– Inch



–For TCER 5867 tapping chucks

–For ISO attribute explanation, see page 15

Designation	Item number	Machine side Chuck size	DCBN-DCBX	OAL	LB	BD1	KWW	BHTA°
			inch	inch	inch	inch	inch	
A393.14-11-0-6NO	03131719	ER 11	0.141	0.709	0.551	0.445	0.110	8,0
A393.14-11-8NO	03131720	ER 11	0.168	0.709	0.551	0.445	0.131	8,0
A393.14-11-10NO	03131721	ER 11	0.194	0.709	0.551	0.445	0.152	8,0
A393.14-20-8NO	03131722	ER 20	0.168	1.240	0.709	0.819	0.131	8,0
A393.14-20-10NO	03131723	ER 20	0.194	1.240	0.701	0.819	0.152	8,0
A393.14-20-12NO	03131724	ER 20	0.220	1.240	0.701	0.819	0.165	8,0
A393.14-20-1/4	03131725	ER 20	0.255	1.240	0.701	0.819	0.191	8,0
A393.14-20-5/16	03131726	ER 20	0.318	1.240	0.858	0.819	0.238	8,0
A393.14-20-7/16	03131727	ER 20	0.323	1.240	0.858	0.819	0.242	8,0
A393.14-20-1/2	03131728	ER 20	0.367	1.240	0.866	0.819	0.275	8,0
A393.14-20-3/8	03131733	ER 20	0.381	1.240	0.858	0.819	0.286	8,0
A393.14-25-1/4	03131738	ER 25	0.255	1.339	0.701	1.016	0.191	8,0
A393.14-25-5/16	03131739	ER 25	0.318	1.339	0.858	1.016	0.238	8,0
A393.14-25-7/16	03131741	ER 25	0.323	1.339	0.858	1.016	0.242	8,0
A393.14-25-1/2	03131742	ER 25	0.367	1.339	0.858	1.016	0.275	8,0
A393.14-25-3/8	03131743	ER 25	0.381	1.339	0.858	1.016	0.286	8,0
A393.14-25-9/16	03131744	ER 25	0.429	1.339	0.976	1.016	0.322	8,0
A393.14-25-1/8P	03131745	ER 25	0.437	1.339	0.976	1.016	0.328	8,0
A393.14-25-5/8	03131746	ER 25	0.480	1.339	0.976	1.016	0.360	8,0
A393.14-25-3/4	03131747	ER 25	0.590	1.339	0.976	1.016	0.442	8,0
A393.14-40-5/8	03131748	ER 40	0.480	1.811	0.976	1.614	0.360	8,0
A393.14-40-1/2P	03131749	ER 40	0.687	1.811	0.976	1.614	0.515	8,0
A393.14-40-M18	03131750	ER 40	0.542	1.811	0.976	1.614	0.406	8,0
A393.14-40-1/8P	03131751	ER 40	0.562	1.811	0.976	1.614	0.421	8,0
A393.14-40-3/4	03131752	ER 40	0.590	1.811	0.976	1.614	0.442	8,0
A393.14-40-M20	03131753	ER 40	0.652	1.811	0.976	1.614	0.489	8,0
A393.14-40-7/8	03131754	ER 40	0.697	1.811	0.976	1.614	0.523	8,0
A393.14-40-3/8P	03131755	ER 40	0.700	1.811	0.976	1.614	0.531	8,0
A393.14-40-M24	03131756	ER 40	0.760	1.811	1.094	1.614	0.570	8,0
A393.14-40-1	03131757	ER 40	0.800	1.811	1.094	1.614	0.600	8,0

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex


Seco Capto™

Others

Operating & setting accessories

Shrinkfit

– Metric/ Inch



–For fitting into ER sealing nuts, for TCER 5867 Tapping chucks and ER 5675 ER Collet chucks
 –For sealing nuts, see Accessories in ER collet chucks or Tapping chucks pages
 –ER40 and ER50 on request, ER08 and ER11 not available
 –For ISO attribute explanation, see page 15

Designation	Item number	For sealing nut size	DCBN	DCBX	BD
			mm inch	mm inch	mm inch
01B58751605	00029961	ER 16	4,5 0.177	5,0 0.197	13,0 0.512
01B58751606	00030314	ER 16	5,5 0.217	6,0 0.236	13,0 0.512
01B58751607	00029963	ER 16	6,5 0.256	7,0 0.276	13,0 0.512
01B58751608	00030315	ER 16	7,5 0.295	8,0 0.315	13,0 0.512
01B58751609	00029967	ER 16	8,5 0.335	9,0 0.354	13,0 0.512
01B58751610	00029968	ER 16	9,5 0.374	10,0 0.394	13,0 0.512
01B587520045	03131184	ER 20	4,0 0.157	4,5 0.177	16,0 0.630
01B58752005	03131182	ER 20	4,5 0.177	5,0 0.197	16,0 0.630
01B58752006	02427909	ER 20	5,5 0.217	6,0 0.236	16,0 0.630
01B58752007	02451138	ER 20	6,5 0.256	7,0 0.276	16,0 0.630
01B587520075	03131185	ER 20	7,0 0.276	7,5 0.295	16,0 0.630
01B58752008	02465404	ER 20	7,5 0.295	8,0 0.315	16,0 0.630
01B58752009	02700032	ER 20	8,5 0.335	9,0 0.354	16,0 0.630
01B58752010	02685743	ER 20	9,5 0.374	10,0 0.394	16,0 0.630
01B58752505	00029973	ER 25	4,5 0.177	5,0 0.197	21,0 0.827
01B58752506	00029978	ER 25	5,5 0.217	6,0 0.236	21,0 0.827
01B58752507	00029981	ER 25	6,5 0.256	7,0 0.276	21,0 0.827
01B58752508	00029982	ER 25	7,5 0.295	8,0 0.315	21,0 0.827
01B58752509	00029983	ER 25	8,5 0.335	9,0 0.354	21,0 0.827
01B58752510	00029992	ER 25	9,5 0.374	10,0 0.394	21,0 0.827
01B58752511	00029998	ER 25	10,5 0.413	11,0 0.433	21,0 0.827
01B58752512	00030000	ER 25	11,5 0.453	12,0 0.472	21,0 0.827

Designation	Item number	For sealing nut size	DCBN mm inch	DCBX mm inch	BD mm inch
01B58752514	00088809	ER 25	13,5 0.531	14,0 0.551	21,0 0.827
01B58752516	00030010	ER 25	15,5 0.610	16,0 0.630	21,0 0.827
01B58753205	00030017	ER 32	4,5 0.177	5,0 0.197	27,0 1.063
01B58753206	00030316	ER 32	5,5 0.217	6,0 0.236	27,0 1.063
01B58753207	00030020	ER 32	6,5 0.256	7,0 0.276	27,0 1.063
01B58753208	00030023	ER 32	7,5 0.295	8,0 0.315	27,0 1.063
01B58753209	00030026	ER 32	8,5 0.335	9,0 0.354	27,0 1.063
01B58753210	00030028	ER 32	9,5 0.374	10,0 0.394	27,0 1.063
01B58753211	00030317	ER 32	10,5 0.413	11,0 0.433	27,0 1.063
01B58753212	00003370	ER 32	11,5 0.453	12,0 0.472	27,0 1.063
01B58753214	00057876	ER 32	13,5 0.531	14,0 0.551	27,0 1.063
01B58753216	00030319	ER 32	15,5 0.610	16,0 0.630	27,0 1.063
01B58753218	00030320	ER 32	17,5 0.689	18,0 0.709	27,0 1.063
01B58753220	00030321	ER 32	19,5 0.768	20,0 0.787	27,0 1.063

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting accessories

Shrinkfit

– Metric/ Inch

Design 1



Design 2



Design 3



Design 4



Design 5



– Tool Boy assembly supports are made of a base unit and a head
– All heads are interchangeable
– For ISO attribute explanation, see page 15

Designation	Item number	For holder size(s)	Design	Weight	
				kg	lbs
M211H32	00029893	HSK-A32	1	7,2	15.870
M211H40	00029894	HSK-A40	1	7,2	15.870
M211H50	00029895	HSK-A50	1	7,4	16.310
M211H63	00029897	HSK-A63	1	6,3	13.890
M211H10	00029892	HSK-A100	1	8,4	18.520
M100H125A	03229707	HSK-A125	2	3,6	7.940
M211S30	00029888	DIN30, DIN30 TF, BT30, BT30 TF, CAT30, CAT30 TF	3	6,6	14.550
M211S40	00029889	DIN40, DIN40 TF, BT40, BT40 TF, CAT40, CAT40 TF	3	6,4	14.110
M211S50	00029891	DIN50, DIN50 TF, BT50, BT50 TF, CAT50, CAT50 TF	3	9,2	20.280
M211H40E	02432816	HSK-E40	4	7,2	15.870
M211C3	02753746	Seco Capto™ C3	4	7,2	15.870
M211C4	02753747	Seco Capto™ C4	4	7,2	15.870
M211C5	02753748	Seco Capto™ C5	4	7,4	16.310
M211C6	02753749	Seco Capto™ C6	4	6,3	13.890
M211C8	02753750	Seco Capto™ C8	4	7,5	16.530
M211V30	02754029	VDI30	5	6,3	13.890
M211V40	02754031	VDI40	5	6,6	14.550
M211V50	02754032	VDI50	5	7,4	16.310


Clamping torques, torque keys, and sockets for standard ER HP Collet chucks




Collet size	BD1	Capacity DCBN-DCBX	Recommended clamping torque	Fixed handle (1)			Torque key (2)				Roller head (3)	
				Fixed handle ref.	SW1xSW2	OAL	Torque key ref.	Torque capacity	SW1xSW2	OAL	Roller head ref.	SW1xSW2
ER HP 08R	10	1,0-5,0 mm 0.039-0.197"	8 Nm 5.900 ft lb				03DYE003025	2,5-25 Nm	9x12 mm (0,35x0,472")	290 mm (11,417")	03ERB010	9x12 mm (0,35x0,472")
ER HP 11R	16	1,0-2,5 mm 0.039-0.098" 3,0-7,0 mm 0.118-0.275"	10 Nm 7.376 ft lb 20 Nm 14.75 ft lb	03LME0912140	9x12 mm (0,35x0,472")	140 mm (5.511")	03DYE003025	2,5-25 Nm	9x12 mm (0,35x0,472")	290 mm (11,417")	03ER016	9x12 mm (0,35x0,472")
ER HP 16R	22	1,0-4,5 mm 0.039-0.138" 5,0-10,0 mm 0.196-0.394"	20 Nm 14.75 ft lb 30 Nm 22.13 ft lb	03LME0912140	9x12 mm (0,35x0,472")	140 mm (5.511")	03DYE010050	10-50 Nm	9x12 mm (0,35x0,472")	60 mm (14.173")	03ER022	9x12 mm (0,35x0,472")
ER HP 16	30	1,0-4,5 mm 0.039-0.138" 5,0-10,0 mm 0.196-0.394"	30 Nm 22.13 ft lb 80 Nm 59.00 ft lb	03LME1418260	14x18 mm (9.551x0.708")	270 mm (10.630")	03DYE10100B	10-100 Nm	14x18 mm (0.551x0.708")	405 mm (15.945")	03ER030B	14x18 mm (0.551x0.708")
ER HP 20	32	1,0-5,5 mm 0.039-0.217" 6,0-13 mm 0.236-0.512"	40 Nm 29.50 ft lb 80 Nm 59.00 ft lb	03LME1418260	14x18 mm (9.551x0.708")	270 mm (10.630")	03DYE10100B	10-100 Nm	14x18 mm (0.551x0.708")	405 mm (15.945")	03ER032B	14x18 mm (0.551x0.708")
ER HP 25	40	1,0-5,5 mm 0.039-0.217" 6,0-13 mm 0.236-0.512"	40 Nm 29.50 ft lb 90 Nm 73.00 ft lb	03LME1418260	14x18 mm (9.551x0.708")	270 mm (10.630")	03DYE10100B	10-100 Nm	14x18 mm (0.551x0.708")	405 mm (15.945")	03ER040	14x18 mm (0.551x0.708")
ER HP 32	50	2,0-5,5 mm 0.078-0.217" 6,0-15,5 mm 0.236-0.590" 16,0-19,5 mm 0.629-0.768" 20,0 mm 0.787"	40 Nm 29.50 ft lb 120 Nm 88.50 ft lb 140 Nm 103.26 ft lb 180 Nm 132.76 ft lb	03LME1418370	14x18 mm (9.551x0.708")	370 mm (11.811")	03DYE040200	40-200 Nm	14x18 mm (0.551x0.708")	510 (20.078")	03ER050	14x18 mm (0.551x0.708")

Bits for ER Collet chucks, used with Torque keys

Design 1



Design 2



Design 1

Design 2


Designation	Item number	Size	SW	BD1	SW1	SW2	Design
03EF1425S	10307702	ER16	25		14	18	1
03EF1430S	10307704	ER20	30		14	18	1
03EF1425E	10307705	ER25		42	14	18	2
03EF1432E	10307706	ER32		50	14	18	2
03EF1440E	10307707	ER40		63	14	18	2

Axial stop end screws for ER HP Collet chucks

Our standard ER HP collet chucks are delivered without axial stop screws. Two types of stop screw can be ordered: a short design (U) for long tool shanks that go through the collet and a longer design (W) for shorter tool shanks ending in the collet (see details below).

Using a stop end screw in an ER HP collet chucks may affect the runout precision and cause imbalance.

For LF-LFN stroke values, see instruction sheet on www.secotools.com



Type	Collet sizes	Screw ref.	TDZ	HFW	SB
Short (U)	ER11R	19BAS08U	M8x1	4	1,6
	ER16, ER16R	19BAS11U	M11x1	6	1,6
	ER20	19BAS14U	M14x1	5	1,5
	ER25	19BAS18U	18x1,5	6	1,6
	ER32	19BAS22U	M22x1,5	6	1,6
Long (W)	ER11R	19BAS08W	M8x1	4	1,2
	ER16, ER16R	19BAS11W	M11x1	6	1,2
	ER20	19BAS14W	M14x1	5	1,6
	ER25	19BAS18W	18x1,5	6	1,6
	ER32	19BAS22W	M22x1,5	6	1,6



Shrinkfit devices

Our range of Shrinkfit devices can meet the needs of any manufacturer, offering fast performance and incredibly reliable precision. These systems incorporate automatic heating cycles and efficient cooling cycles that use forced air or water cooling bells. Additionally, the use of stop rods for height setting further ensures stability, reliability and accuracy.

- Easyshrink EVO with latest technology
- Fast and easy operation due to simple interface
- Extended tool holder life because of individual optimized heat settings
- Ergonomic tool setting ensures safety due to the machine design
- Versatility and flexibility with an all-in-one solution

– Metric/ Inch



Delivery content – 1 Easyshrink Evo device, including:
5 standard heat focusing stoppers for Ø3 to 32 mm
8 stop rods
2 cooling cones
1 pair of gloves
1 operating instruction

–The device accepts only the voltage:
AC 3 x 400V (+/-10%) + PEN/25A/50-60Hz
AC 3 x 400V (+/-10%) + N + PE/25A/50-60Hz
–For other voltages, a specific device is available on demand
–For ISO attribute explanation, see page 15

Designation	Item number	Capacity, tool shank Carbide/ Heavy metal	Capacity, tool shank Steel/ HSS	Shrinking time, approx. (sec.)	Width	Depth	Height	Weight
		mm	mm		mm inch	mm inch	mm inch	kg lbs
ZFM30IN10	03309162	3-32	6-32	10	317,0 12.480	943,0 37.126	920,0 36.220	80,0 176.370

– Metric/ Inch



Delivery content – 1 Refrigeration unit, including:
1 column for Tubes Support
2 cooling bells with connecting tubes
1 Extension Table

–For usage of refrigeration unit, contact bushing are required, see page(s) 418, 419
–For the use on a 60 hz electricity grid, a specific water cooler is required and available on demand
–For ISO attribute explanation, see page 15

Designation	Item number	Cooling Bells Qty.	Cooling time approx. (minutes)	Width	Depth	Height	Weight
				mm inch	mm inch	mm inch	kg lbs
ZFM30RE1	03309164	2	1	490,0 19.291	630,0 24.803	285,0 11.220	25,0 55.120

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™


Others

Operating &
setting acces-
series

Shrinkfit

– Metric/ Inch

Group 1A
Finned support



Group 1B
Support



Group 2
Contact bushing for cooling bells



—For ISO attribute explanation, see page 15

Group	Designation	Item number	For Shrinkfit holder and tool shank sizes Ø mm	BD1	BD2	LB	Weight
				mm inch	mm inch	mm inch	kg lbs
1A	ZFAD05H32	02464615	HSK-A32 / HSK-C32 / HSK-E32 / HSK-B40 / HSK-D40	90,0 3.543	114,0 4.488	60,0 2.362	1,1 2.430
1A	ZFAD05H40	02464616	HSK-A40 / HSK-C40 / HSK-E40 / HSK-B50 / HSK-D50 / HSK-F50	90,0 3.543	114,0 4.488	60,0 2.362	1,0 2.200
1A	ZFAD05H50	02464618	HSK-A50 / HSK-C50 / HSK-E50 / HSK-B63 / HSK-D63 / HSK-F63	90,0 3.543	114,0 4.488	50,0 1.969	0,9 1.980
1A	ZFAD05H63	02464622	HSK-A63 / HSK-C63 / HSK-E63 / HSK-B80 / HSK-D80 / HSK-F80	90,0 3.543	114,0 4.488	50,0 1.969	0,8 1.760
1A	ZFAD05H10	02464611	HSK-A100 / HSK-C100 / HSK-B125 / HSK-D125	90,0 3.543	114,0 4.488	50,0 1.969	0,7 1.540
1A	ZFAD05S30	02464625	SA30	90,0 3.543	114,0 4.488	50,0 1.969	0,9 1.980
1A	ZFAD05S40	02464626	SA40	90,0 3.543	114,0 4.488	50,0 1.969	0,8 1.760
1A	ZFAD05S50	02464628	SA50	90,0 3.543	114,0 4.488	110,0 4.331	1,3 2.870
1A	ZFAD05C3	02549220	Seco Capto™ C3	90,0 3.543	114,0 4.488	50,0 1.969	0,7 1.540
1A	ZFAD05C4	02549221	Seco Capto™ C4	90,0 3.543	114,0 4.488	50,0 1.969	0,9 1.980
1A	ZFAD05C5	02549222	Seco Capto™ C5	90,0 3.543	114,0 4.488	50,0 1.969	0,7 1.540
1A	ZFAD05C6	02549223	Seco Capto™ C6	90,0 3.543	114,0 4.488	50,0 1.969	0,8 1.760
1A	ZFAD05C8	02549225	Seco Capto™ C8	90,0 3.543	114,0 4.488	50,0 1.969	0,7 1.540
1B	ZFAD05H1205	03267331	HSK-A125 / HSK-B160	90,0 3.543	125,0 4.921	110,0 4.331	2,5 5.510
2	ZFAR10D103	02414213	5801 - Ø3	—	—	—	0,6 1.320
2	ZFAR10D104	02414214	5801 - Ø4	—	—	—	0,6 1.320
2	ZFAR10D105	02414215	5801 - Ø5	—	—	—	0,6 1.320
2	ZFAR10D106	02414216	5801 - Ø6	—	—	—	0,6 1.320
2	ZFAR10D108	02414217	5801 - Ø8	—	—	—	0,6 1.320
2	ZFAR10D110	02414218	5801 - Ø10	—	—	—	0,6 1.320
2	ZFAR10D112	02414219	5801 - Ø12	—	—	—	0,6 1.320
2	ZFAR10D114	02414220	5801 - Ø14	—	—	—	0,6 1.320

Group	Designation	Item number	For Shrinkfit holder and tool shank sizes Ø mm	BD1 mm inch	BD2 mm inch	LB mm inch	Weight kg lbs
2	ZFAR10D116	02414221	5801 - Ø16	–	–	–	0,6 1.320
2	ZFAR10D306	02414222	5603 - Ø6, Ø8	–	–	–	0,6 1.320
2	ZFAR10D310	02422100	5603 - Ø10, Ø12 & 5600 - Ø6, Ø8	–	–	–	0,5 1.100
2	ZFAR10D314	02414223	5603 - Ø14, Ø16 & 5600 - Ø10, Ø12	–	–	–	0,6 1.320
2	ZFAR10D318	02414225	5603 - Ø18, Ø20 & 5600 - Ø14, Ø16	–	–	–	0,5 1.100
2	ZFAR10D325	02414226	5603 - Ø25, Ø32 & 5600 - Ø18, Ø20	–	–	–	0,3 0.660
2	ZFAR10D425	02857518	5600 - Ø25, Ø32	–	–	–	0,3 0.660

Guide

HSK-A

HSK-E

DIN

BT JIS

CAT

Combimaster

Graflex

Seco Capto™

Others

Operating &
setting acces-
series

Shrinkfit

– Metric/ Inch

Group 1
Heat focusing stopper

Group 2
Heat focusing stopper
for tools with a larger
head*

Group 3
Stop rods set

Group 4
Pair of protective gloves

Group 5
Cooling cone



—* Maximum tool head that can pass through the inductor is 65 mm
—For ISO attribute explanation, see page 15

Group	Designation	Item number	For tool shank Ø	BD mm inch	BD1 mm inch	Thread fitting/ Ø Front mm	For length capacity, min mm inch	For length capacity, max mm inch	Weight kg lbs
1	ZFAT30C01	03309165	3-6 mm	7,0 0.276	—	—	—	—	0,4 0.880
	ZFAT30C02	03309166	8-14 mm	15,0 0.591	—	—	—	—	0,4 0.880
	ZFAT30C03	03309167	16-18 mm	20,0 0.787	—	—	—	—	0,3 0.660
	ZFAT30C04	03309168	20-25 mm	27,0 1.063	—	—	—	—	0,2 0.440
	ZFAT30C05	03309169	32 mm	33,0 1.299	—	—	—	—	0,2 0.440
	ZFAT30C06	03309170	3-8 mm	8,5 0.335	—	—	—	—	0,4 0.880
2	ZFAT30H01	03309171	3-6 mm	6,5 0.256	—	—	—	—	0,4 0.880
	ZFAT30H02	03309172	8-14 mm	15,0 0.591	—	—	—	—	0,4 0.880
	ZFAT30H03	03309173	16-18 mm	20,0 0.787	—	—	—	—	0,3 0.660
	ZFAT30H04	03309174	20-25 mm	27,0 1.063	—	—	—	—	0,2 0.440
	ZFAT30H05	03309175	32 mm	34,0 1.339	—	—	—	—	0,2 0.440
3	ZFS07IN018	02518546	3-5 mm	—	2,5 0.098	2,5	0,0 0.0	240,0 9.449	0,1 0.220
	ZFS07IN043	02753706	6-32 mm	—	4,2 0.165	4,2	0,0 0.0	240,0 9.449	0,2 0.440
4	ZFAG01	00032423	—	—	—	—	—	—	0,3 0.660
	ZFAR03C	02774585	—	—	110,0 4.331	—	—	—	0,1 0.220

This work is published with the understanding that Seco Tools and its editors are supplying information aimed to present a general orientation and direction of metal cutting and related sciences. If professional services are required for specific applications, the assistance of an appropriate professional should be acquired. The information is provided "as is"; Seco Tools and its editors disclaim all representations and warranties, express or implied, of any kind, including, without limitations, any warranties of merchantability, fitness for a particular purpose, title, or non-infringement. In no event will Seco Tools or its editors be liable to any party for any direct, indirect, special or other consequential damages for any use of the information, even if Seco Tools or its editors are advised of the possibility of such damage. The information provided herein is for reference purposes only. Actual prices, specifications, and product descriptions are finalized at the time of sale and may vary by location. The information provided herein is subject to change without prior notice.

secotools.com
ST20266819 GB
© Seco Tools AB, 2026.
All rights reserved.

Technical specifications are subject to
change without notice.

