

White Lightning® BOLT™ Quick Dry Siliconized Acrylic Latex Caulk

Physical Properties:		BOLT™ Quick Dry Siliconized Acrylic Latex Caulk	
Type:	Adhesive Caulk	Application Temperature:	Above 50°F
Color:	White	Service Temperature:	-30°F to 180°F
Shelf Life:	12 Months	Odor:	Low/None
Flammability:	N/A	Shrinkage:	Low/Moderate
Flash Point:	N/A	Vehicle:	Water
Full Cure Time:	5-7 Days	Weight Solids:	76.3%
Tack Free Time:	10 Minutes	Weight/Gallon:	12.6 lbs/gal

Performance Data:			
Joint Movement Capability:	Good	Mildew Resistance:	Good
Joint Size:	1/2" x 1/4" to 1/8" x 1/8"	Linear Coverage:	
Freeze -Thaw Stability:	Passes Through 5 Cycles	10 oz Cartridge	
Clean-Up:	Water	1/8" Bead Application	96.7 ft
Flexibility:	Good	1/4" Bead Application	24.2 ft
Painting:	Paintable Within 30 Minutes	5.3 oz Squeeze Tube	
Water Resistance:	Good	1/8" Bead Application	53.2 ft
		1/4" Bead Application	13.3 ft

Product Description:

White Lightning® BOLT™ Quick Dry Siliconized Acrylic Latex Caulk is an easy- to-use interior/exterior caulk specially formulated to dry quickly and can be painted within 30 minutes of application.

Basic Uses:

BOLT™ Quick Dry is used for filling joints and openings around doors, windows, baseboards, trim, siding and vents.

Surface Preparation:

Latex or oil based paint may be applied within 30 minutes of application. Allow extra dry time during periods of high humidity or cool temperatures.

Cautions:

Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer to other containers for storage.

Limitations:

For best results apply at temperatures above 50°F. Never use in butt joints, joints subject to heavy abrasion and wear, or those that are frequently under water. Do not apply when rain or moisture is expected.

Specifications:

Exceeds ASTM Spec C-834.



For more information please call or write:

White Lightning® Products • 101 Prospect Ave. NW • Cleveland, OH 44115
1-800-241-5295 Option 1 Customer Service • 1-800-241-5295 Option 2 Technical Service
www.wlcaulk.com